


FEMALE PLUG M8 STRAIGHT



NOTES:
RATED VOLTAGE: 3 contacts 60V AC/DC
4 and 5 contacts 30V AC/DC
CURRENT RATING: 3, 4, 5 contacts 3A
PROTECTION CLASS: IP 67
TEMPERATURE: -25°C / +80°C

CONTACTS POSITION FRONT VIEW:

FEMALE	3 CONTACTS		4 CONTACTS		5 CONTACTS	
CONNECTIONS	PIN	WIRE	PIN	WIRE	PIN	WIRE
	1	BROWN	1	BROWN	1	BROWN
	3	BLUE	2	WHITE	2	WHITE
	4	BLACK	3	BLUE	3	BLUE
			4	BLACK	4	BLACK
					5	GREY

CODING ACCORDING TO IEC 61076-2-104

FOR OPTIONS SEE - NUMERICAL CODE - ON SHEET 2

8	2	I/D CARRIER (SEE MATRIX)	---	---
7	1	LABEL YELLOW	VINYL	---
	-	PRINTING FOR CABLES Ixx	---	---
6	-	CABLE	SEE SHEET 2	---
5	-	OVERMOULDING	TPU	SEE SHEET 2
4	1	COUPLING NUT M8 FEMALE	BRASS	SEE SHEET 2
3	1	INSERT FEMALE BLACK	TPU	---
2	1	O-RING RED	FKM	---
1	3 / 4 / 5	CONTACT M8 FEMALE	COPPER	SELECTIVE Au OVER Ni
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

PENDING APPROVAL

SYMBOLS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
DIMENSION UNITS		SCALE	CURRENT REV DESC:
mm		2:1	
GENERAL TOLERANCES (UNLESS SPECIFIED)			
ANGULAR TOL ± °			
4 PLACES ±			
3 PLACES ±			
2 PLACES ±			
1 PLACE ±			
0 PLACES ±			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			
THIRD ANGLE PROJECTION			
DRAWING		SERIES	MATERIAL NUMBER
A3-SIZE		120086	SEE SHEET 3-4
CUSTOMER			
GENERAL MARKET			
SHEET NUMBER			
1 OF 4			

ENGINEERING NO. - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).

OPTIONS

4

0

X

0

0

0

X

X

X

X

X

X

X

X

40=Nano-Change
M8x1
Double ended

Contacts:
3=3 Contacts
4=4 Contacts
5=5 Contacts

Heads style:
000=Plug Female Straight

Cable type: See Table

Units:
M=Meter
C=Centimeter

Length
Examples:
005=0.5 unit
010=1 unit
100=10 unit



Overmold color:
Blank (Standard)=Black
A = Grey / G=Black / Y=Yellow
For Cable K05 = Yellow Overmould


Coupling Nut:
Blank (Standard)=Knurled Brass Ni Plated
9 = Knurled / Hexagonal SW9 Brass Ni Plated

7 = Teflon

H = 2 pcs. of I/D Carrier PVC Transparent
(Cables Ixx & P82 always with 2 pcs. of I/D Carrier)

COUPLING NUT
FEMALE





CABLE INFORMATION (for more information see Cable Data Sheet).

CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN	SHIELD
E02	3 / 4 / 5	0.25mm²	PVC BLACK	UL 2464/1729	C22.2 I/II A/B 80°C/300V	-30°C to +80°C, >10xO.D.	-10°C to +80°C, >15xO.D.	-	-
E18	3 / 4	0.20mm²	PVC YELLOW	-	-	-30°C to +70°C	-5°C to +70°C	-	-
E51	4	0.25mm²	PVC GREY	-	-	-	-	-	-
E52	3 / 4 / 8	0.34mm²	PVC GREY	-	-	-30°C to +70°C	-5°C to +70°C	-	-
E54	3	0.25mm²	PVC GREY	-	-	-25°C to +70°C	-5°C to +70°C	-	-
H08	3 / 4 / 5	0.25mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, >5xO.D.	-25°C to +80°C, >10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
H09	3 / 4 / 5	0.34mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, >5xO.D.	-25°C to +80°C, >10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
H69	4	0.20mm²	PUR GRAY LS0H	-	-	-	-	-	-
I02	3 / 4	0.25mm²	PVC CEI GREY	-	-	-30°C to +70°C	-5°C to +70°C	-	-
P02	3 / 4 / 5	0.25mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, >7xO.D.	-5°C to +80°C, >15xO.D.	-	-
P03	3 / 4 / 5	0.34mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, >7xO.D.	-5°C to +80°C, >15xO.D.	-	-
P18	4	0.20mm²	PUR YELLOW	-	-	-	-	-	-
P82	3	0.34mm²	PUR IRR ORANGE	-	-	-50°C to +105°C, >5xO.D.	-40°C to +105°C, >7.5xO.D.	-	-
K05	3 / 4 / 5	0.34mm²	TPE YELLOW	UL ITC E195601 or PLC	I/II A/B 90°C/300V	-	-	-	-
L03	3	0.34mm²	Blend PUR ORANGE	-	-	-30°C to +90°C	-5°C to +90°C	-	-
A10	3 / 4 / 5	0.25mm²	PVC YELLOW	UL 2661	I/II A/B 105°C/300V	-	-	-	-

CABLE LENGTH TOLERANCES


OVER	UP TO AND INCLUDING	TOLERANCES
0	305mm	+19mm
305mm	915mm	+45mm
915mm	1830mm	+56mm
1830mm	3660mm	+89mm
3660mm	7320mm	+165mm
7320mm	14640mm	+317mm
14640mm	30500mm	+610mm
30500mm	>	+2% of finished length

DOCUMENT STATUS	RQ	RELEASE DATE	
-----------------	----	--------------	--

10	9	8	7	6	5	4	3	2	1											
PART LIST																				
F	Pos.	Part. No	Engineering No.	Cable Length	Pos.	Part. No	Engineering No.	Cable Length	Pos.	Part. No	Engineering No.	Cable Length	Pos.	Part. No	Engineering No.	Cable Length	Pos.	Part. No	Engineering No.	Cable Length
	1	1200270066	403000E02M020	2m	36	1200868263	403000E02M003	0.3m	71	1200868698	404000E02M1509H	15m	106	1200868003	403000P02M100	10m	106	1200868003	403000P02M100	10m
	2	1200270067	403000E02M030	3m	37	1200868264	403000E02M020H	2m	72	1200868774	404000E02M060	6m	107	1200868148	405000P02M005	0.5m	107	1200868148	405000P02M005	0.5m
	3	1200270068	403000E02M050	5m	38	1200868265	403000E02M035	3.5m	73	1200868776	404000E02M070	7m	108	1200868156	404000P02M020	2m	108	1200868156	404000P02M020	2m
	4	1200270070	403000E02M100	10m	39	1200868266	403000E02M045	4.5m	74	1200271409	403000H08M010	1m	109	1200868157	404000P02M050	5m	109	1200868157	404000P02M050	5m
	5	1200270127	404000E02M020	2m	40	1200868267	403000E02M0501	5m	75	1200271442	403000H08M020G	2m	110	1200868158	404000P02M100	10m	110	1200868158	404000P02M100	10m
	6	1200270129	404000E02M050	5m	41	1200868268	403000E02M060	6m	76	1200868045	403000H08M020	2m	111	1200868274	403000P02C350	3.5m	111	1200868274	403000P02C350	3.5m
	7	1200270131	404000E02M100	10m	42	1200868339	404000E02C200	2m	77	1200868053	404000H08M050	5m	112	1200868275	403000P02M002	0.2m	112	1200868275	403000P02M002	0.2m
	8	1200270132	404000E02M150	15m	43	1200868340	404000E02M015	1.5m	78	1200868060	404000H08M030	3m	113	1200868276	403000P02M002G	0.2m	113	1200868276	403000P02M002G	0.2m
	9	1200270133	404000E02M200	20m	44	1200868341	404000E02M0201	2m	79	1200868101	403000H08M050	5m	114	1200868277	403000P02M003	0.3m	114	1200868277	403000P02M003	0.3m
E	10	1200270400	403000E02M010	1m	45	1200868342	404000E02M040	4m	80	1200868115	403000H08M100	10m	115	1200868278	403000P02M003G	0.3m	115	1200868278	403000P02M003G	0.3m
	11	1200270549	404000E02M010	1m	46	1200868343	404000E02M0501	5m	81	1200868116	403000H08M200	20m	116	1200868279	403000P02M005	0.5m	116	1200868279	403000P02M005	0.5m
	12	1200271410	403000E02M012	1.2m	47	1200868344	404000E02M080	8m	82	1200868117	404000H08M100	10m	117	1200868280	403000P02M006	0.6m	117	1200868280	403000P02M006	0.6m
	13	1200271417	403000E02M006	0.6m	48	1200868345	404000E02M110	11m	83	1200868118	404000H08M200	20m	118	1200868281	403000P02M010	1m	118	1200868281	403000P02M010	1m
	14	1200271418	403000E02M015	1.5m	49	1200868346	404000E02M170	17m	84	1200868122	403000H08M030	3m	119	1200868282	403000P02M012	1.2m	119	1200868282	403000P02M012	1.2m
	15	1200271419	403000E02M025	2.5m	50	1200868347	404000E02M210	21m	85	1200868162	404000H08M040	4m								

Pos.	Part. No	Engineering No.	Cable Length
36	1200868263	403000E02M003	0.3m
37	1200868264	403000E02M020H	2m
38	1200868265	403000E02M035	3.5m
39	1200868266	403000E02M045	4.5m
40	1200868267	403000E02M0501	5m
41	1200868268	403000E02M060	6m
42	1200868339	404000E02C200	2m
43	1200868340	404000E02M015	1.5m
44	1200868341	404000E02M0201	2m
45	1200868342	404000E02M040	4m
46	1200868343	404000E02M0501	5m
47	1200868344	404000E02M080	8m
48	1200868345	404000E02M110	11m
49	1200868346	404000E02M170	17m
50	1200868347	404000E02M210	21m
51	1200868348	404000E02M250	25m
52	1200868423	403000E02M1001	10m
53	1200868442	403000E02M020Y	2m
54	1200868443	403000E02M050Y	5m
55	1200868444	403000E02M100Y	10m
56	1200868452	404000E02M050Y	5m
57	1200868453	404000E02M100Y	10m
58	1200868454	404000E02M150Y	15m
59	1200868467	403000E02M150Y	15m
60	1200868473	404000E02M1001	10m
61	1200868508	404000E02M050H	5m
62	1200868509	404000E02M100H	10m
63	1200868510	404000E02M150H	15m
64	1200868511	404000E02M030H	3m
65	1200868518	404000E02C230	2.3m
66	1200868571	405000E02M120	12m
67	1200868572	405000E02M030	3m
68	1200868685	403000E02M050H	5m
69	1200868696	404000E02M0509H	5m
70	1200868697	404000E02M1009H	10m

Pos.	Part. No	Engineering No.	Cable Length
106	1200868003	403000P02M100	10m
107	1200868148	405000P02M005	0.5m
108	1200868156	404000P02M020	2m
109	1200868157	404000P02M050	5m
110	1200868158	404000P02M100	10m
111	1200868274	403000P02C350	3.5m
112	1200868275	403000P02M002	0.2m
113	1200868276	403000P02M002G	0.2m
114	1200868277	403000P02M003	0.3m
115	1200868278	403000P02M003G	0.3m
116	1200868279	403000P02M005	0.5m
117	1200868280	403000P02M006	0.6m
118	1200868281	403000P02M010	1m
119	1200868282	403000P02M012	1.2m
120	1200868283	403000P02M018	1.8m
121	1200868284	403000P02M022	2.2m
122	1200868285	403000P02M030	3m
123	1200868286	403000P02M032	3.2m
124	1200868287	403000P02M035	3.5m
125	1200868288	403000P02M040	4m
126	1200868289	403000P02M050G	5m
127	1200868290	403000P02M055	5.5m
128	1200868291	403000P02M080	8m
129	1200868292	403000P02M150	15m
130	1200868351	404000P02M003	0.3m
131	1200868352	404000P02M030	3m
132	1200868353	404000P02M040	4m
133	1200868354	404000P02M070	7m
134	1200868355	404000P02M500	50m
135	1200868517	403000P02M200	20m
136	1200868530	404000P02M010	1m
137	1200868627	405000P02M050Y	5m
138	1200868773	404000P02M060	6m
139	1200868775	404000P02M200	20m
140	1200270637	403000E52M050G	5m

SYMBOLS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													
DIMENSION UNITS		SCALE		CURRENT REV DESC:				molex							
mm		2:1													
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 632381				2020/02/03				M8 SINGLE ENDED FEMALE STRAIGHT					
ANGULAR TOL ± °		DRWN: SSM													
4 PLACES ±		CHK'D:				PRODUCT CUSTOMER DRAWING									
3 PLACES ±		APPR:													
2 PLACES ±		INITIAL REVISION:				DOCUMENT NUMBER				DOC TYPE		DOC PART		REVISION	
1 PLACE ±		DRWN: AKONDRACIUK 2017/02/16				1200860594				PSD		000		A4	
0 PLACES ±		APPR: MIWASIECZKO 2017/11/16													
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER			
				A3-SIZE		120086		SEE PART LIST		GENERAL MARKET		3 OF 4			

10	9	8	7	6	5	4	3	2	1
----	---	---	---	---	---	---	---	---	---

10	9	8	7	6	5	4	3	2	1		
PART LIST											
Pos.	Part. No	Engineering No	Cable Length	Pos.	Part. No	Engineering No	Cable Length	Pos.	Part. No	Engineering No	Cable Length
141	1200860340	403000K05M050	5m	176	1200271180	403000P82M020	2m	211	1200868029	404000E18M030	3m
142	1200868431	403000K05M150	15m	177	1200271305	404000P82M050	5m	212	1200270078	403000E54M050A	5m
143	1200270642	403000L03M005A	0.5m	178	1200271450	404000P82M0507	5m	213	1200868018	403000E54M030A	3m
144	1200270080	403000I02M003	0.3m	179	1200868183	403000P82M0507	5m	214	1200270143	404000E51M020A	2m
145	1200270081	403000I02M020	2m	180	1200868192	403000P82M0207	2m	215	1200270145	404000E51M050A	5m
146	1200270082	403000I02M030	3m	181	1200868212	403000P82M005	0.5m	216	1200860667	405000P02M200	20m
147	1200270083	403000I02M050	5m	182	1200868213	404000P82M005	0.5m	217	1200868849	405000H08M010	1m
148	1200270084	403000I02M100	10m	183	1200868232	404000P82M010	1m	218	1200868857	405000E02M010	1m
149	1200270148	404000I02M020	2m	184	1200868233	403000P82M010	1m	219			
150	1200270149	404000I02M050	5m	185	1200868420	403000P82M1007	10m	220			
151	1200270360	404000I02M100	10m	186	1200868461	404000P82M0207Y	2m	221			
152	1200860041	404000I02M030	3m	187	1200868470	403000P82M0207Y	2m	222			
153	1200868269	403000I02M005	0.5m	188	1200868481	404000P82M010Y	1m	223			
154	1200868270	403000I02M006	0.6m	189	1200868482	403000P82M010Y	1m	224			
155	1200868271	403000I02M010	1m	190	1200868567	404000P82M0307Y	3m	225			
156	1200868272	403000I02M025	2.5m	191	1200868602	404000P82M050Y	5m	226			
157	1200868273	403000I02M150	15m	192	1200270341	404000P18M050	5m	227			
158	1200868349	404000I02M003	0.3m	193	1200270346	404000P18M100	10m	228			
159	1200868350	404000I02M050G	5m	194	1200270863	404000P18M005	0.5m	229			
160	1200868445	403000I02M030Y	3m	195	1200271449	403000P18M070	7m	230			
161	1200868446	403000I02M050Y	5m	196	1200860101	403000A10M015	1.5m	231			
162	1200868447	403000I02M100Y	10m	197	1200860102	403000A10M020	2m	232			
163	1200868455	404000I02M020Y	2m	198	1200860107	403000A10M050	5m	233			
164	1200868456	404000I02M050Y	5m	199	1200860111	403000A10M100	10m	234			
165	1200868460	404000I02M100Y	10m	200	1200860112	403000A10M150	15m	235			
166	1200868507	403000I02M020Y	2m	201	1200860144	404000A10M020	2m	236			
167	1200868566	404000I02M030Y	3m	202	1200860145	404000A10M030	3m	237			
168	1200270147	404000H69M020	2m	203	1200860147	404000A10M050	5m	238			
169	1200868100	404000H69M100	10m	204	1200860155	404000A10M100	10m	239			
170	1200868184	404000H69M010	1m	205	1200860191	405000A10M020	2m	240			
171	1200270445	404000H69M050	5m	206	1200270140	404000E18M050	5m	241			
172	1200271440	403000H69M050	5m	207	1200270581	403000E18M020	2m	242			
173	1200271441	403000H69M020	2m	208	1200270606	403000E18M100	10m	243			
174	1200270032	403000P82M050	5m	209	1200868017	403000E18M050	5m	244			
175	1200271042	404000P82M0207	2m	210	1200868028	404000E18M020	2m	245			

PENDING
APPROVAL

SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		CURRENT REV DESC:										
	mm		1:1												
	GENERAL TOLERANCES (UNLESS SPECIFIED)														
	ANGULAR TOL		± °		EC NO: 632381 DRWN: SSM 2020/02/03 CHK'D: APPR:										
	4 PLACES		±												
	3 PLACES		±												
	2 PLACES		±		INITIAL REVISION: DRWN: AKONDRACIUK 2017/02/16 APPR: MIWASIECZKO 2017/11/16										
	1 PLACE		±												
	0 PLACES		±												
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
						A3-SIZE		120086		SEE PART LIST		GENERAL MARKET		4 OF 4	

DOCUMENT STATUS	RQ	RELEASE DATE	
-----------------	----	--------------	--

10	9	8	7	6	5	4	3	2	1
----	---	---	---	---	---	---	---	---	---

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9