



Product: [1522A](#) 



RGB Video, Mini #30-5 Coax Stranded TC, CL2

### Product Description

RGB Video Coax, CL2-Rated, 5-30 AWG stranded tinned copper conductors, foam HDPE insulation, Duofoil® +90% tinned copper braid shield, overall Beldfoil® shield, inner PVC jackets, PVC jacket

### Technical Specifications

#### Physical Characteristics (Overall)

##### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
30	7x38	TC - Tinned Copper	0.013 in	5

Conductor Count:	5
------------------	---

##### Insulation

Material	Nominal Diameter
PE - Polyethylene (Foam)	0.056 in

##### Color Chart

Number	Color
1	Red
2	Green
3	Blue
4	White
5	Yellow

##### Inner Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Alum / Poly / Alum	Duofoil®	100%
Braid	2	TC - Tinned Copper		90%

##### Inner Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.102 in

##### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]
Tape	Alum / Poly	Beldfoil®	100%

##### Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.338 in

#### Electrical Characteristics

##### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR

100 Ohm/1000ft	100 Ohm/1000ft	9.5 Ohm/1000ft	9.5 Ohm/1000ft
----------------	----------------	----------------	----------------

#### Capacitance

Nom. Capacitance Conductor to Other Conductor	Nom. Capacitance Conductor to Shield
17.3 pF/ft	17.3 pF/ft

#### Impedance

Nominal Characteristic Impedance
75 Ohm

#### Return Loss (RL)

Frequency [MHz]	Minimum Return (RL)
10-40 MHz	25 dB

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.8 dB/100ft
5 MHz	1.5 dB/100ft
10 MHz	2.2 dB/100ft
30 MHz	4 dB/100ft
50 MHz	5.4 dB/100ft
100 MHz	8.2 dB/100ft
200 MHz	12.5 dB/100ft
400 MHz	18.9 dB/100ft
700 MHz	26.5 dB/100ft
900 MHz	30.8 dB/100ft
1000 MHz	32.8 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	78%

#### Voltage

UL Voltage Rating	Voltage Rating [V]
300 V RMS	30 V RMS
300 V RMS (CL2)	

Electrical Characteristics Notes:	30 V RMS (UL AWM Style 1354); 300 V RMS (CL2)
-----------------------------------	---

#### Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-40°C To +60°C

#### Mechanical Characteristics

Bulk Cable Weight:	63 lbs/1000ft
Max. Pull Tension:	70 lbs
Min Bend Radius/Minor Axis:	3.5 in

#### Standards

NEC/(UL) Compliance:	CL2
UL AWM Style Compliance:	UL Style 1354 (each coax); UL Style 2688 (overall)
CPR Euroclass:	Eca
RG Type:	Sub-miniature 59
Series Type:	Sub-miniature 59

#### Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Part Number

#### Variants

Item #	Color	Putup Type	Length	UPC
1522A 010500	Black	Reel	500 ft	612825358398
1522A 0101000	Black	Reel	1,000 ft	612825356561

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

### History

Update and Revision:	Revision Number: 0.247 Revision Date: 06-24-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9