

Panel feed-through - Q 1,5/2L90/11KU-DSI - 1670280

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Panel feed-through, for internal wall mounting, with dip-solder connection, length of the solder pin: 3.8 mm, hole Ø 2-pos. = 19.0 mm - 0.3



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 017918 146450 |
| Weight per Piece (excluding packing) | 22.35 GRM |
| Custom tariff number | 85366990 |
| Country of origin | Poland |

Technical data

General

| | |
|--------------------------------------|---|
| Connection | If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load. |
| Color | green |
| Connection method | QUICKON connection Dip-solder connection |
| Note on the internal connection type | The product must be screwed to the PCB before soldering. Self-tapping screws in acc. with ISO 1481-ST 2,9 x 6,5 C. |
| Number of positions | 2 |
| Wrench size, union nut | 22 mm |
| Tightening torque, union nut | 2.5 Nm |
| Wrench size, contact carrier | 22 mm |
| Tightening torque contact carrier | 3.75 Nm |
| Tightening torque, counter nut | 3.75 Nm |

Panel feed-through - Q 1,5/2L90/11KU-DSI - 1670280

Technical data

General

| | |
|--|----------------------|
| Conductor cross section stranded min. | 0.75 mm ² |
| Conductor cross section stranded max. | 1.5 mm ² |
| Conductor cross section AWG/kcmil min. | 18 |
| Conductor cross section AWG/kcmil max | 16 |

Conductor

| | |
|---|--|
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 Cl.2-5, min. wire diameter 0.2 mm |
| Wire insulation material | PVC/PE |
| Wire diameter including insulation | >= 3 mm |
| External cable diameter | 4 mm ... 7.5 mm |

Ambient conditions

| | |
|---|--|
| Degree of protection | IP65 |
| | IP67 |
| Ambient temperature (operation) | -25 °C ... 80 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Temperature when conductor connected | -5 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.) |

Electrical characteristics

| | |
|--------------------------------|--------|
| Nominal current I _N | 17.5 A |
| Rated voltage (III/3) | 250 V |
| Rated voltage (III/2) | 320 V |
| Rated voltage (II/2) | 630 V |
| Rated surge voltage (III/3) | 4 kV |
| Rated surge voltage (III/2) | 4 kV |
| Rated surge voltage (II/2) | 4 kV |

Mechanical characteristics

| | |
|------------------------|--|
| QUICKON connectability | 10 (if the conductor is connected more than once, seal and cap may need to be replaced.) |
| PC QUICKON thread type | Pg11 |
| Impact category | 3 |

Material data

| | |
|---|----------------------------------|
| Contact material | Copper alloy |
| Contact surface material | Pre-nickel plated and tin-plated |
| Contact carrier material | PA 66 |
| Inflammability class according to UL 94 | V0 |
| Surge voltage category | III |

Panel feed-through - Q 1,5/2L90/11KU-DSI - 1670280

Technical data

Material data

| | |
|------------------|---|
| Pollution degree | 3 |
|------------------|---|

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |
| eCl@ss 5.0 | 27143423 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |
| eCl@ss 8.0 | 27449001 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001297 |
| ETIM 3.0 | EC000516 |
| ETIM 4.0 | EC000516 |
| ETIM 5.0 | EC000516 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211923 |
| UNSPSC 7.0901 | 39121522 |
| UNSPSC 11 | 39121522 |
| UNSPSC 12.01 | 39121522 |
| UNSPSC 13.2 | 39121522 |

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Panel feed-through - Q 1,5/2L90/11KU-DSI - 1670280

Approvals

Approval details

| | |
|--------------------|-------|
| UL Recognized | |
| Nominal current IN | 15 A |
| Nominal voltage UN | 250 V |

| | |
|--------------------|-------|
| cUL Recognized | |
| Nominal current IN | 11 A |
| Nominal voltage UN | 250 V |

| | |
|------|--|
| GOST | |
|------|--|

| | |
|------------------|--|
| cULus Recognized | |
|------------------|--|

Accessories

Accessories

Flat nut

Mounting material - Q-MU PG13,5 M - 1670905



Counter nut, (metal), to lock the contact carrier in the case of aligning

Mounting material

Panel feed-through - Q 1,5/2L90/11KU-DSI - 1670280

Accessories

Nut - Q-MU PG11 - 1670471



Nut (plastic) to lock the contact carrier Pg11 / 24 WAF

Protective cap

Filler plugs - Q-PROT13/16 - 1670222



Closing caps, for Pg13/ Pg16, for closing unoccupied connections

Filler plugs - Q-PROT 9/11 - 1670235



Closing cap for Pg9/Pg11 to close unoccupied connections

Nut - Q-SMU PG13,5 SET - 1670756




Locking nut, can only be released with wrench, Pg13.5/ WAF 24, coding 1


Drawings

Panel feed-through - Q 1,5/2L90/11KU-DSI - 1670280


Drilling diagram



Dimensioned drawing



Panel feed-through - Q 1,5/2L90/11KU-DSI - 1670280



For aligning PCB versions, 30 mm pitch, Pg11 in rows. To lock the contact carrier, the Q-MU PG 11 nut should be used.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9