

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -





ALL RIGHTS RESERVED.

REVISIONS



P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

LED SCHEMATIC	
LED1	LED2
GREEN	YELLOW
9-  +10	11-  +12

MODULAR JACK WITH LED



RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05 (TOP VIEW)



RECOMMENDED SUGGESTED PANEL CUTOUT


NOTE:

- MATERIAL:
 - HOUSING: PA46, WITH 30% GF, UL94 V-0, BLACK COLOR.
 - CONTACTS: PHOSPHOR BRONZE.
 - SHELL: BRASS.
 - LED SOLDER TAIL: STEEL.
- FINISH:
 - CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA, GOLD FLASH ON SOLDER TAIL AREA, 1.27um [50u"] MIN. NICKEL UNDERPLATING OVERALL. SHELL: 0.508um [20μ"] MIN. NICKEL PLATED. a POST DIPPED WITH TIN ON PCB GROUND TABS. LED SOLDER TAIL: 2.032um [80μ"] MIN. BRIGHT-TIN PLATED.
- LED MUST BE REFLOW COMPATIBLE TO FOLLOWING TEMPERATURE PROFILE (FOR 1 CYCLE): ABOVE 160°C FOR 120 SECONDS, PEAKING AT 245°C FOR 20~40 SECONDS.
- LED DEFECT RATE IS 6000PPM MAX. AFTER IR REFLOW PROCESS AS NOTE 3.
- WAVE SOLDER CAPABLE TO 265°C PER TE SPEC 109-202, CONDITION B.
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

YELLOW	GREEN	0.762μm [30μ"]	7-1734577-3
LED2	LED1	MIN. GOLD THICKNESS	PART NUMBER
INDICATOR COLOR			


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. HSING 21JUL2009	 TE Connectivity	
		CHK S. CHIEN 21JUL2009		
		APVD W. KODAMA 21JUL2009	NAME	
DIMENSIONS: mm		PRODUCT SPEC	MODULAR JACK CONNECTOR RJ45, 8P8C, VERTICAL, DIP TYPE.	
		APPLICATION SPEC		
		WEIGHT	SIZE	CAGE CODE
MATERIAL		FINISH	DRAWING NO	
SEE NOTE		SEE NOTE	RESTRICTED TO	
		CUSTOMER DRAWING	A300779C-1734577	
		SCALE	SHEET	
		1:1	3 of 5	
			REV	
			D	

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-




- NOTES:
- MATERIAL:
TRAY: PET.
POLYLONE: POLYLONE
SHIPPING BOX: CORRUGATED FIBER.
 - DIMENSION:
TRAY: L=300mm, W=270mm, H=19mm
SHIPPING CARTON: L=560mm, W=310mm, H=210mm
 - QUANTITY: SEE TABLE
 - WEIGHT: SEE TABLE

15 KG	13.3 KG	100	20	2000
GROSS WEIGHT	NET WEIGHT	PCS/ TRAY	TRAY/ BOX	PCS/ BOX

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. HSING 21JUL2009		 TE Connectivity											
		CHK S. CHIEN 21JUL2009													
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME											
		0 PLC ± -		MODULAR JACK CONNECTOR RJ45, 8P8C, VERTICAL, DIP TYPE.											
		1 PLC ± 0.3													
		2 PLC ± 0.2													
		3 PLC ± 0.15													
		4 PLC ± -													
		ANGLES ± 3°													
MATERIAL		FINISH		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO					
SEE NOTE		SEE NOTE		A3		00779		C-1734577		—					
CUSTOMER DRAWING										SCALE 1:1		SHEET 4 OF 5		REV D	

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-


PACKAGE ONLY FOR 6-1734577-3



NOTES:

1. MATERIAL:
TRAY: PET.
POLYLONE: POLYLONE
BOX: CORRUGATED FIBER.
2. DIMENSION:
TRAY: L=308mm, W=180mm, H=23.6mm
INNER BOX: L=315mm, W=190mm, H=130mm
BOX: L=420mm, W=345mm, H=275mm
3. QUANTITY: SEE TABLE
4. WEIGHT: SEE TABLE

17.0 KG	13.3 KG	70	350	1400	6-1734577-3
GROSS WEIGHT	NET WEIGHT	PCS/ TRAY	TRAY/ INNER BOX	PCS/ BOX	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. HSING	21JUL2009	 TE Connectivity			
DIMENSIONS: mm		CHK S. CHIEN	21JUL2009	NAME MODULAR JACK CONNECTOR RJ45, 8P8C, VERTICAL, DIP TYPE.			
		APVD W. KODAMA	21JUL2009				
		PRODUCT SPEC —					
		APPLICATION SPEC —					
		WEIGHT —					
MATERIAL SEE NOTE	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± — 1 PLC ± 0.3 2 PLC ± 0.2 3 PLC ± 0.15 4 PLC ± — ANGLES ± 3°	FINISH SEE NOTE		SIZE A3	CAGE CODE 00779	DRAWING NO C-1734577	RESTRICTED TO —
CUSTOMER DRAWING				SCALE 1:1	SHEET 5 of 5	REV D	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9