

For more Information  
please call

1-800-Belden1



## Description:

22 AWG stranded (7x30) tinned copper conductor, polypropylene insulation, twisted pairs individually shielded with Beldfoil® (100% coverage), overall PVC jacket and 22 AWG stranded tinned copper drain wire.

## Physical Characteristics (Overall)

### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
6	22	7x30	TC - Tinned Copper	0.762

### Insulation

**Insulation Material:**

Insulation Material	Dia. (mm)
PP - Polypropylene	1.27

### Inner Shield

**Inner Shield Material:**

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

**Inner Shield Drain Wire AWG:**

AWG
22

**Inner Shield Drain Wire Stranding:** Stranded

**Inner Shield Drain Wire Conductor Material:** TC - Tinned Copper

### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

### Overall Cabling

**Overall Nominal Diameter:** 8.941 mm

### Pair

**Pair Color Code Chart:**

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown

**Pair Lay Length & Direction:**

Lay Length (mm)	Twists/ft. (twist/m)
44.449825	22.475

## Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +80°C
UL Temperature Rating:	80°C (UL AWM Style 2919)
Bulk Cable Weight:	110.573 Kg/Km
Max. Recommended Pulling Tension:	698.367 N
Min. Bend Radius (Install)/Minor Axis:	88.900 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 2919 (30 V 80°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

### Plenum/Non-Plenum

Plenum (Y/N):	No
Non-Plenum Number:	88778, 87778, 82778

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

50

### Nom. Inductance:

Inductance (µH/m)

0.59058

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

98.43

### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

180.455

### Nominal Velocity of Propagation:

VP (%)

66

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

49.215

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 34.779 Ohm/km

**Max. Operating Voltage - UL:**

Voltage
30 V RMS (UL AWM Style 2919)
300 V RMS (CM)

**Max. Recommended Current:**

Current
2 Amps per conductor @ 25°C

**Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8778 060100	30 MT	3.583 KG	CHROME		6 FS PR #22 PP PVC
8778 0601000	305 MT	35.380 KG	CHROME	C	6 FS PR #22 PP PVC
8778 060250	76 MT	8.845 KG	CHROME	C	6 FS PR #22 PP PVC
8778 060500	152 MT	18.144 KG	CHROME	C	6 FS PR #22 PP PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 04-18-2008

© 2011 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9