

## FO connecting cable - FOC-HCS-GI-1005/M12-C/SCRJ/5 - 1416651

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PCF-GI cable, assembled with M12 connector to SC-RJ

### Product description

PCF-GI cable, assembled with M12 connector to SC-RJ

### Product Features

- ✓ 2.2 mm individual wires made from polyvinyl chloride (PVC)
- ✓ Assembled patch cable with test report
- ✓ M12-OPTIC with recessed ferrules to protect against damage
- ✓ optimized polishing for even better attenuation values
- ✓ Rugged installation cable for indoor use
- ✓ Gradient index fiber for maximum performance requirements in terms of transmission bandwidth
- ✓ Rugged polyurethane (PUR) outer sheath
- ✓ Highly tear-resistant aramid strain relief elements
- ✓ Pin connector pattern in accordance with DIN/IEC 61754-27
- ✓ Included in PROFINET planning guideline (v1.14)
- ✓ Robust connector, IP65/IP67
- ✓ Can be used in 10/100/1000 Mbps Ethernet systems
- ✓ Halogen-free, ozone, and UV resistant
- ✓



**Ethernet**

### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	360.0 GRM
Custom tariff number	85444290
Country of origin	Germany

## FO connecting cable - FOC-HCS-GI-1005/M12-C/SCRJ/5 - 1416651

### Technical data

#### Mechanical characteristics

Number of positions	2
Fiber type	PCF
Fiber	200/230 µm
Ferrule diameter	2.50 mm
Connection method	M12 circular connector
Cable diameter	8.00 mm
Type of cable	Break-out cable
Duty cycle testing	Flexible cable conduit capable
Length of cable	5 m

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP65/IP67

#### Material data

Inflammability class according to UL 94	V0
Outer sheath, material	PUR
External sheath, color	Green
Ferrule material	Zirconia ceramics

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061803
eCl@ss 6.0	27061090
eCl@ss 7.0	27061090

#### ETIM

ETIM 3.0	EC000034
ETIM 4.0	EC000034
ETIM 5.0	EC000034

# FO connecting cable - FOC-HCS-GI-1005/M12-C/SCRJ/5 - 1416651


## Classifications

### UNSPSC

UNSPSC 6.01	30211832
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	39121429

## Drawings

Dimensional drawing



## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9