

# UTP



## Full plastic circular connector

### Description

"UTP" full plastic industrial circular connectors are a range of multiway connectors.

"UTP" provides the complete answer to the need for economical lightweight, robust circular connectors and is unique in offering a plastic bayonet coupling ring incorporating a metal wave spring, which locks with an audible positive "click". It is available in 8 shell sizes, 10 insert arrangements all intermateable, interchangeable and intermountable with the TRIM TRIO "UTO" (full metal) and "UTG" (plastic with metal coupling ring) industrial connector families.



### Features and benefits

- Available in 8 shell sizes and 10 insert arrangements incl. 2 VDE versions.
- Available in plug and receptacle versions for both male and female contacts.
- Connectors and accessories are moulded from highly durable glass-filled thermoplastic.
- Flammability rating: UL94-V0.
- Plastic bayonet ring:
  - Vibration proof thermoplast
  - Metal wave spring loaded.
  - Locks with audible positive "click"
  - UL recognized File Nr.: E238675

### Performance characteristics

|                        |                            |
|------------------------|----------------------------|
| Operating temperature: | -55°C to +125°C            |
| Insulation resistance: | 5000 MΩ min.               |
| Test potential:        | 2000 VAC                   |
| Durability:            | 250 matings and unmatings. |

Degree of protection per DIN 40050: IP65 in mated condition. "H" version used with water protected backshells.

### Construction

Connector, Bayonet ring and accessories  
 Gass filled thermoplast UL94-V0  
 Colour: black  
 Coupling spring: Spring steel

### Contact accommodation

- "UTP" connectors accept TRIM TRIO size 16 removable snap-lock contacts (see contacts section)
- Contacts to be ordered separately.


## How to order

| Connector family :         | UTP                                                                                     | 0 | 14 | 12 | P | H | -- |
|----------------------------|-----------------------------------------------------------------------------------------|---|----|----|---|---|----|
|                            | UTP                                                                                     | 6 | 14 | 12 | S |   | -- |
| <b>Body variation:</b>     | 0 : Wall mounting receptacle<br>6 : Cable plug                                          |   |    |    |   |   |    |
| <b>Shell size:</b>         |                                                                                         |   |    |    |   |   |    |
| <b>Insert arrangement:</b> |                                                                                         |   |    |    |   |   |    |
| <b>Type of contacts:</b>   | P : Pin contacts<br>S : Socket contacts                                                 |   |    |    |   |   |    |
| <b>Application</b>         | No letter : Standard version<br>H : Water protected version (only receptacle)           |   |    |    |   |   |    |
| <b>Design variation</b>    | No letter : Moulded-in contact marking (standard version)<br>Others : Specials versions |   |    |    |   |   |    |

# UTP




## Cable plug for pin contacts (UTP6- - -P)



| Part number                     | Shell size | Ø A ±0.2 | B max.      | Ø C ±0.15 | Ø D ±0.15 | Ø E ±0.2 |
|---------------------------------|------------|----------|-------------|-----------|-----------|----------|
| <b>UTP6104P / UTP6103PVDE</b>   | <b>10</b>  | 26.7     | 31.8        | 10.9      | 12.2      | 19.1     |
| <b>UTP6128P</b>                 | <b>12</b>  | 31.4     |             | 13.8      | 15.1      |          |
| <b>UTP61412P</b>                | <b>14</b>  | 34.5     |             | 17.0      | 18.3      |          |
| <b>UTP61619P</b>                | <b>16</b>  | 37.8     |             | 19.9      | 21.5      |          |
| <b>UTP61823P / UTP6187PVDEU</b> | <b>18</b>  | 40.8     | 31.8 / 33.0 | 22.4      | 24.0      |          |
| <b>UTP62028P</b>                | <b>20</b>  | 43.9     | 31.8        | 25.6      | 27.2      |          |
| <b>UTP62235P</b>                | <b>22</b>  | 47.0     |             | 28.5      | 30.4      |          |
| <b>UTP62448P</b>                | <b>24</b>  | 50.1     |             | 31.7      | 33.5      |          |

Part numbers are suitable for both standard and IP65 water protection versions.

## Cable plug for socket contacts (UTP6- - -S)




| Part number                     | Shell size | Ø A ±0.2 | B max.       | Ø C ±0.15 | Ø D ±0.15 | Ø E ±0.2 |
|---------------------------------|------------|----------|--------------|-----------|-----------|----------|
| <b>UTP6104S / UTP6103SVDE</b>   | <b>10</b>  | 26.7     | 23.9 / 26.75 | 10.9      | 12.2      | 19.1     |
| <b>UTP6128S</b>                 | <b>12</b>  | 31.4     | 23.9         | 13.8      | 15.1      |          |
| <b>UTP61412S</b>                | <b>14</b>  | 34.5     |              | 17.0      | 18.3      |          |
| <b>UTP61619S</b>                | <b>16</b>  | 37.8     |              | 19.9      | 21.5      |          |
| <b>UTP61823S / UTP6187SVDEU</b> | <b>18</b>  | 40.8     | 23.9 / 29.0  | 22.4      | 24.0      |          |
| <b>UTP62028S</b>                | <b>20</b>  | 43.9     | 24.9         | 25.6      | 27.2      |          |
| <b>UTP62235S</b>                | <b>22</b>  | 47.0     |              | 28.5      | 30.4      |          |
| <b>UTP62448S</b>                | <b>24</b>  | 50.1     | 26.2         | 31.7      | 33.5      |          |

Part numbers are suitable for both standard and IP65 water protection versions.

# UTP



## Wall mounting receptacle for pin contacts (UTP0- - - -P)




| Part number              | Shell size | A max.    | B ±0.15 | C ±0.2    | Ø D ±0.15 | E ±0.25 | F ±0.25 | Ø G ±0.1 | Ø J ±0.1 |
|--------------------------|------------|-----------|---------|-----------|-----------|---------|---------|----------|----------|
| UTP0104P / UTP0103PVDE   | 10         | 31.7      | 2.3     | 11.3      | 15.0      | 18.3    | 23.8    | 3.2      | 15.1     |
| UTP0128P                 | 12         |           |         |           | 19.0      | 20.6    | 26.2    |          | 18.2     |
| UTP01412P                | 14         |           |         |           | 22.2      | 23.0    | 28.6    |          | 21.4     |
| UTP01619P                | 16         |           |         |           | 25.3      | 24.6    | 31.0    |          | 24.6     |
| UTP01823P / UTP0187PVDEU | 18         | 31.7/34.0 | 2.5     | 11.3/17.9 | 28.5      | 27.0    | 33.3    | 3.2      | 27.8     |
| UTP02028P                | 20         | 33.3      | 3.5     | 14.5      | 31.7      | 29.4    | 36.5    |          | 30.9     |
| UTP02235P                | 22         |           |         | 34.9      | 31.8      | 39.7    | 34.1    |          |          |
| UTP02448P                | 24         |           |         | 15.3      | 38.0      | 34.9    | 42.9    | 3.9      | 37.3     |

For IP65 waterprotected version add "H" behind "P" e.g. UTP01412PH

A square flange sealing has to be ordered separately to guarantee a sealing with the equipment. Refer to "Circular accessories" section (UTFD--).

## Wall mounting receptacle for socket contacts (UTP0- - - -S)




| Part number              | Shell size | A max.    | B<br>±0.15 | C<br>±0.2 | Ø D<br>±0.15 | E<br>±0.25 | F<br>±0.25 | Ø G<br>±0.1 | Ø J<br>±0.1 |
|--------------------------|------------|-----------|------------|-----------|--------------|------------|------------|-------------|-------------|
| UTP0104S / UTP0103SVDE   | 10         | 24.3/27.6 | 2.3        | 11.3      | 15.0         | 18.3       | 23.8       | 3.2         | 15.1        |
| UTP0128S                 | 12         | 24.3      |            |           | 19.0         | 20.6       | 26.2       |             | 18.2        |
| UTP01412S                | 14         |           |            |           | 22.2         | 23.0       | 28.6       |             | 21.4        |
| UTP01619S                | 16         |           |            |           | 25.3         | 24.6       | 31.0       |             | 24.6        |
| UTP01823S / UTP0187SVDEU | 18         | 24.3/30.4 | 2.5        | 11.3/17.9 | 28.5         | 27.0       | 33.3       | 3.2         | 27.8        |
| UTP02028S                | 20         | 27.0      | 14.5       | 31.7      | 29.4         | 36.5       | 30.9       |             |             |
| UTP02235S                | 22         | 28.0      |            | 34.9      | 31.8         | 39.7       | 34.1       |             |             |
| UTP02448S                | 24         | 30.4      | 3.5        | 15.3      | 38.0         | 34.9       | 42.9       | 3.9         | 37.3        |


For IP65 waterprotected version add "H" behind "S" e.g. UTP01412SH

A square flange sealing has to be ordered separately to guarantee a sealing with the equipment. Refer to "Circular accessories" section (UTFD--).

# Circular accessories




## Plastic cable clamp with strain relief (UTG--AC)



| Part number | Shell size | Cable range $\varnothing$ | $\varnothing A \pm 0.4$ | $L \pm 0.5$ |
|-------------|------------|---------------------------|-------------------------|-------------|
| UTG10AC     | 10         | 3.0 - 8.7                 | 21.0                    | 40.0        |
| UTG12AC     | 12         | 3.0 - 12.8                | 24.0                    | 40.0        |
| UTG14AC     | 14         | 4.0 - 13.8                | 27.0                    | 46.0        |
| UTG16AC     | 16         | 5.0 - 17.0                | 30.2                    | 46.0        |
| UTG18AC     | 18         | 5.0 - 19.0                | 33.3                    | 50.0        |
| UTG20AC     | 20         | 5.0 - 21.0                | 36.5                    | 55.0        |
| UTG22AC     | 22         | 5.0 - 23.0                | 39.7                    | 60.0        |
| UTG24AC     | 24         | 8.0 - 27.0                | 42.9                    | 65.0        |

For threading specifications see last page of this section "Circular accessories"


## Plastic cable clamp with strain relief nut for waterprotected (IP65) applications (UTG--PG)




| Part number | Shell size | Sealing*<br>outer dia x inner dia's | $L \pm 1$ | $A \pm 0.5$ |
|-------------|------------|-------------------------------------|-----------|-------------|
| UTG10PG     | 10         | 13.5 x 5 x 8                        | 54        | 21.0        |
| UTG12PG     | 12         | 16 x 7 x 10.5 x 13 x 16             | 57        | 24.0        |
| UTG14PG     | 14         | 18.5 x 7 x 10.5 x 13 x 16           | 62        | 27.0        |
| UTG16PG     | 16         | 20.5 x 8 x 10.5 x 13 x 16           | 68        | 30.2        |
| UTG18PG     | 18         | 20.5 x 8 x 10.5 x 13 x 16           | 71        | 33.3        |
| UTG20PG     | 20         | 26 x 11 x 15 x 18 x 22              | 82        | 36.5        |
| UTG22PG     | 22         | 26 x 11 x 15 x 18 x 22              | 88        | 39.7        |
| UTG24PG     | 24         | 35 x 19 x 23 x 27 x 31              | 103       | 42.9        |

\*In order to accommodate different cable dia's, the sealing exists of different layers which can be pulled out easily. Cable clamp has a PG style cable gland. For threading specifications see last page of this section "Circular accessories"

# Circular accessories




## Plastic cable clamp with strain relief nut for waterprotected (IP65) applications (UTG--ST)



| Part number | Shell size | Cable range | Dia. A $\pm 0.5$ | L $\pm 1$ |
|-------------|------------|-------------|------------------|-----------|
| UTG10ST     | 10         | 2 - 6       | 21.0             | 64        |
| UTG12ST     | 12         | 3 - 7       | 24.0             | 64        |
| UTG14ST     | 14         | 6 - 9       | 27.0             | 69        |
| UTG16ST     | 16         | 7 - 12      | 30.2             | 72        |
| UTG18ST     | 18         |             | 33.3             | 76        |
| UTG20ST     | 20         | 9 - 16      | 36.5             | 80        |
| UTG22ST     | 22         |             | 39.7             | 86        |
| UTG24ST     | 24         | 13 - 20     | 42.9             | 91        |

Cable clamp has a PG style cable gland. For threading specifications see last page of this section "Circular"


## Metal cable clamp with strain relief (UT0--AC)




| Part number | Shell size | Max cable dia. Excl. sealing | $\varnothing A \pm 0.2$ | B maxi | C maxi |
|-------------|------------|------------------------------|-------------------------|--------|--------|
| UT010AC     | 10         | 5.0                          | 16.3                    | 21.6   | 31.0   |
| UT012AC     | 12         | 8.2                          | 19.4                    | 25.0   | 31.5   |
| UT014AC     | 14         | 10.0                         | 22.5                    | 27.4   | 34.0   |
| UT016AC     | 16         | 13.0                         | 25.8                    | 29.4   | 34.0   |
| UT018AC     | 18         | 16.0                         | 29.2                    | 35.2   | 31.4   |
| UT020AC     | 20         | 16.0                         | 32.5                    | 35.2   | 32.0   |
| UT022AC     | 22         | 19.3                         | 35.7                    | 41.1   | 31.0   |
| UT024AC     | 24         | 20.6                         | 38.8                    | 42.4   | 31.0   |

For threading specifications see last page of this section "Circular accessories"

# Circular accessories




**Short cable clamp with strain relief nut for waterprotected applications (IP68). (UT0--JCS)**  
**Long cable clamp with strain relief nut for waterprotected applications (IP68). (UT0--JC)**



| Part number   |              | Shell size | Clamping range<br>(Ø en mm) min / max | L ± 1         |              | Thread A                   |
|---------------|--------------|------------|---------------------------------------|---------------|--------------|----------------------------|
| Short version | Long version |            |                                       | Short version | Long version |                            |
| UT010JCS      | UT010JC      | 10         | 03 / 06                               | 48.5          | 60.5         | 9/16 – 24 UNEF Class 2A    |
| UT012JCS      | UT012JC      | 12         | 06 / 10                               | 49.5          | 61.5         | 11/16 – 24 UNEF Class 2A   |
| UT014JCS      | UT014JC      | 14         | 06 / 10                               | 53.5          | 67.5         | 13/16 – 20 UNEF Class 2A   |
| UT016JCS      | UT016JC      | 16         | 9.5 / 14                              | 62.5          | 73.5         | 15/16 – 20 UNEF Class 2A   |
| UT018JCS      | UT018JC      | 18         | 9.5 / 14                              | 65.5          | 76.0         | 1" 1/16 – 18 UNEF Class 2A |
| UT020JCS      | UT020JC      | 20         | 11.5 / 18                             | 70.5          | 84.0         | 1" 3/16 – 18 UNEF Class 2A |
| UT022JCS      | UT022JC      | 22         | 11.5 / 18                             | 76.5          | 88.0         | 1" 5/16 – 18 UNEF Class 2A |
| UT024JCS      | UT024JC      | 24         | 11.5 / 18                             | 82.0          | 92.0         | 1" 7/16 – 18 UNEF Class 2A |

Cable clamp has a Metric style cable gland. For threading specifications see last page of this section "Circular accessories"

**Short cable clamp with large strain relief nut for waterprotected applications (IP68). (UT0--JCSL)**  
**Long cable clamp with large strain relief nut for waterprotected applications (IP68). (UT0--JCL)**




| Part number   |              | Shell size | Clamping range<br>(Ø en mm) min / max | L ± 1         |              | Thread A                   |
|---------------|--------------|------------|---------------------------------------|---------------|--------------|----------------------------|
| Short version | Long version |            |                                       | Short version | Long version |                            |
| UT010JCSL     | UT010JCL     | 10         | 05 / 08                               | 49.5          | 61.5         | 9/16 – 24 UNEF Class 2A    |
| UT012JCSL     | UT012JCL     | 12         | 08 / 12                               | 49.5          | 62.5         | 11/16 – 24 UNEF Class 2A   |
| UT014JCSL     | UT014JCL     | 14         | 08 / 12                               | 54.5          | 68.5         | 13/16 – 20 UNEF Class 2A   |
| UT016JCSL     | UT016JCL     | 16         | 11.5 / 18                             | 68.5          | 79.5         | 15/16 – 20 UNEF Class 2A   |
| UT018JCSL     | UT018JCL     | 18         | 11.5 / 18                             | 71.5          | 82.0         | 1" 1/16 – 18 UNEF Class 2A |
| UT020JCSL     | UT020JCL     | 20         | 15 / 24                               | 77.5          | 91.0         | 1" 3/16 – 18 UNEF Class 2A |
| UT022JCSL     | UT022JCL     | 22         | 15 / 24                               | 83.5          | 95.0         | 1" 5/16 – 18 UNEF Class 2A |
| UT024JCSL     | UT024JCL     | 24         | 15 / 24                               | 89.0          | 99.0         | 1" 7/16 – 18 UNEF Class 2A |

Cable clamp has a Metric style cable gland. For threading specifications see last page of this section "Circular accessories"




**Short shielded cable clamp with strain relief nut for waterprotected applications (IP68). (UT0S----JCS)**  
**Long shielded cable clamp with strain relief nut for waterprotected applications (IP68). (UT0S----JC)**



| Part number   |              | Shell size | Clamping range<br>(Ø en mm) min / max | L ± 1         |              | Thread A                   |
|---------------|--------------|------------|---------------------------------------|---------------|--------------|----------------------------|
| Short version | Long version |            |                                       | Short version | Long version |                            |
| UT0S10JCS     | UT0S10JC     | 10         | 04 / 6.5                              | 58.5          | 70.5         | 9/16 – 24 UNEF Class 2A    |
| UT0S12JCS     | UT0S12JC     | 12         | 07 / 10.5                             | 61.5          | 74.5         | 11/16 – 24 UNEF Class 2A   |
| UT0S14JCS     | UT0S14JC     | 14         | 07 / 10.5                             | 66.5          | 80.5         | 13/16 – 20 UNEF Class 2A   |
| UT0S16JCS     | UT0S16JC     | 16         | 10 / 14.5                             | 72.5          | 83.5         | 15/16 – 20 UNEF Class 2A   |
| UT0S18JCS     | UT0S18JC     | 18         | 10 / 14.5                             | 75.5          | 86.0         | 1" 1/16 – 18 UNEF Class 2A |
| UT0S20JCS     | UT0S20JC     | 20         | 13.5 / 18                             | 84.5          | 97.5         | 1" 3/16 – 18 UNEF Class 2A |
| UT0S22JCS     | UT0S22JC     | 22         | 13.5 / 18                             | 90.0          | 101.5        | 1" 5/16 – 18 UNEF Class 2A |
| UT0S24JCS     | UT0S24JC     | 24         | 13.5 / 18                             | 95.5          | 105.5        | 1" 7/16 – 18 UNEF Class 2A |

Cable clamp has a Metric style cable gland. For threading specifications see last page of this section "Circular accessories"

**Short shielded cable clamp with large strain relief nut for waterprotected applications (IP68). (UT0S----JCSL)**  
**Long shielded cable clamp with large strain relief nut for waterprotected applications (IP68). (UT0S----JCL)**




| Part number   |              | Shell size | Clamping range<br>(Ø en mm) min / max | L ± 1         |              | Thread A                   |
|---------------|--------------|------------|---------------------------------------|---------------|--------------|----------------------------|
| Short version | Long version |            |                                       | Short version | Long version |                            |
| UT0S10JCSL    | UT0S10JCL    | 10         | 05 / 8.5                              | 59.5          | 71.5         | 9/16 – 24 UNEF Class 2A    |
| UT0S12JCSL    | UT0S12JCL    | 12         | 08 / 12.5                             | 61.5          | 74.5         | 11/16 – 24 UNEF Class 2A   |
| UT0S14JCSL    | UT0S14JCL    | 14         | 08 / 12.5                             | 66.5          | 80.5         | 13/16 – 20 UNEF Class 2A   |
| UT0S16JCSL    | UT0S16JCL    | 16         | 13.5 / 18                             | 82.5          | 93.5         | 15/16 – 20 UNEF Class 2A   |
| UT0S18JCSL    | UT0S18JCL    | 18         | 13.5 / 18                             | 85.5          | 96.0         | 1" 1/16 – 18 UNEF Class 2A |
| UT0S20JCSL    | UT0S20JCL    | 20         | 17 / 24                               | 93.0          | 106.5        | 1" 3/16 – 18 UNEF Class 2A |
| UT0S22JCSL    | UT0S22JCL    | 22         | 17 / 24                               | 99.0          | 110.5        | 1" 5/16 – 18 UNEF Class 2A |
| UT0S24JCSL    | UT0S24JCL    | 24         | 17 / 24                               | 104.5         | 114.5        | 1" 7/16 – 18 UNEF Class 2A |

Cable clamp has a Metric style cable gland. For threading specifications see last page of this section "Circular accessories"




## Metal right angle cable clamp with strain relief nut (UTG--LPGN / UTO--LPGN)



| Part number<br>For UTP / UTG | Part number<br>For UTO / UTOW | Shell<br>size | A max | B max | Cable range               |
|------------------------------|-------------------------------|---------------|-------|-------|---------------------------|
| UTG10LPGN                    | UT010LPGN                     | 10            | 48.0  | 30.0  | 13.5 x 5 x 8              |
| UTG12LPGN                    | UT012LPGN                     | 12            | 50.0  | 33.5  | 16 x 7 x 10.5 x 13        |
| UTG14LPGN                    | UT014LPGN                     | 14            | 52.0  | 36.5  | 18.5 x 7 x 10.5 x 13 x 16 |
| UTG16LPGN                    | UT016LPGN                     | 16            | 55.0  | 39.5  | 20.5 x 8 x 10.5 x 13 x 16 |
| UTG18LPGN                    | UT018LPGN                     | 18            | 60.0  | 46.0  | 20.5 x 8 x 10.5 x 13 x 16 |
| UTG20LPGN                    | UT020LPGN                     | 20            | 58.0  | 47.0  | 26 x 11 x 15 x 18 x 22    |
| UTG22LPGN                    | UT022LPGN                     | 22            | 58.0  | 48.5  | 26 x 11 x 15 x 18 x 22    |
| UTG24LPGN                    | UT024LPGN                     | 24            | 67.0  | 54.5  | 35 x 19 x 23 x 27 x 31    |

Cable clamp has a PG style cable gland. For threading specifications see last page of this section "Circular accessories"

## Metal shrink boot adaptor (UTG--AD) for UTP and UTG



| Part number | Shell size | Ø A ±0.2 | B    |
|-------------|------------|----------|------|
| UTG10AD     | 10         | 21.0     | 19.2 |
| UTG12AD     | 12         | 24.0     |      |
| UTG14AD     | 14         | 27.0     |      |
| UTG16AD     | 16         | 30.0     | 21.5 |
| UTG18AD     | 18         | 33.3     |      |
| UTG20AD     | 20         | 36.5     | 22.8 |
| UTG22AD     | 22         | 39.7     |      |
| UTG24AD     | 24         | 42.9     | 21.9 |


Standard plating is anodised black. For tin plating add "T" at the end of the part number e.g. UTG12ADT  
For threading specifications see last page of this section "Circular accessories"



# Circular accessories




## Metal shrink boot adaptor for UTO and UTOW



| Part number | Shell size | Ø A ±0.2 | B    |
|-------------|------------|----------|------|
| UT010AD     | 10         | 21       | 24.7 |
| UT012AD     | 12         | 24       |      |
| UT014AD     | 14         | 27       |      |
| UT016AD     | 16         | 30       | 27   |
| UT018AD     | 18         | 33.3     |      |
| UT020AD     | 20         | 36.5     |      |
| UT022AD     | 22         | 39.7     |      |
| UT024AD     | 24         | 42.9     |      |

For threading specifications see last page of this section "Circular accessories"

## Environmental dustcap for plugs (UTG6--DCG)




| Part number | Shell size | A max. | B    |
|-------------|------------|--------|------|
| UTG610DCG   | 10         | 20.0   | 20.8 |
| UTG612DCG   | 12         | 24.0   |      |
| UTG614DCG   | 14         | 27.5   |      |
| UTG616DCG   | 16         | 30.5   |      |
| UTG618DCG   | 18         | 33.5   |      |
| UTG620DCG   | 20         | 36.5   | 22.5 |
| UTG622DCG   | 22         | 40.0   |      |
| UTG624DCG   | 24         | 43.0   |      |

For dustcap without chain skip "G" e.g. UTG612DC

# Circular accessories



## Metal environmental dustcap for receptacles (UT0--DCG)




| Part number | Shell size | A max. |
|-------------|------------|--------|
| UT010DCG    | 10         | 20.8   |
| UT012DCG    | 12         | 24.9   |
| UT014DCG    | 14         | 28.1   |
| UT016DCG    | 16         | 31.3   |
| UT018DCG    | 18         | 34.4   |
| UT020DCG    | 20         | 37.6   |
| UT022DCG    | 22         | 40.8   |
| UT024DCG    | 24         | 43.9   |

For dustcap without chain skip "G" e.g. UTG12DC

For jam dustcap consult factory

## Plastic environmental dustcap for receptacles (UTP--DCG)




| Part number | Shell size | Ø A ±0.2 | B max. |
|-------------|------------|----------|--------|
| UTP10DCG    | 10         | 26.7     | 19.3   |
| UTP12DCG    | 12         | 31.4     | 20.0   |
| UTP14DCG    | 14         | 34.5     | 20.2   |
| UTP16DCG    | 16         | 37.8     |        |
| UTP18DCG    | 18         | 40.8     |        |
| UTP20DCG    | 20         | 43.9     | 21.8   |
| UTP22DCG    | 22         | 47.0     |        |
| UTP24DCG    | 24         | 50.1     |        |


For dustcap without chain skip "G" e.g. UTP12DC

For jam dustcap consult factory

# Circular accessories




## Sealing for wall mounting receptacle (UTFD1-B)



| Part number | Shell size | Ø F ±0.1 | R ±0.25 | S ±0.25 | Ø V |
|-------------|------------|----------|---------|---------|-----|
| UTFD12B     | 10         | 15.9     | 18.3    | 23.8    | 3.3 |
| UTFD13B     | 12         | 19.0     | 20.6    | 26.2    |     |
| UTFD14B     | 14         | 22.2     | 23.0    | 28.6    |     |
| UTFD15B     | 16         | 25.4     | 24.6    | 31.0    |     |
| UTFD16B     | 18         | 28.6     | 27.0    | 33.3    |     |
| UTFD17B     | 20         | 31.8     | 29.4    | 36.5    |     |
| UTFD18B     | 22         | 34.9     | 31.8    | 39.7    |     |
| UTFD19B     | 24         | 38.1     | 34.9    | 42.9    | 4.0 |

## Adaptors for flexible cable protection systems (conduits)




Adaptors for flexible cable protections systems that fit to the TRIM TRIO circular connectors are available from cable protection systems manufacturers (e.g. PMA).

2 solutions are offered:

- UNEF Adaptors that fit directly onto the connectors (left picture)
- METRIC Adaptors that fit onto the metal cable clamp tubes as indicated on pages 43 and 44 (right picture)

These types of adaptors offer extra protection to single wire applications (electrical, coax, Fibre optic ... etc.)

Note: the adaptors are not available from Souriau. They must be ordered directly from the manufacturers



## Cable gland threadings used on cable clamps

| Shell size | Thread size on connectors | PG threading | Metric threading |
|------------|---------------------------|--------------|------------------|
| 10         | 9/16 - 24 UNEF            | PG9          | M16 x 1.5        |
| 12         | 11/16 - 24 UNEF           | PG11         | M20 x 1.5        |
| 14         | 13/16 - 20 UNEF           | PG13.5       | M20 x 1.5        |
| 16         | 15/16 - 20 UNEF           | PG16         | M25 x 1.5        |
| 18         | 1-1/16 - 18 UNEF          | PG16         | M25 x 1.5        |
| 20         | 1-3/16 - 18 UNEF          | PG21         | M32 x 1.5        |
| 22         | 1-5/16 - 18 UNEF          | PG21         | M32 x 1.5        |
| 24         | 1-7/16 - 18 UNEF          | PG29         | M32 x 1.5        |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9