



LC Duplex Single-Boot Connector

106025 LC Duplex Single-Boot Connector

Reduce cable congestion using a LC Duplex connector with only a single cable

Development Background: Molex offers many additional features for fiber optic connectors to provide functionality for OEM's and other customers. By combining the LC duplex interface with a cabled version of the LC loopback connector, we are able to offer a rugged, yet compact connector that is compatible with existing LC adapters and transceivers. The LC connector effectively reduces the required cable diameter, allowing neat and less congested fiber routing within the system.

The LC Duplex Single-Boot connector offers the benefits of a duplex connector with the fiber management of

a simplex style connector. Using a cabled version of the Molex LC loopback style housing, this LC connector provides a robust duplex interface with a two fiber single jacketed cable. The connector is available for either singlemode or multimode fiber types and can be field or factory terminated.

Additionally, the connector is compatible with straight, 90° angled and mini boots, providing cable routing options suitable for most applications.

For additional product information, please visit www.molex.com/link/lcingleboot.html.

Features and Benefits

- Single boot using simplex style cable with two 900 μm buffered fibers provide duplex connectivity while optimizing cable routing space
- Variety of strain relief boots including straight, 90° angled and mini boots offer flexibility for cable routing
- Small housing footprint allows connectors to be ganged or stacked in belly-to-belly cage applications
- Multimode or singlemode styles for factory or field termination can be used in most standard applications with common fiber types
- RoHS Compliant meets EU environmental requirements for electronic equipment and accessories.

SPECIFICATIONS

Reference Information


Packaging: individually bagged
 Mates With: 106059, 106125, 106126, 106127, and 106128 series LC adapters
 Designed In: Inches

Mechanical

Mating Durability: IL<0.2dB change over 200 cycles

Physical

Housing: UL 94V-0 rated polymer
 Ferrule: Zirconia Ceramic
 Operating Temperature: -40 to +85°C



LC Duplex Single-Boot Connectors with Mini boot (top), Straight boot (middle), and 90° boot (bottom) options



APPLICATIONS



LC Duplex Single-Boot Connector

106025 LC Duplex Single-Boot Connector

- Telecommunication
 - Cross Connects
 - Routers
 - SFP and SFP+
- Storage
 - Servers
 - Switches
- Premise
 - Computer connections
 - Optical DVI



ORDERING INFORMATION

LC Single Boot Duplex Connector (for field termination)

Order No.	Ferrule Diameter	Boot	Housing Color
106025-2320	Singlemode 125.5µm	3.3mm Straight	Blue
106025-2360	Multimode 127µm	3.3mm Straight	Beige
106025-2370	Singlemode 125.5µm	3mm 90° Angled	Blue
106025-2380	Multimode 127µm	3mm 90° Angled	Beige
106025-2330	Singlemode 125.5µm	3mm Mini**	Blue
106025-2340	Multimode 127µm	3mm Mini**	Beige

Cable Assembly

Cable assemblies are custom designed to meet customers requirements. Please contact Molex Fiber Optics to request a customized cable assembly using the LC Duplex Single-Boot connector.

** Molex Mini style straight boots are to be used in areas where space is limited and bending stress will not be seen. This boot does not provide bend relief and is recommended to be used with bend insensitive fibers for best results.

www.molex.com/link/lcingleboot.html

Americas Headquarters
Lisle, Illinois 60532 U.S.A.
1-800-78MOLEX
amerinfo@molex.com

Asia Pacific North Headquarters
Yamato, Kanagawa, Japan
81-46-265-2325
apninfo@molex.com

Asia Pacific South Headquarters
Jurong, Singapore
65-6268-6868
apsinfo@molex.com

European Headquarters
Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters
2222 Wellington Ct.
Lisle, IL 60532 U.S.A.
P: 630-969-4550 F: 630-969-1352

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9