

TIGHT STABILITY INDUSTRIAL GRADE CRYSTAL OSCILLATOR

ASET SERIES



RoHS
Compliant



3.2 x 2.5 x 0.9mm

FEATURES:

- Highly reliable seam-sealed package
- Low current consumption 7mA
- Low phase noise and jitter
- Industrial grade tight temperature stability available (± 10 ppm / -40 to +85°C)
- Fast start-up time 0.2ms typical
- CMOS output with Tri-state function

APPLICATIONS:

- Home networking by AC socket
- Wireless LAN
- Mobile communications
- PLC modem
- WiMax

STANDARD SPECIFICATIONS:

PARAMETERS	
ABRACON P/N:	ASET Series
Frequency:	4.000MHz to 54.000MHz
Standard Frequencies:	5, 10, 12, 16, 20, 24, 26, 27, 32, 40, 44MHz
Output level:	CMOS
Operating temperature:	- 40°C to +85°C
Storage temperature:	- 40°C to +85°C
Overall Frequency Stability*:	± 15 ppm (see options)
Supply voltage (Vdd):	3.0Vdc $\pm 10\%$ (see options)
Supply Current (Idd):	7mA max.
Stand-by Current	10 μ A max.
Symmetry:	45/55 % @ 50 % Vdd
Rise and Fall Times(Tr/Tf):	5ns max. / 10 %Vdd-90%Vdd
Start-up time:	0.2ms typical, 3ms max.
Output load:	15pF max.
Output Voltage :	VOH = 0.9*Vdd min.
	VOL = 0.1*Vdd max.
Aging @ 25°C:	± 2 ppm/ first year, ± 7 ppm/ 10 years
Phase Noise (@ 10 kHz offset):	-143dBc/Hz Typ.
Jitter:	1 σ 3ps typ.

* Overall frequency stability includes initial tolerance @ +25°C, and temperature stability.

OPTIONS AND PART IDENTIFICATION:

(Left blank if standard)

ASET - - Frequency - -

P/N and Vdd (V)		Frequency	Freq. Stability		Packaging	
Blank	3.0 $\pm 10\%$	XX.XXXX MHz	Blank	± 15 ppm	Blank	Bulk
A	2.7 $\pm 10\%$		Y	± 10 ppm	T	Tape and Reel
B	3.3 $\pm 10\%$		R7*	± 7 ppm		
C	2.8 $\pm 10\%$		R5*	± 5 ppm		
D	2.5 $\pm 10\%$					

* Contact ABRACON for availability



TIGHT STABILITY INDUSTRIAL GRADE CRYSTAL OSCILLATOR

ASET SERIES




RoHS
Compliant




3.2 x 2.5 x 0.9mm

OUTLINE DRAWING:



Recommended land pattern



Resist layer is required on the path for the by-pass capacitor.

Note : It is recommended to use an approximately 0.01µF bypass capacitor between PIN 3 and 6.



PIN	FUNCTION
1	OE
2	N.C.
3	GND
4	Output
5	N.C.
6	Vdd

Dimensions: Inches (mm)

TAPE & REEL: T= tape and reel (1,000 pcs/reel)

REFLOW PROFILE

Dimensions: mm



Need a test socket for the ASET Series? To view compatible **PRECISION TEST & BURN-IN SOCKETS** for these parts, [click here](#). P/N: AXS-3225-04-05

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS
ISO 9001 :2008
CERTIFIED



Visit www.abracon.com for Terms & Conditions of Sale
 30332 Esperanza, Rancho Santa Margarita, California 92688
 tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Revised: 07.21.11

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9