

SENCITY® Omni-S 3x3 WiFi MIMO Antenna 1399.17.0208

Description

Small omni-directional MIMO antenna for WiFi + LTE 2600 applications
Dual band WiFi / WLAN and LTE 2600 3 x 3 MIMO antenna
Supports the 2.4 GHz and 5 GHz and LTE 2.5 to 2.7 GHz bands
Three ports each with broad-band antenna radiator technology
IEEE 802.11 b/g/a/h/p and 802.11 n / ac
For industrial indoor environment - IP65 protected



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2
Frequency (MHz)	2400 - 2690	5150 - 5935
VSWR	1.7	1.7
Impedance (Ohm)	50	50
Gain (dBi)	5	6
3dB beamwidth (h) (°)	360	360
3dB beamwidth (v) (°)	65	65
Composite power max (W)	50	30
Ambient temperature (°C)	25	25
Port Isolation (dB)	20	20

Ports

	Port 1	Port 2	Port 3
Connector	N, plug (male)	N, plug (male)	N, plug (male)
Cable Type	S_04262_D-09	S_04262_D-09	S_04262_D-09
Cable Length (m)	0.9	0.9	0.9
Min. radius static (mm)	28	28	28
Polarization	vertical	vertical	vertical
DC grounded	Yes	Yes	Yes

Connections

	Band 1	Band 2
Port 1	X	X
Port 2	X	X
Port 3	X	X

General Data

Three cable pigtails with connector N (male) directly attached to the antenna body

Mechanical Data

Dimensions (mm)	32 x 282 x 92 (Height x Width x Depth)
Weight (kg)	0.6

Environmental Data

Environmental conditions	indoor
Operation temperature (°C)	-40 to 85
Operating conditions	ETSI EN 300 019-2-3 V2.2.2 (2003-04) T3.3
Storage temperature (°C)	-40 to 85
Transport temperature (°C)	-40 to 85
IP rating	IP65

SENCITY® Omni-S 3x3 WiFi MIMO Antenna 1399.17.0208

2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
Lead-free soldered	yes
WEEE 2012/19/EU	special marking needed
REACH 1907/2006/EC	compliant

Vibration and mechanical shock: ETSI EN 300-19-2-3 T3.3

Flammability rating antenna radome: UL 94 V0 / RF pigtail cable: UL 1581 § 1080 (VW-1)

UV protection antenna: UL746C f1 / RF pigtail cable: ISO 4892-2A

Material Data

Radome colour	RAL 9010 (white)
Radome material	PC (Polycarbonate)
Back plate/base plate material	Aluminium

Related Products

9091.99.0240 Ceiling Bracket_Mimo Omni

Related Documents

Mounting instruction	DOC-0000325773
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00147451
3D-model	DOC-0000322462

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

1399.17.0208

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9