

3M™ Copper-Coated Polyester Cloth Tape X-7001 Double-Coated with Conductive Adhesive

Data Sheet

April 2013

Product Description

3M™ Copper-Coated Polyester Cloth Tape X-7001 consists of a flexible copper-plated polyester fabric backing that is coated on both sides with a unique electrically conductive pressure-sensitive acrylic adhesive.

- Copper-plated polyester woven fabric backing
- Conductive acrylic adhesive on both sides

Agency Approvals & Self Certifications

RoHS
2011/65/EU

"RoHS 2011/65/EU" means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

Applications

The X-7001 tape is typically used to bond two surfaces together, both electrically and physically. An example would be adhering a conductive gasket to another conductive gasket to a conductive surface as part of the EMI shielding solution for an electronic enclosure. The unique metallized fabric backing offers the additional benefits of excellent flexibility and conformability. The fabric backing also minimizes the possibility of finger lacerations.

Typical Properties

Properties	Typical Value
Total thickness (backing plus adhesive) ¹	5.0 mil (0,13 mm)
Adhesion to steel ¹	58 oz/in (6,4 N/10 mm)
Electrical resistance through adhesive ²	0.015 Ω (over a 25 x 25 mm area)

* Foot notes: 1. ASTM-D-1000 Test method

2. S/3M Test method 1

3M™ Copper-Coated Polyester Cloth Tape X-7001 Double-Coated with Conductive Adhesive

Conductivity Since X-7001 tape double-sided metallized fabric conductive tape would typically be used as an electrical path between two surfaces, its most important feature is its conductivity. Conductive particles in the acrylic adhesive provide a multitude of electrical paths between the application substrate and the surface of the aluminum foil on each side. The resistance of the conductive path through the adhesive (measured over a 25 x 25 mm area) typically measures 15-20 milliohms

Specifications 3M Copper-Coated Polyester Cloth Tape X-7001 consists of a flexible copper-plated polyester fabric backing that is coated on both sides with a unique electrically conductive pressure-sensitive acrylic adhesive.

The tape shall be coated on one side with pressure-sensitive adhesive, which shall not require heat, moisture or other preparation prior to or subsequent to application. The adhesive coating shall be smooth and uniform and be free of lumps and bare spots. There shall be no separator between adjacent layers of the roll. The tape shall perform at a temperature of -40F° (-40°C) to 266°F (130°C) without substantial loss of tensile or electrical properties.

Shelf-Life This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

Availability The X-7001 tape is available in standard and custom widths and lengths. Standard length is 10 m.

Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1.800.676.8381.

Important Notice All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability This product will be free from defects in material and manufacture at the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

3M is a trademark of 3M Company.



Electrical Markets Division

6801 River Place Blvd.
Austin, TX 78726-9000
800.245.3573
FAX: 800.245.0329
www.3M.com/electrical

Please recycle
© 3M 2013 All rights reserved
78-8126-6595-4 Rev B

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9