


Ceramic Disc Capacitors (Straight Leads) Gap-Kap 1 kV to 3 kV



Simplified Outline

FEATURES

- High reliability
- Straight leads
- Lead (Pb)-free available

APPLICATIONS

- Monitors
- Color TV

DESIGN

The capacitors consist of a ceramic disc both sides of which are silver-plated. Connection leads are made of tinned copper having a diameter of 0.8 mm.

The capacitors are supplied with straight leads and lead spacings from 5.0 mm to 10.0 mm. Encapsulation is phenolic resin coated, flammable resistant in accordance with "UL94V-0".

INTRODUCTION

BCcomponents Gap-Kap capacitors provide a safe reliable discharge path for stray transient overvoltages and static voltage build-up. Combination of capacitor-spark-gap construction allows the circuit designer to specify lower voltage components and consequently lower cost, with assurance that overvoltage conditions will be prevented.

The Gap-Kap capacitor is ideally suited for many industrial commercial equipment applications. A typical application in color TV monitors utilizes a minimum capacitance Gap-Kap which is inserted between the grid lead and chassis ground. This protects the components of control circuitry by providing a low impedance path to ground for transient voltages of 1500 volts and above.

CAPACITANCE RANGE:

At 1 kHz, 1 ± 0.2 V (RMS); 0.75 to 22 000 pF

RATED DC VOLTAGE:

1 kV; 1.5 kV; 3 kV

INSULATION RESISTANCE AT 500 V (DC):

$\geq 10\,000\text{ M}\Omega$ min.

TOLERANCE ON CAPACITANCE:

$\pm 10\%$; $\pm 20\%$

DISSIPATION FACTOR:

At 1 kHz, 1 ± 0.2 V (RMS); 2.5 % max



RoHS
COMPLIANT

TEMPERATURE COEFFICIENTS:

EIA code Z5P or Z5U

SECTIONAL SPECIFICATIONS:

Class 2 IEC 60 384-9,

EIA 198

OPERATING TEMPERATURE RANGE:

- 30 to + 85 °C

MARKING

Marking indicates capacitance value and tolerance in accordance with "EIA 198" and voltage marks.

The capacitors meet the essential requirements of IEC 60 384-9 and EIA 198. Unless stated otherwise all electrical values apply at an ambient temperature of 25 ± 3 °C, at normal atmospheric conditions.

ORDERING INFORMATION

C (pF)	TOL. (%)	VOLTAGE		D _{max} (mm)	T _{max} (mm)	LEAD SPACING S (mm)	CLEAR TEXT CODE 16 th DIGIT: R = RoHS COMPLIANT
		WORKING (kV _{DC})	ARC (kV _{DC})				
0.75	max	1.0	1.0 - 2.0	11.0	5.0	5.0	S758X43000183L5.
						6.4	S758X43000183L6.
1000	± 20	1.5	2.0 - 3.0	11.0	4.5	5.0	S102M43Z5P283L5.
						6.4	S102M43Z5P283L6.
4700	± 20	3.0	4.0 - 6.0	24.5	6.0	10.0	S472M96Z5P483L0.
10 000	± 20	1.5	2.0 - 3.0	17.5	5.0	10.0	S103M69Z5U283L0.
22 000	± 20	1.5	2.0 - 3.0	24.5	4.5	10.0	S223M96Z5U283L0.

PACKAGING

PACKAGING TYPE	SIZE CODE	LEAD SPACE (mm)	VOLTAGE (VDC)	SPQ	BOX DIMENSIONS L × W × H (mm)
Bulk (long lead L ≥ 25.4 mm)	20 to 47	all	all	1000	245 x 120 x 65
				1000	
	1000				
	500				
	250				
	53 to 75				
	84 to 96				

Note

The capacitors are supplied in bulk packaging (cardboard boxes).



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9