

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0736442110

Status:


Active

Overview:

[hdm](#)

Description:

2.00mm (.079") Pitch HDM® Board-to-Board Backplane Header, Vertical, SMC, Press-Fit, Guide Post Location B, Polarizing Key Position F, 72 Circuits



Documents:

[Drawing \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR19980
UL	E29179

General

Product Family	Backplane Connectors
Series	73644
Application	Backplane
Comments	Standard Press-Fit, Tin/Lead (SnPb)
Component Type	PCB Header
Overview	hdm
Product Name	HDM®
Style	N/A

Physical

Circuits (Loaded)	72
Circuits (maximum)	72
Color - Resin	Black, Natural
Durability (mating cycles max)	250
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	Yes
Keying to Mating Part	Yes
Material - Metal	Phosphor Bronze, Stainless Steel
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Columns	12
Number of Pairs	Open Pin Field
Number of Rows	6
Orientation	Vertical
PC Tail Length (in)	0.138 In
PC Tail Length (mm)	3.50 mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness Recommended (in)	0.098 In
PCB Thickness Recommended (mm)	2.50 mm
Packaging Type	Tube
Pitch - Mating Interface (in)	0.079 In
Pitch - Mating Interface (mm)	2.00 mm
Pitch - Term. Interface (in)	0.079 In
Pitch - Term. Interface (mm)	2.00 mm
Plating min: Mating (µin)	30
Plating min: Mating (µm)	0.75
Plating min: Termination (µin)	15
Plating min: Termination (µm)	0.375
Polarized to PCB	No

EU RoHS

Not RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[73644Series](#)

Mates With
73632 HDM PLUS® Board-to-Board Daughtercard Receptacle. 73780 HDM® Board-to-Board Daughtercard Receptacle

Application Tooling | [FAQ](#)
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global	
Description	Product #
Flat Rock Tooling for	0622013700
Pneumatic Press	
HDM® Backplane	0621001400
Insertion Signal	
Contact Tool	
Extraction Tool	0621001000

Stackable	No
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-55°C to +105°C
Termination Interface: Style	Through Hole - Compliant Pin

Electrical

Current - Maximum per Contact	1A
Data Rate	1.0 Gbps
Real Signals (per 25mm)	75
Shielded	No
Voltage - Maximum	250V AC

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-70873-0818
Sales Drawing	SDA-73644-****



HDM and High Density Metric are trademarks of Amphenol Corporation

This document was generated on 05/14/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

NOTES:

1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0, COLOR: BLACK, TERMINAL - PHOSPHOR BRONZE.
2. FINISHES: SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MINIMUM THICKNESS; NICKEL (Ni) AND GOLD FLASH OVERALL SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MIN. THICKNESS; SELECTIVE TIN/LEAD (Sb/Pb) IN TAIL AREA; NICKEL (Ni) OVERALL.
3. THIS PART CONFORMS TO MOLEX PRODUCT SPECIFICATION PS-73670-9999.
4. FOR MIXED CONTACT MATING LENGTHS, CONSULT FACTORY FOR AVAILABILITY.
5. DIMENSIONS ARE IN MILLIMETERS.
6. FOR SPECIFIC MATERIAL NUMBERS, REFER TO SHEET 2.
7. PACKAGE PER PK-70873-0818.
8. PARTS MARKED WITH PART NUMBER AND DATE CODE, ON EITHER SIDE, APPROXIMATELY WHERE SHOWN.



2	D
1	J
MFG. SH.	REV.

REVISIONS: 2 = 0, 1 = 0, REVISE ONLY ON CAD SYSTEM

TITLE		SALES ASSY, HDM BACKPLANE MODULE, POLAR/GUIDE OPTION	
MOLEX INCORPORATED LISLE, ILL. 60532		SHEET NO. 1 OF 2	DATE 96/12/18
PART NO. SEE CHART		SDA-73644-****	
FILE NAME S73644X1 DGN		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
DIV. DA		SIZE B	

DIMENSIONS SHOWN (METRIC) INCH	
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°	
3 PLACE	± N/A ---
2 PLACE	± N/A ± 0.05
1 PLACE	--- ± 0.10
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	
DRWG. BY JRR	CHK'D. BY SMR
APP'D. BY CAB	SCALE 2 : 1

REVISED ECR UDT2000-0348 BINGHAM 99/10/12		I
REVISED ECR UDT1999-0662 BINGHAM 99/05/18		H
REVISED ECR UDT1999-2260 THOMAS 03/04/25		J
REVISED ECR UDT1999-0476 BINGHAM 98/12/21		G
LTR. REVISIONS		LTR. REVISIONS

	10	9	8	7	6	5	4	3	2	1	73644																																																		
	MATERIAL NUMBER	NUMBER OF SIGNAL CONTACTS	PLATING	DIM "A"	DIM "B"	DIM "M"																																																							
F	73644-00**	72	SELECTIVE GOLD/GOLD FLASH	31.60	22.00	5.00																																																							
	73644-01**	72	SELECTIVE GOLD/GOLD FLASH	31.60	22.00	5.50																																																							
	73644-02**	72	SELECTIVE GOLD/GOLD FLASH	31.60	22.00	6.00																																																							
	73644-10**	144	SELECTIVE GOLD/GOLD FLASH	55.60	46.00	5.00																																																							
	73644-11**	144	SELECTIVE GOLD/GOLD FLASH	55.60	46.00	5.50																																																							
E	73644-12**	144	SELECTIVE GOLD/GOLD FLASH	55.60	46.00	6.00																																																							
	73644-20**	72	SELECTIVE GOLD/SELECTIVE TIN-LEAD	31.60	22.00	5.00																																																							
	73644-21**	72	SELECTIVE GOLD/SELECTIVE TIN-LEAD	31.60	22.00	5.50																																																							
	73644-22**	72	SELECTIVE GOLD/SELECTIVE TIN-LEAD	31.60	22.00	6.00																																																							
	73644-30**	144	SELECTIVE GOLD/SELECTIVE TIN-LEAD	55.60	46.00	5.00																																																							
D	73644-31**	144	SELECTIVE GOLD/SELECTIVE TIN-LEAD	55.60	46.00	5.50																																																							
	73644-32**	144	SELECTIVE GOLD/SELECTIVE TIN-LEAD	55.60	46.00	6.00																																																							
							MATERIAL NUMBER ASSIGNMENT 73644- * * * * 0 = 72-CIRCUIT, GOLD/GOLD FLASH 1 = 144-CIRCUIT, GOLD/GOLD FLASH 2 = 72-CIRCUIT, GOLD/TIN-LEAD 3 = 144-CIRCUIT, GOLD/TIN-LEAD 0 = 5.00 MATING LENGTH 1 = 5.50 MATING LENGTH 2 = 6.00 MATING LENGTH <table><thead><tr><th>NUMBER</th><th>GUIDE POST LOCATION</th><th>POLAR KEY POSITION</th></tr></thead><tbody><tr><td>00</td><td>B</td><td rowspan="2">A</td></tr><tr><td>01</td><td>A</td></tr><tr><td>02</td><td>B</td><td rowspan="2">B</td></tr><tr><td>03</td><td>A</td></tr><tr><td>04</td><td>B</td><td rowspan="2">C</td></tr><tr><td>05</td><td>A</td></tr><tr><td>06</td><td>B</td><td rowspan="2">D</td></tr><tr><td>07</td><td>A</td></tr><tr><td>08</td><td>B</td><td rowspan="2">E</td></tr><tr><td>09</td><td>A</td></tr><tr><td>10</td><td>B</td><td rowspan="2">F</td></tr><tr><td>11</td><td>A</td></tr><tr><td>12</td><td>B</td><td rowspan="2">G</td></tr><tr><td>13</td><td>A</td></tr><tr><td>14</td><td>B</td><td rowspan="2">H</td></tr><tr><td>15</td><td>A</td></tr><tr><td>16</td><td>B</td><td rowspan="3">N/A</td></tr><tr><td>17</td><td>A</td></tr><tr><td>18</td><td>N/A</td></tr></tbody></table>					NUMBER	GUIDE POST LOCATION	POLAR KEY POSITION	00	B	A	01	A	02	B	B	03	A	04	B	C	05	A	06	B	D	07	A	08	B	E	09	A	10	B	F	11	A	12	B	G	13	A	14	B	H	15	A	16	B	N/A	17	A	18	N/A
NUMBER	GUIDE POST LOCATION	POLAR KEY POSITION																																																											
00	B	A																																																											
01	A																																																												
02	B	B																																																											
03	A																																																												
04	B	C																																																											
05	A																																																												
06	B	D																																																											
07	A																																																												
08	B	E																																																											
09	A																																																												
10	B	F																																																											
11	A																																																												
12	B	G																																																											
13	A																																																												
14	B	H																																																											
15	A																																																												
16	B	N/A																																																											
17	A																																																												
18	N/A																																																												
							LOCATION A LOCATION B REF. MATERIAL NUMBER 73644-0009 GUIDE PIN IS IN LOCATION A POLARIZING KEY IS IN LOCATION B, POSITION E REF. MATERIAL NUMBER 73644-0008 GUIDE PIN IS IN LOCATION B POLARIZING KEY IS IN LOCATION A, POSITION E																																																						
							DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2° <table><thead><tr><th></th><th>INCH</th><th>METRIC</th></tr></thead><tbody><tr><td>3 PLACE</td><td>± N/A</td><td>---</td></tr><tr><td>2 PLACE</td><td>± N/A</td><td>± N/A</td></tr><tr><td>1 PLACE</td><td>---</td><td>± N/A</td></tr></tbody></table> DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DRWG. BY: JRR CHK'D. BY: SMR APP'D. BY: CAB SCALE: ---:--- FILE NAME: S73644X2 DGN THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						INCH	METRIC	3 PLACE	± N/A	---	2 PLACE	± N/A	± N/A	1 PLACE	---	± N/A																																						
	INCH	METRIC																																																											
3 PLACE	± N/A	---																																																											
2 PLACE	± N/A	± N/A																																																											
1 PLACE	---	± N/A																																																											
							SALES ASSY, HDM BACKPLANE MODULE, POLAR/GUIDE OPTION MOLEX INCORPORATED LISLE, ILL. 60532 U.S.A. PART NO. SEE CHART DRWG. NO. SDA-73644-***** REVISIONS DATE 96 / 12 / 18																																																						
10	9	8	7	6	5	4	3	2	1																																																				

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9