

# SPECIFICATION CONTROL DRAWING

**44AM111X**

TITLE

ONE CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, 600 VOLT

Date

11-21-05

Revision

D

This specification sheet forms a part of the latest issue of Raychem Specification 44 and MIL-DTL-27500 as applicable.




TABLE I. CABLE CONSTRUCTION DETAILS

| PART NUMBER<br><u>1/</u> | CONDUCTOR<br>SIZE<br>(AWG) | SHIELD<br>SIZE<br>(AWG) | JACKET<br>THICKNESS<br>(in.) |         | OUTSIDE<br>DIAMETER<br>(in.) |         | MAXIMUM<br>WEIGHT<br>(lbs/1000 ft.) |
|--------------------------|----------------------------|-------------------------|------------------------------|---------|------------------------------|---------|-------------------------------------|
|                          |                            |                         | MINIMUM                      | MAXIMUM | NOMINAL                      | MAXIMUM |                                     |
| 44AM111X-26-*            | 26                         | 38                      | .005                         | .010    | .065                         | .071    | 4.9                                 |
| 44AM111X-24-*            | 24                         | 38                      | .005                         | .010    | .071                         | .077    | 6.1                                 |
| 44AM111X-22-*            | 22                         | 38                      | .005                         | .010    | .078                         | .084    | 7.6                                 |
| 44AM111X-20-*            | 20                         | 38                      | .005                         | .010    | .088                         | .094    | 9.9                                 |
| 44AM111X-18-*            | 18                         | 38                      | .005                         | .010    | .098                         | .104    | 13.0                                |
| 44AM111X-16-*            | 16                         | 38                      | .005                         | .010    | .105                         | .112    | 15.5                                |
| 44AM111X-14-*            | 14                         | 38                      | .005                         | .010    | .122                         | .129    | 21.8                                |
| 44AM111X-12-*            | 12                         | 38                      | .005                         | .010    | .141                         | .148    | 31.0                                |

TABLE II. CABLE PERFORMANCE DETAILS

| PART NUMBER<br><u>1/</u> | BEND TESTING                                 |              |                                              |              |
|--------------------------|----------------------------------------------|--------------|----------------------------------------------|--------------|
|                          | MANDREL DIAMETER<br>(inch) (± 3%)            |              | WEIGHT<br>(lb) (± 3%)                        |              |
|                          | IMMERSION AND<br>CROSSLINKED<br>VERIFICATION | COLD<br>BEND | IMMERSION AND<br>CROSSLINKED<br>VERIFICATION | COLD<br>BEND |
|                          |                                              |              |                                              |              |
| 44AM111X-26-*            | 3.00                                         | 3.00         | .125                                         | .750         |
| 44AM111X-24-*            | 3.00                                         | 3.00         | .188                                         | .750         |
| 44AM111X-22-*            | 3.00                                         | 3.00         | .188                                         | 1.50         |
| 44AM111X-20-*            | 3.00                                         | 3.00         | .188                                         | 1.50         |
| 44AM111X-18-*            | 3.00                                         | 3.00         | .250                                         | 1.50         |
| 44AM111X-16-*            | 3.00                                         | 3.00         | .250                                         | 1.50         |
| 44AM111X-14-*            | 3.00                                         | 3.00         | .500                                         | 4.50         |
| 44AM111X-12-*            | 6.00                                         | 6.00         | .500                                         | 4.50         |

NOTE: Nominal values are for information only.  
Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.  
Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

BLOCKING: 150 ± 3°C for 6 hours

CROSSLINKED VERIFICATION: 200 ± 5°C for 6 hours

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz, 15 seconds (minimum), 30 seconds (maximum)

FLAMMABILITY: 30 seconds (maximum); 3 in. (maximum); no flaming of facial tissue

IMMERSION: Diameter increase 5% (maximum); no cracking, no dielectric breakdown

JACKET COLOR: White preferred

JACKET CONCENTRICITY: 70% (minimum)

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 200% (minimum)

Tensile Strength, 4000 lbf/in<sup>2</sup> (minimum)

JACKET FLAWS:

Spark Test, 1.5 kV (rms)

Impulse Dielectric Test, 6.0 kV (peak)

LOW TEMPERATURE-COLD BEND: -55 ± 5°C for 4 hours

SHIELD COVERAGE: 85% (minimum)

VOLTAGE WITHSTAND TEST (POST ENVIRONMENTAL): 1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:

The "X" in the part numbers on page 1 shall be replaced by the applicable conductor material designators as follows:

- 1 tin coated copper
- 2 silver coated copper
- 3 nickel coated copper
- 4 silver coated high strength copper alloy (AWG's 26 - 16 only)
- 6 nickel coated high strength copper alloy (AWG's 26 - 20 only)

The "\*" in the part numbers on page 1 shall be replaced by color code designators with a dash separating the component wire color from the jacket color.

1/ Example: AWG 24, tin-coated copper, white component wire; white jacket:

44AM1111-24-9-9

1/ See footer section on page 1

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[44AM1111-22-9-9CS2275](#)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9