Power Supply Monitor with Reset

ADM709

FEATURES
Precision Supply Voltage Monitor
+5 V, +3.3 V, +3 V Power Supply Monitor
35 μA Quiescent Current
140 ms (min) Power-On Reset Pulse
Low Cost
8-Pin DIP/SO Packages
Upgrade for MAX709

APPLICATIONS
Microprocessor Systems
Computers
Controllers
Intelligent Instruments
Critical μP Monitoring
Automotive Systems
Critical μP Power Monitoring

FUNCTIONAL BLOCK DIAGRAM





Typical Operating Circuit

GENERAL DESCRIPTION

The ADM709 contains a power supply monitor which generates a system reset during power-up, power-down and brownout conditions. When V_{CC} falls below the reset threshold, $\overline{RESET}$ goes low and holds the μP in reset. On power-up the $\overline{RESET}$ output is held low for 140 ms after V_{CC} rises above the threshold. The $\overline{RESET}$ output remains operational with V_{CC} as low as 1 V.

Three supply-voltage threshold levels are available suitable for +5 V, +3.3 V and for +3 V supply monitoring. The actual reset voltage threshold is given below.

The ADM709 is available in 8-pin DIP and SOIC packages.

Table I. Reset Threshold

Suffix	Voltage (V)
L	4.65
M	4.40
T	3.08
S	2.93
R	2.63

ORDERING GUIDE

Model	Reset Threshold	Temperature Range	Package Option*
ADM709LAN	4.65 V	–40°C to +85°C	N-8
ADM709LAR	4.65 V	–40°C to +85°C	SO-8
ADM709MAN	4.40 V	–40°C to +85°C	N-8
ADM709MAR	4.40 V	–40°C to +85°C	SO-8
ADM709TAN	3.08 V	–40°C to +85°C	N-8
ADM709TAR	3.08 V	–40°C to +85°C	SO-8
ADM709SAN	2.93 V	–40°C to +85°C	N-8
ADM709SAR	2.93 V	–40°C to +85°C	SO-8
ADM709RAN	2.63 V	–40°C to +85°C	N-8
ADM709RAR	2.63 V	–40°C to +85°C	SO-8

*N = Plastic DIP; SO = SOIC.

REV. 0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

© Analog Devices, Inc., 1995

One Technology Way, P.O. Box 9106, Norwood. MA 02062-9106, U.S.A.
Tel: 617/329-4700 **Fax: 617/326-8703**

ADM709–SPECIFICATIONS (V_{CC} = Full Operating Range, $T_A = T_{MIN}$ to T_{MAX} unless otherwise noted)

Parameter	Min	Typ	Max	Units	Test Conditions/Comments
V_{CC} Operating Voltage Range	1.0		5.5	V	T_A = 0°C to +70°C
	1.2		5.5	V	T_A = –40°C to +85°C
Supply Current		35	85	µA	V_{CC} < 3.6 V, T_A = 0°C to +70°C
		35	110	µA	V_{CC} < 3.6 V, T_A = –40°C to +85°C
		65	150	µA	V_{CC} < 5.5 V, T_A = 0°C to +70°C
		65	200	µA	V_{CC} < 5.5 V, T_A = –40°C to +85°C
Reset Threshold	4.5	4.65	4.75	V	ADM709L
	4.25	4.40	4.50	V	ADM709M
	3.00	3.08	3.15	V	ADM709T
	2.85	2.93	3.00	V	ADM709S
	2.55	2.63	2.70	V	ADM709R
V_{CC} to $\overline{RESET}$ Delay		20		µs	V_{CC} = Reset Threshold max–min
$\overline{RESET}$ Active Time-Out Period	140	280	380	ms	V_{CC} = Reset Threshold max, V_{CC} Rising
$\overline{RESET}$ Output Voltage			0.3	V	ADM709R/S/T, I_{SINK} = 1.2 mA. V_{CC} = Reset Threshold min
			0.4	V	ADM709L/M, I_{SINK} = 3.2 mA. V_{CC} = Reset Threshold min
			0.3	V	I_{SINK} = 50 µA. $V_{CC} \geq$ 1.0 V
			0.4	V	I_{SINK} = 100 µA. $V_{CC} \geq$ 1.2 V
	0.8 × V_{CC}			V	ADM709R/S/T, I_{SOURCE} = 500 µA, $V_{CC} \geq$ Reset Threshold max
	V_{CC}–1.5 V			V	ADM709L/M, I_{SOURCE} = 800 µA, $V_{CC} \geq$ Reset Threshold max

Specifications subject to change without notice.

ABSOLUTE MAXIMUM RATINGS*

(T_A = +25°C unless otherwise noted)

V_{CC} ..... –0.3 V to +6 V
$\overline{RESET}$ Output ..... –0.3 V to V_{CC} + 0.3 V
V_{CC} Input Current ..... 20 mA
$\overline{RESET}$ Output Current ..... 20 mA
Power Dissipation, N-8 DIP ..... 727 mW
  θ_{JA} Thermal Impedance ..... 135°C/W
Power Dissipation, SO-8 SOIC ..... 470 mW
  θ_{JA} Thermal Impedance ..... 110°C/W
Operating Temperature Range
  Industrial (A Version) ..... –40°C to +85°C
Lead Temperature (Soldering, 10 secs) ..... +300°C
Vapor Phase (60 secs) ..... +215°C
Infrared (15 secs) ..... +220°C
Storage Temperature Range ..... –65°C to +150°C
ESD Rating ..... >5 kV

*Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those listed in the operational sections of this specification is not implied. Exposure to absolute maximum ratings for extended periods of time may affect device reliability.

PIN FUNCTION DESCRIPTION

Mnemonic	Pin No.	Function
NC	1, 4, 5, 6, 8	No Connect Pins.
V_{CC}	2	+5 V, +3.3 V, +3 V Power Supply Input.
$\overline{RESET}$	7	Logic Output. It remains low while V_{CC} is below the reset threshold voltage and for 280 ms (typ) after V_{CC} rises above the threshold.
GND	3	Ground, 0 V.

PIN CONFIGURATION



NC = NO CONNECT



Figure 1. Functional Block Diagram



Figure 2. Typical Operating Circuit

CIRCUIT INFORMATION

RESET Output

RESET is an active low output which provides a reset signal to the microprocessor whenever the V_{CC} supply voltage is below the reset threshold. An internal timer holds RESET low for 140 ms after the voltage on V_{CC} rises above the threshold. This is intended as a power-on reset signal for the processor. It allows time for the power supply and microprocessor to stabilize after power up. Similarly a power supply brownout will initiate a processor reset. On power-down, the RESET output remains low with V_{CC} as low as 1 V. This ensures that the microprocessor is held in a stable shutdown condition as the power supply drops.



Figure 3. Power Off/On RESET Timing



Figure 4. RESET Output vs. V_{CC}

RESET at Voltages < 1 V

The ADM709 RESET output is guaranteed to operate with supply voltages as low as 1 V. If it is desired that the RESET output remains low below 1 V, then a pull-down resistor should be connected between the RESET output and GND. A resistor of 100 kΩ is suitable. This is illustrated in Figure 5.



Figure 5. RESET Valid @ V_{CC} < 1 V

Glitch Immunity

The ADM709 is immune to short transient which may occur on the V_{CC} line. This is important so that spurious resets are not generated as a result of minor glitches on the power supply.

Additional glitch immunity may be obtained by connecting a capacitor (0.1 µF or greater) as close as possible to the V_{CC} pin on the device.

Microprocessors with Bidirectional I-O

Some microprocessors or microcontrollers such as the MC68HC11 have bidirectional reset lines. In order to avoid signal contention, a resistor of 4.7 kΩ should be connected between the ADM709 RESET output and the microcontroller RESET line. This arrangement is shown in Figure 6.



Figure 6. Interfacing to Microprocessors with Bidirectional RESET

OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).

8-Lead Plastic DIP
(N-8)



8-Lead SOIC
(SO-8)



C2022–18–4/95

PRINTED IN U.S.A.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9