


ESE24 Detector Switches

Type: **ESE24**

Bidirectional operation, midpoint auto-return Type




■ Features

- A lever-type detector switch with high reliability using sliding mechanical contacts
- Long over-travel (through-operation available)
- Used as an operation switch (an input device)

■ Recommended Applications

- Detection of media in portable electronic equipment (CD-ROM, DVD, Digital still cameras, etc.)
- Operating switches for other electronic equipment.

■ Explanation of Part Number



6th & 7th	Mounting Method & Style
SV	Vertical type for wave soldering
SH	Horizontal type for wave soldering
MV	Vertical type for reflow soldering
MH	Horizontal type for reflow soldering

■ Specifications

Rating	50 μ A 3 V DC to 10 mA 5 V DC (Resistive load)	
Contact Resistance	500 m Ω max. (Initial)	
Insulation Resistance	100 M Ω min. (at 100 V DC for 1 minute)	
Dielectric Withstanding Voltage	100 V AC (50 Hz or 60 Hz) for 1 minute	
Operating Force	350 mN max.	
Mounting Height	· ESE24SV Type 5.6 mm · ESE24SH Type 4.65 mm · ESE24MV Type 5.6 mm · ESE24MH Type 3.0 mm	
Poles and Throws	1-pole 2-throws (OFF at midpoint)	
Full Travel (Pushing distance)	· ESE24SV Type 6.1 mm (2.45 mm) · ESE24SH Type 2.6 mm (2.45 mm) · ESE24MV Type 6.1 mm (2.45 mm) · ESE24MH Type 1.4 mm (2.45 mm)	
Operating Life	50,000 cycles min.	
Temperature Range	-10 °C to +70 °C (Standard), -40 °C to +85 °C (Automotive)	
Heat Resistance	+80 °C for 96 hours	
Low Temperature Resistance	-25 °C for 96 hours	
Humidity Resistance	+40 °C 90 % to 95 % RH for 96 hours	
Minimum Quantity/Packing Unit	ESE24MH, MV, SV, SH	200 pcs. Polyethylene Bag (Bulk) ^{*1}
	ESE24MH□T	1,000 pcs. Embossed Taping (Reel Pack) ^{*2}
	ESE24MV□T	500 pcs. Embossed Taping (Reel Pack)
Quantity/Carton	ESE24MH, MV, SV, SH	10,000 pcs. Polyethylene Bag (Bulk)
	ESE24MH□T	6,000 pcs. Embossed Taping (Reel Pack)
	ESE24MV□T	3,000 pcs. Embossed Taping (Reel Pack)

*1 ESE24SH type: 160 pcs. (Polyethylene Bag), 8,000 pcs. (Reel Pack)

*2 ESE24SV, ESE24SH are excluded

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.
 Should a safety concern arise regarding this product, please be sure to contact us immediately.


■ Dimensions in mm (not to scale)

No. 1 ESE24SV3 Vertical type for wave soldering 1-pole 2-throws 7.05 to 7.55 (Pushing position) 4.45 (Rotative center) PWB mounting hole for reference (Pitch tolerance: ± 0.05) (PWB thickness=0.8) 6-$\phi 1.10^{+0.05}_0$ 2.50 2.50 2.90 7.5 4.3 2.7 29° 24' 68° 26' 5.6 0.2 6.1 (Full position) 8.05 (ON starting position) 8.55 1.0 2.5 2.5 1.0 2.9 3.8 0.3 1.4 2.7 3.0 1.0	No. 2 ESE24SH1 Horizontal type for wave soldering 1-pole 2-throws 8.4 7.25 2.5 2.5 1.6 2.55 2.75 1.0 2.50 2.50 7.16 2-$\phi 1.20^{+0.05}_0$ 3-$\phi 1.10^{+0.05}_0$ 3.55 to 4.05 (Pushing position) 0.95 (Rotative center) PWB mounting hole for reference (Pitch tolerance: ± 0.05) (PWB thickness=0.8) 7.5 4.3 2.7 29° 24' 68° 10.2 2.6 (Full position) 4.55 (ON starting position) 5.05 3.5 4.65 3.65 1.0 1.0 3.0 1.65 3.0
No. 3 ESE24MV1 Vertical type for reflow soldering 1-pole 2-throws ESE24MV1T (Embossed Taping) 7.05 to 7.55 (Pushing position) 4.45 (Rotative center) PWB mounting hole for reference (Tolerance: ± 0.05) 2-$\phi 1.10^{+0.05}_0$ 5.50 3.60 5.80 2.50 2.50 6-1.40 1.0 2.5 2.5 1.0 5.5 7.5 4.3 2.7 29° 24' 68° 26' 5.6 6.1 (Full position) 8.05 (ON starting position) 8.55 1.0 4.0 5.4 3.0 1.0	No. 4 ESE24MH1 Horizontal type for reflow soldering 1-pole 2-throws ESE24MH1T (Embossed Taping) 0.25 7.25 0.25 2.00 7.50 2.00 1.60 7.25 2-$\phi 0.70$ (Hole) 1.60 4.50 2.20 2.50 2.50 3-1.40 1.5 7.5 1.5 4.3 2.7 29° 24' 68° 26' 0.2 0.9 1.2 1.6 3.85 4.7 1.5 1.4 (Full position) 3.35 (ON starting position) 1.0 2.5 2.5 1.0 3.0 0.5 2.0 1.0 0.6 0.1 C0.2 Positioning boss PWB mounting hole for reference (Tolerance: ± 0.05) 2.35 to 2.85 (Pushing position) 0.25 (Rotative center) Positioning boss

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.
Should a safety concern arise regarding this product, please be sure to contact us immediately.

Circuit Diagram

1-pole 2-throws (N . O)




Terminal No. Lever position	1	c	2
(F)		○	
(a)	○	○	
(b)		○	○

Packaging Specifications


Standard Reel Dimensions in mm (not to scale)

Taping Reel




Embossed Carrier Taping

ESE24MH□T



ESE24MV□T



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[ESE-24CMV1TEE](#) [ESE-24MH1T](#) [ESE-24MV1](#) [ESE-24SH1](#) [ESE-24SV3](#) [ESE-24CSV3](#) [ESE-24MV1T](#) [ESE-24CSH1](#) [ESE-24CSV6](#) [ESE-24SH6](#) [ESE-24MV6T](#) [ESE-24SV6](#) [ESE-24CMH6T](#) [ESE-24MH6T](#) [ESE-24CMH1T](#) [ESE-24CMV6T](#) [ESE-24CSH6](#) [ESE-24CMV1T](#) [ESE-24CMV9T](#) [ESE-24CMH9T](#)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9