CMLDM7002A
CMLDM7002AG*
CMLDM7002AJ

SURFACE MOUNT SILICON DUAL N-CHANNEL ENHANCEMENT-MODE MOSFETS

SOT-563 CASE

* Device is ***Halogen Free*** by design

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

These CENTRAL SEMICONDUCTOR devices are dual N-Channel enhancement-mode MOSFETs, manufactured by the N-Channel DMOS Process, designed for high speed pulsed amplifier and driver applications. The CMLDM7002A utilizes the USA pinout configuration, while the CMLDM7002AJ utilizes the Japanese pinout configuration. These devices offer low $r_{DS\ (ON)}$ and low $V_{DS(ON)}$.

MARKING CODES: **CMLDM7002A: L02**
CMLDM7002AG*: C2G
CMLDM7002AJ: 02J

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Drain-Source Voltage	V_{DS}	60	V
Drain-Gate Voltage	V_{DG}	60	V
Gate-Source Voltage	V_{GS}	40	V
Continuous Drain Current	I_D	280	mA
Continuous Source Current (Body Diode)	I_S	280	mA
Maximum Pulsed Drain Current	I_{DM}	1.5	A
Maximum Pulsed Source Current	I_{SM}	1.5	A
Power Dissipation (Note 1)	P_D	350	mW
Power Dissipation (Note 2)	P_D	300	mW
Power Dissipation (Note 3)	P_D	150	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	357	°C/W

ELECTRICAL CHARACTERISTICS PER TRANSISTOR: (T_A=25°C unless otherwise noted)

SYMBOL	**TEST CONDITIONS**	**MIN**	**MAX**	**UNITS**
I_{GSSF}, I_{GSSR}	V_{GS}=20V, V_{DS}=0		100	nA
I_{DSS}	V_{DS}=60V, V_{GS}=0		1.0	μA
I_{DSS}	V_{DS}=60V, V_{GS}=0, T_J=125°C		500	μA
$I_{D(ON)}$	V_{GS}=10V, V_{DS}=10V	500		mA
BV_{DSS}	V_{GS}=0, I_D=10μA	60		V
$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250μA	1.0	2.5	V
$V_{DS(ON)}$	V_{GS}=10V, I_D=500mA		1.0	V
$V_{DS(ON)}$	V_{GS}=5.0V, I_D=50mA		0.15	V
V_{SD}	V_{GS}=0, I_S=400mA		1.2	V
$r_{DS(ON)}$	V_{GS}=10V, I_D=500mA		2.0	Ω
$r_{DS(ON)}$	V_{GS}=10V, I_D=500mA, T_J=125°C		3.5	Ω
$r_{DS(ON)}$	V_{GS}=5.0V, I_D=50mA		3.0	Ω
$r_{DS(ON)}$	V_{GS}=5.0V, I_D=50mA, T_J=125°C		5.0	Ω
g_{FS}	V_{DS}=10V, I_D=200mA	80		mS

Notes: (1) Ceramic or aluminum core PC Board with copper mounting pad area of 4.0mm^2
(2) FR-4 Epoxy PC Board with copper mounting pad area of 4.0mm^2
(3) FR-4 Epoxy PC Board with copper mounting pad area of 1.4mm^2

CMLDM7002A
CMLDM7002AG*
CMLDM7002AJ

SURFACE MOUNT SILICON DUAL N-CHANNEL ENHANCEMENT-MODE MOSFETS

ELECTRICAL CHARACTERISTICS PER TRANSISTOR - Continued: (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	TYP	MAX	UNITS
C_{rss}	V_{DS}=25V, V_{GS}=0, f=1.0MHz		5.0	pF
C_{iss}	V_{DS}=25V, V_{GS}=0, f=1.0MHz		50	pF
C_{oss}	V_{DS}=25V, V_{GS}=0, f=1.0MHz		25	pF
$Q_{g(tot)}$	V_{DS}=30V, V_{GS}=4.5V, I_D=100mA	0.592		nC
Q_{gs}	V_{DS}=30V, V_{GS}=4.5V, I_D=100mA	0.196		nC
Q_{gd}	V_{DS}=30V, V_{GS}=4.5V, I_D=100mA	0.148		nC
t_{on}, t_{off}	V_{DD}=30V, V_{GS}=10V, I_D=200mA			
	R_G=25Ω, R_L=150Ω		20	ns

SOT-563 CASE - MECHANICAL OUTLINE



DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.0027	0.007	0.07	0.18
B	0.008		0.20	
C	0.017	0.024	0.45	0.60
D	0.059	0.067	1.50	1.70
E	0.020		0.50	
F	0.059	0.067	1.50	1.70
G	0.043	0.051	1.10	1.30
H	0.006	0.012	0.15	0.30

SOT-563 (REV: R2)

PIN CONFIGURATIONS

CMLDM7002A (USA Pinout)
CMLDM7002AG*



LEAD CODE:
1) Gate Q1
2) Source Q1
3) Drain Q2
4) Gate Q2
5) Source Q2
6) Drain Q1

MARKING CODES:
CMLDM7002A: L02
CMLDM7002AG*: C2G

CMLDM7002AJ (Japanese Pinout)



LEAD CODE:
1) Source Q1
2) Gate Q1
3) Drain Q2
4) Source Q2
5) Gate Q2
6) Drain Q1

MARKING CODE: 02J

* Device is ***Halogen Free*** by design

R8 (8-June 2015)

CMLDM7002A
CMLDM7002AG*
CMLDM7002AJ

SURFACE MOUNT SILICON DUAL N-CHANNEL ENHANCEMENT-MODE MOSFETS

TYPICAL ELECTRICAL CHARACTERISTICS

Output Characteristics



Transfer Characteristics



Capacitance



Drain Source On Resistance



Power Derating



R8 (8-June 2015)

CMLDM7002A
CMLDM7002AG*
CMLDM7002AJ

SURFACE MOUNT SILICON DUAL N-CHANNEL ENHANCEMENT-MODE MOSFETS

SERVICES

- Bonded Inventory
- Custom Electrical Screening
- Custom Electrical Characteristic Curves
- SPICE Models
- Custom Packaging
- Package Base Options
- Custom Device Development / Multi Discrete Modules (MDM™)
- Bare Die Available for Hybrid Applications

LIMITATIONS AND DAMAGES DISCLAIMER: In no event shall Central be liable for any collateral, indirect, punitive, incidental, consequential, or exemplary damages in connection with or arising out of a purchase order or contract or the use of products provided hereunder, regardless of whether Central has been advised of the possibility of such damages. Excluded damages shall include, but not be restricted to: cost of removal or reinstallation, rework, ancillary costs to the procurement of substitute products, loss of profits, loss of savings, loss of use, loss of data, or business interruption. No claim, suit, or action shall be brought against Central more than two (2) years after the related cause of action has occurred.

In no event shall Central's aggregate liability from any warranty, indemnity, or other obligation arising out of or in connection with a purchase order or contract, or any use of any Central product provided hereunder, exceed the total amount paid to Central for the specific products sold under a purchase order or contract with respect to which losses or damages are claimed. The existence of more than one (1) claim against the specific products sold to Buyer under a purchase order or contract shall not enlarge or extend this limit.

Buyer understands and agrees that the foregoing liability limitations are essential elements of a purchase order or contract and that in the absence of such limitations, the material and economic terms of the purchase order or contract would be substantially different.

R8 (8-June 2015)

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9