

Thermofit[®] Molded Parts
Specification Control Drawing

NOTES

1. All dimensions are in $\frac{\text{inches}}{[\text{millimeters}]}$; $\frac{\text{lbs}}{[\text{gms}]}$
2. Dimensions appearing in table are as follows:
- a - As Supplied
 - b - After Unrestricted Recovery
3. Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
4. Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.
5. Weight shown in table of dimensions is based on polyolefin part.





TABLE OF DIMENSIONS																	
PART NUMBER	H		J			P	R	S	T	U	JO	PP	RR	HW	JW	Weight	
	Min	Max	Min -3,-4, -25	Min -5,-6,-8, -12,-100	Max												
	a	b	a	a	b	±10%	Ref	Ref	Ref	Ref	±10%	±10%	±10%	±20%	±20%	Nom	
222D211	.88	.45	.88	.55	.25	4.14	.73	.47	.12	.04	3.45	.27	.49	.06	.045	.01	
	[22,4]	[11,4]	[22,4]	[14,0]	[6,4]	[105,2]	[18,5]	[11,9]	[3,05]	[1,02]	[87,6]	[6,9]	[12,4]	[1,52]	[1,14]	[5,0]	
222D221	1.01	.59	1.01	.63	.29	4.88	.78	.60	.12	.04	3.90	.33	.59	.06	.045	.02	
	[25,7]	[15,0]	[25,7]	[16,0]	[7,4]	[124,0]	[19,8]	[15,2]	[3,05]	[1,02]	[99,1]	[8,4]	[15,0]	[1,52]	[1,14]	[9,0]	
222D232	1.16	.74	1.16	.72	.33	5.76	.82	.75	.12	.04	4.50	.41	.61	.07	.045	.02	
	[29,5]	[18,8]	[29,5]	[18,3]	[8,4]	[146,3]	[20,8]	[19,1]	[3,05]	[1,02]	[114,3]	[10,4]	[15,5]	[1,78]	[1,14]	[9,0]	
222D242	1.34	.90	1.34	.84	.38	6.78	.86	.90	.12	.04	5.22	.48	.62	.07	.045	.03	
	[34,0]	[22,9]	[34,0]	[21,3]	[9,7]	[172,2]	[21,8]	[22,9]	[3,05]	[1,02]	[132,6]	[12,2]	[15,7]	[1,78]	[1,14]	[14,0]	
222D253	1.47	1.16	1.47	.91	.41	7.29	.96	1.15	.12	.065	5.66	.61	.70	.08	.045	.03	
	[37,3]	[29,5]	[37,3]	[23,1]	[10,4]	[185,2]	[24,4]	[29,2]	[3,05]	[1,65]	[143,8]	[15,5]	[17,8]	[2,03]	[1,14]	[14,0]	
222D263	1.72	1.34	1.72	1.07	.48	8.41	1.08	1.32	.12	.065	6.66	.72	.78	.08	.045	.05	
	[43,7]	[34,0]	[43,7]	[27,2]	[12,2]	[213,6]	[27,4]	[33,5]	[3,05]	[1,65]	[169,2]	[18,3]	[19,8]	[2,03]	[1,14]	[24,0]	
222D274	1.97	1.62	1.97	1.24	.56	8.84	1.16	1.59	.12	.065	6.82	.83	.82	.09	.055	.10	
	[50,0]	[41,1]	[50,0]	[31,5]	[14,2]	[224,5]	[29,5]	[40,4]	[3,05]	[1,65]	[173,2]	[21,1]	[20,8]	[2,29]	[1,40]	[46,0]	
222D285	2.47	1.85	2.47	1.54	.69	8.95	1.31	1.81	.12	.08	6.62	.95	.92	.10	.055	.10	
	[62,7]	[47,0]	[62,7]	[39,1]	[17,5]	[227,3]	[33,3]	[46,0]	[3,05]	[2,03]	[168,1]	[24,1]	[23,4]	[2,54]	[1,40]	[46,0]	
222D296	2.73	2.35	2.73	1.70	.77	9.19	1.38	2.28	.12	.08	6.19	1.18	.93	.10	.055	.10	
	[69,3]	[59,7]	[69,3]	[43,2]	[19,6]	[233,4]	[35,1]	[57,9]	[3,05]	[2,03]	[157,2]	[30,0]	[23,6]	[2,54]	[1,40]	[46,0]	
222D299	3.22	2.64	3.22	2.01	.90	9.33	1.75	2.55	.12	.08	5.95	1.31	1.23	.10	.055	.11	
	[81,8]	[67,1]	[81,8]	[51,1]	[22,9]	[237,0]	[44,5]	[64,8]	[3,05]	[2,03]	[151,1]	[33,3]	[31,2]	[2,54]	[1,40]	[48,0]	

STE **Raychem**
TE Connectivity
TE CONNECTIVITY
300 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025
(415) 361-6055

IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED.
CHECK FOR THE LATEST REVISION.

Revision : R
Date : 20APR11

Part Number : 222D211 thru 299
Description : Boot, 90°, With Lip

Thermofit[®] Molded Parts
Specification Control Drawing

Part Number : 222D211 thru 299
Description : Boot, 90°, With Lip

COMPATABILITY CHART					
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION
-3	Polyolefin, Semi-rigid	RT-301	/42;/86;/87;/180	S-1017;S-1048;S-1052;S-1030	Adhesive
-4	Polyolefin, Flexible	RT-1304	/42;/86;/87;/180	S-1017;S-1048;S-1052;S-1030	Adhesive
-5	Elastomer, Flexible	RT-501	N/A		
-6	Silicone	RT-602	N/A		
-8	Polyolefin, Space	RT-1308	N/A		
-12	*VITON, Flexible	RT-1312	N/A		
-25	Elastomer, Fluid Resistant	RT-1325	/42;/86	S-1017;S-1048	Adhesive
-100	Polyolefin, Semi-flexible ZEROHAL™	RT-1323	/184	S-1030	Adhesive

*VITON is a Registered Trademark of Dupont

ORDERING INFORMATION

222D2XX -X -XX /XXX

Base part number _____

Material dash number _____
(See Compatability Chart)

Modification number _____
(If necessary, see front of scd binder
for a complete list)

Adhesive slash number _____
(If necessary, see Compatability Chart)

THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR
NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

STE **Raychem**
TE Connectivity
TE CONNECTIVITY
300 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025
(415) 361-6055

Revision : R
Date : 20APR11

Part Number : 222D211 thru 299
Description : Boot, 90°, With Lip

CAD FILE MP92422

IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED.
CHECK FOR THE LATEST REVISION.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9