

SENCITY® Ultra 1399.17.0120

Description

Indoor DAS omni-directional antenna for In-Building Coverage
Ultra broad band, multi band covering AMPS, GSM, PCS, CDMA, UMTS, WiFi, WLAN 2.4 and 5.6 GHz, LTE, 4.9 GHz Homeland Security, Tetra, Tetrapol, DVB-T, DVB-H
High gain



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	380 - 560	560 - 960	1710 - 5500	5500 - 5875
VSWR	2	2	1.5	1.5
Impedance (Ohm)	50	50	50	50
Gain (dBi)	3.5	5	8	10
Composite power max (W)	800	500	300	300
Ambient temperature (°C)	25	25	25	25

Ports

	Port 1
Connector	N, jack (female)
Polarization	vertical

General Data

IMD level -150 dBc at carrier power 2x 43dBm

PIM 2x43dBm <-150dBc (@1800MHz)

Requires a ground plane of min. 620 x 620 mm (included in antenna shipment) for 380 MHz to 690 MHz operation (please also refer to Mounting Instruction DOC-0000331648)

VSWR tested with ground plane and max. ceiling tile thickness of 15mm across 380 MHz to 5875 MHz

Mechanical Data

Dimensions (mm) 153.6 x 78.6 x 255 (Height x Width x Depth)
Weight (kg) 0.8

Environmental Data

Environmental conditions indoor
Operation temperature (°C) 0 to 55
Storage temperature (°C) -40 to 80
Transport temperature (°C) -40 to 80
Flammability rating UL 94-HB
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant
Lead-free soldered yes
WEEE 2012/19/EU special marking needed
REACH 1907/2006/EC compliant

Material Data

Radome colour RAL 9010 (white)
Radome material ASA (acrylic ester-styrene-acrylonitrile)
Back plate/base plate colour RAL 9010 (white)

SENCITY® Ultra 1399.17.0120

Back plate/base plate material

Aluminium

Related Products

Mounting screws for false ceiling installation included 620mm x 630mm aluminium foil included in antenna shipment (see also Mounting Instruction DOC-0000331648)

Related Documents

Mounting instruction

DOC-0000331648

Painting instruction

DOC-0000256180

Security instruction

DOC-0000278984

Outline drawing

DOU-00143233

Additional Information

Radiator grounded for remote connectivity surveillance

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

1399.17.0120

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9