

SENCITY® Spot-S WiFi Antenna 1351.30.0001

Description

Small directional, planar, linear vertical polarized WiFi antenna with 13.5 dBi gain
 4.9 up to 5.3 GHz for public safety wireless-networks
 WLAN/WiFi IEEE 802.11 a/h for Japan, Israel
 Rugged design, meets EN 50155 railway and EN 60068 industrial standards
 Fire retardant acc. to EN 45545-2 and NFPA130
 For outdoor and indoor applications
 Ingress protection IP 66 and IP 67

Wall mounting material included



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2
Frequency (MHz)	4900 - 4940	4940 - 5350
VSWR	1.5	1.5
Impedance (Ohm)	50	50
Gain (dBi)	13	13.5
3dB beamwidth (h) (°)	40	40
3dB beamwidth (v) (°)	35	35
Composite power max (W)	30	30
Ambient temperature (°C)	25	25
Front to back ratio (dB)	20	20
Sidelobes (h)	15	
Vertical electrical tilt (°)	0	0

Ports

	Port 1
Connector	QN, jack (female)
Polarization	vertical

General Data

Mechanical Data

Dimensions (mm)	101 x 81 x 36 (Height x Width x Depth)
Weight (kg)	0.11
Windload	frontal: 15 N at 160 km/h , Wind speed survival: 220 km/h
Included mounting material	Wall mounting material

Environmental Data

Environmental conditions	indoor/outdoor
Operation temperature (°C)	-40 to 85
Storage temperature (°C)	-40 to 85
Transport temperature (°C)	-40 to 85
RoHS 2011/65/EU	compliant
Lead-free soldered	yes
REACH 2006/1907/EC	compliant

FLAMMABILITY: EN 45545-2 (2013) HL3 and NFPA130 (2013), also BS 6853 and DIN 5510-2

ENVIRONMENT: Meets EN 50155 (2016) and EN 60068 related tests

IP RATING: IP 66 / IP 67 (IEC 60529)

SOLAR RADIATION: EN 50125-3:2004 §4.9, 1120 W/m² for 20h

SENCITY® Spot-S WiFi Antenna 1351.30.0001

AIR PRESSURE: EN 50125-3:2004 §4.2, Altitude Class A1 (up to 1400m)
AIR PULE PRESSURE: EN 50125-3:2004 §4.2, 1 kPa/s
RAIN: EN 50125-3:2004 §4.6, delivery rate: 6 mm/min
VIBRATION / SHOCK: EN 50125-3:2004 §4.13, position profile: "outside the track"
POLLUTION: EN 50125-3:2004 §4.11, pollution levels: 4B1, 4S1
CORROSION: MIL-F-14072 E Type 1 "exposed"
MECHANICAL IMPACT (HAMMER IMPACT): EN 60068-2-75 (IEC 62262/2002-02 IK06)

Material Data

Radome colour	RAL 7044 (grey)
Radome material	PC (Polycarbonate)

Related Products

9091.99.0238 Outdoor Spot-S Antenna Down-Sidetilt Bracket
9091.99.0237 L-Bracket for SPOT-S antennas

Related Documents

Mounting instruction	DOC-0000287053
Painting instruction	DOC-0000278984
Security instruction	DOC-0000256179
Outline drawing	DOU-00146393
3D-model	DOC-0000816257

Additional Information

Following Declaration of Conformity for SENCITY Spot-S antennas are available on request:

- * Industrial standards EN 60068 / EN 60529 / IEC 61373: Ref. DOC-0000318049
- * Railway rolling stock, environmental standards EN 50155 and fire behaviour EN 45545-2k, NFPA130: Ref. DOC-0000380375

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

1351.30.0001

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9