



Safety Data Sheet according to Regulation (EC) No1907/2006

Page 1 of 10

SDS No. : 388221
V002.4

Loctite V5004 Part A It/Gr

Revision: 10.04.2014
printing date: 15.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite V5004 Part A It/Gr

Contains:

Benzyl 2-methylacrylate
Isobornyl methacrylate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Acrylic Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Limited
2 Bishop Square Business Park
AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933
Fax-no.: +44 1606 863762

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

Classification (DPD):

Xi - Irritant


R36/37/38 Irritating to eyes, respiratory system and skin.

Dangerous for the environment

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:		
Signal word:	Warning	
Hazard statement:	H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.	
Precautionary statement:	***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements***	
Precautionary statement: Prevention	P261 Avoid breathing vapours. P273 Avoid release to the environment.	
Precautionary statement: Response	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P337+P313 If eye irritation persists: Get medical advice/attention.	

Label elements (DPD):

Xi - Irritant



Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S23 Do not breathe vapour.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water and soap.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients**General chemical description:**

Part A of two part adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Benzyl 2-methylacrylate 2495-37-6	219-674-4	>= 50- < 60 %	Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315 Serious eye irritation 2 H319
Isobornyl methacrylate 7534-94-3	231-403-1	>= 10- < 20 %	Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315 Serious eye irritation 2 H319 Chronic hazards to the aquatic environment 2 H411
Trimethylenediamine 109-76-2	203-702-7	>= 0,1- < 0,5 %	Skin corrosion/irritation 1A H314 Acute toxicity 3 H311 Flammable liquids 3 H226 Acute toxicity 4 H302 Chronic hazards to the aquatic environment 3 H412

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Benzyl 2-methylacrylate 2495-37-6	219-674-4	>= 50 - < 60 %	Xi - Irritant; R36/37/38
Isobornyl methacrylate 7534-94-3	231-403-1	>= 10 - < 20 %	N - Dangerous for the environment; R51/53 Xi - Irritant; R36/37/38
Trimethylenediamine 109-76-2	203-702-7	>= 0,1 - < 0,5 %	R52/53 T - Toxic; R24 C - Corrosive; R35 Xn - Harmful; R22 R10

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder
Fine water spray

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.
Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures:

Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Store in a cool, well-ventilated place.

7.3. Specific end use(s)

Acrylic Adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Great Britain

Ingredient	ppm	mg/m ³	Type	Category	Remarks
PARAFFIN WAX, FUME 8002-74-2		2	Time Weighted Average (TWA):		EH40 WEL
PARAFFIN WAX, FUME 8002-74-2		6	Short Term Exposure Limit (STEL):		EH40 WEL

Biological Exposure Indices:

None

8.2. Exposure controls:**Respiratory protection:**

Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A

Hand protection:

Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; ≥ 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; ≥ 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid light blue
Odor	Acrylic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 93 °C (> 199.4 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure (50 °C (122 °F))	< 700 mbar
Density ()	0,9700 g/cm3
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

May cause respiratory irritation.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Benzyl 2-methylacrylate 2495-37-6	LD50	5.000 mg/kg	oral		rat	

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
---------------------------------	---------------	-------	-------------------------	------------------	---------	--------

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
---------------------------------	---------------	-------	-------------------------	------------------	---------	--------

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Harmful to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Benzyl 2-methylacrylate 2495-37-6	LC50	4,67 mg/l	Fish	48 h	Daphnia magna	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isobornyl methacrylate 7534-94-3	LC50	1,79 mg/l	Fish	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
Isobornyl methacrylate 7534-94-3	EC50	1,1 mg/l	Daphnia	48 h		OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl methacrylate 7534-94-3	EC50	2,66 mg/l	Algae	96 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Trimethylenediamine 109-76-2	EC50	49 mg/l	Daphnia	24 h	Daphnia magna	

12.2. Persistence and degradability**Persistence and Biodegradability:**

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Benzyl 2-methylacrylate 2495-37-6	readily biodegradable		74 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Isobornyl methacrylate 7534-94-3			26,8 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Trimethylenediamine 109-76-2		aerobic	38 - 39 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

Cured adhesives are immobile.

Bioaccumulative potential:

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Benzyl 2-methylacrylate 2495-37-6	2,53					
Isobornyl methacrylate 7534-94-3	5,09					OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Trimethylenediamine 109-76-2	-1,43					

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Product disposal:**

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.4. Packaging group

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 %
(1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.
R22 Harmful if swallowed.
R24 Toxic in contact with skin.
R35 Causes severe burns.
R36/37/38 Irritating to eyes, respiratory system and skin.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
H226 Flammable liquid and vapor.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.



Safety Data Sheet according to Regulation (EC) No1907/2006

Page 1 of 19

Loctite V5004 Part B It/Gr

SDS No. : 409150

V003.0

Revision: 02.10.2014

printing date: 15.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite V5004 Part B It/Gr

Contains:

Methyl methacrylate
Methacrylic acid
Tetrahydrofurfuryl methacrylate
2-Hydroxyethyl methacrylate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Limited
2 Bishop Square Business Park
AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933

Fax-no.: +44 1606 863762

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (CLP):**

Flammable liquids	Category 2
H225 Highly flammable liquid and vapor.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Toxic to reproduction	Category 1B
H360 May damage fertility or the unborn child.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

Classification (DPD):

F - Highly flammable
R11 Highly flammable.
Toxic for reproduction - category 1.
R60 May impair fertility.
R61 May cause harm to the unborn child.
Xi - Irritant
R41 Risk of serious damage to eyes.
R37/38 Irritating to respiratory system and skin.
Sensitizing
R43 May cause sensitisation by skin contact.
Dangerous for the environment
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements**Label elements (CLP):****Hazard pictogram:****Signal word:**

Danger

Hazard statement:

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H360 May damage fertility or the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Supplemental information

Restricted to professional users.

Precautionary statement:

For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements

**Precautionary statement:
Prevention**

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Label elements (DPD):

F - Highly flammable

T - Toxic



Risk phrases:

R11 Highly flammable.
R37/38 Irritating to respiratory system and skin.
R41 Risk of serious damage to eyes.
R43 May cause sensitisation by skin contact.
R60 May impair fertility.
R61 May cause harm to the unborn child.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S16 Keep away from sources of ignition - No smoking.
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37/39 Wear suitable gloves and eye/face protection.
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.
S46 If swallowed, seek medical advice immediately and show this container or label.

Restricted to professional users.

Contains:

Methyl methacrylate,
Methacrylic acid,
Tetrahydrofurfuryl methacrylate,
2-Hydroxyethyl methacrylate

2.3. Other hazards

Non corrosive to skin in accordance with the in vitro test method, B40 skin corrosion - Human skin model assay, equivalent to test method OECD 431 or based on analogy to similar products tested.

SECTION 3: Composition/information on ingredients

General chemical description:

Part B of a two part adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Methyl methacrylate 80-62-6	201-297-1 01-2119452498-28	20- 40 %	Flammable liquids 2 H225 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315 Skin sensitizer 1 H317
Phenoxyethyl methacrylate 10595-06-9	234-201-1	5- 15 %	Serious eye damage/eye irritation 2 H319 Skin corrosion/irritation 2 H315
Methacrylic acid 79-41-4	201-204-4 01-2119463884-26	> 5- < 10 %	Acute toxicity 4; Oral H302 Acute toxicity 3; Dermal H311 Acute toxicity 4; Inhalation H332 Skin corrosion/irritation 1A H314
Tetrahydrofurfuryl methacrylate 2455-24-5	219-529-5	1- 10 %	Skin irritation 2; Dermal H315 Serious eye irritation 2 H319 Specific target organ toxicity - single exposure 3; Inhalation H335 Toxic to reproduction 1B H360 Chronic hazards to the aquatic environment 3 H412
2-Hydroxyethyl methacrylate 868-77-9	212-782-2 01-2119490169-29	1- 10 %	Skin irritation 2 H315 Skin sensitizer 1 H317 Serious eye irritation 2 H319
Cumene hydroperoxide 80-15-9	201-254-7	0,1- < 0,9 %	Acute toxicity 4; Dermal H312 Specific target organ toxicity - repeated exposure 2 H373 Acute toxicity 4; Oral H302 Organic peroxides E H242 Acute toxicity 3; Inhalation H331 Skin corrosion 1B H314 Chronic hazards to the aquatic environment 2 H411
Butyl hydroxytoluene 128-37-0	204-881-4 01-2119480433-40 01-2119555270-46 01-2119565113-46	0,25- < 0,5 %	Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Methyl methacrylate 80-62-6	201-297-1 01-2119452498-28	20 - 40 %	Xi - Irritant; R37/38 R43 F - Highly flammable; R11
Phenoxyethyl methacrylate 10595-06-9	234-201-1	5 - 15 %	Xi - Irritant; R36/38
Methacrylic acid 79-41-4	201-204-4 01-2119463884-26	> 5 - < 10 %	C - Corrosive; R35 Xn - Harmful; R20/21/22
Tetrahydrofurfuryl methacrylate 2455-24-5	219-529-5	1 - 10 %	
2-Hydroxyethyl methacrylate 868-77-9	212-782-2 01-2119490169-29	1 - 10 %	Xi - Irritant; R36/38 R43
Cumene hydroperoxide 80-15-9	201-254-7	0,1 - < 0,9 %	T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 C - Corrosive; R34 O - Oxidizing; R7 N - Dangerous for the environment; R51/53
Butyl hydroxytoluene 128-37-0	204-881-4 01-2119480433-40 01-2119555270-46 01-2119565113-46	0,25 - < 0,5 %	N - Dangerous for the environment; R50/53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder
Fine water spray

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

In case of fire, keep containers cool with water spray.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.
Remove sources of ignition.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.
Keep away from sources of ignition - no smoking.

Hygiene measures:

Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.
Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Store in a cool, well-ventilated place.
Keep away from sources of ignition.

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

Ingredient	ppm	mg/m ³	Type	Category	Remarks
METHYL METHACRYLATE 80-62-6	100	416	Short Term Exposure Limit (STEL):		EH40 WEL
METHYL METHACRYLATE 80-62-6	50	208	Time Weighted Average (TWA):		EH40 WEL
METHACRYLIC ACID 79-41-4	40	143	Short Term Exposure Limit (STEL):		EH40 WEL
METHACRYLIC ACID 79-41-4	20	72	Time Weighted Average (TWA):		EH40 WEL
2,6-DI-TERT-BUTYL-P-CRESOL 128-37-0		10	Time Weighted Average (TWA):		EH40 WEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Methyl methacrylate 80-62-6	aqua (freshwater)					0,94 mg/L	
Methyl methacrylate 80-62-6	aqua (marine water)					0,094 mg/L	
Methyl methacrylate 80-62-6	aqua (intermittent releases)					0,94 mg/L	
Methyl methacrylate 80-62-6	STP					10 mg/L	
Methyl methacrylate 80-62-6	sediment (freshwater)				5,74 mg/kg		
Methyl methacrylate 80-62-6	soil				1,47 mg/kg		
Methacrylic acid 79-41-4	aqua (freshwater)					0,82 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	aqua (freshwater)					0,482 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	aqua (marine water)					0,482 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	STP					10 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	aqua (intermittent releases)					1 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	sediment (freshwater)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	sediment (marine water)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	soil				0,476 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	soil				1,04 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	STP					100 mg/L	
2,6-Di-tert-butyl-p-cresol 128-37-0	sediment (freshwater)				1,29 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	oral				16,7 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (marine water)					0,4 µg/L	
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (intermittent releases)					4 µg/L	
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (freshwater)					4 µg/L	
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (freshwater)		0,000199 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Methyl methacrylate 80-62-6	Workers	Dermal	Acute/short term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	Workers	Dermal	Long term exposure - systemic effects		13,67 mg/kg bw/day	
Methyl methacrylate 80-62-6	Workers	inhalation	Long term exposure - systemic effects		210 mg/m3	
Methyl methacrylate 80-62-6	Workers	Dermal	Long term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	Workers	inhalation	Long term exposure - local effects		210 mg/m3	
Methyl methacrylate 80-62-6	Workers	Dermal	Acute/short term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	Workers	Dermal	Long term exposure - systemic effects		8,2 mg/kg bw/day	
Methyl methacrylate 80-62-6	Workers	inhalation	Long term exposure - systemic effects		74,3 mg/m3	
Methyl methacrylate 80-62-6	Workers	Dermal	Long term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	Workers	inhalation	Long term exposure - local effects		105 mg/m3	
Methacrylic acid 79-41-4	Workers	inhalation	Long term exposure - local effects		88 mg/m3	
Methacrylic acid 79-41-4	Workers	inhalation	Long term exposure - systemic effects		29,6 mg/m3	
Methacrylic acid 79-41-4	Workers	Dermal	Long term exposure - systemic effects		4,25 mg/kg bw/day	
Methacrylic acid 79-41-4	Workers	inhalation	Long term exposure - local effects		6,55 mg/m3	
Methacrylic acid 79-41-4	Workers	inhalation	Long term exposure - systemic effects		6,3 mg/m3	
Methacrylic acid 79-41-4	Workers	Dermal	Long term exposure - systemic effects		2,55 mg/kg bw/day	
2-Hydroxyethyl methacrylate 868-77-9	Workers	Dermal	Long term exposure - systemic effects		1,3 mg/kg bw/day	
2-Hydroxyethyl methacrylate 868-77-9	Workers	inhalation	Long term exposure - systemic effects		4,9 mg/m3	
2-Hydroxyethyl methacrylate 868-77-9	Workers	Dermal	Long term exposure - systemic effects		0,83 mg/kg bw/day	
2-Hydroxyethyl methacrylate 868-77-9	Workers	inhalation	Long term exposure - systemic effects		2,9 mg/m3	
2-Hydroxyethyl methacrylate 868-77-9	Workers	oral	Long term exposure - systemic effects		0,83 mg/kg bw/day	
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	inhalation	Long term exposure - systemic effects		1,74 mg/m3	
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	Dermal	Long term exposure - systemic effects		8,3 mg/kg bw/day	
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	Dermal	Long term exposure -		5 mg/kg bw/day	

			systemic effects			
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	inhalation	Long term exposure - systemic effects		5,8 mg/m ³	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid light pink
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	> 100 °C (> 212 °F)
Flash point	10,00 °C (50 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure (50 °C (122 °F))	< 700 mbar
Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable

Evaporation rate
Vapor density
Oxidising properties

No data available / Not applicable
No data available / Not applicable
No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

carbon oxides.
nitrogen oxides

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

STOT-single exposure:

May cause respiratory irritation.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye damage.

Sensitizing:

May cause an allergic skin reaction.

Reproductive toxicity:

May damage fertility. May damage the unborn child.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methacrylic acid 79-41-4	LD50	1.320 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Tetrahydrofurfuryl methacrylate 2455-24-5	LD50	4.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	
Butyl hydroxytoluene 128-37-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methacrylic acid 79-41-4	LC50	4,7 mg/l	inhalation	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg	dermal			Expert judgement
Methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg			rabbit	Dermal Toxicity Screening

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methacrylic acid 79-41-4	Category 1A (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methyl methacrylate 80-62-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	Buehler test

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Methyl methacrylate 80-62-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		
2-Hydroxyethyl methacrylate 868-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Methyl methacrylate 80-62-6	LOAEL=2000 ppm	inhalation	14 weeks 6 hrs/day, 5 days/wk	mouse	Dose Range Finding Study
Methyl methacrylate 80-62-6	NOAEL=1000 ppm	inhalation	14 weeks 6 hrs/day, 5 days/wk	mouse	Dose Range Finding Study
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Do not empty into drains / surface water / ground water.
Harmful to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Methyl methacrylate 80-62-6	LC50	350 mg/l	Fish		Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methyl methacrylate 80-62-6	EC50	69 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methyl methacrylate 80-62-6	EC50	170 mg/l	Algae	4 d	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	100 mg/l	Algae	4 d	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid 79-41-4	LC50	> 100 - 180 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methacrylic acid 79-41-4	EC50	> 8,2 mg/l	Algae			OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC10	8,2 mg/l	Algae			OECD Guideline 201 (Alga, Growth Inhibition Test)
Tetrahydrofurfuryl methacrylate 2455-24-5	LC50	34,7 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl methacrylate 868-77-9	LC50	227 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	160 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50	345 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	24,1 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butyl hydroxytoluene 128-37-0	EC50	0,48 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butyl hydroxytoluene 128-37-0	NOEC	0,316 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Methyl methacrylate 80-62-6	readily biodegradable	aerobic	95 %	EU Method C.4-B (Determination of the "Ready" Biodegradability Modified OECD Screening Test)
Methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Tetrahydrofurfuryl methacrylate 2455-24-5		aerobic	75 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Butyl hydroxytoluene 128-37-0		aerobic	4,5 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

Cured adhesives are immobile.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Methyl methacrylate 80-62-6	1,38					
Methacrylic acid 79-41-4	0,93					
Tetrahydrofurfuryl methacrylate 2455-24-5	1,8					
Cumene hydroperoxide 80-15-9		9,1		calculation		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene hydroperoxide 80-15-9	2,16					
Butyl hydroxytoluene 128-37-0	5,1					

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Methyl methacrylate 80-62-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Methacrylic acid 79-41-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Hydroxyethyl methacrylate 868-77-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butyl hydroxytoluene 128-37-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number**

ADR	1133
RID	1133
ADNR	1133
IMDG	1133
IATA	1133

14.2. UN proper shipping name

ADR	ADHESIVES
RID	ADHESIVES
ADNR	ADHESIVES
IMDG	ADHESIVES
IATA	Adhesives

14.3. Transport hazard class(es)

ADR	3
RID	3
ADNR	3
IMDG	3
IATA	3

14.4. Packaging group

ADR	II
RID	II
ADNR	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADNR	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D
-----	------------------------

	Tunnelcode: (D/E)
RID	Special provision 640D
ADNR	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 30 - 40 %
(1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

R11 Highly flammable.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R21/22 Harmful in contact with skin and if swallowed.
R23 Toxic by inhalation.
R34 Causes burns.
R35 Causes severe burns.
R36/38 Irritating to eyes and skin.
R37/38 Irritating to respiratory system and skin.
R43 May cause sensitisation by skin contact.
R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R7 May cause fire.
H225 Highly flammable liquid and vapor.
H242 Heating may cause a fire.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9