

C28.4 SeriesCAPACITORS FOR MOTOR APPLICATIONS


Typical applications: the capacitor is used in series to the auxiliary winding of a single-phase motor, allowing it to start and increase its torque while working.
Main application fields: low power electric motors, compressors.

Vendor part number: C284AAR4800AO2J

Capacitance:	8.0 μ F	Rated current:	1.18 Arms
Capacitance tolerance:	$\pm$ 5 %	Max. dV/dt:	20 V/ μ s
Class of operation:	CLASS A-30.000 hours, 420Vac/25/085/21	Can diameter:	30 mm.
	CLASS B-10.000 hours, 470Vac/25/085/21	Can height:	68 mm.

General technical data

Reference standards:	EN 60252-1: 2011/A1:2013	Filling Resin:	Epoxy
Approvals:	IMQ	Plates:	Self-healing metal layer
Type of Service:	Continuous	Test voltage terminal-terminal:	2 Vn for 2 s
Operating Temperature:	- 25 / +85 °C	Test voltage terminal-can:	2.000 Volt for 2 s
Storage Temperature:	- 25 / +85 °C	Total Harmonic Distortion:	Up to 10%
Rated voltage Vn (AC):	470 Vac	Fire Load:	45 MJ/kg
Rated frequency (Hz):	50-60Hz	Leakage-Clearance in air between parts under voltage	Min. 5mm
Voltage rise/fall time(max):	20 V / μ sec	Leakage-Clearance in air between parts under voltage and accessible metal parts:	Min. 6mm
Maximum Permissible Voltage:	1.10 x Rated Voltage	Vibration test:	IEC 60068-2-6
Maximum Permissible Current:	1.30 x Rated Current	Termination:	H05V2-U Stiff Cable 0.75mm2, white
Dissipation factor, TgD:	12 x 10E-4 at 20°C, 1 kHz	Can:	Polypropylene with self-extinguishing features V2 (UL94)
Safety class:	S3	Disk:	Polypropylene with self-extinguishing features V2 (UL94)
Maximum Altitude:	No power derating applicable up to an altitude of 2200 meters. At higher altitudes than 2200 meters, please contact us for the Power derating	Cable Terminals:	Stripped
Mounting:	Any position	Nut:	No
Dielectric:	Polypropylene film	Washer:	No



General Disclaimer

All product specifications, statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute a warranty and we specifically disclaim any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application.

Prototype Sample Disclaimer

All The Customer acknowledges the following limitations of the prototype samples:

- (1) Prototype samples are manufactured from preliminary designs and manufacturing processes; may not represent final designs; have not been released for commercial use and are not subject to the same quality control procedures applicable to released products.
- (2) Prototype samples are not qualified parts and are provided "as-is" by KEMET Electronics Corporation, which specifically disclaims any and all warranties and guarantees, explicit or implied, including, without limitation, the warranties of merchantability and fitness for a particular purpose or use.
- (3) Prototype samples are not intended for commercial use; are provided for engineering evaluation only and are not recommended for use in the Customer's production line. (4) The Customer assumes the risk of any and all uses that the Customer makes of the prototype samples.

Data sheet edition

The present data sheet replaces and supersedes any former one released by KEMET.

KEMET's product warranty is set forth at www.kemet.com under Terms and Conditions of Sale.

COPYRIGHT KEMET ELECTRONICS CORPORATION 2017, all rights reserved.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9