


Features

- Superior circuit protection
- Overcurrent and overvoltage protection
- Blocks surges up to rated limits
- High-speed performance
- Small SMT package
- Agency listing:


Applications

- Voice / VDSL cards
- Protection modules and dongles
- Process control equipment
- Test and measurement equipment
- General electronics

TBU-CA Series - TBU® High-Speed Protectors

General Information

The TBU-CA Series of Bourns® TBU® products are low capacitance single bidirectional high-speed protection components, constructed using MOSFET semiconductor technology, and designed to protect against faults caused by short circuits, AC power cross, induction and lightning surges.



TBU® Device

The TBU® high-speed protector placed in the system circuit will monitor the current with the MOSFET detection circuit triggering to provide an effective barrier behind which sensitive electronics will not be exposed to large voltages or currents during surge events. The TBU® device is provided in a surface mount DFN package and meets industry standard requirements such as RoHS and Pb Free solder reflow profiles.

Agency Listing

Description	
UL	File Number: E315805

Absolute Maximum Ratings (@ T_A = 25 °C Unless Otherwise Noted)

Symbol	Parameter	Part Number	Value	Unit
V_{imp}	Peak impulse voltage withstand with duration less than 10 ms	TBU-CA025-xxx-WH TBU-CA040-xxx-WH TBU-CA050-xxx-WH TBU-CA065-xxx-WH TBU-CA085-xxx-WH	250 400 500 650 850	V
V_{rms}	Continuous A.C. RMS voltage	TBU-CA025-xxx-WH TBU-CA040-xxx-WH TBU-CA050-xxx-WH TBU-CA065-xxx-WH TBU-CA085-xxx-WH	100 200 250 300 425	V
T_{op}	Operating temperature range		-55 to +125	°C
T_{stg}	Storage temperature range		-65 to +150	°C
T_{jmax}	Maximum Junction Temperature		+125	°C
ESD	HBM ESD protection per IEC 61000-4-2		±2	kV

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Fax: +886-2 2562-4116
Europe: Tel: +41-41 768 5555 • Fax: +41-41 768 5510
The Americas: Tel: +1-951 781-5500 • Fax: +1-951 781-5700
www.bourns.com

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.
Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.


Electrical Characteristics (@ T_A = 25 °C Unless Otherwise Noted)

Symbol	Parameter		Part Number	Min.	Typ.	Max.	Unit
$I_{trigger}$	Current required for the device to go from operating state to protected state		TBU-CAxxx-050-WH TBU-CAxxx-100-WH TBU-CAxxx-200-WH TBU-CAxxx-300-WH TBU-CAxxx-500-WH	50 100 200 300 500	75 150 300 450 750	100 200 400 600 1000	mA
R_{device}	Series resistance of the TBU device	V_{imp} = 250 V $I_{trigger}$ (min.) = 50 mA V_{imp} = 250 V $I_{trigger}$ (min.) = 100 mA V_{imp} = 250 V $I_{trigger}$ (min.) = 200 mA V_{imp} = 250 V $I_{trigger}$ (min.) = 300 mA V_{imp} = 250 V $I_{trigger}$ (min.) = 500 mA	TBU-CA025-050-WH TBU-CA025-100-WH TBU-CA025-200-WH TBU-CA025-300-WH TBU-CA025-500-WH		13.3 7.1 4.2 3.2 2.6	15.3 8.2 4.8 3.8 3.0	Ω
		V_{imp} = 400 V $I_{trigger}$ (min.) = 50 mA V_{imp} = 400 V $I_{trigger}$ (min.) = 100 mA V_{imp} = 400 V $I_{trigger}$ (min.) = 200 mA V_{imp} = 400 V $I_{trigger}$ (min.) = 300 mA V_{imp} = 400 V $I_{trigger}$ (min.) = 500 mA	TBU-CA040-050-WH TBU-CA040-100-WH TBU-CA040-200-WH TBU-CA040-300-WH TBU-CA040-500-WH		14.3 8.1 5.2 4.3 3.6	16.5 9.4 6.0 5.0 4.2	
		V_{imp} = 500 V $I_{trigger}$ (min.) = 50 mA V_{imp} = 500 V $I_{trigger}$ (min.) = 100 mA V_{imp} = 500 V $I_{trigger}$ (min.) = 200 mA V_{imp} = 500 V $I_{trigger}$ (min.) = 300 mA V_{imp} = 500 V $I_{trigger}$ (min.) = 500 mA	TBU-CA050-050-WH TBU-CA050-100-WH TBU-CA050-200-WH TBU-CA050-300-WH TBU-CA050-500-WH		15.7 9.5 6.6 5.6 5.0	18.0 10.9 7.5 6.5 5.7	
		V_{imp} = 650 V $I_{trigger}$ (min.) = 50 mA V_{imp} = 650 V $I_{trigger}$ (min.) = 100 mA V_{imp} = 650 V $I_{trigger}$ (min.) = 200 mA V_{imp} = 650 V $I_{trigger}$ (min.) = 300 mA V_{imp} = 650 V $I_{trigger}$ (min.) = 500 mA	TBU-CA065-050-WH TBU-CA065-100-WH TBU-CA065-200-WH TBU-CA065-300-WH TBU-CA065-500-WH		17.7 11.5 8.6 7.6 7.0	20.3 13.2 9.8 8.8 8.0	
		V_{imp} = 850 V $I_{trigger}$ (min.) = 50 mA V_{imp} = 850 V $I_{trigger}$ (min.) = 100 mA V_{imp} = 850 V $I_{trigger}$ (min.) = 200 mA V_{imp} = 850 V $I_{trigger}$ (min.) = 300 mA V_{imp} = 850 V $I_{trigger}$ (min.) = 500 mA	TBU-CA085-050-WH TBU-CA085-100-WH TBU-CA085-200-WH TBU-CA085-300-WH TBU-CA085-500-WH		21.4 15.2 12.3 11.3 10.7	24.5 17.4 14.0 13.0 12.2	
t_{block}	Time for the device to go from normal operating state to protected state					1	µs
I_Q	Current through the triggered TBU® device with 50 Vdc circuit voltage			0.25	0.50	1.00	mA
V_{reset}	Voltage below which the triggered TBU® device will transition to normal operating state			12	16	20	V
$R_{th(j-l)}$	Junction to package pads - FR4 using recommended pad layout				98		°C/W
$R_{th(j-l)}$	Junction to package pads - FR4 using heat sink on board (6 cm^2) (1 in^2)				40		°C/W

Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Reference Application

The TBU® devices are general use protectors used in a wide variety of applications. The maximum voltage rating of the TBU® device should never be exceeded. Where necessary, an OVP should be employed to limit the maximum voltage. A cost-effective protection solution combines Bourns® TBU® protection devices with a pair of Bourns® MOVs. For bandwidth sensitive applications, a Bourns® GDT may be substituted for the MOV.



Basic TBU Operation


The TBU® device, constructed using MOSFET semiconductor technology, placed in the system circuit will monitor the current with the MOSFET detection circuit triggering to provide an effective barrier behind which sensitive electronics are not exposed to large voltages or currents during surge events. The TBU® device operates in approximately 1 µs - once line current exceeds the TBU® device's trigger current Itrigger. When operated, the TBU® device restricts line current to less than 1 mA typically. When operated, the TBU® device will block all voltages including the surge up to rated limits.

After the surge, the TBU® device resets when the voltage across the TBU® device falls to the V_{reset} level. The TBU® device will automatically reset on lines which have no DC bias or have DC bias below V_{reset} (such as unpowered signal lines).


If the line has a normal DC bias above V_{reset}, the voltage across the TBU® device may not fall below V_{reset} after the surge. In such cases, special care needs to be taken to ensure that the TBU® device will reset, with software monitoring as one method used to accomplish this. Bourns application engineers can provide further assistance.

Performance Graphs


Typical V-I Characteristics (TBU-CA050-300-WH)




Typical Trigger Current vs. Temperature



Power Derating Curve




Typical Resistance vs. Temperature



Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Product Dimensions




Pad Designation

Pad #	Pin Out
1	Line In/Out
2	NU
3	Line Out/In

Recommended Pad Layout

TBU® High-Speed Protectors have a 100 % matte-tin termination finish. For improved thermal dissipation, the recommended layout uses PCB copper areas which extend beyond the exposed solder pad. The exposed solder pads should be defined by a solder mask which matches the pad layout of the TBU® device in size and spacing. It is recommended that they should be the same dimension as the TBU® pads but if smaller solder pads are used, they should be centered on the TBU® package terminal pads and not more than 0.10-0.12 mm (0.004-0.005 in.) smaller in overall width or length. Solder pad areas should not be larger than the TBU® pad sizes to ensure adequate clearance is maintained. The recommended stencil thickness is 0.10-0.12 mm (0.004-0.005 in.) with a stencil opening size 0.025 mm (0.0010 in.) less than the solder pad size. Extended copper areas beyond the solder pad significantly improve the junction to ambient thermal resistance, resulting in operation at lower junction temperatures with a corresponding benefit of reliability. All pads should soldered to the PCB, including pads marked as NC or NU but no electrical connection should be made to these pads. For minimum parasitic capacitance, it is recommended that signal, ground or power signals are not routed beneath any pad.




Dark grey areas show added PCB copper area for better thermal resistance.

Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Reflow Profile

Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate (Tsmax to Tp)	3 °C/sec. max.
Preheat - Temperature Min. (Tsmin) - Temperature Max. (Tsmax) - Time (tsmin to tsmax)	 150 °C 200 °C 60-180 sec.
Time maintained above: - Temperature (TL) - Time (tL)	 217 °C 60-150 sec.
Peak/Classification Temperature (Tp)	260 °C
Time within 5 °C of Actual Peak Temp. (tp)	20-40 sec.
Ramp-Down Rate	6 °C/sec. max.
Time 25 °C to Peak Temperature	8 min. max.



How to Order

TBU - CA 085 - 500 - WH

TBU® Product

Series
- CA = Bi-Series

Impulse Voltage Rating
- 025 = 250 V
- 040 = 400 V
- 050 = 500 V
- 065 = 650 V
- 085 = 850 V

Trigger Current
- 050 = 50 mA
- 100 = 100 mA
- 200 = 200 mA
- 300 = 300 mA
- 500 = 500 mA

Hold to Trip Ratio Suffix
- W = Hold to Trip Ratio

Package Suffix
- H = DFN Package

Typical Part Marking




MANUFACTURER'S TRADEMARK

PRODUCT CODE
- 1ST DIGIT INDICATES PRODUCT FAMILY:
  A = TBU-CA SERIES
- 2ND & 3RD DIGITS INDICATE IMPULSE VOLTAGE:
  25 = 250 V 40 = 400 V 50 = 500 V
  65 = 650 V 85 = 850 V
- 4TH & 5TH DIGITS INDICATE TRIGGER CURRENT:
  05 = 50 mA 10 = 100 mA 20 = 200 mA
  30 = 300 mA 50 = 500 mA

MANUFACTURING DATE CODE
- 1ST DIGIT INDICATES THE YEAR'S 6-MONTH PERIOD.
- 2ND DIGIT INDICATES THE WEEK NUMBER IN THE 6-MONTH PERIOD.
- 3RD & 4TH DIGITS INDICATE SPECIFIC LOT FOR THE WEEK.


6-MONTH PERIOD CODES:
A = JAN-JUN 2009 C = JAN-JUN 2010 E = JAN-JUN 2011
B = JUL-DEC 2009 D = JUL-DEC 2010 F = JUL-DEC 2011

Thermal Resistance vs Additional PCB Cu Area



Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Packaging Specifications



QUANTITY: 3000 PIECES PER REEL

A		B		C		D		G	N
Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Ref.	Ref.
326 (12.835)	330 (13.002)	1.5 (.059)	2.5 (.098)	12.8 (.504)	13.5 (.531)	20.2 (.795)	-	16.5 (.650)	102 (4.016)

A_0		B_0		D		D_1		E		F	
Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	max.
4.3 (.169)	4.5 (.177)	6.7 (.264)	6.9 (.272)	1.5 (.059)	1.6 (.063)	1.5 (.059)	-	1.65 (.065)	1.85 (.073)	7.4 (.291)	7.6 (.299)
K_0		P		P_0		P_2		t		W	
Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
1.0 (.039)	1.2 (.047)	7.9 (.311)	8.1 (.319)	3.9 (.159)	4.1 (.161)	1.9 (.075)	2.1 (.083)	0.25 (.010)	0.35 (.014)	15.7 (.618)	16.3 (.642)

DIMENSIONS: MM (INCHES)

"TBU" is a registered trademark of Bourns, Inc. in the United States and other countries.
Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9