



## Features

- RoHS compliant\*
- Values from 0.02 to 9.10 ohms
- Tolerance of 1 % or 5 %
- Five package sizes available
- Tape and reel packaging

**BOURNS®**

## CRL Series - Low Value Chip Resistors

### Electrical Characteristics

| Characteristic  | Model CRL0603                             | Model CRL0805                    | Model CRL1206                    | Model CRL2010                    | Model CRL2512                    |
|---|---|----------------------------------|----------------------------------|----------------------------------|----------------------------------|
| Power Rating @ 70 °C  | 0.100 watt                                | 0.125 watt                       | 0.250 watt                       | 0.50 watt                        | 1.00 watt                        |
| Operating Temperature Range   | -55 to +125 °C                            |                                  |                                  |                                  |                                  |
| Derated to Zero Load at   | +125 °C                                   |                                  |                                  |                                  |                                  |
| Maximum Working Voltage   | (PR) <sup>1/2</sup>                       | (PR) <sup>1/2</sup>              | (PR) <sup>1/2</sup>              | (PR) <sup>1/2</sup>              | (PR) <sup>1/2</sup>              |
| Resistance Range<br>E24 Values:<br>See Value Table:                                 | 0.10 to 9.10 Ω<br>N/A                     | 0.10 to 9.10 Ω<br>0.05 to 0.09 Ω | 0.10 to 9.10 Ω<br>0.02 to 0.09 Ω | 0.10 to 9.10 Ω<br>0.02 to 0.09 Ω | 0.10 to 9.10 Ω<br>0.02 to 0.09 Ω |
| Temperature Coefficient<br>0.05 Ω to 9.10 Ω<br>0.03 Ω to 0.04 Ω<br>0.01 Ω to 0.02 Ω | ±200 PPM/°C<br>±400 PPM/°C<br>±600 PPM/°C |                                  |                                  |                                  |                                  |

### Value Table

| Value (Ω) | CRL0603<br>1 % | CRL0603<br>5 % | CRL0805<br>1 % | CRL0805<br>5 % | CRL1206<br>1 % | CRL1206<br>5 % | CRL2010<br>1 % | CRL2010<br>5 % | CRL2512<br>1 % | CRL2512<br>5 % |
|-----------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 0.02      | Not Available  | Not Available  | Not Available  | Not Available  | A              | A              | P              | P              | P              | P              |
| 0.03      | Not Available  | Not Available  | Not Available  | Not Available  | A              | A              | P              | P              | P              | P              |
| 0.04      | Not Available  | Not Available  | Not Available  | Not Available  | A              | A              | P              | P              | P              | P              |
| 0.05      | Not Available  | Not Available  | A              | A              | A              | A              | P              | P              | P              | P              |
| 0.06      | Not Available  | Not Available  | A              | A              | A              | A              | A              | A              | A              | A              |
| 0.07      | Not Available  | Not Available  | A              | A              | A              | A              | A              | A              | A              | A              |
| 0.08      | Not Available  | Not Available  | A              | A              | A              | A              | A              | A              | A              | A              |
| 0.09      | Not Available  | Not Available  | A              | A              | A              | A              | A              | A              | A              | A              |

P = Popular Value

A = Available Value (may have greater minimum order quantity)

### Environmental Characteristics

| Description                  | Method   | Limit  |
|------------------------------|--|--|
| Short Time Overload          | 2.5 x (PR) <sup>1/2</sup> for 5 seconds.<br>(IEC 115-1 4.13)                           | 1 % Tolerance: ΔR ≤ ±(1 % + 0.001 Ω)<br>5 % Tolerance: ΔR ≤ ±(2 % + 0.001 Ω)   |
| Load Life                    | (PR) <sup>1/2</sup> for 1000 hours; 1.5 hours on; 0.5 hours off.<br>(IEC 115-1 4.25.1) | 1 % Tolerance: ΔR ≤ ±(1 % + 0.001 Ω)<br>5 % Tolerance: ΔR ≤ ±(2 % + 0.001 Ω)   |
| Resistance to Soldering Heat | 260 °C for 10 seconds.<br>(IEC 115-1 4.18)   | 1 % Tolerance: ΔR ≤ ±(0.5 % + 0.001 Ω)<br>5 % Tolerance: ΔR ≤ ±(1 % + 0.001 Ω) |
| Thermal Shock                | 5 cycles from -55 °C to +125 °C, 30 minutes at temperature.<br>(IEC 115-1 4.19)        | 1 % Tolerance: ΔR ≤ ±(0.5 % + 0.001 Ω)<br>5 % Tolerance: ΔR ≤ ±(1 % + 0.001 Ω) |

\*RoHS Directive 2002/95/EC Jan 27, 2003 including Annex.

Specifications are subject to change without notice.

Customers should verify actual device performance in their specific applications.

# CRL Series - Low Value Chip Resistors

**BOURNS®**

## Chip Dimensions

| Dimension      | Model CRL0603                             | Model CRL0805                             | Model CRL1206                             | Model CRL2010                             | Model CRL2512                             |
|----------------|---|---|---|---|---|
| L              | $\frac{1.60 \pm 0.10}{(0.063 \pm 0.004)}$ | $\frac{2.00 \pm 0.15}{(0.079 \pm 0.006)}$ | $\frac{3.20 \pm 0.15}{(0.126 \pm 0.006)}$ | $\frac{5.00 \pm 0.20}{(0.197 \pm 0.008)}$ | $\frac{6.30 \pm 0.20}{(0.248 \pm 0.008)}$ |
| W              | $\frac{0.80 \pm 0.10}{(0.031 \pm 0.004)}$ | $\frac{1.25 \pm 0.10}{(0.049 \pm 0.004)}$ | $\frac{1.60 \pm 0.15}{(0.063 \pm 0.006)}$ | $\frac{2.50 \pm 0.20}{(0.098 \pm 0.008)}$ | $\frac{3.10 \pm 0.20}{(0.122 \pm 0.008)}$ |
| H              | $\frac{0.45 \pm 0.10}{(0.018 \pm 0.004)}$ | $\frac{0.50 \pm 0.10}{(0.020 \pm 0.004)}$ | $\frac{0.60 \pm 0.10}{(0.024 \pm 0.004)}$ | $\frac{0.60 \pm 0.10}{(0.024 \pm 0.004)}$ | $\frac{0.60 \pm 0.10}{(0.024 \pm 0.004)}$ |
| l <sub>1</sub> | $\frac{0.30 \pm 0.20}{(0.012 \pm 0.008)}$ | $\frac{0.40 \pm 0.20}{(0.016 \pm 0.008)}$ | $\frac{0.50 \pm 0.25}{(0.020 \pm 0.010)}$ | $\frac{0.60 \pm 0.25}{(0.024 \pm 0.010)}$ | $\frac{0.60 \pm 0.25}{(0.024 \pm 0.010)}$ |
| l <sub>2</sub> | $\frac{0.30 \pm 0.20}{(0.012 \pm 0.008)}$ | $\frac{0.40 \pm 0.20}{(0.016 \pm 0.008)}$ | $\frac{0.50 \pm 0.25}{(0.020 \pm 0.010)}$ | $\frac{0.60 \pm 0.25}{(0.024 \pm 0.010)}$ | $\frac{0.60 \pm 0.20}{(0.024 \pm 0.008)}$ |

## Dimensional Drawing



DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$

## Derating Curve



## How to Order

**CRL 0603 - F W - R090 E LF**

Model \_\_\_\_\_  
(CRL = Chip Resistor Low Value)

- Size \_\_\_\_\_
- 0603
  - 0805
  - 1206
  - 2010
  - 2512

Resistance Tolerance \_\_\_\_\_  
F = ±1 %  
J = ±5 %

TCR (PPM/°C) \_\_\_\_\_  
W = ±200 (0.05 to 9.10 Ω)  
V = ±400 (0.03 to 0.04 Ω)  
U = ±600 (0.01 Ω to 0.02 Ω)

Resistance Value (1 % or 5 %) \_\_\_\_\_  
• R stands for decimal point. Three significant digits: (R090 = 0.09 Ω; 9R10 = 9.10 Ω)

Packaging \_\_\_\_\_  
• CRL0603, CRL0805, CRL1206: E = Paper Tape, Plastic Reel, 5,000 pcs.  
• CRL2010, CRL2512: E = Embossed Plastic Tape, Plastic Reel, 4,000 pcs.

Termination \_\_\_\_\_  
LF = Tin-plated (RoHS compliant)

# CRL Series - Low Value Chip Resistors

**BOURNS®**

## Packaging Dimensions - Tape

| Dimension      | Model CRL0603                             | Model CRL0805  | Model CRL1206  | Model CRL2010                             | Model CRL2512                              |
|----------------|---|--|--|---|--|
| A              | $\frac{1.10 \pm 0.10}{(0.043 \pm 0.004)}$ | $\frac{1.65 + 0.20 / - 0.10}{(0.065 + 0.008 / -.004)}$ | $\frac{1.95 + 0.10 / - 0.05}{(0.077 + 0.004 / -.002)}$ | $\frac{2.80 \pm 0.20}{(0.110 \pm 0.008)}$ | $\frac{3.50 \pm 0.20}{(0.138 \pm 0.008)}$  |
| B              | $\frac{1.90 \pm 0.10}{(0.075 \pm 0.004)}$ | $\frac{2.40 + 0.20 / - 0.10}{(0.094 + 0.008 / -.004)}$ | $\frac{3.50 \pm 0.10}{(0.138 \pm 0.004)}$              | $\frac{5.50 \pm 0.20}{(0.217 \pm 0.008)}$ | $\frac{6.70 \pm 0.20}{(0.264 \pm 0.008)}$  |
| W              | $\frac{8.00 \pm 0.20}{(0.315 \pm 0.008)}$ | $\frac{8.00 \pm 0.20}{(0.315 \pm 0.008)}$              | $\frac{8.00 \pm 0.20}{(0.315 \pm 0.008)}$              | $\frac{12.0 \pm 0.30}{(0.472 \pm 0.012)}$ | $\frac{12.00 \pm 0.30}{(0.472 \pm 0.012)}$ |
| F              | $\frac{3.50 \pm 0.05}{(0.138 \pm 0.002)}$ | $\frac{3.50 \pm 0.05}{(0.138 \pm 0.002)}$              | $\frac{3.50 \pm 0.05}{(0.138 \pm 0.002)}$              | $\frac{5.50 \pm 0.05}{(0.217 \pm 0.002)}$ | $\frac{5.50 \pm 0.05}{(0.217 \pm 0.002)}$  |
| P <sub>0</sub> | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$ | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$              | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$              | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$ | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$  |

## Packaging Dimensions - Reel

| Dimension | Model CRL0603                              | Model CRL0805                              | Model CRL1206                              | Model CRL2010                              | Model CRL2512                              |
|-----------|--|--|--|--|--|
| N         | $\frac{80.00 \pm 1.00}{(3.150 \pm 0.040)}$ | $\frac{80.00 \pm 1.00}{(3.150 \pm 0.040)}$ | $\frac{80.00 \pm 1.00}{(3.150 \pm 0.040)}$ | $\frac{80.00 \pm 0.20}{(3.150 \pm 0.008)}$ | $\frac{80.00 \pm 0.20}{(3.150 \pm 0.008)}$ |
| D         | $\frac{20.50}{(0.807)}$                    | $\frac{20.50}{(0.807)}$                    | $\frac{20.50}{(0.807)}$                    | $\frac{20.00}{(0.787)}$ MIN.               | $\frac{20.00}{(0.787)}$ MIN.               |
| T         | $\frac{10.00 \pm 1.50}{(0.394 \pm 0.059)}$ | $\frac{10.00 \pm 1.50}{(0.394 \pm 0.059)}$ | $\frac{10.00 \pm 1.50}{(0.394 \pm 0.059)}$ | $\frac{16.70}{(0.657)}$ MAX.               | $\frac{16.70}{(0.657)}$ MAX.               |



REV. 02/11

Specifications are subject to change without notice.  
Customers should verify actual device performance in their specific applications.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9