

## A General Specifications

## Electrical Capacity (Resistive Load)

- Power Level (silver):** 6A @ 125V AC & 3A @ 250V AC  
4A @ 30V DC for On-None-On & On-None-Off; 3A @ 30V DC for all other circuits
- Logic Level (gold):** 0.4VA maximum @ 28V AC/DC maximum (Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)
- Logic/Power Level (gold over silver):** Combines silver & gold ratings  
Note: Find additional explanation of dual rating & operating range in Supplement section.

## Other Ratings

- Contact Resistance:** 10 milliohms maximum for silver; 20 milliohms maximum for gold
- Insulation Resistance:** 1,000 megohms minimum @ 500V DC
- Dielectric Strength:** 1,000V AC minimum between contacts for 1 minute minimum;  
1,500V AC minimum between contacts and case for 1 minute minimum
- Mechanical Life:** 100,000 operations minimum; 50,000 operations minimum for flat, locking & splashproof devices
- Electrical Life:** 25,000 operations minimum for silver; 50,000 operations minimum for gold;  
50,000 operations minimum for silver at 3A @ 125V AC
- Angle of Throw:** 25°

## Materials &amp; Finishes

- Toggle:** Brass with chrome plating
- Bushing:** Brass with nickel plating
- Case:** Diallyl phthalate resin (UL94V-0)
- Movable Contactor:** Phosphor bronze with silver or gold plating
- Movable Contacts:** Silver alloy (code W); copper with gold plating (code G); or silver alloy with gold plating (code A)
- Stationary Contacts:** Silver with silver plating (code W); copper or brass with gold plating (code G);  
or silver with gold plating (code A)
- Terminals:** Copper or brass with silver plating; or copper or brass with gold plating
- Frame:** Stainless steel
- Support Bracket:** Brass with tin plating

## Environmental Data

- Operating Temp Range:** -30°C through +85°C (-22°F through +185°F)
- Humidity:** 90 ~ 95% humidity for 96 hours @ 40°C (104°F)
- Vibration:** 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
- Shock:** 50G (490m/s<sup>2</sup>) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)
- Sealing:** Splashproof bushing options B3, D3, D8, L3, & L8, which have o-rings inside & outside the bushing, meet IP67 of IEC60529 Standards.

## Installation

- Mounting Torque:** 3.0Nm (26.55 lb•in) double nut for large bushing;  
1.5Nm (13 lb•in) double nut & 0.7Nm (6 lb•in) single nut for all other bushings

## Processing

- Soldering:** Wave Soldering (PC version) for Gold: See Profile A in Supplement section.  
Manual Soldering for Gold: See Profile A in Supplement section.  
Wave Soldering (PC version) for Silver: See Profile B in Supplement section.  
Manual Soldering for Silver: See Profile B in Supplement section.  
Note: Lever must be in OFF (center) position while soldering.
- Cleaning:** These devices are not process sealed. Hand clean locally using alcohol based solution.

## Standards &amp; Certifications

- Flammability Standards:** UL94V-0 for case
- UL:** File No. E44145 - Recognized only when ordered with marking on switch.  
Add "/U" or "/CUL" before dash in part number to order UL recognized switch.  
All models recognized at 6A @ 125V AC, 3A @ 250V AC or 0.4VA maximum @ 28V DC maximum.
- CSA:** File No. 023535\_0\_000 - Certified only when ordered with marking on switch.  
Add "/C" before dash in part number to order CSA certified switch.  
All models certified at 6A @ 125V AC or 3A @ 250V AC or 0.4VA maximum @ 28V maximum.

# Distinctive Characteristics

Antirotation design, standard on noncylindrical levers, mates toggle and bushing; bottom of toggle has two flattened sides which fit into a complementary opening inside bushing.

Antijamming design protects contacts from damage due to excessive downward force on actuator.

High torque bushing construction prevents rotation or separation from frame during installation.

High insulating barriers increase isolation of circuits in multipole devices and provide added protection to contact points.


Molded diallyl phthalate case has a UL flammability rating of 94V-0.

Epoxy sealed terminals prevent entry of solder flux and other contaminants.



Prominent external insulating barriers increase insulation resistance and dielectric strength.

Interlocked actuator block, lever, and interior guide prevent switch failure due to biased lever movement.

Clinching of frame to case well above base and terminals provides 1,500V dielectric strength.




Actual Size




Bushing Mount

Page A48



Bracket PC Mount

Page A60



Angle PC Mount

Page A66

A  
Toggles

Rockers

Pushbuttons

Illuminated PB

Programmable

Keylocks

Rotaries

Slides

Tactiles

Tilt

Touch

Indicators

Accessories

Supplement

M20

1

3

S

S1

## Poles

|   |                      |
|---|----------------------|
| 1 | SPST<br>SPDT         |
| 2 | DPST<br>DPDT<br>SP3T |
| 3 | 3PDT                 |
| 4 | 4PDT<br>DP3T         |

## Small Toggles

|      |                                  |
|------|----------------------------------|
| S    | .413" (10.5mm) Bat               |
| S2   | .200" (5.08mm) Bat               |
| S3   | .256" (6.5mm) Bat                |
| E    | .450" (11.4mm) Flatted           |
| * E2 | .256" (6.5mm) Flatted            |
| E4   | .840" (21.3mm) Flatted           |
| * Q  | .550" (14.0mm) Cone              |
| * Q2 | .640" (16.26mm) Cone             |
| * Q4 | .840" (21.3mm) Cone              |
| * C  | .571" (14.5mm) Color Tipped Cone |
| D    | .840" (21.3mm) Color Capped Cone |

Specify cap color for toggles C & D  
at the end of the part number.

\* Available on 1- and 2-pole only.

## Small Bushings

|    |                                                                                    |
|----|------------------------------------------------------------------------------------|
| S1 | .350" (8.9mm) Threaded with Keyway                                                 |
| S4 | 6mm .350" (8.9mm) Threaded with Keyway                                             |
| S2 | .350" (8.9mm) Smooth with Keyway                                                   |
| A1 | .280" (7.1mm) Threaded with Keyway                                                 |
| A2 | .280" (7.1mm) Smooth with Keyway                                                   |
| D1 | .350" (8.9mm) Threaded with D Flat                                                 |
| D4 | 6mm .350" (8.9mm) Threaded with D Flat                                             |
| D3 | .350" (8.9mm) Threaded Splashproof with D Flat (combines only with S, S2 & S3)     |
| D8 | 6mm .350" (8.9mm) Threaded Splashproof with D Flat (combines only with S, S2 & S3) |

## Circuits

|     |      |      |      |
|-----|------|------|------|
| * 1 | ON   | NONE | OFF  |
| 2   | ON   | NONE | ON   |
| 3   | ON   | OFF  | ON   |
| 5   | ON   | NONE | (ON) |
| 8   | (ON) | OFF  | (ON) |
| 9   | ON   | OFF  | (ON) |
| **4 | ON   | ON   | ON   |
| **6 | (ON) | ON   | (ON) |
| **7 | ON   | ON   | (ON) |

( ) = Momentary

\* ON-NONE-OFF circuit available in 1- and 2-pole only.

\*\* 3-ON circuits

## Large Toggles

|    |                              |
|----|------------------------------|
| B  | .453" (11.5mm) Large Bat     |
| B2 | .689" (17.5mm) Large Bat     |
| R  | .610" (15.5mm) Large Flatted |

## Large Bushings

|    |                                                     |
|----|-----------------------------------------------------|
| B1 | Large .472" (12mm) Threaded with Keyway             |
| B3 | Large .472" (12mm) Threaded Splashproof with D Flat |

## Locking Lever

|   |                                  |
|---|----------------------------------|
| L | .201" (5.1mm) Dia. Locking Lever |
|---|----------------------------------|

## Bushings For Locking Levers

|    |                                                                   |
|----|-------------------------------------------------------------------|
| L1 | .291" (7.4mm) Threaded with Keyway for Lever Lock                 |
| L4 | 6mm .291" (7.4mm) Threaded with Keyway for Lever Lock             |
| L2 | Smooth with Keyway for Lever Lock                                 |
| L3 | .295" (7.5mm) Threaded Splashproof with D Flat for Lever Lock     |
| L8 | 6mm .295" (7.5mm) Threaded Splashproof with D Flat for Lever Lock |

## IMPORTANT:



Switches are supplied without UL, cULus & CSA marking unless specified.  
**UL, cULus & CSA recognized only when ordered with marking on the switch.**  
Specific models, ratings, & ordering instructions are noted on General Specifications page.

ORDERING EXAMPLE

W

| Contact Materials & Ratings |                                                                        |
|-----------------------------|------------------------------------------------------------------------|
| W                           | Silver; Rated<br>6A @ 125V AC & 3A @ 250V AC                           |
| G                           | Gold; Rated<br>0.4VA max @ 28V AC/DC max                               |
| A                           | Gold over Silver; Rated<br>6A @ 125V AC & 0.4VA max @<br>28V AC/DC max |

01

| Terminals |                            |
|-----------|----------------------------|
| 01        | Solder Lug*                |
| 02        | Quick Connect              |
| 03        | .250" (6.35mm) Straight PC |
| 05        | .425" (10.8mm) Wirewrap    |
| 06        | .750" (19.05mm) Wirewrap   |
| 07        | .964" (24.5mm) Wirewrap    |
| 08        | 1.062" (27.0mm) Wirewrap   |


| Optional Caps         |                              |
|-----------------------|------------------------------|
| For Small Bat Toggles |                              |
| B                     | For S Bat Toggle             |
| C                     | Conical Cap for S Bat Toggle |
| For Large Bat Toggles |                              |
| R                     | For B Toggle                 |
| V                     | For B2 Toggle                |

| Cap for Locking Lever |                                    |
|-----------------------|------------------------------------|
| No Code               | Nickel Plated Supplied with Switch |
| A                     | Black                              |
| C                     | Red                                |
| G                     | Blue                               |





| Cap Colors |                            |
|------------|----------------------------|
| A          | Black                      |
| B          | White                      |
| C          | Red                        |
| E          | Yellow                     |
| F          | Green                      |
| G          | Blue                       |
| H          | Gray (for K1 & K2 paddles) |

\* Wire harness & cable assemblies offered only in Americas

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE  
M2013SS1W01









### POLES & CIRCUITS

| Pole | Model                                     | Toggle Position<br>( ) = Momentary                                                        |                                                                                             |                                                                                         | Connected Terminals                                                                       |                                                                                             |                                                                                         | Throw & Schematics                                                                            |
|------|-------------------------------------------|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
|      |                                           | Down<br> | Center<br> | Up<br> | Down<br> | Center<br> | Up<br> |                                                                                               |
| SP   | M2011                                     | ON                                                                                        | NONE                                                                                        | OFF                                                                                     | 2-3                                                                                       | OPEN                                                                                        | OPEN                                                                                    | SPST<br>   |
| SP   | M2012<br>M2013<br>M2015<br>M2018<br>M2019 | ON<br>ON<br>ON<br>(ON)<br>ON                                                              | NONE<br>OFF<br>NONE<br>OFF<br>OFF                                                           | ON<br>ON<br>(ON)<br>(ON)<br>(ON)                                                        | 2-3                                                                                       | OPEN                                                                                        | 2-1                                                                                     | SPDT<br>   |
| DP   | M2021                                     | ON                                                                                        | NONE                                                                                        | OFF                                                                                     | 2-3 5-6                                                                                   | OPEN                                                                                        | OPEN                                                                                    | DPST<br>   |
| DP   | M2022<br>M2023<br>M2025<br>M2028<br>M2029 | ON<br>ON<br>ON<br>(ON)<br>ON                                                              | NONE<br>OFF<br>NONE<br>OFF<br>OFF                                                           | ON<br>ON<br>(ON)<br>(ON)<br>(ON)                                                        | 2-3 5-6                                                                                   | OPEN                                                                                        | 2-1 5-4                                                                                 | DPDT<br>   |
| 3P   | M2032<br>M2033<br>M2035<br>M2038<br>M2039 | ON<br>ON<br>ON<br>(ON)<br>ON                                                              | NONE<br>OFF<br>NONE<br>OFF<br>OFF                                                           | ON<br>ON<br>(ON)<br>(ON)<br>(ON)                                                        | 2-3 5-6<br>8-9                                                                            | OPEN                                                                                        | 2-1 5-4<br>8-7                                                                          | 3PDT<br>   |
| 4P   | M2042<br>M2043<br>M2045<br>M2048<br>M2049 | ON<br>ON<br>ON<br>(ON)<br>ON                                                              | NONE<br>OFF<br>NONE<br>OFF<br>OFF                                                           | ON<br>ON<br>(ON)<br>(ON)<br>(ON)                                                        | 2-3 5-6<br>8-9 11-12                                                                      | OPEN                                                                                        | 2-1 5-4<br>8-7 11-10                                                                    | 4PDT<br> |


### For 3 Throw (3-On)

#### Connected Terminals & Schematic

| Pole | Model                   | Down             | Center         | Up                 | Down                                                                                | Center                                                                               | Up                                                                                    |
|------|-------------------------|------------------|----------------|--------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SP   | M2024<br>M2026<br>M2027 | ON<br>(ON)<br>ON | ON<br>ON<br>ON | ON<br>(ON)<br>(ON) |  |  |  |
| DP   | M2044<br>M2046<br>M2047 | ON<br>(ON)<br>ON | ON<br>ON<br>ON | ON<br>(ON)<br>(ON) |  |  |  |


The SP3T model utilizes a double pole base.

External connection must be made during field installation.



The DP3T model utilizes a four pole base.

External connection must be made during field installation.



## SMALL TOGGLES




**S** .413" (10.5mm)  
Bat

**S2** .200" (5.08mm)  
Bat

**S3** .256" (6.5mm)  
Bat

### Important:

Toggle length changes based on bushing selected. All illustrations are shown with .350" long bushing. When using a .280" long bushing, toggle length increases .070".



**Standard Material & Finish:** Brass with Bright Chrome  
Contact factory for optional finishes.





**E** .450" (11.4mm)  
Flatted

**E2** .256" (6.5mm)  
Flatted

**E4** .840" (21.3mm)  
Flatted

**C** .571" (14.5mm)  
Color Tipped Cone  
Supplied with Cap AT445

Material: Polycarbonate



Only Available in 1- & 2-Pole

Only Available in 1- & 2-Pole





**Q** .550" (14.0mm)  
Cone

**Q2** .640" (16.26mm)  
Cone

**Q4** .840" (21.3mm)  
Cone

**D** .840" (21.3mm)  
Color Capped Cone  
Supplied with Cap AT460

Material: Polyethylene



Only Available in 1- & 2-Pole

Only Available in 1- & 2-Pole


Only Available in 1- & 2-Pole

Cap Colors Available:

**A** Black **B** White **C** Red **E** Yellow **F** Green **G** Blue **H** Gray (For K1 & K2 only)


### SMALL BUSHINGS

#### S1 1/4-40 .350" (8.9mm) Threaded with Keyway




Maximum Panel Thickness with  
Standard Hardware: .102" (2.6mm)

#### S4 6mm/.350" (8.9mm) Threaded with Keyway




Maximum Panel Thickness with  
Standard Hardware: .102" (2.6mm)

#### S2 .350" (8.9mm) Smooth with Keyway




#### A1 1/4-40 .280" (7.1mm) Threaded with Keyway




When using this bushing, toggle length is  
increased by .070". Maximum Panel Thickness  
with Standard Hardware: .031" (0.8mm)

#### A2 .280" (7.1mm) Smooth with Keyway




When using this bushing, toggle  
length is increased by .070".

#### D1 1/4-40 .350" (8.9mm) Threaded with D Flat




Maximum Panel Thickness with  
Standard Hardware: .102" (2.6mm)

#### D4 6mm/.350" (8.9mm) Threaded with D Flat




Maximum Panel Thickness with  
Standard Hardware: .102" (2.6mm)

#### D3 1/4-40 .350" (8.9mm) Threaded Splashproof with D Flat



D3 combines only with S, S2 & S3 toggles.  
Maximum Panel Thickness with  
Standard Hardware: .193" (4.9mm)

#### D8 6mm/.350" (8.9mm) Threaded Splashproof with D Flat




D8 combines only with S, S2 & S3 toggles.  
Maximum Panel Thickness with  
Standard Hardware: .193" (4.9mm)


#### Standard Hardware Supplied for Small Bushings

| Bushing Codes | S1/S4 | A1 | D1/D4 | D3/D8 | L1/L4 | L3/L8 |
|---------------|-------|----|-------|-------|-------|-------|
| Hex Nut       | 2     | 2  | 2     | 1     | 2     | 1     |
| Locking Ring  | 1     | 1  | 0     | 0     | 1     | 0     |
| Lockwasher    | 1     | 1  | 1     | 0     | 1     | 0     |
| O-ring        | 0     | 0  | 0     | 1     | 0     | 1     |


For S1, S2, A1, A2  
or S4 Bushing with  
Keyway & for L1  
or L4 Bushing



For S1, A1 or  
S4 Bushing with  
Locking Ring & for  
L1 or L4 Bushing



For D1, D4, D3 or  
D8 Bushing with  
D Flat & for L3  
or L8 Bushing







## LARGE TOGGLES

**Toggle & Bushing Combinations:** These toggles combine with the 12mm bushings B1 & B3.


**B** .453" (11.5mm)  
Large Bat



**B2** .689" (17.5mm)  
Large Bat




**R** .610" (15.5mm)  
Large Flatted



**Standard Material & Finish:** Brass with Bright Chrome  
Optional Finishes: Contact factory for satin chrome or black.

## LARGE BUSHINGS


**B1** Large .472" (12.0mm)  
Threaded with Keyway



Maximum Panel Thickness with  
Standard Hardware: .216" (5.5mm)

**Standard Hardware for B1:**  
1 hex face nut AT503M, 1 locking ring AT506M,  
1 lockwasher AT508, and 1 hex backup nut AT527M

**B3** Large .472" (12.0mm)  
Threaded Splashproof with D Flat




Maximum Panel Thickness with  
Standard Hardware: .256" (6.5mm)


**Standard Hardware for B3:**  
1 hex face nut AT503M  
and 1 o-ring AT401P

## Panel Cutouts


**For B1 Bushing  
with Keyway**



**For B1 Bushing  
with Locking Ring**




**For B3 Bushing  
with D Flat**






### LOCKING LEVER & BUSHINGS


#### LL1 1/4-40 .291" (7.4mm) Threaded with Keyway



#### LL4 6mm/.291" (7.4mm) Threaded with Keyway




#### LL2 Smooth with Keyway




Maximum Panel Thickness with Standard Hardware: .047" (1.2mm)  
Standard Hardware for L1 & L4: 2 hex nuts AT513H or AT513M,  
1 locking ring AT507H or AT507M, and 1 lockwasher AT509

#### LL3 1/4-40 .295" (7.5mm) Threaded Splashproof with D Flat



#### LL8 6mm/.295" (7.5mm) Threaded Splashproof with D Flat



Maximum Panel Thickness with Standard Hardware: .047" (1.2mm)  
Standard Hardware for L3 and L8: 1 hex nut AT513H or AT513M and 1 o-ring AT516

Lever Material & Finish: Brass with Chrome Plating

#### Locking Mechanism

on-none-on



2 positions lock

on-none-(on)




1 position locks

on-off-(on)  
on-on-(on)




2 positions lock

on-off-on  
on-on-on



3 positions lock

(on)-off-(on)  
(on)-on-(on)




1 position locks

#### No Code

Supplied with Cap AT427

Cap Material:  
Brass with Nickel Plating



Lever

Color Codes for Optional Anodized Aluminum Caps

**A** Black

**C** Red

**G** Blue

## CONTACT MATERIALS & RATINGS

**W**

Silver over Silver

Power Level

6A @ 125V AC & 3A @ 250V AC

**G**

Gold over Brass or Copper

Logic Level

6A @ 125V AC & 3A @ 250V AC

Note: See Supplement section to find complete explanation of operating range.

**A**

Gold over Silver

Power Level  
or Logic Level


6A @ 125V AC  
or 0.4VA maximum @ 28V AC/DC maximum

Note: This dual rated option is suitable when two or more identical switches are used in logic and in power circuits within the same application. See Supplement section to find complete explanation of dual rating and operating range.

## TERMINALS


**01**

Solder Lug





**02**

.062" (1.57mm) Wide Quick Connect




**03**


.250" (6.35mm) Straight PC




Single Pole



Double Pole



Three Pole




Four Pole

**05**

.425" (10.8mm) Wirewrap or Extended PC

**07**

.964" (24.5mm) Wirewrap or Extended PC



**06**

.750" (19.05mm) Wirewrap or Extended PC

**08**

1.062" (27.0mm) Wirewrap or Extended PC

If using as extended PC terminal, refer to the above footprints.


Dimension A = terminal lengths as shown beside the terminal codes at the left.

## OPTIONAL CAPS & CAP COLORS

**B**

AT415 Lever Cap for S Bat Toggle


Material: Polyethylene



**C**

AT444 Conical Cap for S Bat Toggle


Material: Polyethylene



**R**

AT434 Lever Cap for B Toggle


Material: Polyvinyl Chloride



**V**

AT406 Lever Cap for B2 Toggle

Material: Polyvinyl Chloride



Cap Colors Available:

**A**

Black

**B**

White

**C**

Red

**E**

Yellow

**F**

Green




**G**

Blue

### TYPICAL SWITCH DIMENSIONS

#### Solder Lug

#### Single Pole






M2012SS1W01

M2011 model does not have terminal 1.

#### Solder Lug

#### Double Pole






M2022SS1W01

M2021 model does not have terminals 1 & 4.

#### Solder Lug




#### Three Pole



M2032SS1W01

#### Solder Lug


#### Four Pole




M2042SS1W01

## STANDARD HARDWARE FOR SMALL & LARGE BUSHINGS


**AT513H for Inch**  
**AT513M for Metric**  
**Hex Nut**  
Brass/Nickel




**AT507H for Inch**  
**AT507M for Metric**  
**Locking Ring**  
Steel with Zinc/Chromate




**AT509**  
**Lockwasher**  
Steel with Zinc/Chromate  
(not supplied with splashproof models)




**AT516**  
**O-ring for**  
**Splashproof Models**  
Nitrile Butadiene Rubber




**AT503M**  
**Hex Face Nut**  
Brass/Chrome




**AT506M**  
**Locking Ring**  
Steel with Zinc/Chromate




**AT508**  
**Lockwasher**  
Steel with Zinc/Chromate  
(not supplied with splashproof models)



**AT527M**  
**Hex Nut**  
Steel with Nickel Plating




**AT401P**  
**O-ring for Splashproof Models**  
Nitrile butadiene rubber




## OPTIONAL SPLASHPROOF BOOTS

Various optional nuts and ON-OFF plates are available; dimensions are shown in the Accessories & Hardware section.


**AT428 (M-metric H-Inch)**  
**.445" (11.3mm)**  
**Boot for S Toggle**  
Silicon Rubber




**AT402**  
**.760" (19.3mm)**  
**Boot for B2 Toggle**  
Silicon Rubber




**AT402S**  
**.567" (14.4mm)**  
**Boot for B Toggle**  
Silicon Rubber



**AT401A/H/S**  
**.461" (11.7mm)**  
**Boot, Nut and O-ring for B2 Toggle**  
More details in Accessories section



**AT4181** ← NEW  
**.732" (18.6mm)**  
**Boot, Nut and O-ring for B2 Toggle**  
More details in Accessories section



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9