

			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>010</td><td>RELEASED</td><td>PATLAN 2/13/2008</td><td></td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	010	RELEASED	PATLAN 2/13/2008																																																			
			REVISIONS																																																																	
			REV	DESCRIPTION	DATE	APPROVED																																																														
010	RELEASED	PATLAN 2/13/2008																																																																		
<table><tr><td colspan="2">DESIGNED FOR USE WITH</td></tr><tr><td colspan="2">RG 174, 316/U CABLE</td></tr><tr><td colspan="2">CABLE ENTRY DIAMETER</td></tr><tr><td colspan="2">MINIMUM</td></tr><tr><td>SLEEVE</td><td>.067</td></tr><tr><td>CONTACT</td><td>.021</td></tr></table>				DESIGNED FOR USE WITH		RG 174, 316/U CABLE		CABLE ENTRY DIAMETER		MINIMUM		SLEEVE	.067	CONTACT	.021																																																					
DESIGNED FOR USE WITH																																																																				
RG 174, 316/U CABLE																																																																				
CABLE ENTRY DIAMETER																																																																				
MINIMUM																																																																				
SLEEVE	.067																																																																			
CONTACT	.021																																																																			
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A, Fig. 310.2</td><td>Temperature Rating -65°C To +165°C</td></tr><tr><td>Frequency Range (GHz) DC to 3.0</td><td>Recommended Mating Torque N/A</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 250</td><td>Mating Characteristics:</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR -- 1.15 + .01 X (f GHz)</td><td>Insertion (MAX Lbs) 3</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C</td></tr><tr><td>Insertion Loss .06 V/F (GHz)</td><td>Withdrawal (MIN Oz) 1</td><td>Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td>RF Leakage (dB MIN) -60dB Min @ 2-3 GHz</td><td>Force to Engage and Disengage (In-Lbs MAX) 2</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 190</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750</td><td>Axial (Lbs) 6.0 MIN</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Radial (In-Oz) N/A</td><td></td></tr><tr><td>Center Contact 3.0</td><td>Cable Retention</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Axial Force (Lbs) 20 MIN</td><td></td></tr><tr><td>Cable to Housing .05</td><td>Torque (In-Oz) N/A</td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500</td><td>Weight (Grams) TBD</td><td></td></tr><tr><td>I.R.(Megohms MIN) 10,000</td><td></td><td></td></tr></table>			ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating -65°C To +165°C	Frequency Range (GHz) DC to 3.0	Recommended Mating Torque N/A	Vibration MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics:	Shock MIL-STD-202, Method 213, Condition I	VSWR -- 1.15 + .01 X (f GHz)	Insertion (MAX Lbs) 3	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C	Insertion Loss .06 V/F (GHz)	Withdrawal (MIN Oz) 1	Moisture Resistance MIL-STD-202, Method 106	RF Leakage (dB MIN) -60dB Min @ 2-3 GHz	Force to Engage and Disengage (In-Lbs MAX) 2	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	Corona, 70,000 Ft (VRMS MIN) 190	Center Contact Captivation		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Axial (Lbs) 6.0 MIN		Contact Resistance (Milliohms MAX)	Radial (In-Oz) N/A		Center Contact 3.0	Cable Retention		Outer Contact 2.0	Axial Force (Lbs) 20 MIN		Cable to Housing .05	Torque (In-Oz) N/A		RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500	Weight (Grams) TBD		I.R.(Megohms MIN) 10,000			<table><tr><th>COMPONENT</th><th>MATERIAL</th><th>FINISH</th></tr><tr><td>HOUSING COUPLING NUT</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>PTFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>FERRULE</td><td>COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>REAR DIELECTRIC</td><td>NYLON</td><td>N/A</td></tr></table>			COMPONENT	MATERIAL	FINISH	HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204	REAR DIELECTRIC	NYLON	N/A
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																		
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating -65°C To +165°C																																																																		
Frequency Range (GHz) DC to 3.0	Recommended Mating Torque N/A	Vibration MIL-STD-202, Method 204, Condition D																																																																		
Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics:	Shock MIL-STD-202, Method 213, Condition I																																																																		
VSWR -- 1.15 + .01 X (f GHz)	Insertion (MAX Lbs) 3	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C																																																																		
Insertion Loss .06 V/F (GHz)	Withdrawal (MIN Oz) 1	Moisture Resistance MIL-STD-202, Method 106																																																																		
RF Leakage (dB MIN) -60dB Min @ 2-3 GHz	Force to Engage and Disengage (In-Lbs MAX) 2	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																																		
Corona, 70,000 Ft (VRMS MIN) 190	Center Contact Captivation																																																																			
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Axial (Lbs) 6.0 MIN																																																																			
Contact Resistance (Milliohms MAX)	Radial (In-Oz) N/A																																																																			
Center Contact 3.0	Cable Retention																																																																			
Outer Contact 2.0	Axial Force (Lbs) 20 MIN																																																																			
Cable to Housing .05	Torque (In-Oz) N/A																																																																			
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500	Weight (Grams) TBD																																																																			
I.R.(Megohms MIN) 10,000																																																																				
COMPONENT	MATERIAL	FINISH																																																																		
HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																																		
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																		
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																		
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204																																																																		
REAR DIELECTRIC	NYLON	N/A																																																																		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES <table><tr><td>FRAC. ± 1/64</td><td>DEC. ± .005</td><td>ANGLES ± 1°</td></tr></table> These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°	<table><tr><td>DRAWN BY</td><td>PATLAN</td><td>DATE</td><td>2/12/98</td></tr><tr><td>CHECKED BY</td><td></td><td></td><td></td></tr><tr><td>APP'D BY</td><td></td><td>4/3/98</td><td></td></tr><tr><td colspan="4">USE ASS'Y PROCEDURE</td></tr><tr><td colspan="4">NO. AP. 20-530 408-04927</td></tr></table>			DRAWN BY	PATLAN	DATE	2/12/98	CHECKED BY				APP'D BY		4/3/98		USE ASS'Y PROCEDURE				NO. AP. 20-530 408-04927				<table><tr><td colspan="4"></td></tr><tr><td colspan="4">AMP Incorporated</td></tr><tr><td colspan="4">140 Fourth Avenue</td></tr><tr><td colspan="4">Waltham, MA 02451-7599</td></tr><tr><td colspan="4">TITLE OSM FLANGE MOUNT CABLE JACK-SOLDER ATTACHMENT M39012/58-3007 CATA</td></tr><tr><td>SIZE</td><td>B</td><td>CODE IDENT NO.</td><td>26805</td></tr><tr><td colspan="2">SCALE</td><td>4 : 1</td><td></td></tr><tr><td colspan="2"></td><td></td><td>SHEET 1 OF 1</td></tr></table>							AMP Incorporated				140 Fourth Avenue				Waltham, MA 02451-7599				TITLE OSM FLANGE MOUNT CABLE JACK-SOLDER ATTACHMENT M39012/58-3007 CATA				SIZE	B	CODE IDENT NO.	26805	SCALE		4 : 1					SHEET 1 OF 1					
FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°																																																																		
DRAWN BY	PATLAN	DATE	2/12/98																																																																	
CHECKED BY																																																																				
APP'D BY		4/3/98																																																																		
USE ASS'Y PROCEDURE																																																																				
NO. AP. 20-530 408-04927																																																																				
AMP Incorporated																																																																				
140 Fourth Avenue																																																																				
Waltham, MA 02451-7599																																																																				
TITLE OSM FLANGE MOUNT CABLE JACK-SOLDER ATTACHMENT M39012/58-3007 CATA																																																																				
SIZE	B	CODE IDENT NO.	26805																																																																	
SCALE		4 : 1																																																																		
			SHEET 1 OF 1																																																																	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9