

		REVISIONS																																																							
		REV	DESCRIPTION	DATE	APPROVED																																																				
		01 ₁	REVISED	KYLE 9-8-97	 9/9/97																																																				
<table><tr><td colspan="2">ELECTRICAL</td><td colspan="2">MECHANICAL</td></tr><tr><td colspan="2">Nominal Impedance (Ohms) <u>50</u></td><td colspan="2">Interface Dimensions MIL-STD-348A,</td></tr><tr><td colspan="2">Frequency Range (GHz) DC to <u>10.0</u></td><td colspan="2">Fig. SMC: 312-2, SMA: 310-1</td></tr><tr><td colspan="2">VSWR <u>1.03 + .007f(GHz)</u></td><td colspan="2">Force to Engage and SMA SMC</td></tr><tr><td colspan="2">Dielectric Withstanding Voltage</td><td colspan="2">Disengage (In-Lbs MAX) <u>2.0</u> <u>1.0</u></td></tr><tr><td colspan="2">(VRMS MIN) @ Sea Level <u>1,000</u></td><td colspan="2">Center Contact Captivation</td></tr><tr><td colspan="2">Contact Resistance (Milliohms MAX)</td><td colspan="2">Axial (Lbs) <u>6.0</u></td></tr><tr><td colspan="2">Center Contact <u>6.0</u></td><td colspan="2">Radial (In-Oz) <u>4.0</u></td></tr><tr><td colspan="2">I.R.(Megohms MIN) <u>1,000</u></td><td colspan="2"><u>.XXX</u> = in</td></tr><tr><td colspan="2"></td><td colspan="2"><u>XX.X</u> = mm (REF)</td></tr></table>		ELECTRICAL		MECHANICAL		Nominal Impedance (Ohms) <u>50</u>		Interface Dimensions MIL-STD-348A,		Frequency Range (GHz) DC to <u>10.0</u>		Fig. SMC: 312-2, SMA: 310-1		VSWR <u>1.03 + .007f(GHz)</u>		Force to Engage and SMA SMC		Dielectric Withstanding Voltage		Disengage (In-Lbs MAX) <u>2.0</u> <u>1.0</u>		(VRMS MIN) @ Sea Level <u>1,000</u>		Center Contact Captivation		Contact Resistance (Milliohms MAX)		Axial (Lbs) <u>6.0</u>		Center Contact <u>6.0</u>		Radial (In-Oz) <u>4.0</u>		I.R.(Megohms MIN) <u>1,000</u>		<u>.XXX</u> = in				<u>XX.X</u> = mm (REF)		<table><tr><td>HOUSING COUPLING NUT</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>PTFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>RETAINING RING</td><td>BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H</td><td>N/A</td></tr><tr><td>GASKET</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr></table>	HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A	GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
ELECTRICAL		MECHANICAL																																																							
Nominal Impedance (Ohms) <u>50</u>		Interface Dimensions MIL-STD-348A,																																																							
Frequency Range (GHz) DC to <u>10.0</u>		Fig. SMC: 312-2, SMA: 310-1																																																							
VSWR <u>1.03 + .007f(GHz)</u>		Force to Engage and SMA SMC																																																							
Dielectric Withstanding Voltage		Disengage (In-Lbs MAX) <u>2.0</u> <u>1.0</u>																																																							
(VRMS MIN) @ Sea Level <u>1,000</u>		Center Contact Captivation																																																							
Contact Resistance (Milliohms MAX)		Axial (Lbs) <u>6.0</u>																																																							
Center Contact <u>6.0</u>		Radial (In-Oz) <u>4.0</u>																																																							
I.R.(Megohms MIN) <u>1,000</u>		<u>.XXX</u> = in																																																							
		<u>XX.X</u> = mm (REF)																																																							
HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																							
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A																																																							
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																							
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A																																																							
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																																							
<table><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td></tr><tr><td>FRAC. ± 1/64</td><td>DEC. ±.005</td><td>ANGLES ± 1°</td></tr><tr><td colspan="3">DRAWN BY S.G DATE 10-28-87</td></tr><tr><td colspan="3">CHECKED BY S.A 11-3-87</td></tr><tr><td colspan="3">APPD BY B.C 11-6-87</td></tr><tr><td colspan="3">These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td></tr><tr><td colspan="3">USE ASSY PROCEDURE</td></tr><tr><td colspan="3">NO. A.P. <u>N/A</u></td></tr></table>		COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			FRAC. ± 1/64	DEC. ±.005	ANGLES ± 1°	DRAWN BY S.G DATE 10-28-87			CHECKED BY S.A 11-3-87			APPD BY B.C 11-6-87			These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			USE ASSY PROCEDURE			NO. A.P. <u>N/A</u>			<table><tr><td colspan="4"></td></tr><tr><td colspan="4">AMP Incorporated</td></tr><tr><td colspan="4">140 Fourth Avenue</td></tr><tr><td colspan="4">Waltham, MA 02451-7599</td></tr><tr><td colspan="4">TITLE "OSM" PLUG TO "SMC" PLUG ADAPTER</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>5081-2241-00</td><td>REV 01₁</td></tr><tr><td colspan="2">SCALE 6:1</td><td colspan="2">SHEET 1 OF 1</td></tr></table>					AMP Incorporated				140 Fourth Avenue				Waltham, MA 02451-7599				TITLE "OSM" PLUG TO "SMC" PLUG ADAPTER				SIZE B	CODE IDENT NO. 26805	5081-2241-00	REV 01 ₁	SCALE 6:1		SHEET 1 OF 1	
COMPONENT	MATERIAL	FINISH																																																							
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES																																																									
FRAC. ± 1/64	DEC. ±.005	ANGLES ± 1°																																																							
DRAWN BY S.G DATE 10-28-87																																																									
CHECKED BY S.A 11-3-87																																																									
APPD BY B.C 11-6-87																																																									
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.																																																									
USE ASSY PROCEDURE																																																									
NO. A.P. <u>N/A</u>																																																									
AMP Incorporated																																																									
140 Fourth Avenue																																																									
Waltham, MA 02451-7599																																																									
TITLE "OSM" PLUG TO "SMC" PLUG ADAPTER																																																									
SIZE B	CODE IDENT NO. 26805	5081-2241-00	REV 01 ₁																																																						
SCALE 6:1		SHEET 1 OF 1																																																							

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9