

New Metcal MX-500 Soldering and Rework System



Metcal's MX-500 Soldering and Rework System has been reimagined, adding features and a new look to a bench top icon. The system utilizes SmartHeat® Technology, wherein each cartridge is equipped with a self-regulating heater which 'senses' its own temperature and closely maintains its pre-set idle temperature for the life of the heater-tip. The tip temperature is determined by the inherent metallurgical properties of the heater; no external adjustment or equipment is required. The MX-500 retains switchable dual port, 40W operation while introducing numerous new features in a new housing.

FEATURES AND BENEFITS

- **Integrated Power Indication Meter:** a built in net power meter which will display a graphical and numerical representation of the power applied to the cartridge.
- **User Programmable PowerSave Mode:** the time to enter PowerSave Mode is adjustable from 10 to 120 minutes.
- **Ground Fault Interrupt:** AC ground monitor detects power line ground failures and immediately alerts the operator and shuts down the system. Only after the power line ground has been restored, can the MX-500 be restarted and soldering operations can be resumed.
- **Universal Power Supply:** automatically senses the input line voltage and adjusts accordingly, which allows for worldwide operation without adaptors or a change in performance.
- **Compatibility with all MX products:** the MX-500 redesign allows full compatibility with existing and previous MX upgrade kits, tip-cartridges, hand-pieces and accessories.
- **Greater process control with SmartHeat® Technology**
- **Reduced space requirements**

MX-500 SYSTEMS CONFIGURATION & UPGRADE KITS

ONE HAND-PIECE SYSTEM

MX-500S Soldering / Rework System
Power supply, MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand




POWER SUPPLY WITHOUT HAND-PIECE

MX-500P: MX-500 dual port switchable power supply

UPGRADE KITS

MX-UK1: MX-H1-AV Advanced Soldering and Rework Hand-piece with MX-W1AV TipSaver Workstand



TWO HAND-PIECE SYSTEMS

MX-500SPT Rework System
Power supply, MX-PTZ precision tweezer hand-piece with MX-W4PT TipSaver workstand and MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



MX-UK2: MX-H2-UF Ultra Fine Soldering and Rework Hand-piece with MX-W1AV TipSaver Workstand



MX-500DS Desoldering System
Power supply, MX-DS1 desoldering hand-piece with MX-W5DS TipSaver workstand and MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



MX-UK4: MX-PTZ Precision Tweezers Hand-piece with MX-W4PT TipSaver Workstand



MX-UK5: MX-DS1 Desoldering Hand-piece with MX-W5DS TipSaver Workstand



MX-TALON-01: MX-Talon Tweezer Hand-piece with WST Workstand



www.metcal.com

HAND SOLDERING SERIES

New Metcal MX-500 Soldering and Rework System



HAND-PIECES AND CARTRIDGE SERIES

The MX-500 Series offers users a choice of hand-pieces to meet the customer's application needs. Each hand-piece has its own range of cartridges with many choices available for tip geometry and temperature.

MX-RM3E



MX-H1-AV



MX-H2-UF



TALON



MX-PTZ



MX-DS1



STTC Soldering & SMT Rework



UFTC Ultra-Fine



TATC TALON



PTTC Tweezers



STDC Desolder



These six hand-pieces are compatible with the Metcal MX-500 and MX-5200 Soldering and Rework Systems.

ACCESSORIES

AC-Y10	Yellow sponge, pack of 10	WS1	Sleeper Soldering Workstand
AC-BP	Brass pad, pack of 10	MX-W1AV	TipSaver Soldering Workstand
AC-BRUSH	Soft Brass brush	MX-W4PT	TipSaver Precision Tweezer Workstand
MX-CP1	Cartridge removal pad	MX-W5DS	TipSaver Desoldering Workstand
AC-TC	Desolder Tip Cleaner	WST	Talon Workstand

TECHNICAL SPECIFICATIONS

Ambient Operating Temperature	10 to 40°C
Maximum Enclosure Temperature	55°C
Input Line Voltage	100 – 240 VAC, grounded circuit
Input Line Frequency	50/60 Hz
Rated Power Consumption	70 Watts
Output Power	40 Watts max. *
Output Frequency	13.56 MHz *
Power Supply Dimensions w x d x h	12.1cm (4.8") x 12.1cm (4.8") x 22.2cm (8.8")
Certification / Marking	cNRTLus, CE
Tip-to- Ground Potential	<2mV
Tip-to-Ground Resistance	<2 ohms
Idle Temperature Stability	± 1.1°C in still air
Hand-piece Cable Length	L=183cm (72"), burn proof, ESD safe
Hand-piece Connector	F connector
Weight of the power supply	2.65 Kg (5.85 lbs)

* RF SmartHeat Technology provides greater power.
More details at www.metcal.com/smartheat



HAND SOLDERING SERIES

www.metcal.com

10/2013

METCAL

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9