

K5V

Illuminated Tact Switch



Features

- Gold plated dome contact SPST/SPDT
- Excellent ergonomics
- High bright leds
- Reduced space usage on board
- 40 N overload
- Tape and reel
- RoHS compliant and compatible

Typical Applications

- When backlighting and switch are required to be a "2 in 1" component
- The dome contact secures a superior contact reliability in time
- The ergonomics of K5V provides a long travel, a sharp tactile feel and an audible click
- Server, storage, automotive, network infrastructure, medical

Specification

FUNCTION: momentary action

CONTACT ARRANGEMENT: Normally Open + Normally Closed

TERMINALS:

THT: Through hole terminals with positioning pegs

SMT: Surface mount terminals with positioning pegs

PM: Panel mount solder terminals with wire hole

Electrical

POWER MIN/MAX: 0.02VA / 1.0VA

VOLTAGE MIN/MAX: 20mVdc – 32 Vdc

CURRENT MIN/MAX: 0.1mA – 100mA

CONTACT RESISTANCE: <150m Ω

INSULATION RESISTANCE: >1G Ω initial, >10M Ω after damp heat

BOUNCE TIME: <5ms

Environmental

OPERATING TEMPERATURE: -40°C to 85°C

STORAGE TEMPERATURE: -50°C to 85°C

RELATIVE HUMIDITY: 90 to 96% according to NF EN 60068-2-30

PROTECTION: dust protection and flux tight

OVERLOAD: 40N min

Mechanical

Version	Operating force FA ¹ Newtons (grams)	Operating life (operations)	Travel (total travel) mm(mm)
THT, SMT, PM	4.0 (400)	25,000	1.2 (2.4)

¹ Tolerances of operating force FA is ± 25%.

Packaging

THT:

60 pieces per tray; 1800 pieces per box

SMT:

330 pieces per reel (reel ø 360mm); 1320 pieces per box

PM:

60 pieces per tray; 2100 pieces per box

Process

SMT

Soldering: Compatible with the lead free soldering profile
No washing

THT

Soldering: Compatible with the lead free soldering profile
No washing

PM

Soldering: Low wattage soldering iron (25-50 watts max).
Solder time 3 seconds max. No washing

Materials

LEAD FREE


CONTACTS: Au over Ni

SOLDERING: Au over Ni



HOUSING: Thermoplastic UL94 V0

How To Order

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and and place it in the appropriate box.




Tactile Switches

[illegible]

The diagrams show the following connections:

- Single Color LED:** Pin 1 is connected to the anode (triangle symbol) of the LED. Pin 2 is connected to the cathode (line symbol) of the LED. Pin 4 is connected to the common ground. Pin 3 is connected to the other terminal of the LED, which is also labeled 'A' and 'C'.
- Bi-Color LED - YG:** Pin 1 is connected to the anode of the yellow LED. Pin 2 is connected to the cathode of the yellow LED. Pin 3 is connected to the anode of the green LED. Pin 4 is connected to the cathode of the green LED. The common ground is connected to the other terminal of the green LED, which is also labeled 'AG/CY' and 'CG/AY'.
- Bi-Color LED - RG:** Pin 1 is connected to the anode of the red LED. Pin 2 is connected to the cathode of the red LED. Pin 3 is connected to the anode of the green LED. Pin 4 is connected to the cathode of the green LED. The common ground is connected to the other terminal of the green LED, which is also labeled 'AG/CR' and 'CG/AR'.





TOP VIEW

Areas important for switch stability on PCB

Dimensions (mm) and (inches):

- Top horizontal dimensions: 1.2 (.047), 5.8 (.228), 1.2 (.047)
- Top internal horizontal dimensions: 1.9 (.075), 1.9 (.075)
- Left vertical dimensions: 2 (.079), 3.5 (.138), 2 (.079)
- Right vertical dimensions: 4.05 (.159), 0.85 (.033), 4.2 (.165), 0.85 (.033)
- Bottom horizontal dimensions: 1.4 (.055), 7 (.276)
- Bottom circular feature: $\varnothing 1.35 \pm 0.05$ ($\varnothing .053 \pm .002$)



Labels: 1, 2, 3, 4, A, B, C



First Angle Projection

C&K

Tactile Switches




Dimensions are shown: mm
Specifications and dimensions subject to change

K5V Illuminated Tact Switch


Tactile Switches

K5V PM


PRODUCT IDENTIFICATION AND DATE CODES



ELECTRICAL DIAGRAM




TERMINAL REFERENCES



TRAY

SUITABLE FOR PANEL THICKNESS OF 1.8MM MAX



Dimensions are shown: mm
Specifications and dimensions subject to change

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9