Power MOSFET, N-Channel, SUPERFET® III, Easy Drive, 650 V, 6 A, 600 m Ω

Description

SUPERFET III MOSFET is ON Semiconductor's brand-new high voltage super-junction (SJ) MOSFET family that is utilizing charge balance technology for outstanding low on-resistance and lower gate charge performance. This advanced technology is tailored to minimize conduction loss, provide superior switching performance, and withstand extreme dv/dt rate. Consequently, SUPERFET III MOSFET Easy drive series helps manage EMI issues and allows for easier design implementation.

Features

- 700 V @ $T_J = 150$ °C
- Typ. $R_{DS(on)} = 474 \text{ m}\Omega$
- Ultra Low Gate Charge (Typ. Q_g = 11 nC)
- Low Effective Output Capacitance (Typ. Coss(eff.) = 127 pF)
- 100% Avalanche Tested
- These Devices are Pb-Free and are RoHS Compliant

Applications


- Computing / Display Power Supplies
- Telecom / Server Power Supply
- Industrial Power Supplies
- Lighting / Charger / Adapter




ON Semiconductor®

www.onsemi.com

| V _{DSS} | R _{DS(ON)} MAX | I _D MAX |
|------------------|-------------------------|--------------------|
| 650 V | 600 mΩ @ 10 V | 6 A |




N-Channel MOSFET



TO-220F CASE 340BF

MARKING DIAGRAM



\$Y = ON Semiconductor Logo &Z = Assembly Plant Code &3 = Numeric Date Code

&K = Lot Code

FCPF600N65S3R0 = Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C, Unless otherwise specified)

| Symbol | Parameter | | Value | Unit |
|-----------------------------------|--|-------------------------------------|-------------|------|
| V _{DSS} | Drain to Source Voltage | | 650 | V |
| V _{GSS} | Gate to Source Voltage | DC | ±30 | V |
| | | AC (f > 1 Hz) | ±30 | V |
| I _D | Drain Current | Continuous (T _C = 25°C) | 6* | А |
| | | Continuous (T _C = 100°C) | 3.8* | 1 |
| I _{DM} | Drain Current | Pulsed (Note 1) | 15* | А |
| E _{AS} | Single Pulsed Avalanche Energy (Note 2) | | 24 | mJ |
| I _{AS} | Avalanche Current (Note 2) | | 1.6 | А |
| E _{AR} | Repetitive Avalanche Energy (Note 1) | | 0.24 | mJ |
| dv/dt | MOSFET dv/dt | | 100 | V/ns |
| | Peak Diode Recovery dv/dt (Note 3) | | 20 | |
| P _D | Power Dissipation | (T _C = 25°C) | 24 | W |
| | | Derate Above 25°C | 0.19 | W/°C |
| T _J , T _{STG} | Operating and Storage Temperature Range | | -55 to +150 | °C |
| TL | Maximum Lead Temperature for Soldering, 1/8" from Case for 5 s | | 300 | °C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
*Drain current limited by maximum junction temperature.

THERMAL CHARACTERISTICS

| Symbol | Parameter | FCPF600N65S3R0L | Unit | |
|----------------|---|-----------------|------|--|
| $R_{	hetaJC}$ | Thermal Resistance, Junction to Case, Max. | 5.29 | °C/W | |
| $R_{	heta JA}$ | Thermal Resistance, Junction to Ambient, Max. | 62.5 | C/VV | |

PACKAGE MARKING AND ORDERING INFORMATION

| Part Number | Top Marking | Package | Packing Method | Reel Size | Tape Width | Quantity |
|-----------------|----------------|---------|----------------|-----------|------------|----------|
| FCPF600N65S3R0L | FCPF600N65S3R0 | TO-220F | Tube | N/A | N/A | 50 Units |

^{1.} Repetitive rating: pulse-width limited by maximum junction temperature.
2. $I_{AS} = 1.6 \text{ A}$, $R_G = 25 \Omega$, starting $T_J = 25^{\circ}\text{C}$.
3. $I_{SD} \le 3 \text{ A}$, di/dt $\le 200 \text{ A}/\mu\text{s}$, $V_{DD} \le 400 \text{ V}$, starting $T_J = 25^{\circ}\text{C}$.

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

| Symbol | Parameter | Test Conditions | Min | Тур | Max | Unit |
|--|--|--|-----|------|------|------|
| OFF CHARACT | ERISTICS | | | | | |
| BV _{DSS} | Drain to Source Breakdown Voltage | $V_{GS} = 0 \text{ V, } I_D = 1 \text{ mA, } T_J = 25^{\circ}\text{C}$ | 650 | _ | _ | V |
| | | V _{GS} = 0 V, I _D = 1 mA, T _J = 150°C | 700 | - | _ | V |
| $\Delta BV_{DSS} \! / \! \Delta T_{J}$ | Breakdown Voltage Temperature Coefficient | I _D = 1 mA, Referenced to 25°C | - | 0.66 | - | V/°C |
| I _{DSS} | Zero Gate Voltage Drain Current | V _{DS} = 650 V, V _{GS} = 0 V | - | - | 1 | μΑ |
| | | V _{DS} = 520 V, T _C = 125°C | - | 0.3 | _ | |
| I _{GSS} | Gate to Body Leakage Current | V _{GS} = ±30 V, V _{DS} = 0 V | - | - | ±100 | nA |
| ON CHARACTE | ERISTICS | | | | | |
| V _{GS(th)} | Gate Threshold Voltage | $V_{GS} = V_{DS}$, $I_D = 0.6 \text{ mA}$ | 2.5 | - | 4.5 | V |
| R _{DS(on)} | Static Drain to Source On Resistance | V _{GS} = 10 V, I _D = 3 A | - | 474 | 600 | mΩ |
| 9 _{FS} | Forward Transconductance | V _{DS} = 20 V, I _D = 3 A | - | 3.6 | - | S |
| DYNAMIC CHA | RACTERISTICS | | | | | |
| C _{iss} | Input Capacitance | V _{DS} = 400 V, V _{GS} = 0 V, f = 1 MHz | - | 465 | - | pF |
| C _{oss} | Output Capacitance | | - | 10 | _ | pF |
| C _{oss(eff.)} | Effective Output Capacitance | V _{DS} = 0 V to 400 V, V _{GS} = 0 V | - | 127 | _ | pF |
| C _{oss(er.)} | Energy Related Output Capacitance | V _{DS} = 0 V to 400 V, V _{GS} = 0 V | - | 17 | _ | pF |
| Q _{g(tot)} | Total Gate Charge at 10V | V _{DS} = 400 V, I _D = 3 A, V _{GS} = 10 V | - | 11 | - | nC |
| Q _{gs} | Gate to Source Gate Charge | (Note 4) | - | 3 | _ | nC |
| Q _{gd} | Gate to Drain "Miller" Charge | | - | 4.9 | _ | nC |
| ESR | Equivalent Series Resistance | f = 1 MHz | - | 0.9 | - | Ω |
| SWITCHING CH | HARACTERISTICS | | | _ | | |
| t _{d(on)} | Turn-On Delay Time | V _{DD} = 400 V, I _D = 3 A, | - | 11 | - | ns |
| t _r | Turn-On Rise Time | $V_{GS} = 10 \text{ V}, R_g = 4.7 \Omega$ (Note 4) | - | 9 | - | ns |
| t _{d(off)} | Turn-Off Delay Time | | - | 29 | - | ns |
| t _f | Turn-Off Fall Time | | - | 14 | - | ns |
| SOURCE-DRAI | N DIODE CHARACTERISTICS | | • | | | • |
| I _S | Maximum Continuous Source to Drain | Diode Forward Current | _ | _ | 6 | Α |
| I _{SM} | Maximum Pulsed Source to Drain Diod | e Forward Current | _ | - | 15 | Α |
| V_{SD} | Source to Drain Diode Forward Voltage | V _{GS} = 0 V, I _{SD} = 3 A | _ | - | 1.2 | V |
| t _{rr} | Reverse Recovery Time | V _{GS} = 0 V, I _{SD} = 3 A, | _ | 198 | - | ns |
| Q _{rr} | Reverse Recovery Charge | dI _F /dt = 100 A/μs | _ | 1.6 | - | μС |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Essentially independent of operating temperature typical characteristics.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance Variation vs. Drain Current and Gate Voltage




Figure 5. Capacitance Characteristics




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and




Figure 6. Gate Charge Characteristics

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)




Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 11. Eoss vs. Drain to Source Voltage




Figure 8. On-Resistance Variation vs. Temperature




Figure 10. Maximum Drain Current vs. Case Temperature

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)




Figure 12. Transient Thermal Response Curve




Figure 13. Gate Charge Test Circuit & Waveform




Figure 14. Resistive Switching Test Circuit & Waveforms




Figure 15. Unclamped Inductive Switching Test Circuit & Waveforms





Figure 16. Peak Diode Recovery dt/dt Test Circuit & Waveforms

SUPERFET is a registered trademark of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries.

TO-220 FULLPAK 3LD CASE 340BF ISSUE O

DATE 31 AUG 2016



| DOCUMENT NUMBER: | 98AON13839G | Electronic versions are uncontrolled except accessed directly from the Document Repository. versions are uncontrolled except when stan | | |
|------------------|---------------------------|--|-------------|--|
| STATUS: | ON SEMICONDUCTOR STANDARD | | ' ' | |
| NEW STANDARD: | | "CONTROLLED COPY" in red. | | |
| DESCRIPTION: | TO-220 FULLPAK 3LD | | PAGE 1 OF 2 | |



| DOCUMEN | T7NUMBER: |
|----------|-----------|
| 98AON138 | 39G |

PAGE 2 OF 2

| ISSUE | REVISION | DATE |
|-------|---|-------------|
| 0 | RELEASED FOR PRODUCTION FROM FAIRCHILD TO220V03 TO ON SEMICONDUCTOR. REQ. BY B. NG. | 31 AUG 2016 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

ON Semiconductor and una are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. arising out of the application to use of any product or circuit, and specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death. associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

Europe, Middle East and Africa Technical Support:

Phone: 421 33 790 2910

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru_4 moschip.ru_9