

SPECIFICATION CONTROL DRAWING

55PC1233

TITLE

THREE CONDUCTOR CABLE, SHIELDED, JACKETED, 600 VOLT

Date

5-26-00

Revision


A

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0213

SHIELD - NICKEL-COATED COPPER

JACKET - RADIATION-CROSSLINKED,
MODIFIED ETFE



CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (in.)		DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
			LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC1233-26-*	26	38	.0055	.0070	.102	.107	.112	9.89	10.39
55PC1233-24-*	24	38	.0060	.0075	.113	.118	.123	12.42	12.93
55PC1233-22-*	22	38	.0060	.0075	.126	.131	.136	16.05	16.62
55PC1233-20-*	20	38	.0060	.0075	.144	.149	.154	21.74	22.41
55PC1233-18-*	18	38	.0060	.0080	.166	.171	.176	29.93	30.81
55PC1233-16-*	16	38	.0060	.0080	.182	.187	.192	36.40	37.38
55PC1233-14-*	14	38	.0060	.0080	.214	.219	.224	52.21	53.41
55PC1233-12-*	12	38	.0060	.0080	.254	.260	.266	75.71	77.19
55PC1233-10-*	10	36	.0070	.0090	.311	.320	.329	118.63	121.46
55PC1233-8-*	8	34	.0070	.0090	.458	.471	.483	215.79	222.03

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms)

CROSSLINKING PROOF TEST: 300 ± 3°C for 1 hour

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz

JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 50% (minimum)

Tensile Strength, 5000 lbf/in² (minimum)

JACKET FLAWS:

Spark Test, 1000 volts (rms) 100% test

Impulse Dielectric Test, 6.0 kV (peak), 100 % test

SHIELD COVERAGE: 85% (minimum)

VOLTAGE WITHSTAND TEST (POST ENVIRONMENTAL):

1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:

The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.

Example: AWG 22, red, blue and yellow component wires; white jacket: 55PC1233-22-2/6/4-9

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

Raychem

300 Constitution Drive, Menlo Park, California 94025
1-800-2 Raychem Fax: 1-650-361-6297

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

[55PC1233-8-2/4/6-9CS2970](#) [55PC1233-22-9/93/96-9](#) [55PC1233-24-3/6/9-9](#) [55PC1233-22-2/4/6-9](#) [55PC1233-10-2/4/6-9CS2970](#) [55PC1233-12-MST3-9CS2861](#) [55PC1233-22-MST3-9CS2861](#) [55PC1233-20-9/93/96-9](#) [55PC1233-22-3/6/9-9CS2712](#) [55PC1233-20-MST3-9CS2861](#) [55PC1233-16-MST3-9CS2861](#) [55PC1233-24-2/4/6-9](#) [55PC1233-20-2/4/6-9](#) [55PC1233-8-2/4/6-9CS2502](#) [55PC1233-20-2/4/6-9CS2502](#)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9