The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.

Fixed Attenuators (SMA Type)

AT-100, AT-200, and AT-300 Series



AT-103(40)



AT-206(40)



AT-310(40)

■Features

1.Abundant Variations of Attenuators

Attenuation amounts are available in abundant variations from 0 to 4 dB in 0.5 dB steps, from 4 to 10 dB in 1 dB steps, and in 12, 13, 14, 15, 20, 26 and 30 dB so that levels can be finely adjusted.

2.SMA Type

The coupling portions are available in all types of plug and jack combinations and stainless steel is used for the external cladding to form a small and durable structure.

3.High Degree of Matching and High Reliability

The design of the attenuation element uses a distributed constant circuit and metal film resistor. A high degree of matching is achieved as indicated in the VSWR of the appended tables. Furthermore, these attenuators show stable characteristics for environments of varying temperature, humidity, and gases.

■Product Specifications

Ratings	Rated frequency range (Note) Characteristic impedance Maximum Input Power	DC to 18.0 GHz 50 ohms 1 W	Operating temperature range Operating relative humidity	–10℃ to +65℃ 95% Max.

Note: The frequency range will differ depending on the model.

Item	Standard	Conditions
1.Vibration	No electrical discontinuity of 1 μs or more No damage, cracks, or parts dislocation	Frequency of 10 to 2000 Hz, overall amplitude of 1.52 mm, acceleration of 98 m/s² for 2 hours in each of 3 directions
2.Shock		Acceleration of 490 m/s², sine half-wave waveform, 3 cycles in each of the 3 axis
3.Temperature cycle	No damage, cracks, or parts dislocation	Temperature: -55℃ → +15℃ to +35℃ → +85℃ → +15℃ to +35℃ Time: 30 → 15 max. → 30 → 15 max. (Minutes) 5 cycles

●The test method conforms to MIL-STD-202.

■Materials

Part	Material	Finish
Connector Body	Stainless steel	Passivated
Insulator	PTFE	——
Male contacts	Beryllium copper	Gold plating
Female contacts	Beryllium copper	Gold plating
Attenuation element	Metal film	——

■Ordering Information

AT - 1 00-(0) (40)

❶ ❷ ❸ ❹

❶ AT: Indicates a fixed attenuator	❸ Attenuation 01 : 1dB 06 : 6dB 00-(0) : 0dB (Through) 00-(0.5) : 0.5dB 00-(3.5) : 3.5dB
❷ Indicates the Series Name (Coupling Portion) 1: SMA plug - jack 2: SMA plug - plug 3: SMA jack - jack	❹ (40): RoHS compliant

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.


■Specifications

Part Number	Attenuation (dB)		V.S.W.R.(Max)			Power (W)	Connectors	Weight (g)	RoHS
	DC～12.4GHz	12.4～18GHz	DC～4GHz	4～12.4GHz	2.4～18GHz				
AT-100-(0)(40)	$0^{+0.5}_{0}$	$0^{+1.0}_{0}$	1.15	1.20	1.30	1	HRM-J・P	8	YES
AT-100-(0.5)(40)	0.5±0.5	$0.5^{+1.0}_{-0.5}$	1.15	1.20	1.30	1	HRM-J・P	8	
AT-101(40)	1±0.5	1±1.0	1.15	1.20	1.30	1	HRM-J・P	8	
AT-100-(1.5)(40)	1.5±0.5	1.5±1.0	1.15	1.20	1.30	1	HRM-J・P	8	
AT-102(40)	2±0.5	2±1.0	1.15	1.20	1.30	1	HRM-J・P	8	
AT-100-(2.5)(40)	2.5±0.5	2.5±1.0	1.15	1.20	1.30	1	HRM-J・ P	8	
AT-103(40)	3±0.5	3±1.0	1.15	1.20	1.30	1	HRM-J・P	8	
AT-100-(3.5)(40)	3.5±0.5	3.5±1.0	1.15	1.20	1.30	1	HRM-J・P	8	
AT-104(40)	4±0.5	4±1.0	1.15	1.20	1.30	1	HRM-J・P	8	
AT-105(40)	5±0.7	5±1.2	1.15	1.20	1.30	1	HRM-J・P	8	
AT-106(40)	6±0.7	6±1.2	1.15	1.20	1.30	1	HRM-J・P	8	
AT-107(40)	7±0.7	7±1.2	1.15	1.20	1.30	1	HRM-J・P	8	
AT-108(40)	8±0.7	8±1.2	1.15	1.20	1.30	1	HRM-J・P	8	
AT-109(40)	9±1.0	9±1.25	1.15	1.20	1.30	1	HRM-J・P	8	
AT-110(40)	10±1.0	10±1.25	1.15	1.20	1.30	1	HRM-J・P	8	
AT-112(40)	12±1.0	12±1.25	1.15	1.20	1.30	1	HRM-J・P	8	
AT-113(40)	13±1.0	13±1.25	1.15	1.20	1.30	1	HRM-J・P	8	
AT-114(40)	14±1.2	14±1.3	1.15	1.20	1.30	1	HRM-J・P	8	
AT-115(40)	15±1.2	15±1.3	1.15	1.20	1.30	1	HRM-J・P	8	
AT-120(40)	20±1.2	20±1.3	1.15	1.20	1.30	1	HRM-J・P	8	
AT-203(40)	3±0.5	3±1.0	1.15	1.20	1.30	1	HRM-P・P	9	
AT-206(40)	6±0.7	6±1.2	1.15	1.20	1.30	1	HRM-P・P	9	
AT-210(40)	10±1.0	10±1.25	1.15	1.20	1.30	1	HRM-P・P	9	
AT-220(40)	20±1.2	20±1.3	1.15	1.20	1.30	1	HRM-P・P	9	
AT-303(40)	3±0.5	3±1.0	1.15	1.20	1.30	1	HRM-J・J	7	
AT-306(40)	6±0.7	6±1.2	1.15	1.20	1.30	1	HRM-J・J	7	
AT-310(40)	10±1.0	10±1.25	1.15	1.20	1.30	1	HRM-J・J	7	
AT-320(40)	20±1.2	20±1.3	1.15	1.20	1.30	1	HRM-J・J	7	


Part Number	Attenuation (dB)	V.S.W.R.(Max)		Power (W)	Connectors	Weight (g)	RoHS
	DC～8GHz	DC～4GHz	4～8GHz				
AT-126(40)	26±1.0	1.15	1.20	1	HRM-J・P	8	YES
AT-130(40)	30±1.2	1.15	1.20	1	HRM-J・P	8	

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.


■External Dimensions




AT-100 Type



AT-126,130 Type




AT-200 Type




AT-300 Type


■Typical Data


AT-103(40)







AT-120(40)







AT-130(40)







AT-206(40)






AT-310(40)





Input Power Characteristics



Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9