




## Mini-Mac Applicator Application Tooling Specification Mechanical Feed-Front Metal Strip Order No. 63895-0700



### FEATURES


- Directly adapts to most automatic wire processing machines
- Applicator designed to industry standard mounting and shut height 135.80mm (5.346")
- Quick set-up time; plus the crimp height, track and feed adjustments can be set without removing the applicator from the press
- Fine adjustment allows users to achieve target with little effort by adjusting in increments of .015mm (.0006") for conductor crimp height and .063mm (.0025") for insulation height
- Independent adjustment rings allow users to quickly adjust the conductor or insulation crimp height without affecting each other.

### SCOPE

Products: Quick Disconnect, Female, Flag, for 0.50-1.00mm<sup>2</sup> (18-20 AWG) Wire, Accepts 6.35mm (.250") by 0.81mm (.032") Tab Crimp Terminals.

| Terminal Series No.                                                            | Terminal Order No. |            | Wire Size |                 | Insulation Diameter |           |                   |      | Strip Length |           |
|--------------------------------------------------------------------------------|--------------------|------------|-----------|-----------------|---------------------|-----------|-------------------|------|--------------|-----------|
|                                                                                |                    |            |           |                 | IPC/WHMA-A620 ♦     |           | Terminal (Max) ♦♦ |      |              |           |
|                                                                                |                    |            | AWG       | mm <sup>2</sup> | mm                  | In.       | mm                | In.  | mm           | In.       |
| 94030                                                                          | 94030-5000         | 94030-5001 | -         | 1.00            | 2.10-2.60           | .083-.102 | 2.60              | .102 | 6.00-7.00    | .236-.276 |
|                                                                                |                    |            | 18        | 0.80            |                     |           |                   |      |              |           |
|                                                                                |                    |            | -         | 0.80            |                     |           |                   |      |              |           |
|                                                                                |                    |            | 20        | 0.50            |                     |           |                   |      |              |           |
|                                                                                |                    |            | -         | 0.50            |                     |           |                   |      |              |           |
| ♦ To achieve optimum IPC-A620 insulation crimps, use this insulation OD range. |                    |            |           |                 |                     |           |                   |      |              |           |
| ♦♦ Overall insulation OD specification for terminal.                           |                    |            |           |                 |                     |           |                   |      |              |           |

### DEFINITION OF TERMS



The above terminal drawing is a generic terminal representation. It is not an image of any terminal listed in the scope.

**CRIMP SPECIFICATION**

After crimping, the crimp profiles should measure the following:

| Terminal<br>Series No. | Wire Size |                 | Conductor    |           |                        |      | Insulation   |           |                        |      | Pull Force<br>Minimum |       |
|------------------------|-----------|-----------------|--------------|-----------|------------------------|------|--------------|-----------|------------------------|------|-----------------------|-------|
|                        |           |                 | Crimp Height |           | Crimp Width<br>Maximum |      | Crimp Height |           | Crimp Width<br>Maximum |      |                       |       |
|                        | AWG       | mm <sup>2</sup> | mm           | In.       | mm                     | In.  | mm           | In.       | mm                     | In.  | N                     | Lb.   |
| 94030                  | -         | 1.00            | 1.60-1.70    | .063-.067 | 2.35                   | .093 | 3.00-3.10    | .118-.122 | 3.45                   | .136 | 156.9                 | 35.27 |
|                        | 18        | 0.80            | 1.50-1.60    | .059-.063 | 2.35                   | .093 | 2.90-3.00    | .114-.118 | 3.45                   | .136 | 117.7                 | 26.46 |
|                        | -         | 0.80            | 1.50-1.60    | .059-.063 | 2.35                   | .093 | 2.90-3.00    | .114-.118 | 3.45                   | .136 | 117.7                 | 26.46 |
|                        | 20        | 0.50            | 1.40-1.50    | .055-.059 | 2.35                   | .093 | 2.80-2.90    | .110-.114 | 3.45                   | .136 | 78.5                  | 17.64 |
|                        | -         | 0.50            | 1.40-1.50    | .055-.059 | 2.35                   | .093 | 2.80-2.90    | .110-.114 | 3.45                   | .136 | 78.5                  | 17.64 |


\* Tool Qualification Notes:

1. Pull Force should be measured with no influence from the insulation crimp.
2. The above specifications are guidelines to an optimum crimp.

**PARTS LIST**

| <b>Mini-Mac Applicator 63895-0700</b>                                        |                 |                        |                          |                 |
|------------------------------------------------------------------------------|-----------------|------------------------|--------------------------|-----------------|
| <b>Item</b>                                                                  | <b>Order No</b> | <b>Engineering No.</b> | <b>Description</b>       | <b>Quantity</b> |
| <b>Perishable Tooling</b>                                                    |                 |                        |                          |                 |
|                                                                              | 63895-0770      | 63895-0770             | Tool Kit (All "Y" Items) | REF             |
| 1                                                                            | 63475-0002      | 63475-0002             | Conductor Punch-2.20pw   | 1 Y             |
| 2                                                                            | 63895-0702      | 63895-0702             | Anvil                    | 1 Y             |
| 3                                                                            | 63476-0002      | 63476-0002             | Insulation Punch-3.20pw  | 1 Y             |
| 4                                                                            | 63445-3242      | 63445-3242             | Insulation Anvil         | 1 Y             |
| 5                                                                            | 63895-0705      | 63895-0705             | Cut Punch Left           | 1 Y             |
| 6                                                                            | 63895-0706      | 63895-0706             | Cut Punch Right          | 1 Y             |
| 7                                                                            | 63895-0703      | 63895-0703             | Cut-Off Die-Front        | 2 Y             |
| 8                                                                            | 63895-0735      | 63895-0735             | Lifter                   | 1 Y             |
| 9                                                                            | 63895-0734      | 63895-0734             | Retainer Lifter          | 1 Y             |
| <b>Other Components (Ref. 50750)</b>                                         |                 |                        |                          |                 |
| 10                                                                           | 11-18-5015      | 60805A122              | Front Cover              | 1               |
| 11                                                                           | 11-24-1067      | 4996-4                 | Cut Off Plunger Spring   | 1               |
| 12                                                                           | 63443-2310      | 63443-2310             | 3.50mm Spacer            | 1               |
| 13                                                                           | 63600-2995      | 63600-2995             | Compression Spring       | 2               |
| 14                                                                           | 63890-0042      | 63890-0042             | Terminal Drag Cover      | 1               |
| 15                                                                           | 63890-0046      | 63890-0046             | Rear Cover               | 1               |
| 16                                                                           | 63890-0866      | 63890-0866             | Collar-6.40 Long         | 1               |
| 17                                                                           | 63895-0731      | 63895-0731             | Guide Cut Punch          | 1               |
| 18                                                                           | 63895-0732      | 63895-0732             | Key 37                   | 1               |
| 19                                                                           | 63895-0733      | 63895-0733             | Key 16                   | 1               |
| 20                                                                           | 63895-0736      | 63895-0736             | Wire Stop                | 1               |
| 21                                                                           | 63895-0737      | 63895-0737             | Punch Spacer 3.65        | 1               |
| 22                                                                           | 63895-0738      | 63895-0738             | Tooling Washer           | 1               |
| <b>Frame</b>                                                                 |                 |                        |                          |                 |
| 23                                                                           | 63801-3201      | 63801-3201             | Top                      | 1               |
| 24                                                                           | 63801-3281      | 63801-3281             | Base                     | 1               |
| 25                                                                           | 63801-4650      | 63801-4650             | Track                    | 1               |
| <b>Hardware</b>                                                              |                 |                        |                          |                 |
| 26                                                                           | N/A             | N/A                    | M2.5 by 20 Long SHCS     | 2**             |
| 27                                                                           | N/A             | N/A                    | M3 by 6 Long FHCS        | 2**             |
| 28                                                                           | N/A             | N/A                    | M3 by 6 Long SHCS        | 4**             |
| 29                                                                           | N/A             | N/A                    | M4 by 12 Long BHCS       | 2**             |
| 30                                                                           | N/A             | N/A                    | M4 by 50 Long SHCS       | 2**             |
| 31                                                                           | N/A             | N/A                    | M8 by 35 Long BHCS       | 1**             |
| 32                                                                           | N/A             | N/A                    | 2.5mm by 8 Lg Roll Pin   | 3**             |
| ** Available from an industrial supply company such as MSC (1-800-645-7270). |                 |                        |                          |                 |

## Assembly Drawing



## NOTES

1. Molex recommends an extra perishable tooling kit be maintained at your facility.
2. Verify tooling alignment by manually cycling the press with applicator before crimping under power. Check that all screws are tight.
3. Slugs, terminals, dirt, and oil should be kept clear of work area.
4. Wear safety glasses at all times.
5. For recommended maintenance refer to the Mini-Mac Applicator Manual (Document no. 63880-0000).

**CAUTION:** This applicator should only be used in a press with a shut height of 135.80 mm (5.346"). Tooling damage could result at a lower setting.

**CAUTION:** To prevent injury, never operate this applicator without the guards supplied with the press or wire-processing machine in place. Reference the press or wire processing manufacturer's instruction manual.

**CAUTION:** Molex crimp specifications are valid only when used with Molex terminals, applicators and tooling.

## Contact Information

For more information on Molex application tooling please contact Molex at 1-800-786-6539.

**Americas Headquarters**  
Lisle, Illinois 60532 U.S.A.  
1-800-78MOLEX  
amerinfo@molex.com

**Far East North Headquarters**  
Yamato, Kanagawa, Japan  
81-462-65-2324  
feninfo@molex.com

**Far East South Headquarters**  
Jurong, Singapore  
65-6-268-6868  
fesinfo@molex.com

**European Headquarters**  
Munich, Germany  
49-89-413092-0  
eurinfo@molex.com

**Corporate Headquarters**  
2222 Wellington Ct.  
Lisle, IL 60532 U.S.A.  
630-969-4550  
Fax: 630-969-1352

Visit our Web site at <http://www.molex.com>

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9