

Distribution Units have combinations of **four, five or six outlets** together with **neon indicator**, fuse and switch options. The **three sizes** are available in various combinations and, other than the compact version, all have shuttered outlets. The larger enclosed versions are also available with **EMI filtering**.




IEC Distribution Units



PXD301/050/01/1

- Five Shuttered Outlets
- 5 x 20mm Fuseholder
- Neon Indicator
- Filtered or Non-filtered
- EN60320 Inlet
- 10A, 250V a.c.



IEC Panel Mount Distribution Unit



PXD100/050/01/1

- Five Shuttered Outlets
- 5 x 20mm Fuseholder
- Neon Indicator
- Screw Fit to Panel
- 10A, 250V a.c.



IEC Distribution Unit



PXD303/050/01/1
 PXD306/050/01/1

- Five Shuttered Outlets
- 5 x 20mm Fuseholder
- Neon Indicator
- Filtered or Non-filtered
- 2 Metre Cable with BS1363 Plug
- 10A, 250V a.c.



| Part No. | Inlet | Outlet | EMI Filter | Neon Indicator | Fuse | Illuminated Switch | Approvals |
|-----------------|-----------------------------------|-------------|------------|----------------|------|--------------------|-----------|
| Panel Style: | | | | | | | |
| PXD100/050/01/1 | | 5 Shuttered | | 1 | 1 | | Ⓢ |
| Box Style: | | | | | | | |
| PXD301/050/01/1 | 1 | 5 Shuttered | | 1 | 1 | | Ⓢ |
| PXD301/050/07/1 | 1 | 5 Shuttered | | | | Red | |
| PXD301/050/08/1 | 1 | 5 Shuttered | | | | Green | |
| PXD301/550/01/1 | 1 | 5 Shuttered | ● | 1 | 1 | | |
| PXD301/550/07/1 | 1 | 5 Shuttered | ● | | | Red | Ⓢ |
| PXD301/550/08/1 | 1 | 5 Shuttered | ● | | | Green | |
| PXD303/050/01/1 | 2m cable with BS1363 plug | 5 Shuttered | | 1 | 1 | | |
| PXD303/050/07/1 | 2m cable with BS1363 plug | 5 Shuttered | | | | Red | |
| PXD303/050/08/1 | 2m cable with BS1363 plug | 5 Shuttered | | | | Green | |
| PXD303/550/01/1 | 2m cable with BS1363 plug | 5 Shuttered | ● | 1 | 1 | | |
| PXD303/550/07/1 | 2m cable with BS1363 plug | 5 Shuttered | ● | | | Red | |
| PXD303/550/08/1 | 2m cable with BS1363 plug | 5 Shuttered | ● | | | Green | |
| PXD306/050/01/1 | 2m cable with CEE7 Sheet VII plug | 5 Shuttered | | 1 | 1 | | Ⓢ |

IEC Distribution Unit



PXD301/050/07/1

- Five Shuttered Outlets
- Illuminated Switch
- Filtered or Non-Filtered
- EN60320 Inlet
- 10A, 250V a.c.




IEC Distribution Unit



PXD303/050/08/1

- Five Shuttered Outlets
- Illuminated Switch
- Filtered or Non-Filtered
- 2m Cable and BS1363 plug
- 10A, 250V a.c.



Specifications

| | |
|--------------------|--|
| Mouldings: | Thermoplastic |
| Housing: | ABS |
| Connectors: | Nylon |
| Contacts: | Outlets: Brass, Tin Plated Inlets: Brass, Nickel Plated |
| Voltage Rating: | 250V a.c. 50/60Hz |
| Current Rating: | 10A |
| Proof Voltage: | 2kV |
| Temp. Range: | -5°C to +60°C |
| Mating Connectors: | PX0686, PX0686/SE |
| RoHS | Compliant |

Filter


| | |
|---------------------------------|---|
| Max. Earth Leakage: Current: | <0.35mA (at 250V, 50Hz) |
| Capacitor | 2 x 2.2nF (Y), 1 x 15nF (X) |
| Inductance: | 2 x 0.35mH |
| Fuse: | 5 x 20mm, 10A (ceramic HRC type, IEC 127) |

Compact Distribution Unit



PXD200

- Four Outlets
- EN60320 Inlet
- 10A, 250V ac
- cULus Approval



Compact Distribution Unit



PXD201

- Four Outlets
- 2m Cable with BS1363 connector, Schuko connector (CEE7) or NEMA 5/15 connector
- 10A, 250V a.c.



Specifications

| | |
|-----------------|--|
| Mouldings: | Thermoplastic |
| Housing: | ABS, UL94V-0 |
| Connectors: | BS1363, CEE7, NEMA 5/15 |
| Contacts: | Outlets: Brass, Tin Plated Inlets: Brass, Nickel Plated |
| Voltage Rating: | 250V a.c. 50/60Hz |
| Current Rating: | 10A |
| Proof Voltage: | 2kV |
| Temp. Range: | -5°C to +60°C |
| Approvals | cULus Listed (PXD200) |
| RoHS | Compliant |


| Part No. | Inlet | Outlet |
|----------|----------------------------|--------|
| PXD200 | 1 | 4 |
| PXD201 | 2m cable with BS 1363 plug | 4 |
| PXD201/1 | 2m cable with Schuko plug | 4 |
| PXD201/2 | 2m cable with NEMA 5/15 | 4 |

Compact Distribution Unit



PXD701/061/10/1

- Six Shuttered Outlets
- 5 x 20mm Fuseholder
- Filtered or Non Filtered
- Switch, Fuse, Neon Indicator
- With IEC Inlet
- 10A, 250V a.c.




IEC Mount Distribution Unit



PXD500/061/10/1

- Six Shuttered Outlets
- 5 x 20mm Fuseholder
- Switch, Fuse, Neon Indicator
- Screw Fit to Panel
- 10A, 250V




Compact Distribution Unit



PXD703/061/10/1
 PXD706/061/10/1

- Six Shuttered Outlets
- 5 x 20mm Fuseholder
- Filtered or Non Filtered
- Switch, Fuse, Neon Indicator
- 2 Metre Cable with BS1363 or CEE7 Plug
- 10A, 250V



| Specifications | | Part No. | Inlet | Outlet | EMI Filter | Switch | Fuse | Neon Indicator |
|-----------------|--|---------------------------------|-----------------------------------|-------------|------------|--------|------|----------------|
| Mouldings: | Thermoplastic | Panel Style: PXD500/061/10/1 | | 6 Shuttered | | 1 | 1 | 1 |
| Housing: | ABS | Box Style: PXD701/061/10/1 | 1 | 6 Shuttered | | 1 | 1 | 1 |
| Connectors: | Nylon | PXD701/561/10/1 | 1 | 6 Shuttered | ● | 1 | 1 | 1 |
| Contacts: | Outlets: Brass, Tin Plated Inlets: Brass, Nickel Plated | PXD703/061/10/1 | 2m cable with BS 1363 plug | 6 Shuttered | | 1 | 1 | 1 |
| Voltage Rating: | 250V a.c. 50/60Hz | PXD703/561/10/1 | 2m cable with BS 1363 plug | 6 Shuttered | ● | 1 | 1 | 1 |
| Current Rating: | 10A | PXD706/061/10/1 | 2m cable with CEE7 Sheet VII plug | 6 Shuttered | | 1 | 1 | 1 |
| Proof Voltage: | 2kV | | | | | | | |
| Temp. Range: | -5°C to +60°C | | | | | | | |
| RoHS | Compliant | | | | | | | |

Filter

| | |
|-----------------------------|---|
| Max. Earth Leakage Current: | <0.35mA (at 250V, 50Hz) |
| Capacitor | 2 x 2.2nF (Y), 1 x 15nF (X) |
| Inductance: | 2 x 0.35mH |
| Fuse: | 5 x 20mm, 10A (ceramic HRC type, IEC 127) |

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9