DC Film Capacitors
MKT Radial Potted Type



Dimensions in mm

APPLICATIONS

Blocking and coupling, bypass and energy reservoir, telecom, industrial, consumer

REFERENCE STANDARDS

IEC 60384-2

MARKING

C-value; tolerance; rated voltage; manufacturer's symbol; year and week of manufacturer; manufacturer's type

DIELECTRIC

Polyester film

ELECTRODES

Metallized

CONSTRUCTION

Mono construction

Triple construction for 630 V, 0.00068 µF to 0.0018 µF

RATED (DC) VOLTAGE

50 V, 63 V, 250 V, 400 V, 630 V

RATED (AC) VOLTAGE

32 V, 40 V, 63 V, 160 V, 220 V

FEATURES

- 5.08 mm lead pitch
- Supplied loose in box, taped on ammopack or reel
- Compliant to RoHS Directive 2002/95/EC

Pb-free

e3

RoHS COMPLIANT

ENCAPSULATION

Flame retardant plastic case and epoxy resin (UL-class 94 V-0)

CLIMATIC TESTING CLASS ACC. TO IEC 60068-1

55/100/56 for rated voltage 50 V and 63 V
55/105/56 for rated voltage > 63 V

CAPACITANCE RANGE (E12 SERIES)

0.00068 µF to 1.5 µF

CAPACITANCE TOLERANCE

± 10 %, ± 5 %

LEADS

Tinned wire

RATED TEMPERATURE

85 °C

MAXIMUM APPLICATION TEMPERATURE

100 °C for rated voltage 50 V and 63 V
105 °C for rated voltage > 63 V

PERFORMANCE GRADE

Grade 1 (long life)

DETAIL SPECIFICATION

For more detailed data and test requirements contact:
dc-film@vishay.com

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

COMPOSITION OF CATALOG NUMBER

TYPE AND PITCHES	
370	5.08 mm

CAPACITANCE (numerically)

Example:
104 = 10 x 10 = 100 nF

MULTIPLIER (nF)	
0.1	2
1	3
10	4
100	5

BFC2	370	XX	YY	Y
2222 (*)	370	XX	YY	Y

(*) Old ordering number

TYPE	PACKAGING	LEAD CONFIGURATION	PREFERRED TYPES				
			C-TOL.	63 V	100 V	250 V	400 V
370 (standard size)	Loose in box	Lead length 4.0 mm + 1.0 mm/- 0.5 mm	± 10 %	11	21	41	51
			± 5 %	12	22	42	52
		Lead length 26.0 mm ± 2.0 mm	± 10 %	15	25	45	55
			± 5 %	16	26	46	56
	Taped on reel (1)	H = 18.5 mm; P_0 = 12.7 mm; Reel diameter = 356 mm	± 10 %	18	28	48	58
			± 5 %	19	29	49	59
	Ammopack (2)	H = 18.5 mm; P_0 = 12.7 mm	± 10 %	75	85	35	65
			± 5 %	76	86	36	66

TYPE	PACKAGING	LEAD CONFIGURATION	PREFERRED TYPES				
			C-TOL.	100 V	250 V	400 V	630 V
370 (compact size)	Loose in box	Lead length 4.0 mm + 1.0 mm/- 0.5 mm	± 10 %	CE	EE	FE	GE
			± 5 %	CF	EF	FF	GF
		Lead length 26.0 mm ± 2.0 mm	± 10 %	CH	EH	FH	GH
			± 5 %	CI	EI	FI	GI
	Taped on reel (1)	H = 18.5 mm; P_0 = 12.7 mm; Reel diameter = 356 mm	± 10 %	CL	EL	FL	GL
			± 5 %	CM	EM	FM	GM
	Ammopack (2)	H = 18.5 mm; P_0 = 12.7 mm	± 10 %	CB	EB	FB	GB
			± 5 %	CC	EC	FC	GC

Notes
(1) Reel diameter = 356 mm is available on request
(2) H = In-tape height; P_0 = Sprocket hole distance; for detailed specifications refer to packaging information
For detailed tape specifications refer to packaging information: www.vishay.com/doc?28139 or end of catalog

SPECIFIC REFERENCE DATA (Standard size)

DESCRIPTION	VALUE			
Tangent of loss angle:	at 1 kHz		at 10 kHz	at 100 kHz
C ≤ 0.1 µF	≤ 75 x 10^{-4}		≤ 130 x 10^{-4}	≤ 220 x 10^{-4}
0.1 µF < C ≤ 0.47 µF	≤ 75 x 10^{-4}		≤ 130 x 10^{-4}	≤ 300 x 10^{-4}
0.47 µF < C ≤ 1.5 µF	≤ 75 x 10^{-4}		≤ 130 x 10^{-4}	-
Rated voltage pulse slope $(dU/dt)_R$ at	50 V_{DC}/63 V_{DC}	100 V_{DC}	250 V_{DC}	400 V_{DC}
	60 V/µs	110 V/µs	330 V/µs	630 V/µs
R between leads, for C ≤ 0.33 µF at 10 V; 1 min at 100 V; 1 min	> 15 000 MΩ	> 15 000 MΩ	> 30 000 MΩ	> 30 000 MΩ
RC between leads 0.33 µF < C ≤ 1.0 µF at 10 V; 1 min C > 1.0 µF at 10 V; 1 min C > 0.33 µF at 100 V; 1 min	> 5000 s > 1000 s	> 5000 s		
R between interconnecting leads and case (foil method)	> 30 000 MΩ	> 30 000 MΩ	> 30 000 MΩ	> 30 000 MΩ
Withstanding (DC) voltage (cut off current 10 mA)(1);rise time ≤ 1000 V/s rise time 100 V/s	100 V; 1 min	160 V; 1 min	400 V; 1 min	640 V; 1 min
Withstanding (DC) voltage between leads and case	200 V; 1 min	200 V; 1 min	500 V; 1 min	800 V; 1 min
Maximum application temperature	100 °C	105 °C		

Note
(1) See "Voltage Proof Test for Metallized Film Capacitors": www.vishay.com/doc?28169

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

SPECIFIC REFERENCE DATA (Compact size)

DESCRIPTION	VALUE			
Tangent of loss angle:	at 1 kHz		at 10 kHz	at 100 kHz
C ≤ 0.1 µF	≤ 75 x 10^{-4}		≤ 130 x 10^{-4}	≤ 220 x 10^{-4}
0.1 µF < C ≤ 0.47 µF	≤ 75 x 10^{-4}		≤ 130 x 10^{-4}	≤ 300 x 10^{-4}
C > 0.47 µF	≤ 75 x 10^{-4}		≤ 130 x 10^{-4}	-
Rated voltage pulse slope $(dU/dt)_R$ at	100 V_{DC}	250 V_{DC}	400 V_{DC}	630 V_{DC}
	37 V/µs	44 V/µs	200 V/µs	540 V/µs
R between leads, for C ≤ 0.33 µF at 100 V; 1 min	> 15 000 MΩ	> 30 000 MΩ	> 30 000 MΩ	> 30 000 MΩ
RC between leads C > 0.33 µF at 100 V; 1 min	> 5000 s			
R between interconnecting leads and case (foil method)	> 30 000 MΩ	> 30 000 MΩ	> 30 000 MΩ	> 30 000 MΩ
Withstanding (DC) voltage (cut off current 10 mA)[1];rise time ≤ 1000 V/s rise time 100 V/s	160 V; 1 min	400 V; 1 min	640 V; 1 min	1008 V; 1 min
Withstanding (DC) voltage between leads and case	200 V; 1 min	500 V; 1 min	800 V; 1 min	1260 V; 1 min
Maximum application temperature	100 °C	105 °C		

Note

[1] See “Voltage Proof Test for Metallized Film Capacitors”: www.vishay.com/doc?28169

U_{RDC} = 63 V; U_{RAC} = 40 V

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) [1]	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								
			AMMOPACK		LOOSE IN BOX				REEL		C-VALUE
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.056	2.5 x 6.5 x 7.2	0.18	**75…** (2000)	**76…** (2000)	**11…** (2000)	**12…** (2000)	**15…** (1000)	**16…** (1000)	**18…** (2000)	**19…** (2000)	**563**
0.068											**683**
0.082											**823**
0.10											**104**
0.12											**124**
0.15											**154**
0.18											**184**
0.22	3.5 x 8.0 x 7.2	0.3	**75…** (1500)	**76…** (1500)	**11…** (2000)	**12…** (2000)	**15…** (1000)	**16…** (1000)	**18…** (1500)	**19…** (1500)	**224**
0.27											**274**
0.33											**334**
0.39											**394**
0.47											**474**
0.56	4.5 x 9.0 x 7.2	0.42	**75…** (1000)	**76…** (1000)	**11…** (2000)	**12…** (2000)	**15…** (1000)	**16…** (1000)	**18…** (1000)	**19…** (1000)	**564**
0.68											**684**
0.82	6.0 x 11.0 x 7.2	0.64	**75…** (750)	**76…** (750)	**11…** (2000)	**12…** (2000)	**15…** (1000)	**16…** (1000)	**18…** (1000)	**19…** (1000)	**824**
1.0											**105**
1.2 [2]											**125**
1.5 [2]											**155**

Notes

- SPQ = Standard Packing Quantity

[1] Weight for short lead product only

[2] For C = 1.2 µF and C = 1.5 µF: U_{RDC} = 50 V and U_{RAC} = 32 V

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

U_{RDC} = 100 V; U_{RAC} = 63 V (standard size)

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) [1]	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								C-VALUE
			AMMOPACK		LOOSE IN BOX				REEL		
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.0010	2.5 x 6.5 x 7.2	0.18	**85...** (2000)	**86...** (2000)	**21...** (2000)	**22...** (2000)	**25...** (1000)	**26...** (1000)	**28...** (2000)	**29...** (2000)	**102**
0.0012											**122**
0.0015											**152**
0.0018											**182**
0.0022											**222**
0.0027											**272**
0.0033											**332**
0.0039											**392**
0.0047											**472**
0.0056											**562**
0.0068											**682**
0.0082											**822**
0.010											**103**
0.012											**123**
0.015											**153**
0.018											**183**
0.022											**223**
0.027											**273**
0.033											**333**
0.039											**393**
0.047											**473**
0.056											**563**
0.068											**683**
0.082											**823**
0.10											**104**
0.12	3.5 x 8.0 x 7.2	0.30	**85...** (1500)	**86...** (1500)	**21...** (2000)	**22...** (2000)	**25...** (1000)	**26...** (1000)	**28...** (1500)	**29...** (1500)	**124**
0.15											**154**
0.18											**184**
0.22	4.5 x 9.0 x 7.2	0.42	**85...** (1000)	**86...** (1000)	**21...** (2000)	**22...** (2000)	**25...** (1000)	**26...** (1000)	**28...** (1000)	**29...** (1000)	**224**
0.27											**274**
0.33											**334**
0.39	6.0 x 11.0 x 7.2	0.64	**85...** (750)	**86...** (750)	**21...** (2000)	**22...** (2000)	**25...** (1000)	**26...** (1000)	**28...** (1000)	**29...** (1000)	**394**
0.47											**474**

Notes

- SPQ = Standard Packing Quantity

[1] Weight for short lead product only

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

U_{RDC} = 100 V; U_{RAC} = 40 V (compact size)

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) (1)	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								C-VALUE
			AMMOPACK		LOOSE IN BOX				REEL		
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.12 0.15 0.18 0.22 0.27 0.33	3.5 x 8.0 x 7.2	0.30	CB... (1500)	CC... (1500)	CE... (2000)	CF... (2000)	CH... (1000)	CI... (1000)	CL... (1500)	CM... (1500)	124 154 184 224 274 334
0.39 0.47	4.5 x 9.0 x 7.2	0.42	CB... (1000)	CC... (1000)	CE... (2000)	CF... (2000)	CH... (1000)	CI... (1000)	CL... (1000)	CM... (1000)	394 474
0.56	6.0 x 11.0 x 7.2	0.64	CB... (750)	CC... (750)	CE... (2000)	CF... (2000)	CH... (1000)	CI... (1000)	CL... (1000)	CM... (1000)	564

Notes

- SPQ = Standard Packing Quantity

(1) Weight for short lead product only

U_{RDC} = 250 V; U_{RAC} = 160 V (standard size)

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) (1)	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								C-VALUE
			AMMOPACK		LOOSE IN BOX				REEL		
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.0010 0.0012 0.0015 0.0018 0.0022 0.0027 0.0033 0.0039 0.0047 0.0056 0.0068 0.0082 0.010 0.012 0.015 0.018	2.5 x 6.5 x 7.2	0.18	35... (2000)	36... (2000)	41... (2000)	42... (2000)	45... (1000)	46... (1000)	48... (2000)	49... (2000)	102 122 152 182 222 272 332 392 472 562 682 822 103 123 153 183
0.022 0.027 0.033	3.5 x 8.0 x 7.2	0.30	35... (1500)	36... (1500)	41... (2000)	42... (2000)	45... (1000)	46... (1000)	48... (1500)	49... (1500)	223 273 333
0.039 0.047 0.056	4.5 x 9.0 x 7.2	0.42	35... (1000)	36... (1000)	41... (2000)	42... (2000)	45... (1000)	46... (1000)	48... (1000)	49... (1000)	393 473 563
0.068 0.082 0.10	6.0 x 11.0 x 7.2	0.64	35... (750)	36... (750)	41... (2000)	42... (2000)	45... (1000)	46... (1000)	48... (1000)	49... (1000)	683 823 104

Notes

- SPQ = Standard Packing Quantity

(1) Weight for short lead product only

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

U_{RDC} = 250 V; U_{RAC} = 63 V (compact size)

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) (1)	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								C-VALUE
			AMMOPACK		LOOSE IN BOX				REEL		
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.022 0.027	2.5 x 6.5 x 7.2	0.18	**EB...** (2000)	**EC...** (2000)	**EE...** (2000)	**EF...** (2000)	**EH...** (1000)	**EI...** (1000)	**EL...** (2000)	**EM...** (2000)	**223** **273**
0.033 0.039 0.047 0.056 0.068	3.5 x 8.0 x 7.2	0.30	**EB...** (1500)	**EC...** (1500)	**EE...** (2000)	**EF...** (2000)	**EH...** (1000)	**EI...** (1000)	**EL...** (1500)	**EM...** (1500)	**333** **393** **473** **563** **683**
0.082 0.10	4.5 x 9.0 x 7.2	0.42	**EB...** (1000)	**EC...** (1000)	**EE...** (2000)	**EF...** (2000)	**EH...** (1000)	**EI...** (1000)	**EL...** (1000)	**EM...** (1000)	**823** **104**
0.12 0.15 0.18 0.22	6.0 x 11.0 x 7.2	0.64	**EB...** (750)	**EC...** (750)	**EE...** (2000)	**EF...** (2000)	**EH...** (1000)	**EI...** (1000)	**EL...** (1000)	**EM...** (1000)	**124** **154** **184** **224**

Notes

- SPQ = Standard Packing Quantity

(1) Weight for short lead product only

U_{RDC} = 400 V; U_{RAC} = 220 V (standard size)

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) (1)	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								C-VALUE
			AMMOPACK		LOOSE IN BOX				REEL		
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.0010 0.0012 0.0015 0.0018 0.0022 0.0027 0.0033 0.0039 0.0047 0.0056 0.0068 0.0082	2.5 x 6.5 x 7.2	0.18	**65...** (2000)	**66...** (2000)	**51...** (2000)	**52...** (2000)	**55...** (1000)	**56...** (1000)	**58...** (2000)	**59...** (2000)	**102** **122** **152** **182** **222** **272** **332** **392** **472** **562** **682** **822**
0.010 0.012 0.015	3.5 x 8.0 x 7.2	0.30	**65...** (1500)	**66...** (1500)	**51...** (2000)	**52...** (2000)	**55...** (1000)	**56...** (1000)	**58...** (1500)	**59...** (1500)	**103** **123** **153**
0.018 0.022 0.027	4.5 x 9.0 x 7.2	0.42	**65...** (1000)	**66...** (1000)	**51...** (2000)	**52...** (2000)	**55...** (1000)	**56...** (1000)	**58...** (1000)	**59...** (1000)	**183** **223** **273**
0.033 0.039 0.047	6.0 x 11.0 x 7.2	0.64	**65...** (750)	**66...** (750)	**51...** (2000)	**52...** (2000)	**55...** (1000)	**56...** (1000)	**58...** (1000)	**59...** (1000)	**333** **393** **473**

Notes

- SPQ = Standard Packing Quantity

(1) Weight for short lead product only

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

U_{RDC} = 400 V; U_{RAC} = 160 V (compact size)

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) [1]	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								C-VALUE
			AMMOPACK		LOOSE IN BOX				REEL		
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.010 0.012 0.015 0.018	2.5 x 6.5 x 7.2	0.18	**FB...** (2000)	**FC...** (2000)	**FE...** (2000)	**FF...** (2000)	**FH...** (1000)	**FI...** (1000)	**FL...** (2000)	**FM...** (2000)	**103** **123** **153** **183**
0.022 0.027 0.033 0.039	3.5 x 8.0 x 7.2	0.30	**FB...** (1500)	**FC...** (1500)	**FE...** (2000)	**FF...** (2000)	**FH...** (1000)	**FI...** (1000)	**FL...** (1500)	**FM...** (1500)	**223** **273** **333** **393**
0.047 0.056	4.5 x 9.0 x 7.2	0.42	**FB...** (1000)	**FC...** (1000)	**FE...** (2000)	**FF...** (2000)	**FH...** (1000)	**FI...** (1000)	**FL...** (1000)	**FM...** (1000)	**473** **563**
0.068 0.082 0.10	6.0 x 11.0 x 7.2	0.64	**FB...** (750)	**FC...** (750)	**FE...** (2000)	**FF...** (2000)	**FH...** (1000)	**FI...** (1000)	**FL...** (1000)	**FM...** (1000)	**683** **823** **104**

Notes

- SPQ = Standard Packing Quantity

[1] Weight for short lead product only

U_{RDC} = 630 V; U_{RAC} = 220 V (compact size)

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) [1]	CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING								C-VALUE
			AMMOPACK		LOOSE IN BOX				REEL		
			H = 18.5 mm; P_0 = 12.7 mm		Short leads		Long leads				
			C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	C-tol. = ± 10 %	C-tol. = ± 5 %	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	..YYY
Pitch = 5.08 mm ± 0.30 mm; d_t = 0.50 mm ± 0.05 mm											
0.00068 0.00082 0.0010 0.0012 0.0015 0.0018 0.002 0.0022 0.0024 0.0027 0.0033 0.0039 0.0047 0.0056 0.0068 0.0082 0.010	3.5 x 8.0 x 7.2	0.35	**GB...** (1500)	**GC...** (1500)	**GE...** (2000)	**GF...** (2000)	**GH...** (1000)	**GI...** (1000)	**GL...** (1500)	**GM...** (1500)	**681** **821** **102** **122** **152** **182** **202** **222** **242** **272** **332** **392** **472** **562** **682** **822** **103**
0.012 0.015	4.5 x 9.0 x 7.2	0.45	**GB...** (1000)	**GC...** (1000)	**GE...** (2000)	**GF...** (2000)	**GH...** (1000)	**GI...** (1000)	**GL...** (1000)	**GM...** (1000)	**123** **153**
0.018 0.022 0.027 0.033	6.0 x 11.0 x 7.2	0.65	**GB...** (750)	**GC...** (750)	**GE...** (2000)	**GF...** (2000)	**GH...** (1000)	**GI...** (1000)	**GL...** (1000)	**GM...** (1000)	**183** **223** **273** **333**

Notes

- SPQ = Standard Packing Quantity

[1] Weight for short lead product only

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

MOUNTING

Normal Use

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.
For detailed tape specifications refer to packaging information: www.vishay.com/doc?28139 or end of catalog.

Specific Method of Mounting to Withstand Vibration and Shock

In order to withstand vibration and shock tests, it must be ensured that stand-off pips are in good contact with the printed-circuit board:

- For pitches ≤ 15 mm capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

Space Requirements on Printed Circuit Board

The maximum space for length ($l_{max.}$), width ($w_{max.}$) and height ($h_{max.}$) of film capacitors to take in account on the printed circuit board is shown in the drawings.

- For products with pitch ≤ 15 mm, $\Delta w = \Delta l = 0.3$ mm; $\Delta h = 0.1$ mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.



SOLDERING CONDITIONS

For general soldering conditions and wave soldering profile, we refer to the application note:
"Soldering Guidelines for Film Capacitors": www.vishay.com/doc?28171

Storage Temperature

- Storage temperature: T_{stg} = - 25 °C to + 35 °C with with relative humidity of maximum 75 % without condensation

Ratings and Characteristics Reference Conditions

Unless otherwise specified, all electrical values apply to an ambient temperature of 23 °C ± 1 °C, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of 50 % ± 2 %.

For reference testing, a conditioning period shall be applied over 96 h ± 4 h by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

CHARACTERISTICS

Capacitance as a function of ambient temperature (typical curve) for voltage 63 V



Capacitance as a function of ambient temperature (typical curve) for voltages > 63 V



Capacitance as a function of frequency (typical curve)



Impedance as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Maximum RMS current (sinewave) as a function of frequency

The maximum RMS current is defined by $I_{ac} = \omega \times C \times U_{ac}$.

U_{ac} is the maximum AC voltage depending on the ambient temperature in the curves “Max. RMS voltage and AC current as a function of frequency”.

Tangent of loss angle as a function of frequency (typical curve)



Insulation resistance as a function of the ambient temperature (typical curve)



Max. DC and AC voltage as a function of frequency for voltage 63 V



Max. DC and AC voltage as a function of frequency for voltages > 63 V



This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Maximum allowed component temperature rise (ΔT) as a function of the ambient temperature (T_{amb}) for voltage 63 V



Maximum allowed component temperature rise (ΔT) as a function of the ambient temperature (T_{amb}) for voltages > 63 V



HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C

$W_{max.}$ (mm)	HEAT CONDUCTIVITY (mW/°C)
	PITCH 5 mm
2.5	2.5
3.5	3.0
4.5	4.0
6.0	5.5

POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free ambient temperature.
The power dissipation can be calculated according type detail specification “HQN-384-01/101: Technical Information Film Capacitors”.
The component temperature rise (ΔT) can be measured (see section “Measuring the component temperature” for more details) or calculated by ΔT = P/G:

- ΔT = Component temperature rise (°C)
- P = Power dissipation of the component (mW)
- G = Heat conductivity of the component (mW/°C)

MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded (T_{amb}) and maximum loaded condition (T_C).
The temperature rise is given by $\Delta T = T_C - T_{amb}$.
To avoid radiation or convection, the capacitor should be tested in a wind-free box.

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

APPLICATION NOTE AND LIMITING CONDITIONS

These capacitors are not suitable for mains applications as across-the-line capacitors without additional protection, as described hereunder. These mains applications are strictly regulated in safety standards and therefore electromagnetic interference suppression capacitors conforming the standards must be used.

- For capacitors connected in parallel, normally the proof voltage and possibly te rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: dc-film@vishay.com

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage (U_P) shall not be greater than the rated DC voltage (U_{RDC})
2. The peak-to-peak voltage (U_{P-P}) shall not be greater than $2\sqrt{2} \times U_{RAC}$ to avoid the ionisation inception level
3. The voltage peak slope (dU/dt) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by U_{RDC} and divided by the applied voltage.
   For all other pulses following equation must be fulfilled: $2 \times \int_0^T \left(\frac{dU}{dt}\right)^2 \times dt < U_{RDC} \times \left(\frac{dU}{dt}\right)_{rated}$
   T is the pulse duration.
4. The maximum component surface temperature rise must be lower than the limits (see figure max. allowed component temperature rise).
5. Since in circuits used at voltages over 280 V peak-to-peak the risk for an intrinsically active flammability after a capacitor breakdown (short circuit) increases, it is recommended that the power to the component is limited to 100 times the values mentioned in the table: “Heat conductivity”
6. When using these capacitors as across-the-line capacitor in the input filter for mains applications or as series connected with an impedance to the mains the applicant must guarantee that the following conditions are fulfilled in any case (spikes and surge voltages from the mains included).

Voltage Conditions for 6 Above

ALLOWED VOLTAGES	**$T_{amb} \leq 85$ °C**	**85 °C < $T_{amb} \leq$ 100 °C for 63 V** **85 °C < $T_{amb} \leq$ 105 °C for > 63 V**
Maximum continuous RMS voltage	U_{RAC}	See “Max. AC voltage as function of temperature CBB952” per characteristics
Maximum temperature RMS-overvoltage (< 24 h)	1.25 x U_{RAC}	U_{RAC}
Maximum peak voltage (V_{O-P}) (< 2 s)	1.6 x U_{RDC}	1.3 x U_{RDC}

EXAMPLE

C = 330 nF - 63 V used for the voltage signal shown in next drawing.
U_{P-P} = 40 V; U_P = 35 V; T_1 = 100 µs; T_2 = 200 µs
The ambient temperature is 35 °C

Checking conditions:

1. The peak voltage U_P = 35 V is lower than 63 V_{DC}
2. The peak-to-peak voltage 40 V is lower than $2\sqrt{2} \times 40\ V_{AC} = 113\ U_{P-P}$
3. The voltage pulse slope (dU/dt) = 40 V/100 µs = 0.4 V/µs
   This is lower than 60 V/µs (see specific reference data for each version)
4. The dissipated power is 16.2 mW as calculated with fourier terms
   The temperature rise for $W_{max.}$ = 3.5 mm and pitch = 5 mm will be 16.2 mW/3.0 mW/°C = 5.4 °C
   This is lower than 15 °C temperature rise at 35 °C, according figure max. allowed component temperature rise
5. Not applicable
6. Not applicable

Voltage Signal



This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

INSPECTION REQUIREMENTS

General Notes:
Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-2 and Specific Reference Data”.

Group C Inspection Requirements

SUB-CLAUSE NUMBER AND TEST		CONDITIONS	PERFORMANCE REQUIREMENTS
SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1			
4.1	Dimensions (detail)		As specified in chapters “MKT 370 General Data” of this specification
4.3.1	Initial measurements	Capacitance Tangent of loss angle: For C ≤ 470 nF at 100 kHz or for C > 470 nF at 10 kHz	
4.3	Robustness of terminations	Tensile and bending	No visible damage
4.4	Resistance to soldering heat	Method: 1A Solder bath: 280 °C ± 5 °C Duration: 10 s	
4.14	Component solvent resistance	Isopropylalcohol at room temperature Method: 2 Immersion time: 5 min ± 0.5 min Recovery time: Min. 1 h, max. 2 h	
4.4.2	Final measurements	Visual examination	No visible damage Legible marking
		Capacitance	$\lvert\Delta C/C\rvert \leq 2$ % of the value measured initially
		Tangent of loss angle	Increase of tan δ ≤ 0.005 for: C ≤ 100 nF or ≤ 0.010 for: 100 nF < C ≤ 220 nF or ≤ 0.015 for: 220 nF < C ≤ 470 nF and ≤ 0.003 for: C > 470 nF Compared to values measured in 4.3.1
SUB-GROUP C1B OTHER PART OF SAMPLE OF SUB-GROUP C1			
4.6.1	Initial measurements	Capacitance Tangent of loss angle: For C ≤ 470 nF at 100 kHz or for C > 470 nF at 10 kHz	
4.6	Rapid change of temperature	θA = - 55 °C θB = + 100 °C for rated voltage 63 V + 105 °C for rated voltage > 63 V 5 cycles Duration t = 30 min	
4.7	Vibration	Visual examination Mounting: See section “Mounting” of this specification Procedure B4 Frequency range: 10 Hz to 55 Hz Amplitude: 0.75 mm or Acceleration 98 m/s² (whichever is less severe) Total duration 6 h	No visible damage
4.7.2	Final inspection	Visual examination	No visible damage

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

SUB-CLAUSE NUMBER AND TEST		CONDITIONS	PERFORMANCE REQUIREMENTS
4.9	Shock	Mounting: See section “Mounting” of this specification Pulse shape: Half sine Acceleration: 490 m/s² Duration of pulse: 11 ms	
4.9.3	Final measurements	Visual examination	No visible damage
		Capacitance	$\lvert\Delta C/C\rvert \leq 3$ % of the value measured in 4.6.1
		Tangent of loss angle	Increase of tan δ ≤ 0.010 for: $C \leq 220$ nF or ≤ 0.015 for: 220 nF < C ≤ 470 nF and ≤ 0.003 for: C > 470 nF Compared to values measured in 4.6.1
		Insulation resistance	As specified in section “Specific Reference Data 370” of this specification
SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B			
4.10	Climatic sequence		
4.10.2	Dry heat	Temperature: + 100 °C for rated voltage 63 V + 105 °C for rated voltage > 63 V Duration: 16 h	
4.10.3	Damp heat cyclic Test Db, first cycle		
4.10.4	Cold	Temperature: - 55 °C Duration: 2 h	
4.10.6	Damp heat cyclic Test Db, remaining cycles	Voltage proof = U_{RDC} for 1 min within 15 min after removal from testchamber	No breakdown of flash-over
4.10.6.2	Final measurements	Visual examination	No visible damage Legible marking
		Capacitance	$\lvert\Delta C/C\rvert \leq 5$ % of the value measured in 4.4.2 or 4.9.3
		Tangent of loss angle	Increase of tan δ ≤ 0.010 for: $C \leq 220$ nF or ≤ 0.015 for: 220 nF < C ≤ 470 nF and ≤ 0.005 for: C > 470 nF Compared to values measured in 4.3.1 or 4.6.1
		Insulation resistance	≥ 50 % of values specified in section “Specific Reference Data 370” of this specification
SUB-GROUP C2			
4.11	Damp heat steady state	56 days, 40 °C, 90 % to 95 % RH	
4.11.1	Initial measurements	Capacitance Tangent of loss angle at 1 kHz	

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
4.11.3 Final measurements	Voltage proof = U_{RDC} for 1 min within 15 min after removal from testchamber	No breakdown of flash-over
	Visual examination	No visible damage Legible marking
	Capacitance	$\|\Delta C/C\| \leq 5$ % of the value measured in 4.11.1.
	Tangent of loss angle	Increase of tan $\delta \leq 0.005$ Compared to values measured in 4.11.1
	Insulation resistance	≥ 50 % of values specified in section “Specific Reference Data 370” of this specification
SUB-GROUP C3		
4.12 Endurance	Duration: 2000 h 1.25 x U_{RDC} at 85 °C 0.8 x 1.25 U_{RDC} at + 100 °C for rated voltage 63 V 0.8 x 1.25 U_{RDC} at + 105 °C for rated voltage > 63 V	
4.12.1 Initial measurements	Capacitance Tangent of loss angle: For C ≤ 470 nF at 100 kHz or for C > 470 nF at 10 kHz	
4.12.5 Final measurements	Visual examination	No visible damage Legible marking
	Capacitance	$\|\Delta C/C\| \leq 5$ % compared to values measured in 4.12.1
	Tangent of loss angle	Increase of tan δ ≤ 0.005 for at 85 °C ≤ 0.010 for at 100 °C for: C ≤ 220 nF or ≤ 0.015 for: 220 nF < C ≤ 470 nF and ≤ 0.003 for: C > 470 nF Compared to values measured in 4.12.1
	Insulation resistance	≥ 50 % of values specified in section “Specific Reference Data 370” of this specification
SUB-GROUP C4		
4.13 Charge and discharge	10 000 cycles Charged to U_{RDC} Discharge resistance: $R = \frac{U_R}{C \times 2.5 \times (dU/dt)_R}$	
4.13.1 Initial measurements	Capacitance Tangent of loss angle: For C ≤ 470 nF at 100 kHz or for C > 470 nF at 10 kHz	
4.13.3 Final measurements	Capacitance	$\|\Delta C/C\| \leq 3$ % compared to values measured in 4.13.1
	Tangent of loss angle	Increase of tan δ ≤ 0.005 for: C ≤ 100 nF or ≤ 0.010 for: 100 nF < C ≤ 220 nF or ≤ 0.015 for: 220 nF < C ≤ 470 nF and ≤ 0.003 for: C > 470 nF Compared to values measured in 4.13.1
	Insulation resistance	≥ 50 % of values specified in section “Specific Reference Data 370” of this specification

This document is subject to change without notice.
THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9