

## DC Film Capacitors MKT Radial Potted Type



Dimensions in mm

### APPLICATIONS

Blocking and coupling, bypass and energy reservoir, telecom, industrial, consumer

### REFERENCE STANDARDS

IEC 60384-2

### MARKING

C-value; tolerance; rated voltage; manufacturer's symbol; year and week of manufacturer; manufacturer's type

### DIELECTRIC

Polyester film

### ELECTRODES

Metallized

### CONSTRUCTION

Mono construction



Triple construction for 630 V, 0.00068  $\mu$ F to 0.0018  $\mu$ F



### RATED (DC) VOLTAGE

50 V, 63 V, 250 V, 400 V, 630 V

### RATED (AC) VOLTAGE

32 V, 40 V, 63 V, 160 V, 220 V

### FEATURES

- 5.08 mm lead pitch
- Supplied loose in box, taped on ammpack or reel
- Compliant to RoHS Directive 2002/95/EC

### ENCAPSULATION

Flame retardant plastic case and epoxy resin (UL-class 94 V-0)

### CLIMATIC TESTING CLASS ACC. TO IEC 60068-1

55/100/56 for rated voltage 50 V and 63 V

55/105/56 for rated voltage > 63 V

### CAPACITANCE RANGE (E12 SERIES)

0.00068  $\mu$ F to 1.5  $\mu$ F

### CAPACITANCE TOLERANCE

$\pm 10 \%$ ,  $\pm 5 \%$

### LEADS

Tinned wire

### RATED TEMPERATURE

85 °C

### MAXIMUM APPLICATION TEMPERATURE

100 °C for rated voltage 50 V and 63 V

105 °C for rated voltage > 63 V

### PERFORMANCE GRADE

Grade 1 (long life)

### DETAIL SPECIFICATION


For more detailed data and test requirements contact:

[dc-film@vishay.com](mailto:dc-film@vishay.com)



**RoHS**  
COMPLIANT

## COMPOSITION OF CATALOG NUMBER



| TYPE                   | PACKAGING         | LEAD CONFIGURATION                                               | PREFERRED TYPES |      |       |       |       |
|------------------------|-------------------|------------------------------------------------------------------|-----------------|------|-------|-------|-------|
|                        |                   |                                                                  | C-TOL.          | 63 V | 100 V | 250 V | 400 V |
| 370<br>(standard size) | Loose in box      | Lead length<br>4.0 mm + 1.0 mm/- 0.5 mm                          | ± 10 %          | 11   | 21    | 41    | 51    |
|                        |                   |                                                                  | ± 5 %           | 12   | 22    | 42    | 52    |
|                        | Taped on reel (1) | Lead length 26.0 mm ± 2.0 mm                                     | ± 10 %          | 15   | 25    | 45    | 55    |
|                        |                   |                                                                  | ± 5 %           | 16   | 26    | 46    | 56    |
|                        |                   | H = 18.5 mm; P <sub>0</sub> = 12.7 mm;<br>Reel diameter = 356 mm | ± 10 %          | 18   | 28    | 48    | 58    |
|                        |                   |                                                                  | ± 5 %           | 19   | 29    | 49    | 59    |
|                        | Ammopack (2)      | H = 18.5 mm; P <sub>0</sub> = 12.7 mm                            | ± 10 %          | 75   | 85    | 35    | 65    |
|                        |                   |                                                                  | ± 5 %           | 76   | 86    | 36    | 66    |

| TYPE                  | PACKAGING         | LEAD CONFIGURATION                                               | PREFERRED TYPES |       |       |       |       |
|-----------------------|-------------------|------------------------------------------------------------------|-----------------|-------|-------|-------|-------|
|                       |                   |                                                                  | C-TOL.          | 100 V | 250 V | 400 V | 630 V |
| 370<br>(compact size) | Loose in box      | Lead length<br>4.0 mm + 1.0 mm/- 0.5 mm                          | ± 10 %          | CE    | EE    | FE    | GE    |
|                       |                   |                                                                  | ± 5 %           | CF    | EF    | FF    | GF    |
|                       | Taped on reel (1) | Lead length 26.0 mm ± 2.0 mm                                     | ± 10 %          | CH    | EH    | FH    | GH    |
|                       |                   |                                                                  | ± 5 %           | CI    | EI    | FI    | GI    |
|                       |                   | H = 18.5 mm; P <sub>0</sub> = 12.7 mm;<br>Reel diameter = 356 mm | ± 10 %          | CL    | EL    | FL    | GL    |
|                       |                   |                                                                  | ± 5 %           | CM    | EM    | FM    | GM    |
|                       | Ammopack (2)      | H = 18.5 mm; P <sub>0</sub> = 12.7 mm                            | ± 10 %          | CB    | EB    | FB    | GB    |
|                       |                   |                                                                  | ± 5 %           | CC    | EC    | FC    | GC    |

## Notes

(1) Reel diameter = 356 mm is available on request

(2) H = In-tape height; P<sub>0</sub> = Sprocket hole distance; for detailed specifications refer to packaging informationFor detailed tape specifications refer to packaging information: [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139) or end of catalog

## SPECIFIC REFERENCE DATA (Standard size)

| DESCRIPTION                                                                             | VALUE                                  |                          |                          |                     |
|-----------------------------------------------------------------------------------------|----------------------------------------|--------------------------|--------------------------|---------------------|
|                                                                                         | at 1 kHz                               | at 10 kHz                | at 100 kHz               |                     |
| Tangent of loss angle:                                                                  |                                        |                          |                          |                     |
| C ≤ 0.1 μF                                                                              | ≤ 75 x 10 <sup>-4</sup>                | ≤ 130 x 10 <sup>-4</sup> | ≤ 220 x 10 <sup>-4</sup> |                     |
| 0.1 μF < C ≤ 0.47 μF                                                                    | ≤ 75 x 10 <sup>-4</sup>                | ≤ 130 x 10 <sup>-4</sup> | ≤ 300 x 10 <sup>-4</sup> |                     |
| 0.47 μF < C ≤ 1.5 μF                                                                    | ≤ 75 x 10 <sup>-4</sup>                | ≤ 130 x 10 <sup>-4</sup> | -                        |                     |
| Rated voltage pulse slope (dU/dt) <sub>R</sub> at                                       | 50 V <sub>DC</sub> /63 V <sub>DC</sub> | 100 V <sub>DC</sub>      | 250 V <sub>DC</sub>      | 400 V <sub>DC</sub> |
|                                                                                         | 60 V/μs                                | 110 V/μs                 | 330 V/μs                 | 630 V/μs            |
| R between leads, for C ≤ 0.33 μF                                                        |                                        |                          |                          |                     |
| at 10 V; 1 min                                                                          | > 15 000 MΩ                            |                          |                          |                     |
| at 100 V; 1 min                                                                         |                                        | > 15 000 MΩ              | > 30 000 MΩ              | > 30 000 MΩ         |
| RC between leads                                                                        |                                        |                          |                          |                     |
| 0.33 μF < C ≤ 1.0 μF at 10 V; 1 min                                                     | > 5000 s                               |                          |                          |                     |
| C > 1.0 μF at 10 V; 1 min                                                               | > 1000 s                               |                          |                          |                     |
| C > 0.33 μF at 100 V; 1 min                                                             |                                        | > 5000 s                 |                          |                     |
| R between interconnecting leads and case (foil method)                                  | > 30 000 MΩ                            | > 30 000 MΩ              | > 30 000 MΩ              | > 30 000 MΩ         |
| Withstanding (DC) voltage (cut off current 10 mA) <sup>(1)</sup> ; rise time ≤ 1000 V/s | 100 V; 1 min                           | 160 V; 1 min             | 400 V; 1 min             | 640 V; 1 min        |
| Withstanding (DC) voltage between leads and case                                        | 200 V; 1 min                           | 200 V; 1 min             | 500 V; 1 min             | 800 V; 1 min        |
| Maximum application temperature                                                         | 100 °C                                 | 105 °C                   |                          |                     |

## Note

(1) See "Voltage Proof Test for Metallized Film Capacitors": [www.vishay.com/doc?28169](http://www.vishay.com/doc?28169)



# DC Film Capacitors MKT Radial Potted Type

Vishay BCcomponents

**SPECIFIC REFERENCE DATA** (Compact size)

| DESCRIPTION                                                                                                                 | VALUE                                                                            |                                                                                     |                                                             |                                             |
|-----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------|
|                                                                                                                             | at 1 kHz                                                                         | at 10 kHz                                                                           | at 100 kHz                                                  |                                             |
| Tangent of loss angle:<br>$C \leq 0.1 \mu\text{F}$<br>$0.1 \mu\text{F} < C \leq 0.47 \mu\text{F}$<br>$C > 0.47 \mu\text{F}$ | $\leq 75 \times 10^{-4}$<br>$\leq 75 \times 10^{-4}$<br>$\leq 75 \times 10^{-4}$ | $\leq 130 \times 10^{-4}$<br>$\leq 130 \times 10^{-4}$<br>$\leq 130 \times 10^{-4}$ | $\leq 220 \times 10^{-4}$<br>$\leq 300 \times 10^{-4}$<br>- |                                             |
| Rated voltage pulse slope $(dU/dt)_R$ at                                                                                    | 100 V <sub>DC</sub><br>37 V/ $\mu\text{s}$                                       | 250 V <sub>DC</sub><br>44 V/ $\mu\text{s}$                                          | 400 V <sub>DC</sub><br>200 V/ $\mu\text{s}$                 | 630 V <sub>DC</sub><br>540 V/ $\mu\text{s}$ |
| R between leads, for $C \leq 0.33 \mu\text{F}$<br>at 100 V; 1 min                                                           | > 15 000 M $\Omega$                                                              | > 30 000 M $\Omega$                                                                 | > 30 000 M $\Omega$                                         | > 30 000 M $\Omega$                         |
| RC between leads<br>$C > 0.33 \mu\text{F}$ at 100 V; 1 min                                                                  | > 5000 s                                                                         |                                                                                     |                                                             |                                             |
| R between interconnecting leads and case (foil method)                                                                      | > 30 000 M $\Omega$                                                              | > 30 000 M $\Omega$                                                                 | > 30 000 M $\Omega$                                         | > 30 000 M $\Omega$                         |
| Withstanding (DC) voltage (cut off current 10 mA) <sup>(1)</sup> ; rise time $\leq 1000$ V/s<br>rise time 100 V/s           | 160 V; 1 min                                                                     | 400 V; 1 min                                                                        | 640 V; 1 min                                                | 1008 V; 1 min                               |
| Withstanding (DC) voltage between leads and case                                                                            | 200 V; 1 min                                                                     | 500 V; 1 min                                                                        | 800 V; 1 min                                                | 1260 V; 1 min                               |
| Maximum application temperature                                                                                             | 100 °C                                                                           |                                                                                     | 105 °C                                                      |                                             |

**Note**(1) See "Voltage Proof Test for Metallized Film Capacitors": [www.vishay.com/doc?28169](http://www.vishay.com/doc?28169)**U<sub>RDC</sub> = 63 V; U<sub>RAC</sub> = 40 V**

| C<br>(μF)                                                     | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XYYYY AND PACKAGING |                   |                    |                   |                    |                   |                    |                   | C-VALUE |
|---------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--------------------|-------------------|---------|
|                                                               |                                 |                            | AMMOPACK                                    |                   | LOOSE IN BOX       |                   |                    |                   | REEL               |                   |         |
|                                                               |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                   | Short leads        |                   | Long leads         |                   |                    |                   |         |
|                                                               |                                 |                            | C-tol. =<br>± 10 %                          | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % |         |
|                                                               |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       |         |
| Pitch = 5.08 mm ± 0.30 mm; d <sub>t</sub> = 0.50 mm ± 0.05 mm |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   |         |
| 0.056                                                         | 2.5 x 6.5 x 7.2                 | 0.18                       |                                             |                   |                    |                   |                    |                   |                    |                   | 563     |
| 0.068                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 683     |
| 0.082                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 823     |
| 0.10                                                          |                                 |                            | 75...                                       | 76...             | 11...              | 12...             | 15...              | 16...             | 18...              | 19...             | 104     |
| 0.12                                                          |                                 |                            | (2000)                                      | (2000)            | (2000)             | (2000)            | (1000)             | (1000)            | (2000)             | (2000)            | 124     |
| 0.15                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 154     |
| 0.18                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    | 184               |         |
| 0.22                                                          | 3.5 x 8.0 x 7.2                 | 0.3                        |                                             |                   |                    |                   |                    |                   |                    |                   | 224     |
| 0.27                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 274     |
| 0.33                                                          |                                 |                            | 75...                                       | 76...             | 11...              | 12...             | 15...              | 16...             | 18...              | 19...             | 334     |
| 0.39                                                          |                                 |                            | (1500)                                      | (1500)            | (2000)             | (2000)            | (1000)             | (1000)            | (1500)             | (1500)            | 394     |
| 0.47                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 474     |
| 0.56                                                          | 4.5 x 9.0 x 7.2                 | 0.42                       | 75...                                       | 76...             | 11...              | 12...             | 15...              | 16...             | 18...              | 19...             | 564     |
| 0.68                                                          |                                 |                            | (1000)                                      | (1000)            | (2000)             | (2000)            | (1000)             | (1000)            | (1000)             | (1000)            | 684     |
| 0.82                                                          | 6.0 x 11.0 x 7.2                | 0.64                       |                                             |                   |                    |                   |                    |                   |                    |                   | 824     |
| 1.0                                                           |                                 |                            | 75...                                       | 76...             | 11...              | 12...             | 15...              | 16...             | 18...              | 19...             | 105     |
| 1.2 <sup>(2)</sup>                                            |                                 |                            | (750)                                       | (750)             | (2000)             | (2000)            | (1000)             | (1000)            | (1000)             | (1000)            | 125     |
| 1.5 <sup>(2)</sup>                                            |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 155     |

**Notes**

• SPQ = Standard Packing Quantity

(1) Weight for short lead product only

(2) For C = 1.2  $\mu\text{F}$  and C = 1.5  $\mu\text{F}$ : U<sub>RDC</sub> = 50 V and U<sub>RAC</sub> = 32 V

$U_{RDC} = 100 \text{ V}$ ;  $U_{RAC} = 63 \text{ V}$  (standard size)

| C<br>(μF)                                                     | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XYYYY AND PACKAGING |                   |                    |                   |                    |                   |                    |                   |         |
|---------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--------------------|-------------------|---------|
|                                                               |                                 |                            | AMMOPACK                                    |                   | LOOSE IN BOX       |                   |                    |                   | REEL               |                   | C-VALUE |
|                                                               |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                   | Short leads        |                   | Long leads         |                   |                    |                   |         |
|                                                               |                                 |                            | C-tol. =<br>± 10 %                          | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % |         |
|                                                               |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       |         |
| Pitch = 5.08 mm ± 0.30 mm; d <sub>t</sub> = 0.50 mm ± 0.05 mm |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   |         |
| 0.0010                                                        | 2.5 x 6.5 x 7.2                 | 0.18                       | 85...<br>(2000)                             | 86...<br>(2000)   | 21...<br>(2000)    | 22...<br>(2000)   | 25...<br>(1000)    | 26...<br>(1000)   | 28...<br>(2000)    | 29...<br>(2000)   | 102     |
| 0.0012                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 122     |
| 0.0015                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 152     |
| 0.0018                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 182     |
| 0.0022                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 222     |
| 0.0027                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 272     |
| 0.0033                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 332     |
| 0.0039                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 392     |
| 0.0047                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 472     |
| 0.0056                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 562     |
| 0.0068                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 682     |
| 0.0082                                                        |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 822     |
| 0.010                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 103     |
| 0.012                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 123     |
| 0.015                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 153     |
| 0.018                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 183     |
| 0.022                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 223     |
| 0.027                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 273     |
| 0.033                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 333     |
| 0.039                                                         |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 393     |
| 0.047                                                         | 473                             |                            |                                             |                   |                    |                   |                    |                   |                    |                   |         |
| 0.056                                                         | 563                             |                            |                                             |                   |                    |                   |                    |                   |                    |                   |         |
| 0.068                                                         | 683                             |                            |                                             |                   |                    |                   |                    |                   |                    |                   |         |
| 0.082                                                         | 823                             |                            |                                             |                   |                    |                   |                    |                   |                    |                   |         |
| 0.10                                                          | 104                             |                            |                                             |                   |                    |                   |                    |                   |                    |                   |         |
| 0.12                                                          | 3.5 x 8.0 x 7.2                 | 0.30                       | 85...<br>(1500)                             | 86...<br>(1500)   | 21...<br>(2000)    | 22...<br>(2000)   | 25...<br>(1000)    | 26...<br>(1000)   | 28...<br>(1500)    | 29...<br>(1500)   | 124     |
| 0.15                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 154     |
| 0.18                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 184     |
| 0.22                                                          | 4.5 x 9.0 x 7.2                 | 0.42                       | 85...<br>(1000)                             | 86...<br>(1000)   | 21...<br>(2000)    | 22...<br>(2000)   | 25...<br>(1000)    | 26...<br>(1000)   | 28...<br>(1000)    | 29...<br>(1000)   | 224     |
| 0.27                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 274     |
| 0.33                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 334     |
| 0.39                                                          | 6.0 x 11.0 x 7.2                | 0.64                       | 85...<br>(750)                              | 86...<br>(750)    | 21...<br>(2000)    | 22...<br>(2000)   | 25...<br>(1000)    | 26...<br>(1000)   | 28...<br>(1000)    | 29...<br>(1000)   | 394     |
| 0.47                                                          |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   | 474     |

**Notes**

- SPQ = Standard Packing Quantity

<sup>(1)</sup> Weight for short lead product only

DC Film Capacitors  
MKT Radial Potted Type

Vishay BCcomponents

 $U_{RDC} = 100\text{ V}$ ;  $U_{RAC} = 40\text{ V}$  (compact size)

| C<br>( $\mu$ F)                                                       | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XYYYY AND PACKAGING |                       |                        |                       |                        |                       |                        |                       | C-VALUE<br><br>..YYY |
|-----------------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|----------------------|
|                                                                       |                                 |                            | AMMOPACK                                    |                       | LOOSE IN BOX           |                       |                        |                       | REEL                   |                       |                      |
|                                                                       |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                       | Short leads            |                       | Long leads             |                       |                        |                       |                      |
|                                                                       |                                 |                            | C-tol. =<br>$\pm$ 10 %                      | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % |                      |
|                                                                       |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           |                      |
| Pitch = 5.08 mm $\pm$ 0.30 mm; d <sub>t</sub> = 0.50 mm $\pm$ 0.05 mm |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       |                      |
| 0.12                                                                  | 3.5 x 8.0 x 7.2                 | 0.30                       | CB...<br>(1500)                             | CC...<br>(1500)       | CE...<br>(2000)        | CF...<br>(2000)       | CH...<br>(1000)        | CI...<br>(1000)       | CL...<br>(1500)        | CM...<br>(1500)       | 124                  |
| 0.15                                                                  |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 154                  |
| 0.18                                                                  |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 184                  |
| 0.22                                                                  |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 224                  |
| 0.27                                                                  |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 274                  |
| 0.33                                                                  | 334                             |                            |                                             |                       |                        |                       |                        |                       |                        |                       |                      |
| 0.39                                                                  | 4.5 x 9.0 x 7.2                 | 0.42                       | CB...<br>(1000)                             | CC...<br>(1000)       | CE...<br>(2000)        | CF...<br>(2000)       | CH...<br>(1000)        | CI...<br>(1000)       | CL...<br>(1000)        | CM...<br>(1000)       | 394                  |
| 0.47                                                                  |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 474                  |
| 0.56                                                                  | 6.0 x 11.0 x 7.2                | 0.64                       | CB...<br>(750)                              | CC...<br>(750)        | CE...<br>(2000)        | CF...<br>(2000)       | CH...<br>(1000)        | CI...<br>(1000)       | CL...<br>(1000)        | CM...<br>(1000)       | 564                  |

## Notes

- SPQ = Standard Packing Quantity
- <sup>(1)</sup> Weight for short lead product only

 $U_{RDC} = 250\text{ V}$ ;  $U_{RAC} = 160\text{ V}$  (standard size)

| C<br>( $\mu$ F)                                                       | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XXYYY AND PACKAGING |                       |                        |                       |                        |                       |                        |                       | C-VALUE<br>..YYY |
|-----------------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|------------------|
|                                                                       |                                 |                            | AMMOPACK                                    |                       | LOOSE IN BOX           |                       |                        |                       | REEL                   |                       |                  |
|                                                                       |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                       | Short leads            |                       | Long leads             |                       |                        |                       |                  |
|                                                                       |                                 |                            | C-tol. =<br>$\pm 10\%$                      | C-tol. =<br>$\pm 5\%$ | C-tol. =<br>$\pm 10\%$ | C-tol. =<br>$\pm 5\%$ | C-tol. =<br>$\pm 10\%$ | C-tol. =<br>$\pm 5\%$ | C-tol. =<br>$\pm 10\%$ | C-tol. =<br>$\pm 5\%$ |                  |
|                                                                       |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           |                  |
| Pitch = 5.08 mm $\pm$ 0.30 mm; d <sub>t</sub> = 0.50 mm $\pm$ 0.05 mm |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       |                  |
| 0.0010                                                                | 2.5 x 6.5 x 7.2                 | 0.18                       | 35...<br>(2000)                             | 36...<br>(2000)       | 41...<br>(2000)        | 42...<br>(2000)       | 45...<br>(1000)        | 46...<br>(1000)       | 48...<br>(2000)        | 49...<br>(2000)       | 102              |
| 0.0012                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 122              |
| 0.0015                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 152              |
| 0.0018                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 182              |
| 0.0022                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 222              |
| 0.0027                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 272              |
| 0.0033                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 332              |
| 0.0039                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 392              |
| 0.0047                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 472              |
| 0.0056                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 562              |
| 0.0068                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 682              |
| 0.0082                                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 822              |
| 0.010                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 103              |
| 0.012                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 123              |
| 0.015                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 153              |
| 0.018                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 183              |
| 0.022                                                                 | 3.5 x 8.0 x 7.2                 | 0.30                       | 35...<br>(1500)                             | 36...<br>(1500)       | 41...<br>(2000)        | 42...<br>(2000)       | 45...<br>(1000)        | 46...<br>(1000)       | 48...<br>(1500)        | 49...<br>(1500)       | 223              |
| 0.027                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 273              |
| 0.033                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 333              |
| 0.039                                                                 | 4.5 x 9.0 x 7.2                 | 0.42                       | 35...<br>(1000)                             | 36...<br>(1000)       | 41...<br>(2000)        | 42...<br>(2000)       | 45...<br>(1000)        | 46...<br>(1000)       | 48...<br>(1000)        | 49...<br>(1000)       | 393              |
| 0.047                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 473              |
| 0.056                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 563              |
| 0.068                                                                 | 6.0 x 11.0 x 7.2                | 0.64                       | 35...<br>(750)                              | 36...<br>(750)        | 41...<br>(2000)        | 42...<br>(2000)       | 45...<br>(1000)        | 46...<br>(1000)       | 48...<br>(1000)        | 49...<br>(1000)       | 683              |
| 0.082                                                                 |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 823              |
| 0.10                                                                  |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 104              |

## Notes

- SPQ = Standard Packing Quantity
- <sup>(1)</sup> Weight for short lead product only

$U_{RDC} = 250 \text{ V}$ ;  $U_{RAC} = 63 \text{ V}$  (compact size)

| C<br>(μF)                                                     | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XYYYY AND PACKAGING |                   |                    |                   |                    |                   |                    |                   | C-VALUE                         |
|---------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--------------------|-------------------|---------------------------------|
|                                                               |                                 |                            | AMMOPACK                                    |                   | LOOSE IN BOX       |                   |                    |                   | REEL               |                   |                                 |
|                                                               |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                   | Short leads        |                   | Long leads         |                   |                    |                   |                                 |
|                                                               |                                 |                            | C-tol. =<br>± 10 %                          | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % |                                 |
|                                                               |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       |                                 |
| Pitch = 5.08 mm ± 0.30 mm; d <sub>t</sub> = 0.50 mm ± 0.05 mm |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   |                                 |
| 0.022<br>0.027                                                | 2.5 x 6.5 x 7.2                 | 0.18                       | EB...<br>(2000)                             | EC...<br>(2000)   | EE...<br>(2000)    | EF...<br>(2000)   | EH...<br>(1000)    | EI...<br>(1000)   | EL...<br>(2000)    | EM...<br>(2000)   | 223<br>273                      |
| 0.033<br>0.039<br>0.047<br>0.056<br>0.068                     | 3.5 x 8.0 x 7.2                 | 0.30                       | EB...<br>(1500)                             | EC...<br>(1500)   | EE...<br>(2000)    | EF...<br>(2000)   | EH...<br>(1000)    | EI...<br>(1000)   | EL...<br>(1500)    | EM...<br>(1500)   | 333<br>393<br>473<br>563<br>683 |
| 0.082<br>0.10                                                 | 4.5 x 9.0 x 7.2                 | 0.42                       | EB...<br>(1000)                             | EC...<br>(1000)   | EE...<br>(2000)    | EF...<br>(2000)   | EH...<br>(1000)    | EI...<br>(1000)   | EL...<br>(1000)    | EM...<br>(1000)   | 823<br>104                      |
| 0.12<br>0.15<br>0.18<br>0.22                                  | 6.0 x 11.0 x 7.2                | 0.64                       | EB...<br>(750)                              | EC...<br>(750)    | EE...<br>(2000)    | EF...<br>(2000)   | EH...<br>(1000)    | EI...<br>(1000)   | EL...<br>(1000)    | EM...<br>(1000)   | 124<br>154<br>184<br>224        |

## Notes

- SPQ = Standard Packing Quantity

(1) Weight for short lead product only

 $U_{RDC} = 400 \text{ V}$ ;  $U_{RAC} = 220 \text{ V}$  (standard size)

| C<br>( $\mu$ F)                                                                                                      | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XYYYY AND PACKAGING |                       |                        |                       |                        |                       |                        |                       | C-VALUE<br><br>..YYY                                                             |
|----------------------------------------------------------------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|----------------------------------------------------------------------------------|
|                                                                                                                      |                                 |                            | AMMOPACK                                    |                       | LOOSE IN BOX           |                       |                        |                       | REEL                   |                       |                                                                                  |
|                                                                                                                      |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                       | Short leads            |                       | Long leads             |                       |                        |                       |                                                                                  |
|                                                                                                                      |                                 |                            | C-tol. =<br>$\pm$ 10 %                      | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % |                                                                                  |
|                                                                                                                      |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           |                                                                                  |
| Pitch = 5.08 mm $\pm$ 0.30 mm; d <sub>t</sub> = 0.50 mm $\pm$ 0.05 mm                                                |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       |                                                                                  |
| 0.0010<br>0.0012<br>0.0015<br>0.0018<br>0.0022<br>0.0027<br>0.0033<br>0.0039<br>0.0047<br>0.0056<br>0.0068<br>0.0082 | 2.5 x 6.5 x 7.2                 | 0.18                       | 65...<br>(2000)                             | 66...<br>(2000)       | 51...<br>(2000)        | 52...<br>(2000)       | 55...<br>(1000)        | 56...<br>(1000)       | 58...<br>(2000)        | 59...<br>(2000)       | 102<br>122<br>152<br>182<br>222<br>272<br>332<br>392<br>472<br>562<br>682<br>822 |
| 0.010<br>0.012<br>0.015                                                                                              | 3.5 x 8.0 x 7.2                 | 0.30                       | 65...<br>(1500)                             | 66...<br>(1500)       | 51...<br>(2000)        | 52...<br>(2000)       | 55...<br>(1000)        | 56...<br>(1000)       | 58...<br>(1500)        | 59...<br>(1500)       | 103<br>123<br>153                                                                |
| 0.018<br>0.022<br>0.027                                                                                              | 4.5 x 9.0 x 7.2                 | 0.42                       | 65...<br>(1000)                             | 66...<br>(1000)       | 51...<br>(2000)        | 52...<br>(2000)       | 55...<br>(1000)        | 56...<br>(1000)       | 58...<br>(1000)        | 59...<br>(1000)       | 183<br>223<br>273                                                                |
| 0.033<br>0.039<br>0.047                                                                                              | 6.0 x 11.0 x 7.2                | 0.64                       | 65...<br>(750)                              | 66...<br>(750)        | 51...<br>(2000)        | 52...<br>(2000)       | 55...<br>(1000)        | 56...<br>(1000)       | 58...<br>(1000)        | 59...<br>(1000)       | 333<br>393<br>473                                                                |

## Notes

- SPQ = Standard Packing Quantity

(1) Weight for short lead product only

DC Film Capacitors  
MKT Radial Potted Type

Vishay BCcomponents

 $U_{RDC} = 400 \text{ V}$ ;  $U_{RAC} = 160 \text{ V}$  (compact size)

| C<br>(μF)                                                     | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XYYYY AND PACKAGING |                   |                    |                   |                    |                   |                    |                   | C-VALUE                  |
|---------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--------------------------|
|                                                               |                                 |                            | AMMOPACK                                    |                   | LOOSE IN BOX       |                   |                    |                   | REEL               |                   |                          |
|                                                               |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                   | Short leads        |                   | Long leads         |                   |                    |                   |                          |
|                                                               |                                 |                            | C-tol. =<br>± 10 %                          | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % | C-tol. =<br>± 10 % | C-tol. =<br>± 5 % |                          |
|                                                               |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       | XX<br>(SPQ)        | XX<br>(SPQ)       |                          |
| Pitch = 5.08 mm ± 0.30 mm; d <sub>t</sub> = 0.50 mm ± 0.05 mm |                                 |                            |                                             |                   |                    |                   |                    |                   |                    |                   |                          |
| 0.010<br>0.012<br>0.015<br>0.018                              | 2.5 x 6.5 x 7.2                 | 0.18                       | FB...<br>(2000)                             | FC...<br>(2000)   | FE...<br>(2000)    | FF...<br>(2000)   | FH...<br>(1000)    | FI...<br>(1000)   | FL...<br>(2000)    | FM...<br>(2000)   | 103<br>123<br>153<br>183 |
| 0.022<br>0.027<br>0.033<br>0.039                              | 3.5 x 8.0 x 7.2                 | 0.30                       | FB...<br>(1500)                             | FC...<br>(1500)   | FE...<br>(2000)    | FF...<br>(2000)   | FH...<br>(1000)    | FI...<br>(1000)   | FL...<br>(1500)    | FM...<br>(1500)   | 223<br>273<br>333<br>393 |
| 0.047<br>0.056                                                | 4.5 x 9.0 x 7.2                 | 0.42                       | FB...<br>(1000)                             | FC...<br>(1000)   | FE...<br>(2000)    | FF...<br>(2000)   | FH...<br>(1000)    | FI...<br>(1000)   | FL...<br>(1000)    | FM...<br>(1000)   | 473<br>563               |
| 0.068<br>0.082<br>0.10                                        | 6.0 x 11.0 x 7.2                | 0.64                       | FB...<br>(750)                              | FC...<br>(750)    | FE...<br>(2000)    | FF...<br>(2000)   | FH...<br>(1000)    | FI...<br>(1000)   | FL...<br>(1000)    | FM...<br>(1000)   | 683<br>823<br>104        |

## Notes

- SPQ = Standard Packing Quantity

<sup>(1)</sup> Weight for short lead product only $U_{RDC} = 630 \text{ V}$ ;  $U_{RAC} = 220 \text{ V}$  (compact size)

| C<br>( $\mu$ F)                                                                                                                                                        | DIMENSIONS<br>w x h x l<br>(mm) | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 370 XYYYY AND PACKAGING |                       |                        |                       |                        |                       |                        |                       | C-VALUE                                                                                                             |       |                 |                 |                 |                 |                 |                 |                 |                 |                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|----------------------------|---------------------------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------|-------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|------------------|
|                                                                                                                                                                        |                                 |                            | AMMOPACK                                    |                       | LOOSE IN BOX           |                       |                        |                       | REEL                   |                       |                                                                                                                     |       |                 |                 |                 |                 |                 |                 |                 |                 |                  |
|                                                                                                                                                                        |                                 |                            | H = 18.5 mm;<br>P <sub>0</sub> = 12.7 mm    |                       | Short leads            |                       | Long leads             |                       |                        |                       |                                                                                                                     |       |                 |                 |                 |                 |                 |                 |                 |                 |                  |
|                                                                                                                                                                        |                                 |                            | C-tol. =<br>$\pm$ 10 %                      | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % | C-tol. =<br>$\pm$ 10 % | C-tol. =<br>$\pm$ 5 % |                                                                                                                     |       |                 |                 |                 |                 |                 |                 |                 |                 |                  |
|                                                                                                                                                                        |                                 |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           | XX<br>(SPQ)            | XX<br>(SPQ)           |                                                                                                                     | ..YYY |                 |                 |                 |                 |                 |                 |                 |                 |                  |
| Pitch = 5.08 mm $\pm$ 0.30 mm; d <sub>t</sub> = 0.50 mm $\pm$ 0.05 mm                                                                                                  |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       |                                                                                                                     |       |                 |                 |                 |                 |                 |                 |                 |                 |                  |
| 0.00068<br>0.00082<br>0.0010<br>0.0012<br>0.0015<br>0.0018<br>0.002<br>0.0022<br>0.0024<br>0.0027<br>0.0033<br>0.0039<br>0.0047<br>0.0056<br>0.0068<br>0.0082<br>0.010 | 3.5 x 8.0 x 7.2                 | 0.35                       | GB...<br>(1500)                             | GC...<br>(1500)       | GE...<br>(2000)        | GF...<br>(2000)       | GH...<br>(1000)        | GI...<br>(1000)       | GL...<br>(1500)        | GM...<br>(1500)       | 681<br>821<br>102<br>122<br>152<br>182<br>202<br>222<br>242<br>272<br>332<br>392<br>472<br>562<br>682<br>822<br>103 |       |                 |                 |                 |                 |                 |                 |                 |                 |                  |
| 0.012<br>0.015                                                                                                                                                         |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       | 4.5 x 9.0 x 7.2                                                                                                     | 0.45  | GB...<br>(1000) | GC...<br>(1000) | GE...<br>(2000) | GF...<br>(2000) | GH...<br>(1000) | GI...<br>(1000) | GL...<br>(1000) | GM...<br>(1000) | 123<br>153       |
| 0.018<br>0.022<br>0.027<br>0.033                                                                                                                                       |                                 |                            |                                             |                       |                        |                       |                        |                       |                        |                       |                                                                                                                     |       |                 |                 |                 |                 |                 |                 |                 |                 | 6.0 x 11.0 x 7.2 |

## Notes

- SPQ = Standard Packing Quantity

<sup>(1)</sup> Weight for short lead product only

## MOUNTING

### Normal Use

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to packaging information: [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139) or end of catalog.

### Specific Method of Mounting to Withstand Vibration and Shock

In order to withstand vibration and shock tests, it must be ensured that stand-off pips are in good contact with the printed-circuit board:


- For pitches  $\leq 15$  mm capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

### Space Requirements on Printed Circuit Board

The maximum space for length ( $l_{max.}$ ), width ( $w_{max.}$ ) and height ( $h_{max.}$ ) of film capacitors to take in account on the printed circuit board is shown in the drawings.

- For products with pitch  $\leq 15$  mm,  $\Delta w = \Delta l = 0.3$  mm;  $\Delta h = 0.1$  mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.



## SOLDERING CONDITIONS

For general soldering conditions and wave soldering profile, we refer to the application note:

“Soldering Guidelines for Film Capacitors”: [www.vishay.com/doc?28171](http://www.vishay.com/doc?28171)

### Storage Temperature

- Storage temperature:  $T_{stg} = -25\text{ °C}$  to  $+35\text{ °C}$  with relative humidity of maximum 75 % without condensation


### Ratings and Characteristics Reference Conditions

Unless otherwise specified, all electrical values apply to an ambient temperature of  $23\text{ °C} \pm 1\text{ °C}$ , an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50\% \pm 2\%$ .


For reference testing, a conditioning period shall be applied over  $96\text{ h} \pm 4\text{ h}$  by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.

## CHARACTERISTICS


Capacitance as a function of ambient temperature (typical curve)  
for voltage 63 V




Capacitance as a function of ambient temperature (typical curve)  
for voltages > 63 V




Capacitance as a function of frequency (typical curve)




Impedance as a function of frequency



Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency




# DC Film Capacitors MKT Radial Potted Type

Vishay BCcomponents


Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency





Max. AC voltage as a function of frequency

**Maximum RMS current (sinewave) as a function of frequency**

The maximum RMS current is defined by  $I_{ac} = \omega \times C \times U_{ac}$ .

$U_{ac}$  is the maximum AC voltage depending on the ambient temperature in the curves "Max. RMS voltage and AC current as a function of frequency".

Tangent of loss angle as a function of frequency  
(typical curve)Insulation resistance as a function of the ambient temperature  
(typical curve)Max. DC and AC voltage as a function of frequency  
for voltage 63 VMax. DC and AC voltage as a function of frequency  
for voltages > 63 V

Maximum allowed component temperature rise ( $\Delta T$ )  
as a function of the ambient temperature ( $T_{amb}$ ) for voltage 63 V



Maximum allowed component temperature rise ( $\Delta T$ )  
as a function of the ambient temperature ( $T_{amb}$ ) for voltages > 63 V



### HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C

| W <sub>max.</sub><br>(mm) | HEAT CONDUCTIVITY (mW/°C) |
|---------------------------|---------------------------|
|                           | PITCH 5 mm                |
| 2.5                       | 2.5                       |
| 3.5                       | 3.0                       |
| 4.5                       | 4.0                       |
| 6.0                       | 5.5                       |

### POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free ambient temperature.


The power dissipation can be calculated according type detail specification "HQN-384-01/101: Technical Information Film Capacitors".

The component temperature rise ( $\Delta T$ ) can be measured (see section "Measuring the component temperature" for more details) or calculated by  $\Delta T = P/G$ :

- $\Delta T$  = Component temperature rise (°C)
- $P$  = Power dissipation of the component (mW)
- $G$  = Heat conductivity of the component (mW/°C)

### MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded ( $T_{amb}$ ) and maximum loaded condition ( $T_C$ ).

The temperature rise is given by  $\Delta T = T_C - T_{amb}$ .

To avoid radiation or convection, the capacitor should be tested in a wind-free box.

**APPLICATION NOTE AND LIMITING CONDITIONS**

These capacitors are not suitable for mains applications as across-the-line capacitors without additional protection, as described hereunder. These mains applications are strictly regulated in safety standards and therefore electromagnetic interference suppression capacitors conforming the standards must be used.

- For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: [dc-film@vishay.com](mailto:dc-film@vishay.com)

To select the capacitor for a certain application, the following conditions must be checked:

- The peak voltage ( $U_P$ ) shall not be greater than the rated DC voltage ( $U_{RDC}$ )
- The peak-to-peak voltage ( $U_{P-P}$ ) shall not be greater than  $2\sqrt{2} \times U_{RAC}$  to avoid the ionisation inception level
- The voltage peak slope ( $dU/dt$ ) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by  $U_{RDC}$  and divided by the applied voltage.  
For all other pulses following equation must be fulfilled:  $2 \times \int_0^T \left(\frac{dU}{dt}\right)^2 \times dt < U_{RDC} \times \left(\frac{dU}{dt}\right)_{rated}$   
T is the pulse duration.
- The maximum component surface temperature rise must be lower than the limits (see figure max. allowed component temperature rise).
- Since in circuits used at voltages over 280 V peak-to-peak the risk for an intrinsically active flammability after a capacitor breakdown (short circuit) increases, it is recommended that the power to the component is limited to 100 times the values mentioned in the table: "Heat conductivity"
- When using these capacitors as across-the-line capacitor in the input filter for mains applications or as series connected with an impedance to the mains the applicant must guarantee that the following conditions are fulfilled in any case (spikes and surge voltages from the mains included).

**Voltage Conditions for 6 Above**

| ALLOWED VOLTAGES                             | $T_{amb} \leq 85^\circ\text{C}$ | $85^\circ\text{C} < T_{amb} \leq 100^\circ\text{C}$ for 63 V                |
|----------------------------------------------|---------------------------------|-----------------------------------------------------------------------------|
|                                              |                                 | $85^\circ\text{C} < T_{amb} \leq 105^\circ\text{C}$ for > 63 V              |
| Maximum continuous RMS voltage               | $U_{RAC}$                       | See "Max. AC voltage as function of temperature CBB952" per characteristics |
| Maximum temperature RMS-overvoltage (< 24 h) | $1.25 \times U_{RAC}$           | $U_{RAC}$                                                                   |
| Maximum peak voltage ( $U_{O-P}$ ) (< 2 s)   | $1.6 \times U_{RDC}$            | $1.3 \times U_{RDC}$                                                        |

**EXAMPLE**

C = 330 nF - 63 V used for the voltage signal shown in next drawing.

$U_{P-P} = 40\text{ V}$ ;  $U_P = 35\text{ V}$ ;  $T_1 = 100\text{ }\mu\text{s}$ ;  $T_2 = 200\text{ }\mu\text{s}$

The ambient temperature is  $35^\circ\text{C}$

Checking conditions:

- The peak voltage  $U_P = 35\text{ V}$  is lower than  $63\text{ V}_{DC}$
- The peak-to-peak voltage  $40\text{ V}$  is lower than  $2\sqrt{2} \times 40\text{ V}_{AC} = 113\text{ V}_{P-P}$
- The voltage pulse slope ( $dU/dt$ ) =  $40\text{ V}/100\text{ }\mu\text{s} = 0.4\text{ V}/\mu\text{s}$   
This is lower than  $60\text{ V}/\mu\text{s}$  (see specific reference data for each version)
- The dissipated power is  $16.2\text{ mW}$  as calculated with fourier terms  
The temperature rise for  $W_{max.} = 3.5\text{ mm}$  and pitch =  $5\text{ mm}$  will be  $16.2\text{ mW}/3.0\text{ mW}/^\circ\text{C} = 5.4^\circ\text{C}$   
This is lower than  $15^\circ\text{C}$  temperature rise at  $35^\circ\text{C}$ , according figure max. allowed component temperature rise
- Not applicable
- Not applicable

**Voltage Signal**

**INSPECTION REQUIREMENTS****General Notes:**

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-2 and Specific Reference Data”.

**Group C Inspection Requirements**

| SUB-CLAUSE NUMBER AND TEST                                | CONDITIONS                                                                                                                                                                                                                                        | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b>       |                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.1 Dimensions (detail)                                   |                                                                                                                                                                                                                                                   | As specified in chapters “MKT 370 General Data” of this specification                                                                                                                                                                                                                                                                                                                     |
| 4.3.1 Initial measurements                                | Capacitance<br>Tangent of loss angle:<br>For $C \leq 470$ nF at 100 kHz or<br>for $C > 470$ nF at 10 kHz                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.3 Robustness of terminations                            | Tensile and bending                                                                                                                                                                                                                               | No visible damage                                                                                                                                                                                                                                                                                                                                                                         |
| 4.4 Resistance to soldering heat                          | Method: 1A<br>Solder bath: $280\text{ °C} \pm 5\text{ °C}$<br>Duration: 10 s                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.14 Component solvent resistance                         | Isopropylalcohol at room temperature<br>Method: 2<br>Immersion time: $5\text{ min} \pm 0.5\text{ min}$<br>Recovery time: Min. 1 h, max. 2 h                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.4.2 Final measurements                                  | Visual examination<br><br>Capacitance<br>Tangent of loss angle                                                                                                                                                                                    | No visible damage<br>Legible marking<br>$ \Delta C/C  \leq 2\%$ of the value measured initially<br>Increase of $\tan \delta$<br>$\leq 0.005$ for:<br>$C \leq 100$ nF or<br>$\leq 0.010$ for:<br>$100\text{ nF} < C \leq 220\text{ nF}$ or<br>$\leq 0.015$ for:<br>$220\text{ nF} < C \leq 470\text{ nF}$ and<br>$\leq 0.003$ for:<br>$C > 470$ nF<br>Compared to values measured in 4.3.1 |
| <b>SUB-GROUP C1B OTHER PART OF SAMPLE OF SUB-GROUP C1</b> |                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.6.1 Initial measurements                                | Capacitance<br>Tangent of loss angle:<br>For $C \leq 470$ nF at 100 kHz or<br>for $C > 470$ nF at 10 kHz                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.6 Rapid change of temperature                           | $\theta A = -55\text{ °C}$<br>$\theta B = +100\text{ °C}$ for rated voltage 63 V<br>+ $105\text{ °C}$ for rated voltage $> 63$ V<br>5 cycles<br>Duration $t = 30\text{ min}$                                                                      |                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.7 Vibration                                             | Visual examination<br>Mounting:<br>See section “Mounting” of this specification<br>Procedure B4<br>Frequency range: 10 Hz to 55 Hz<br>Amplitude: 0.75 mm or<br>Acceleration $98\text{ m/s}^2$<br>(whichever is less severe)<br>Total duration 6 h | No visible damage                                                                                                                                                                                                                                                                                                                                                                         |
| 4.7.2 Final inspection                                    | Visual examination                                                                                                                                                                                                                                | No visible damage                                                                                                                                                                                                                                                                                                                                                                         |

| SUB-CLAUSE NUMBER AND TEST                                                                                                                                                                                 | CONDITIONS                                                                                                                                                                                                                                                                                                                                                                            | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4.9 Shock                                                                                                                                                                                                  | Mounting:<br>See section "Mounting" of this specification<br>Pulse shape: Half sine<br>Acceleration: 490 m/s <sup>2</sup><br>Duration of pulse: 11 ms                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 4.9.3 Final measurements                                                                                                                                                                                   | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br><br><br><br><br><br><br><br><br>Insulation resistance                                                                                                                                                                                                                                                       | No visible damage<br><br>$ \Delta C/C  \leq 3\%$ of the value measured in 4.6.1<br><br>Increase of $\tan \delta$<br>$\leq 0.010$ for:<br>$C \leq 220$ nF or<br>$\leq 0.015$ for:<br>$220$ nF < $C \leq 470$ nF and<br>$\leq 0.003$ for:<br>$C > 470$ nF<br>Compared to values measured in 4.6.1<br><br>As specified in section "Specific Reference Data 370" of this specification                                                                                               |
| <b>SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B</b>                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 4.10 Climatic sequence<br>4.10.2 Dry heat<br><br>4.10.3 Damp heat cyclic<br>Test Db, first cycle<br>4.10.4 Cold<br><br>4.10.6 Damp heat cyclic<br>Test Db, remaining cycles<br>4.10.6.2 Final measurements | Temperature:<br>+ 100 °C for rated voltage 63 V<br>+ 105 °C for rated voltage > 63 V<br>Duration: 16 h<br><br><br>Temperature: - 55 °C<br>Duration: 2 h<br><br>Voltage proof = $U_{RDC}$ for 1 min within 15 min<br>after removal from testchamber<br><br>Visual examination<br><br><br>Capacitance<br><br><br>Tangent of loss angle<br><br><br><br><br><br><br>Insulation resistance | No breakdown of flash-over<br><br><br>No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 5\%$ of the value measured in 4.4.2 or 4.9.3<br><br>Increase of $\tan \delta$<br>$\leq 0.010$ for:<br>$C \leq 220$ nF or<br>$\leq 0.015$ for:<br>$220$ nF < $C \leq 470$ nF and<br>$\leq 0.005$ for:<br>$C > 470$ nF<br>Compared to values measured in 4.3.1 or 4.6.1<br><br>$\geq 50\%$ of values specified in section "Specific Reference Data 370" of this specification |
| <b>SUB-GROUP C2</b>                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 4.11 Damp heat steady state<br>4.11.1 Initial measurements                                                                                                                                                 | 56 days, 40 °C, 90 % to 95 % RH<br><br>Capacitance<br>Tangent of loss angle at 1 kHz                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

DC Film Capacitors  
MKT Radial Potted Type

## Vishay BCcomponents

| SUB-CLAUSE NUMBER AND TEST  | CONDITIONS                                                                                                                                                                                                                                                       | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4.11.3 Final measurements   | Voltage proof = $U_{RDC}$ for 1 min within 15 min after removal from testchamber<br><br>Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance                                                                          | No breakdown of flash-over<br><br>No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 5\%$ of the value measured in 4.11.1<br><br>Increase of $\tan \delta \leq 0.005$<br>Compared to values measured in 4.11.1<br><br>$\geq 50\%$ of values specified in section “Specific Reference Data 370” of this specification                                                                                                                                                                                                                    |
| <b>SUB-GROUP C3</b>         |                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.12 Endurance              | Duration: 2000 h<br>$1.25 \times U_{RDC}$ at $85\text{ }^{\circ}\text{C}$<br>$0.8 \times 1.25 U_{RDC}$ at $+100\text{ }^{\circ}\text{C}$ for rated voltage 63 V<br>$0.8 \times 1.25 U_{RDC}$ at $+105\text{ }^{\circ}\text{C}$ for rated voltage $> 63\text{ V}$ |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.12.1 Initial measurements | Capacitance<br>Tangent of loss angle:<br>For $C \leq 470\text{ nF}$ at 100 kHz or<br>for $C > 470\text{ nF}$ at 10 kHz                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.12.5 Final measurements   | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance                                                                                                                                                                  | No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 5\%$ compared to values measured in 4.12.1<br><br>Increase of $\tan \delta$<br>$\leq 0.005$ for at $85\text{ }^{\circ}\text{C}$<br>$\leq 0.010$ for at $100\text{ }^{\circ}\text{C}$ for:<br>$C \leq 220\text{ nF}$ or<br>$\leq 0.015$ for:<br>$220\text{ nF} < C \leq 470\text{ nF}$ and<br>$\leq 0.003$ for:<br>$C > 470\text{ nF}$<br>Compared to values measured in 4.12.1<br><br>$\geq 50\%$ of values specified in section “Specific Reference Data 370” of this specification |
| <b>SUB-GROUP C4</b>         |                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.13 Charge and discharge   | 10 000 cycles<br>Charged to $U_{RDC}$<br>Discharge resistance:<br>$R = \frac{U_R}{C \times 2.5 \times (dU/dt)_R}$                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.13.1 Initial measurements | Capacitance<br>Tangent of loss angle:<br>For $C \leq 470\text{ nF}$ at 100 kHz or<br>for $C > 470\text{ nF}$ at 10 kHz                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.13.3 Final measurements   | Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance                                                                                                                                                                                            | $ \Delta C/C  \leq 3\%$ compared to values measured in 4.13.1<br><br>Increase of $\tan \delta$<br>$\leq 0.005$ for:<br>$C \leq 100\text{ nF}$ or<br>$\leq 0.010$ for:<br>$100\text{ nF} < C \leq 220\text{ nF}$ or<br>$\leq 0.015$ for:<br>$220\text{ nF} < C \leq 470\text{ nF}$ and<br>$\leq 0.003$ for:<br>$C > 470\text{ nF}$<br>Compared to values measured in 4.13.1<br><br>$\geq 50\%$ of values specified in section “Specific Reference Data 370” of this specification                                                                    |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9