



26M048B


Technical Specifications


Part Number		Unipolar		Bipolar	
		26M048B1U	26M048B2U	26M048B1B	26M048B2B
Rated voltage	(vdc)	5	12	5	12
Resistance per phase ± 10%	(ohms)	19.60	110.00	19.80	108.00
Inductance per phase, Typ	(mH)	5.30	36.50	13.00	60.70
Rated current per phase *	(amps)	0.26	0.11	0.25	0.11
Holding torque, min *	(oz-in / mNm)	1.3 / 9.2		1.5 / 10.6	
Step angle *	(degrees)	7.5 ± 0.5°			
Steps per revolution *		48			
Detent torque, max	(oz-in / mNm)	0.19 /1.34			
Thermal resistance	(ºC / watt)	N.A.			
Rotor moment of inertia	(oz-in-s^2 / g-cm^2)	6.01 x 10E-3 / 1.1			
Ambient temperature range					
Operating	(ºC)	-20 ~ +70			
Storage	(ºC)	-40 ~ +85			
Bearing type		Sintered Bronze Sleeve			
Insulation resistance at 500vdc	(MΩ)	100			
Dielectric withstanding voltage	(vac)	650 for 2 seconds			
Weight	(lb / g)	.075 /34			
Shaft load ratings, max at 600 rpm					
Radial	(lbs / kg)	.337 /.153			
Axial	(lbs / kg)	.337 /.153			
Leadwires		AWG 28, UL 1429			
Temperature class, max	(ºC)	B(130ºC)			
RoHS		Compliant			

All motor data values at 25ºC unless otherwise specified

* Energise at rated current, 2 phase on


26M024B1B, 26M048B1B
Torque vs Speed
5 vdc, full step, unipolar voltage drive
oz-in
mNm
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0
5.0
4.5
4.0
3.5
3.0
2.5
2.0
1.5
1.0
0.5
0.0
100 200 300 400 500 600 700 pps
250 500 750 1,000 1,250 1,500 1,750
125 250 375 500 625 750 875 rpm
26M024B1U Pull-Out Torque
26M024B1U Pull-In Torque
26M048B1U Pull-Out Torque
26M048B1U Pull-In Torque


26M024B1B, 26M048B1B
Torque vs Speed
5 vdc, full step, bipolar voltage drive
oz-in
mNm
1
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0
6.0
5.0
4.0
3.0
2.0
1.0
0.0
100 200 300 400 500 600 700 pps
250 500 750 1,000 1,250 1,500 1,750
125 250 375 500 625 750 875 rpm
26M024B1B Pull-Out Torque
26M024B1B Pull-In Torque
26M048B1B Pull-Out Torque
26M048B1B Pull-In Torque


35M020B1U, 35M024B1U, 35M048B1U
Torque vs Speed
5 vdc, full step, unipolar voltage drive
oz-in
mNm
1.6
1.4
1.2
1
0.8
0.6
0.4
0.2
0
12.0
10.0
8.0
6.0
4.0
2.0
0.0
100 200 300 400 500 pps
048 125 250 375 500 625
024 250 500 750 1,000 1,250 rpm
020 300 600 900 1,200 1,500
35M020B1U Pull-Out Torque
35M024B1U Pull-Out Torque
35M048B1U Pull-Out Torque
35M048B1U Pull-In Torque
35M020B1U Pull-In Torque
35M024B1U Pull-In Torque

20M SERIES SYNCHRONOUS MOTOR

Technical Specifications

Part Number			20M600B3A	20M720B3A
Ac operating voltage		(vac)	24.0	24.0
Frequency		(Hz)	50.0	60.0
Speed		(rpm)	600.0	720.0
Direction of rotation		-	Reversible	Reversible
Synchronous torque		(oz-in / mNm)	0.38 / 2.68	0.38 / 2.68
Capacitance		(µF)	2.20	2.20
Rotor moment of inertia		($oz\text{-}in\text{-}s^2$ / $g\text{-}cm^2$)	2.24 x $10E^{-3}$ / 0.41	
Weight		(lbs / g)	0.052 /23.5	
Leadwires			AWG 28, UL 1429	
Ambient temperature range	Operating	(ºC)	-20 ~ +70	
	Storage	(ºC)	-40 ~ +85	
Bearing type			Sintered Bronze Sleeve	
Insulation resistance at 500vdc		(Mohms)	100	
Dielectric withstanding voltage		(vac)	650 ± 50 VRMS 2 seconds	
Temperature class, max		(ºC)	B(130ºC)	
RoHS			Compliant	

All motor data values at 25°C unless otherwise specified

* Energise at rated current, 2 phase on

26M SERIES SYNCHRONOUS MOTOR

Technical Specifications


Part Number			26M250B3A	26M250B5A	26M300B3A	26M300B5A
Ac operating voltage		(vac)	24.0	120.0	24.0	120.0
Frequency		(Hz)	50.0	50.0	60.0	60.0
Speed		(rpm)	250.0	250.0	300.0	300.0
Direction of rotation		-	Reversible	Reversible	Reversible	Reversible
Synchronous torque		(oz-in / mNm)	0.89 / 6.25	0.90 / 6.33	0.89 /6.25	0.90 /6.33
Capacitance		(µF)	6.80	0.3	6.80	0.330
Rotor moment of inertia		($oz\text{-}in\text{-}s^2$ / $g\text{-}cm^2$)	6.01 x $10E^{-3}$ / 1.1			
Weight		(lbs / g)	.075 / 34			
Leadwires			AWG 28, UL 1429			
Ambient temperature range	Operating	(ºC)	-20 ~ +70			
	Storage	(ºC)	-40 ~ +85			
Bearing type			Sintered Bronze Sleeve			
Insulation resistance at 500vdc		(Mohms)	100			
Dielectric withstanding voltage		(vac)	650 ± 50 VRMS 2 seconds			
Temperature class, max		(ºC)	B(130ºC)			
RoHS			Compliant			

All motor data values at 25°C unless otherwise specified


* Energise at rated current, 2 phase on

26M-V & 35M-X

26M-V



35M-X



Gear Ratios Available for Can Stack

26M-V GEAR RATIOS

Part suffix	Gear ratio	Efficiency %	Output step angle	Output speed rpm @ 100 PPS*	Running torque @ 100 PPS* oz-in / mN-m
- V 11	2 : 1	90.0%	3.75°	62.50	1.16 / 8.9
- V 16	5 : 1	81.0%	1.5°	25.00	2.41 / 17.01
- V 19	7.5 : 1	73.0%	1.00°	16.66	3.00 / 21.08
- V 21	10 : 1	73.0%	0.75°	12.50	4.00 / 28.24
- V 24	15 : 1	66.0%	0.5°	8.33	5.00 / 35.3
- V 27	20 : 1	66.0%	0.375°	6.25	6.64 / 46.88
- V 31	30 : 1	66.0%	0.25°	4.17	10.00 / 70.6
- V 37	60 : 1	59.0%	0.125°	2.09	16.00 / 112.96

35M-X GEAR RATIOS

Part suffix	Gear ratio	Efficiency %	Output step angle	Output speed rpm @ 240 PPS*	Running torque @ 240 PPS* oz-in / mN-m
- X 24	15 : 1	80.0%	0.500°	20.00	5.0 / 35.30 MAX
- X 27	20 : 1	80.0%	0.375°	15.00	5.0 / 35.30 MAX
- X 31	30 : 1	80.0%	0.250°	10.00	5.0 / 35.30 MAX
- X 37	60 : 1	80.0%	0.125°	5.00	5.0 / 35.30 MAX
- X 39	75 : 1	80.0%	0.100°	4.00	5.0 / 35.30 MAX
- X 45	150 : 1	70.0%	0.050°	2.00	5.0 / 35.30 MAX
- X 52	300 : 1	70.0%	0.025°	1.00	5.0 / 35.30 MAX
- X 64	1350 : 1	65.0%	0.0055°	0.22	5.0 / 35.30 MAX

* Energise at rated current, 2 phase on

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9