

## Potential distributors - PTRVB 8-PV - 3270159

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Potential distributors, Nom. voltage: 250 V, Nominal current: 17.5 A, Cross section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 14 - 26, Connection type: Push-in connection, Width: 8.3 mm, Length: 100 mm, Color: gray, Assembly: NS 35/7,5, NS 35/15

### Product Features

- Bridgeable potential distributor
- High contact quality thanks to push-in technology as a replacement for Wire-Wrap®, TERMI-POINT®, etc.
- Tool-free wiring in a confined space thanks to compact size



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 56.0 g   |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### General

|                                        |                     |
|----------------------------------------|---------------------|
| Number of levels                       | 8                   |
| Number of connections                  | 32                  |
| Nominal cross section                  | 1.5 mm <sup>2</sup> |
| Color                                  | gray                |
| Insulating material                    | PA                  |
| Flammability rating according to UL 94 | V0                  |
| Rated surge voltage                    | 4 kV                |
| Overvoltage category                   | III                 |
| Insulating material group              | I                   |
| Connection in acc. with standard       | IEC 60947-7-1       |

# Potential distributors - PTRVB 8-PV - 3270159

## Technical data

### General

|                                                                                           |                                                                     |
|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| Maximum load current                                                                      | 32 A (The total current of the terminal block must not exceed 32 A) |
| Nominal current $I_N$                                                                     | 17.5 A (with 1.5 mm <sup>2</sup> conductor cross section)           |
| Nominal voltage $U_N$                                                                     | 250 V                                                               |
| Open side panel                                                                           | Yes                                                                 |
| Shock protection test specification                                                       | DIN EN 50274 (VDE 0660-514):2002-11                                 |
| Back of the hand protection                                                               | guaranteed                                                          |
| Finger protection                                                                         | guaranteed                                                          |
| Result of surge voltage test                                                              | Test passed                                                         |
| Surge voltage test setpoint                                                               | 4.8 kV                                                              |
| Result of power-frequency withstand voltage test                                          | Test passed                                                         |
| Power frequency withstand voltage setpoint                                                | 1.5 kV                                                              |
| Result of the test for mechanical stability of terminal points (5 x conductor connection) | Test passed                                                         |
| Result of bending test                                                                    | Test passed                                                         |
| Bending test rotation speed                                                               | 10 rpm                                                              |
| Bending test turns                                                                        | 135                                                                 |
| Bending test conductor cross section/weight                                               | 0.14 mm <sup>2</sup> / 0.2 kg                                       |
|                                                                                           | 1.5 mm <sup>2</sup> / 0.4 kg                                        |
|                                                                                           | 2.5 mm <sup>2</sup> / 0.7 kg                                        |
| Tensile test result                                                                       | Test passed                                                         |
| Conductor cross section tensile test                                                      | 0.14 mm <sup>2</sup>                                                |
| Tractive force setpoint                                                                   | 10 N                                                                |
| Conductor cross section tensile test                                                      | 1.5 mm <sup>2</sup>                                                 |
| Tractive force setpoint                                                                   | 40 N                                                                |
| Conductor cross section tensile test                                                      | 2.5 mm <sup>2</sup>                                                 |
| Tractive force setpoint                                                                   | 50 N                                                                |
| Result of tight fit on support                                                            | Test passed                                                         |
| Tight fit on carrier                                                                      | NS 35                                                               |
| Setpoint                                                                                  | 1 N                                                                 |
| Result of voltage-drop test                                                               | Test passed                                                         |
| Requirements, voltage drop                                                                | ≤ 6,4 mV                                                            |
| Result of temperature-rise test                                                           | Test passed                                                         |
| Short circuit stability result                                                            | Test passed                                                         |
| Conductor cross section short circuit testing                                             | 1.5 mm <sup>2</sup>                                                 |
| Short-time current                                                                        | 0.18 kA                                                             |
| Conductor cross section short circuit testing                                             | 2.5 mm <sup>2</sup>                                                 |
| Short-time current                                                                        | 0.3 kA                                                              |

# Potential distributors - PTRVB 8-PV - 3270159

## Technical data

### General

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Result of aging test                                                    | Test passed |
| Ageing test for screwless modular terminal block temperature cycles     | 192         |
| Result of thermal test                                                  | Test passed |
| Proof of thermal characteristics (needle flame) effective duration      | 30 s        |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C      |
| Static insulating material application in cold                          | -60 °C      |

### Dimensions

|                  |         |
|------------------|---------|
| Width            | 8.3 mm  |
| Length           | 100 mm  |
| Height NS 35/7,5 | 87.5 mm |
| Height NS 35/15  | 95 mm   |

### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Connection method                                                          | Push-in connection   |
| Connection in acc. with standard                                           | IEC 60947-7-1        |
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 2.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.                                           | 26                   |
| Conductor cross section AWG max.                                           | 14                   |
| Conductor cross section flexible min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.                                      | 1.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible                                 | 26                   |
| Max. AWG conductor cross section, flexible                                 | 14                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 1.5 mm <sup>2</sup>  |
| Stripping length                                                           | 8 mm ... 10 mm       |

### Standards and Regulations

|                                        |               |
|----------------------------------------|---------------|
| Connection in acc. with standard       | IEC 60947-7-1 |
| Flammability rating according to UL 94 | V0            |

## Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27141120 |
|------------|----------|

## Potential distributors - PTRVB 8-PV - 3270159

### Classifications

#### eCl@ss


|            |          |
|------------|----------|
| eCl@ss 6.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |
| eCl@ss 9.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

### Drawings

#### Circuit diagram



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9