

**NPN PRE-BIASED SMALL SIGNAL SOT23 SURFACE MOUNT TRANSISTOR**
**Product Summary**

| Part Number | R1 (NOM)      |
|-------------|---------------|
| DDTC113TCA  | 1K $\Omega$   |
| DDTC123TCA  | 2.2K $\Omega$ |
| DDTC143TCA  | 4.7K $\Omega$ |
| DDTC114TCA  | 10K $\Omega$  |
| DDTC124TCA  | 22K $\Omega$  |
| DDTC144TCA  | 47K $\Omega$  |
| DDTC115TCA  | 100K $\Omega$ |
| DDTC125TCA  | 200K $\Omega$ |

**Features and Benefits**

- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDTA)
- Built-In Biasing Resistors, R1 only
- "Lead Free", RoHS Compliant (Note 1)
- Halogen and Antimony Free "Green" Device (Note 2)
- Qualified to AEC-Q101 Standards for High Reliability


**Mechanical Data**

- Case: SOT23
- Case material: Molded Plastic. "Green" Molding Compound.
- Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish
- Weight: 0.008 grams (approximate)

SOT23



Top View




Device Schematic – Top View

**Ordering Information** (Note 3 & 4)

| Product          | Grade      | Marking | Reel size (inches) | Tape width (mm) | Quantity per reel |
|------------------|------------|---------|--------------------|-----------------|-------------------|
| DDTC113TCA-7-F   | Commercial | N01     | 7                  | 8               | 3,000             |
| DDTC123TCA-7-F   | Commercial | N03     | 7                  | 8               | 3,000             |
| DDTC143TCA-7-F   | Commercial | N07     | 7                  | 8               | 3,000             |
| DDTC143TCAQ-7-F  | Automotive | N07     | 7                  | 8               | 3,000             |
| DDTC143TCAQ-13-F | Automotive | N07     | 13                 | 8               | 10,000            |
| DDTC114TCA-7-F   | Commercial | N12     | 7                  | 8               | 3,000             |
| DDTC124TCA-7-F   | Commercial | N16     | 7                  | 8               | 3,000             |
| DDTC144TCA-7-F   | Commercial | N19     | 7                  | 8               | 3,000             |
| DDTC115TCA-7-F   | Commercial | N23     | 7                  | 8               | 3,000             |
| DDTC125TCA-7-F   | Commercial | N25     | 7                  | 8               | 3,000             |

- Notes:
1. No purposefully added lead.
  2. Diodes Inc's "Green" policy can be found on our website at <http://www.diodes.com>.
  3. For packaging details, go to our website at <http://www.diodes.com>.
  4. Products with Q-suffix are automotive grade. Automotive products are electrical and thermal the same as the commercial, except where specified.

**Marking Information**


NXX = Product Type Marking Code (See Table above)  
 YM = Date Code Marking  
 Y = Year (ex: X = 2010)  
 M = Month (ex: 9 = September)

**Date Code Key**

Date Code Key

| Year | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 | 2013 | 2014 | 2015 |
|------|------|------|------|------|------|------|------|------|------|------|
| Code | T    | U    | V    | W    | X    | Y    | Z    | A    | B    | C    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

**Maximum Ratings** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic            | Symbol               | Value | Unit |
|---------------------------|----------------------|-------|------|
| Collector-Base Voltage    | V <sub>CBO</sub>     | 50    | V    |
| Collector-Emitter Voltage | V <sub>CEO</sub>     | 50    | V    |
| Emitter-Base Voltage      | V <sub>EBO</sub>     | 5     | V    |
| Collector Current         | I <sub>C</sub> (Max) | 100   | mA   |

**Thermal Characteristics** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                       | Symbol                            | Value       | Unit |
|------------------------------------------------------|-----------------------------------|-------------|------|
| Power Dissipation (Notes 5 & 6)                      | P <sub>D</sub>                    | 200         | mW   |
| Thermal Resistance, Junction to Ambient Air (Note 5) | R <sub>θJA</sub>                  | 625         | °C/W |
| Operating and Storage Temperature Range              | T <sub>J</sub> , T <sub>STG</sub> | -55 to +150 | °C   |

**Electrical Characteristics** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                             | Symbol               | Min        | Typ      | Max        | Unit | Test Condition                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------------------|----------------------|------------|----------|------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Collector-Base Breakdown Voltage           | BV <sub>CBO</sub>    | 50         | —        | —          | V    | I <sub>C</sub> = 50μA                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Collector-Emitter Breakdown Voltage        | BV <sub>CEO</sub>    | 50         | —        | —          | V    | I <sub>C</sub> = 1mA                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Emitter-Base Breakdown Voltage             | BV <sub>EBO</sub>    | 5          | —        | —          | V    | I <sub>E</sub> = 50μA                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Collector Cutoff Current                   | I <sub>CBO</sub>     | —          | —        | 0.5        | μA   | V <sub>CB</sub> = 50V                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Emitter Cutoff Current                     | I <sub>EBO</sub>     | —          | —        | 0.5        | μA   | V <sub>EB</sub> = 4V                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Collector-Emitter Saturation Voltage       | V <sub>CE(sat)</sub> | —          | —        | 0.3        | V    | I <sub>C</sub> /I <sub>B</sub> = 10mA/1mA DDTC113TCA<br>I <sub>C</sub> /I <sub>B</sub> = 5mA/0.5mA DDTC123TCA<br>I <sub>C</sub> /I <sub>B</sub> = 2.5mA/.25mA DDTC143TCA<br>I <sub>C</sub> /I <sub>B</sub> = 1mA/.1mA DDTC114TCA<br>I <sub>C</sub> /I <sub>B</sub> = 5mA/0.5mA DDTC124TCA<br>I <sub>C</sub> /I <sub>B</sub> = 2.5mA/.25mA DDTC144TCA<br>I <sub>C</sub> /I <sub>B</sub> = 1mA/0.1mA DDTC115TCA<br>I <sub>C</sub> /I <sub>B</sub> = .5mA/.05mA DDTC125TCA |
| DC Current Transfer Ratio                  | h <sub>FE</sub>      | 100<br>120 | 250<br>- | 600<br>630 | —    | I <sub>C</sub> = 1mA, V <sub>CE</sub> = 5V<br>I <sub>C</sub> = 5mA, V <sub>CE</sub> = 5V DDTC143TCAQ                                                                                                                                                                                                                                                                                                                                                                    |
| Input Resistor (R <sub>1</sub> ) Tolerance | ΔR <sub>1</sub>      | -30        | —        | +30        | %    | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Gain-Bandwidth Product*                    | f <sub>T</sub>       | —          | 250      | —          | MHz  | V <sub>CE</sub> = 10V, I <sub>E</sub> = -5mA,<br>f = 100MHz                                                                                                                                                                                                                                                                                                                                                                                                             |

\* Transistor - For Reference Only

Notes: 5. Mounted on FR4 PC Board with minimum recommended pad layout  
6. 150mW per element must not be exceeded.

**Typical Characteristics – DDTC144TCA**




Fig. 1 Derating Curve




Fig. 2  $V_{CE(SAT)}$  vs.  $I_C$




Fig. 3 DC Current Gain




Fig. 4 Output Capacitance




Fig. 5 Collector Current Vs. Input Voltage






Fig. 6 Input Voltage vs. Collector Current

## Package Outline Dimensions



| SOT23                |       |      |       |
|----------------------|-------|------|-------|
| Dim                  | Min   | Max  | Typ   |
| A                    | 0.37  | 0.51 | 0.40  |
| B                    | 1.20  | 1.40 | 1.30  |
| C                    | 2.30  | 2.50 | 2.40  |
| D                    | 0.89  | 1.03 | 0.915 |
| F                    | 0.45  | 0.60 | 0.535 |
| G                    | 1.78  | 2.05 | 1.83  |
| H                    | 2.80  | 3.00 | 2.90  |
| J                    | 0.013 | 0.10 | 0.05  |
| K                    | 0.903 | 1.10 | 1.00  |
| K1                   | -     | -    | 0.400 |
| L                    | 0.45  | 0.61 | 0.55  |
| M                    | 0.085 | 0.18 | 0.11  |
| $\alpha$             | 0°    | 8°   | -     |
| All Dimensions in mm |       |      |       |

## Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| Z          | 2.9           |
| X          | 0.8           |
| Y          | 0.9           |
| C          | 2.0           |
| E          | 1.35          |

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2011, Diodes Incorporated

**www.diodes.com**

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9