

## Aluminum Capacitors Axial Miniature, Long-Life




Fig. 1

| QUICK REFERENCE DATA                               |                                   |                                   |
|----------------------------------------------------|-----------------------------------|-----------------------------------|
| DESCRIPTION                                        | VALUE                             |                                   |
| Nominal case sizes<br>( $\varnothing$ D x L in mm) | 6.3 x 12.7<br>to 10 x 25          | 10 x 30<br>to 21 x 38             |
| Rated capacitance range, $C_R$                     | 1.0 $\mu$ F to 15 000 $\mu$ F     |                                   |
| Tolerance on $C_R$                                 | $\pm 20$ %                        |                                   |
| Rated voltage range, $U_R$                         | 6.3 V to 100 V                    |                                   |
| Category temperature range                         | - 40 °C to + 105 °C               |                                   |
| Endurance test at 105 °C                           | 1000 h                            | 5000 h                            |
| Useful life at 105 °C                              | 2000 h                            | 10 000 h                          |
| Useful life at 40 °C,<br>$I_R$ applied             | 1.3 x $I_R$ applied:<br>200 000 h | 1.8 x $I_R$ applied:<br>500 000 h |
| Shelf life at 0 V, 105 °C                          | 500 h                             |                                   |
| Based on sectional<br>specification                | IEC 60384-4/EN130 300             |                                   |
| Climatic category IEC 60068                        | 40/105/56                         |                                   |

### FEATURES

- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Axial leads, cylindrical aluminum case, insulated with a blue sleeve (case  $\varnothing$  6.3 mm x 12.7 mm and 7.7 mm x 12.7 mm are molded with flame retardant plastic material)
- Mounting ring version not available in insulated form
- Taped versions up to case  $\varnothing$  15 mm x 30 mm available for automatic insertion
- Charge and discharge proof
- Long useful life: 2000 h to 10 000 h at 105 °C, high reliability
- High ripple current capability
- Miniaturized, high CV-product per unit volume
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### APPLICATIONS

- Industrial, automotive, EDP and telecommunication
- Smoothing, filtering, buffering in SMPS; coupling, decoupling, timing
- Portable and mobile equipment (small size, low mass)
- Stand-by applications
- Low mounting height boards, vibration and shock resistant


### MARKING

The capacitors are marked (where possible) with the following information:

- Rated capacitance (in  $\mu$ F)
- Tolerance on rated capacitance, code letter in accordance with IEC 60062 (M for  $\pm 20$  %)
- Rated voltage (in V)
- Upper category temperature (105 °C)
- Date code, in accordance with IEC 60062
- Code for factory of origin
- Name of manufacturer
- Negative terminal identification
- Series number (138)

| <b>SELECTION CHART FOR <math>C_R</math>, <math>U_R</math>, AND RELEVANT NOMINAL CASE SIZES (<math>\varnothing D \times L</math> in mm)</b> |            |            |            |            |            |            |            |            |
|--------------------------------------------------------------------------------------------------------------------------------------------|------------|------------|------------|------------|------------|------------|------------|------------|
| $C_R$<br>( $\mu F$ )                                                                                                                       | $U_R$ (V)  |            |            |            |            |            |            |            |
|                                                                                                                                            | 6.3        | 10         | 16         | 25         | 40         | 50         | 63         | 100        |
| 1.0                                                                                                                                        | -          | -          | -          | -          | -          | -          | -          | 6.3 x 12.7 |
| 2.2                                                                                                                                        | -          | -          | -          | -          | -          | -          | -          | 6.3 x 12.7 |
| 4.7                                                                                                                                        | -          | -          | -          | -          | -          | -          | 6.3 x 12.7 | 7.7 x 12.7 |
| 10                                                                                                                                         | -          | -          | -          | 6.3 x 12.7 | -          | 6.3 x 12.7 | 7.7 x 12.7 | 6.5 x 18   |
| 22                                                                                                                                         | -          | -          | 6.3 x 12.7 | 6.3 x 12.7 | -          | 7.7 x 12.7 | 6.5 x 18   | 8 x 18     |
| 33                                                                                                                                         | -          | -          | -          | 6.3 x 12.7 | 7.7 x 12.7 | -          | -          | -          |
| 47                                                                                                                                         | -          | -          | 6.3 x 12.7 | 7.7 x 12.7 | 6.5 x 18   | -          | 8 x 18     | 10 x 25    |
| 68                                                                                                                                         | -          | -          | -          | -          | -          | -          | -          | 10 x 30    |
| 100                                                                                                                                        | 6.3 x 12.7 | -          | 7.7 x 12.7 | 6.5 x 18   | 8 x 18     | 10 x 18    | 10 x 25    | 12.5 x 30  |
| 150                                                                                                                                        | -          | 7.7 x 12.7 | -          | -          | -          | -          | 10 x 30    | 15 x 30    |
| 220                                                                                                                                        | 7.7 x 12.7 | 6.5 x 18   | 8 x 18     | 10 x 18    | 10 x 25    | -          | 12.5 x 30  | 15 x 30    |
| 330                                                                                                                                        | -          | -          | -          | -          | 10 x 30    | -          | 12.5 x 30  | 18 x 30    |
| 470                                                                                                                                        | 6.5 x 18   | 8 x 18     | 10 x 18    | 10 x 25    | 12.5 x 30  | -          | 15 x 30    | 18 x 38    |
| 680                                                                                                                                        | -          | -          | -          | 10 x 30    | 12.5 x 30  | -          | 18 x 30    | 21 x 38    |
| 1000                                                                                                                                       | 10 x 18    | 10 x 25    | 10 x 30    | 12.5 x 30  | 15 x 30    | -          | 18 x 38    | -          |
| 1500                                                                                                                                       | -          | 10 x 30    | 12.5 x 30  | 15 x 30    | 18 x 30    | -          | 21 x 38    | -          |
| 2200                                                                                                                                       | 10 x 25    | 12.5 x 30  | 15 x 30    | 18 x 30    | 18 x 38    | -          | -          | -          |
| 3300                                                                                                                                       | -          | 15 x 30    | 18 x 30    | 18 x 38    | 21 x 38    | -          | -          | -          |
| 4700                                                                                                                                       | -          | 18 x 30    | 18 x 30    | 18 x 38    | -          | -          | -          | -          |
| 6800                                                                                                                                       | -          | 18 x 38    | 18 x 38    | 21 x 38    | -          | -          | -          | -          |
| 10 000                                                                                                                                     | -          | 18 x 38    | 21 x 38    | -          | -          | -          | -          | -          |
| 15 000                                                                                                                                     | -          | 21 x 38    | -          | -          | -          | -          | -          | -          |

## DIMENSIONS in millimeters AND AVAILABLE FORMS




**Form BR:** Taped on reel

**Form BA:** Taped in box (ammopack)

Case  $\varnothing D \times L = 6.3 \text{ mm} \times 12.7 \text{ mm}$  to  $7.7 \text{ mm} \times 12.7 \text{ mm}$

Fig. 2 - Forms BA and BR




**Form BR:** Taped on reel

Case  $\varnothing D \times L = 6.5 \text{ mm} \times 18 \text{ mm}$  to  $15 \text{ mm} \times 30 \text{ mm}$

**Form BA:** Taped in box (ammopack)

Case  $\varnothing D \times L = 6.5 \text{ mm} \times 18 \text{ mm}$  to  $10 \text{ mm} \times 25 \text{ mm}$

Fig. 3 - Forms BA and BR



**Form AA:** Axial in box

Case  $\varnothing D \times L = 10 \text{ mm} \times 30 \text{ mm}$  to  $21 \text{ mm} \times 38 \text{ mm}$


Fig. 4 - Form AA

**Table 1**

| <b>AXIAL; DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES</b> |              |                            |        |                     |                   |                   |             |                      |            |            |
|------------------------------------------------------------------------|--------------|----------------------------|--------|---------------------|-------------------|-------------------|-------------|----------------------|------------|------------|
| NOMINAL<br>CASE SIZE<br>Ø D x L<br>(mm)                                | CASE<br>CODE | AXIAL: FORM AA, BA, AND BR |        |                     |                   |                   | MASS<br>(g) | PACKAGING QUANTITIES |            |            |
|                                                                        |              | Ø d                        | l      | Ø D <sub>max.</sub> | L <sub>max.</sub> | F <sub>min.</sub> |             | FORM<br>AA           | FORM<br>BA | FORM<br>BR |
| 6.3 x 12.7                                                             | (2)          | 0.6                        | -      | 6.5                 | 12.9              | 17.5              | ≈ 1.1       | -                    | 1000       | 1000       |
| 7.7 x 12.7                                                             | (3)          | 0.6                        | -      | 7.9                 | 12.9              | 17.5              | ≈ 1.3       | -                    | 500        | 500        |
| 6.5 x 18                                                               | 4            | 0.8                        | -      | 6.9                 | 18.5              | 25                | ≈ 1.3       | -                    | 1000       | 1000       |
| 8 x 18                                                                 | 5            | 0.8                        | -      | 8.5                 | 18.5              | 25                | ≈ 1.7       | -                    | 500        | 500        |
| 10 x 18                                                                | 6            | 0.8                        | -      | 10.5                | 18.5              | 25                | ≈ 2.5       | -                    | 500        | 500        |
| 10 x 25                                                                | 7            | 0.8                        | -      | 10.5                | 25.5              | 30                | ≈ 3.3       | -                    | 500        | 500        |
| 10 x 30                                                                | 00           | 0.8                        | 55 ± 1 | 10.5                | 30.5              | 35                | ≈ 4.8       | 340                  | -          | 500        |
| 12.5 x 30                                                              | 01           | 0.8                        | 55 ± 1 | 13.0                | 30.5              | 35                | ≈ 7.4       | 260                  | -          | 400        |
| 15 x 30                                                                | 02           | 0.8                        | 55 ± 1 | 15.5                | 30.5              | 35                | ≈ 11.7      | 200                  | -          | 250        |
| 18 x 30                                                                | 03           | 0.8                        | 55 ± 1 | 18.5                | 30.5              | 35                | ≈ 12.9      | 120                  | -          | -          |
| 18 x 38                                                                | 04           | 0.8                        | 34 ± 1 | 18.5                | 39.5              | 44                | ≈ 19.0      | 125                  | -          | -          |
| 21 x 38                                                                | 05           | 0.8                        | 34 ± 1 | 21.5                | 39.5              | 44                | ≈ 24.0      | 100                  | -          | -          |

**Note**

- For detailed tape dimensions refer to packaging information: [www.vishay.com/doc?28361](http://www.vishay.com/doc?28361)



Mounting holes

Case Ø D x L = 15 mm x 30 mm to 21 mm x 38 mm

Especially for applications with severe shocks and vibrations




Fig. 5 - Mounting hole diagram and outline; **Form MR:** With mounting ring and pins

**Table 2**

| <b>MOUNTING RING; DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES</b> |              |                        |           |                   |                      |            |                   |             |                         |
|--------------------------------------------------------------------------------|--------------|------------------------|-----------|-------------------|----------------------|------------|-------------------|-------------|-------------------------|
| NOMINAL<br>CASE SIZE<br>Ø D x L                                                | CASE<br>CODE | MOUNTING RING: FORM MR |           |                   |                      |            |                   | MASS<br>(g) | PACKAGING<br>QUANTITIES |
|                                                                                |              | Ø d1                   | Ø d2      | D <sub>max.</sub> | Ø D2 <sub>max.</sub> | D3         | L <sub>max.</sub> |             |                         |
| 15 x 30                                                                        | 02           | 0.8                    | 1.0 + 0.4 | 15.5              | 17.5                 | 16.5 ± 0.2 | 33                | ≈ 11.7      | 200                     |
| 18 x 30                                                                        | 03           | 0.8                    | 1.0 + 0.4 | 18.5              | 19.5                 | 18.5 ± 0.2 | 33                | ≈ 12.9      | 240                     |
| 18 x 38                                                                        | 04           | 0.8                    | 1.0 + 0.4 | 18.5              | 19.5                 | 18.5 ± 0.2 | 42                | ≈ 19.0      | 100                     |
| 21 x 38                                                                        | 05           | 0.8                    | 1.0 + 0.4 | 21.5              | 22.5                 | 21.5 ± 0.2 | 42                | ≈ 24.0      | 100                     |

| ELECTRICAL DATA |                                                                                          |
|-----------------|------------------------------------------------------------------------------------------|
| SYMBOL          | DESCRIPTION                                                                              |
| $C_R$           | Rated capacitance at 100 Hz, tolerance $\pm 20\%$                                        |
| $I_R$           | Rated RMS ripple current at 100 Hz, 105 °C                                               |
| $I_{L5}$        | Max. leakage current after 5 min at $U_R$                                                |
| $\tan \delta$   | Max. dissipation factor at 100 Hz                                                        |
| ESR             | Equivalent series resistance at 100 Hz (calculated from $\tan \delta_{\max}$ and $C_R$ ) |
| Z               | Max. impedance at 10 kHz or 100 kHz                                                      |

**Note**

- Unless otherwise specified, all electrical values in Table 3 apply at  $T_{\text{amb}} = 20\text{ °C}$ ,  $P = 86\text{ kPa}$  to  $106\text{ kPa}$ ,  $RH = 45\%$  to  $75\%$ .

**Table 3**

| ELECTRICAL DATA AND ORDERING INFORMATION |                                  |                                         |                                            |                                  |                 |                      |                    |                     |                            |                             |                            |                             |
|------------------------------------------|----------------------------------|-----------------------------------------|--------------------------------------------|----------------------------------|-----------------|----------------------|--------------------|---------------------|----------------------------|-----------------------------|----------------------------|-----------------------------|
| U <sub>R</sub><br>(V)                    | C <sub>R</sub><br>100 Hz<br>(μF) | NOMINAL<br>CASE SIZE<br>Ø D x L<br>(mm) | I <sub>R</sub><br>100 Hz<br>105 °C<br>(mA) | I <sub>L5</sub><br>5 min<br>(μA) | tan δ<br>100 Hz | ESR<br>100 Hz<br>(Ω) | Z<br>10 kHz<br>(Ω) | Z<br>100 kHz<br>(Ω) | ORDERING CODE MAL2138..... |                             |                            |                             |
|                                          |                                  |                                         |                                            |                                  |                 |                      |                    |                     | IN BOX<br>FORM AA          | TAPED<br>ON REEL<br>FORM BR | TAPED<br>IN BOX<br>FORM BA | MOUNTING<br>RING<br>FORM MR |
| 6.3                                      | 100                              | 6.3 x 12.7                              | 99                                         | 5.3                              | 0.24            | 3.800                | 3.000              | 1.800               | -                          | 23101E3                     | 33101E3                    | -                           |
|                                          | 220                              | 7.7 x 12.7                              | 160                                        | 6.8                              | 0.24            | 1.700                | 1.400              | 0.950               | -                          | 23221E3                     | 33221E3                    | -                           |
|                                          | 470                              | 6.5 x 18                                | 250                                        | 9.9                              | 0.24            | 0.810                | 0.640              | 0.500               | -                          | 23471E3                     | 33471E3                    | -                           |
|                                          | 1000                             | 10 x 18                                 | 430                                        | 17                               | 0.24            | 0.380                | 0.300              | 0.240               | -                          | 23102E3                     | 33102E3                    | -                           |
|                                          | 2200                             | 10 x 25                                 | 640                                        | 32                               | 0.29            | 0.210                | 0.180              | 0.150               | -                          | 23222E3                     | 33222E3                    | -                           |
| 10                                       | 150                              | 7.7 x 12.7                              | 140                                        | 7.0                              | 0.2             | 2.100                | 1.300              | 0.950               | -                          | 24151E3                     | 34151E3                    | -                           |
|                                          | 220                              | 6.5 x 18                                | 190                                        | 8.4                              | 0.2             | 1.400                | 0.910              | 0.500               | -                          | 24221E3                     | 34221E3                    | -                           |
|                                          | 470                              | 8 x 18                                  | 300                                        | 13                               | 0.2             | 0.680                | 0.430              | 0.350               | -                          | 24471E3                     | 34471E3                    | -                           |
|                                          | 1000                             | 10 x 25                                 | 520                                        | 24                               | 0.2             | 0.320                | 0.200              | 0.160               | -                          | 24102E3                     | 34102E3                    | -                           |
|                                          | 1500                             | 10 x 30                                 | 670                                        | 34                               | 0.28            | 0.320                | 0.260              | 0.260               | 14152E3                    | 24152E3                     | -                          | -                           |
|                                          | 2200                             | 12.5 x 30                               | 890                                        | 48                               | 0.29            | 0.220                | 0.190              | 0.190               | 14222E3                    | 24222E3                     | -                          | -                           |
|                                          | 3300                             | 15 x 30                                 | 1140                                       | 70                               | 0.30            | 0.160                | 0.130              | 0.150               | 14332E3                    | 24332E3                     | -                          | 44332E3                     |
|                                          | 4700                             | 18 x 30                                 | 1450                                       | 98                               | 0.33            | 0.120                | 0.110              | 0.130               | 14472E3                    | -                           | -                          | 44472E3                     |
|                                          | 6800                             | 18 x 38                                 | 1880                                       | 140                              | 0.34            | 0.085                | 0.074              | 0.110               | 14682E3                    | -                           | -                          | 44682E3                     |
|                                          | 10 000                           | 18 x 38                                 | 1980                                       | 200                              | 0.41            | 0.070                | 0.062              | 0.100               | 14103E3                    | -                           | -                          | 44103E3                     |
|                                          | 15 000                           | 21 x 38                                 | 2200                                       | 300                              | 0.55            | 0.063                | 0.058              | 0.099               | 14153E3                    | -                           | -                          | 44153E3                     |
| 16                                       | 22                               | 6.3 x 12.7                              | 58                                         | 4.7                              | 0.12            | 8.700                | 7.300              | 2.700               | -                          | 25229E3                     | 35229E3                    | -                           |
|                                          | 47                               | 6.3 x 12.7                              | 83                                         | 5.5                              | 0.16            | 5.400                | 3.400              | 1.900               | -                          | 25479E3                     | 35479E3                    | -                           |
|                                          | 100                              | 7.7 x 12.7                              | 130                                        | 7.2                              | 0.16            | 2.500                | 1.600              | 1.000               | -                          | 25101E3                     | 35101E3                    | -                           |
|                                          | 220                              | 8 x 18                                  | 230                                        | 11                               | 0.16            | 1.200                | 0.730              | 0.350               | -                          | 25221E3                     | 35221E3                    | -                           |
|                                          | 470                              | 10 x 18                                 | 360                                        | 19                               | 0.16            | 0.540                | 0.340              | 0.250               | -                          | 25471E3                     | 35471E3                    | -                           |
|                                          | 1000                             | 10 x 30                                 | 630                                        | 36                               | 0.20            | 0.340                | 0.270              | 0.260               | 15102E3                    | 25102E3                     | -                          | -                           |
|                                          | 1500                             | 12.5 x 30                               | 860                                        | 52                               | 0.20            | 0.230                | 0.190              | 0.190               | 15152E3                    | 25152E3                     | -                          | -                           |
|                                          | 2200                             | 15 x 30                                 | 1090                                       | 74                               | 0.21            | 0.170                | 0.140              | 0.150               | 15222E3                    | 25222E3                     | -                          | 45222E3                     |
|                                          | 3300                             | 18 x 30                                 | 1420                                       | 110                              | 0.24            | 0.120                | 0.100              | 0.130               | 15332E3                    | -                           | -                          | 45332E3                     |
|                                          | 4700                             | 18 x 30                                 | 1480                                       | 150                              | 0.28            | 0.100                | 0.090              | 0.120               | 15472E3                    | -                           | -                          | 45472E3                     |
|                                          | 6800                             | 18 x 38                                 | 1930                                       | 220                              | 0.28            | 0.072                | 0.062              | 0.100               | 15682E3                    | -                           | -                          | 45682E3                     |
|                                          | 10 000                           | 21 x 38                                 | 2100                                       | 320                              | 0.38            | 0.065                | 0.057              | 0.098               | 15103E3                    | -                           | -                          | 45103E3                     |
| 25                                       | 10                               | 6.3 x 12.7                              | 46                                         | 4.5                              | 0.09            | 14.000               | 12.000             | 2.800               | -                          | 26109E3                     | 36109E3                    | -                           |
|                                          | 22                               | 6.3 x 12.7                              | 61                                         | 5.1                              | 0.14            | 10.000               | 5.500              | 2.500               | -                          | 26229E3                     | 36229E3                    | -                           |
|                                          | 33                               | 6.3 x 12.7                              | 74                                         | 5.7                              | 0.14            | 6.800                | 3.600              | 1.900               | -                          | 26339E3                     | 36339E3                    | -                           |
|                                          | 47                               | 7.7 x 12.7                              | 96                                         | 6.4                              | 0.14            | 4.700                | 2.600              | 1.000               | -                          | 26479E3                     | 36479E3                    | -                           |

**ORDERING EXAMPLE**

Electrolytic capacitor 138 series

470  $\mu\text{F}$ /10 V;  $\pm 20\%$ 

Nominal case size:  $\varnothing 8\text{ mm} \times 18\text{ mm}$ ; Form BA

Ordering code: MAL213834471E3

Former 12 NC: 2222 138 34471



| ELECTRICAL DATA AND ORDERING INFORMATION |                                  |                                         |                                            |                                  |                 |                      |                    |                     |                            |                             |                            |                             |
|------------------------------------------|----------------------------------|-----------------------------------------|--------------------------------------------|----------------------------------|-----------------|----------------------|--------------------|---------------------|----------------------------|-----------------------------|----------------------------|-----------------------------|
| U <sub>R</sub><br>(V)                    | C <sub>R</sub><br>100 Hz<br>(μF) | NOMINAL<br>CASE SIZE<br>Ø D x L<br>(mm) | I <sub>R</sub><br>100 Hz<br>105 °C<br>(mA) | I <sub>L5</sub><br>5 min<br>(μA) | tan δ<br>100 Hz | ESR<br>100 Hz<br>(Ω) | Z<br>10 kHz<br>(Ω) | Z<br>100 kHz<br>(Ω) | ORDERING CODE MAL2138..... |                             |                            |                             |
|                                          |                                  |                                         |                                            |                                  |                 |                      |                    |                     | IN BOX<br>FORM AA          | TAPED<br>ON REEL<br>FORM BR | TAPED<br>IN BOX<br>FORM BA | MOUNTING<br>RING<br>FORM MR |
| 25                                       | 100                              | 6.5 x 18                                | 160                                        | 9.0                              | 0.13            | 2.100                | 1.200              | 0.550               | -                          | 26101E3                     | 36101E3                    | -                           |
|                                          | 220                              | 10 x 18                                 | 270                                        | 15                               | 0.13            | 0.940                | 0.550              | 0.270               | -                          | 26221E3                     | 36221E3                    | -                           |
|                                          | 470                              | 10 x 25                                 | 440                                        | 28                               | 0.13            | 0.440                | 0.260              | 0.170               | -                          | 26471E3                     | 36471E3                    | -                           |
|                                          | 680                              | 10 x 30                                 | 580                                        | 38                               | 0.14            | 0.360                | 0.260              | 0.250               | 16681E3                    | 26681E3                     | -                          | -                           |
|                                          | 1000                             | 12.5 x 30                               | 790                                        | 54                               | 0.15            | 0.250                | 0.180              | 0.190               | 16102E3                    | 26102E3                     | -                          | -                           |
|                                          | 1500                             | 15 x 30                                 | 1020                                       | 79                               | 0.15            | 0.170                | 0.130              | 0.150               | 16152E3                    | 26152E3                     | -                          | 46152E3                     |
|                                          | 2200                             | 18 x 30                                 | 1320                                       | 110                              | 0.17            | 0.130                | 0.100              | 0.130               | 16222E3                    | -                           | -                          | 46222E3                     |
|                                          | 3300                             | 18 x 38                                 | 1720                                       | 170                              | 0.17            | 0.090                | 0.071              | 0.110               | 16332E3                    | -                           | -                          | 46332E3                     |
|                                          | 4700                             | 18 x 38                                 | 1840                                       | 240                              | 0.21            | 0.076                | 0.063              | 0.100               | 16472E3                    | -                           | -                          | 46472E3                     |
|                                          | 6800                             | 21 x 38                                 | 2100                                       | 340                              | 0.27            | 0.068                | 0.058              | 0.099               | 16682E3                    | -                           | -                          | 46682E3                     |
| 40                                       | 33                               | 7.7 x 12.7                              | 91                                         | 6.6                              | 0.11            | 5.300                | 2.700              | 1.000               | -                          | 27339E3                     | 37339E3                    | -                           |
|                                          | 47                               | 6.5 x 18                                | 120                                        | 7.8                              | 0.10            | 3.400                | 1.900              | 0.650               | -                          | 27479E3                     | 37479E3                    | -                           |
|                                          | 100                              | 8 x 18                                  | 180                                        | 12                               | 0.10            | 1.600                | 0.900              | 0.400               | -                          | 27101E3                     | 37101E3                    | -                           |
|                                          | 220                              | 10 x 25                                 | 350                                        | 22                               | 0.10            | 0.720                | 0.410              | 0.200               | -                          | 27221E3                     | 37221E3                    | -                           |
|                                          | 330                              | 10 x 30                                 | 490                                        | 30                               | 0.09            | 0.470                | 0.320              | 0.300               | 17331E3                    | 27331E3                     | -                          | -                           |
|                                          | 470                              | 12.5 x 30                               | 650                                        | 42                               | 0.09            | 0.340                | 0.230              | 0.220               | 17471E3                    | 27471E3                     | -                          | -                           |
|                                          | 680                              | 12.5 x 30                               | 750                                        | 58                               | 0.10            | 0.250                | 0.180              | 0.180               | 17681E3                    | 27681E3                     | -                          | -                           |
|                                          | 1000                             | 15 x 30                                 | 970                                        | 84                               | 0.10            | 0.170                | 0.120              | 0.140               | 17102E3                    | 27102E3                     | -                          | 47102E3                     |
|                                          | 1500                             | 18 x 30                                 | 1250                                       | 120                              | 0.12            | 0.130                | 0.098              | 0.120               | 17152E3                    | -                           | -                          | 47152E3                     |
|                                          | 2200                             | 18 x 38                                 | 1640                                       | 180                              | 0.12            | 0.093                | 0.069              | 0.100               | 17222E3                    | -                           | -                          | 47222E3                     |
|                                          | 3300                             | 21 x 38                                 | 1810                                       | 270                              | 0.15            | 0.079                | 0.061              | 0.100               | 17332E3                    | -                           | -                          | 47332E3                     |
|                                          |                                  |                                         |                                            |                                  |                 |                      |                    |                     |                            |                             |                            |                             |
| 50                                       | 10                               | 6.3 x 12.7                              | 51                                         | 5.0                              | 0.09            | 14.00                | 7.000              | 2.700               | -                          | 21109E3                     | 31109E3                    | -                           |
|                                          | 22                               | 7.7 x 12.7                              | 82                                         | 6.2                              | 0.09            | 6.500                | 3.002              | 1.100               | -                          | 21229E3                     | 31229E3                    | -                           |
|                                          | 100                              | 10 x 18                                 | 230                                        | 14                               | 0.08            | 1.300                | 0.700              | 0.300               | -                          | 21101E3                     | 31101E3                    | -                           |
| 63                                       | 4.7                              | 6.3 x 12.7                              | 35                                         | 4.6                              | 0.09            | 30.00                | 17.000             | 5.000               | -                          | 28478E3                     | 38478E3                    | -                           |
|                                          | 10                               | 7.7 x 12.7                              | 59                                         | 5.3                              | 0.08            | 13.00                | 8.000              | 1.800               | -                          | 28109E3                     | 38109E3                    | -                           |
|                                          | 22                               | 6.5 x 18                                | 100                                        | 6.8                              | 0.07            | 5.100                | 3.600              | 0.850               | -                          | 28229E3                     | 38229E3                    | -                           |
|                                          | 47                               | 8 x 18                                  | 150                                        | 9.9                              | 0.07            | 2.400                | 1.700              | 0.500               | -                          | 28479E3                     | 38479E3                    | -                           |
|                                          | 100                              | 10 x 25                                 | 280                                        | 17                               | 0.07            | 1.100                | 0.800              | 0.270               | -                          | 28101E3                     | 38101E3                    | -                           |
|                                          | 150                              | 10 x 30                                 | 410                                        | 23                               | 0.11            | 0.730                | 0.440              | 0.400               | 18151E3                    | 28151E3                     | -                          | -                           |
|                                          | 220                              | 12.5 x 30                               | 560                                        | 32                               | 0.11            | 0.500                | 0.310              | 0.290               | 18221E3                    | 28221E3                     | -                          | -                           |
|                                          | 330                              | 12.5 x 30                               | 660                                        | 46                               | 0.12            | 0.370                | 0.230              | 0.220               | 18331E3                    | 28331E3                     | -                          | -                           |
|                                          | 470                              | 15 x 30                                 | 860                                        | 63                               | 0.12            | 0.260                | 0.160              | 0.160               | 18471E3                    | 28471E3                     | -                          | 48471E3                     |
|                                          | 680                              | 18 x 30                                 | 1130                                       | 90                               | 0.12            | 0.190                | 0.120              | 0.140               | 18681E3                    | -                           | -                          | 48681E3                     |
|                                          | 1000                             | 18 x 38                                 | 1460                                       | 130                              | 0.12            | 0.130                | 0.086              | 0.110               | 18102E3                    | -                           | -                          | 48102E3                     |
|                                          | 1500                             | 21 x 38                                 | 1680                                       | 190                              | 0.13            | 0.100                | 0.072              | 0.110               | 18152E3                    | -                           | -                          | 48152E3                     |
| 100                                      | 1.0                              | 6.3 x 12.7                              | 16                                         | 4.2                              | 0.09            | 140.0                | 55.000             | 10.00               | -                          | 29108E3                     | 39108E3                    | -                           |
|                                          | 2.2                              | 6.3 x 12.7                              | 24                                         | 4.4                              | 0.09            | 65.00                | 25.000             | 8.000               | -                          | 29228E3                     | 39228E3                    | -                           |
|                                          | 4.7                              | 7.7 x 12.7                              | 40                                         | 4.9                              | 0.08            | 27.00                | 17.000             | 5.000               | -                          | 29478E3                     | 39478E3                    | -                           |
|                                          | 10                               | 6.5 x 18                                | 67                                         | 6.0                              | 0.07            | 11.00                | 8.000              | 2.400               | -                          | 29109E3                     | 39109E3                    | -                           |
|                                          | 22                               | 8 x 18                                  | 100                                        | 8.4                              | 0.07            | 5.100                | 3.600              | 1.400               | -                          | 29229E3                     | 39229E3                    | -                           |
|                                          | 47                               | 10 x 25                                 | 190                                        | 13                               | 0.07            | 2.400                | 1.700              | 0.670               | -                          | 29479E3                     | 39479E3                    | -                           |
|                                          | 68                               | 10 x 30                                 | 300                                        | 18                               | 0.07            | 1.700                | 1.100              | 0.970               | 19689E3                    | 29689E3                     | -                          | -                           |
|                                          | 100                              | 12.5 x 30                               | 410                                        | 24                               | 0.07            | 1.100                | 0.770              | 0.670               | 19101E3                    | 29101E3                     | -                          | -                           |
|                                          | 150                              | 15 x 30                                 | 550                                        | 34                               | 0.07            | 0.780                | 0.520              | 0.460               | 19151E3                    | 29151E3                     | -                          | 49151E3                     |
|                                          | 220                              | 15 x 30                                 | 650                                        | 48                               | 0.07            | 0.540                | 0.370              | 0.330               | 19221E3                    | 29221E3                     | -                          | 49221E3                     |
|                                          | 330                              | 18 x 30                                 | 880                                        | 70                               | 0.08            | 0.380                | 0.270              | 0.240               | 19331E3                    | -                           | -                          | 49331E3                     |
|                                          | 470                              | 18 x 38                                 | 1130                                       | 98                               | 0.08            | 0.270                | 0.190              | 0.170               | 19471E3                    | -                           | -                          | 49471E3                     |
|                                          | 680                              | 21 x 38                                 | 1330                                       | 140                              | 0.09            | 0.210                | 0.140              | 0.140               | 19681E3                    | -                           | -                          | 49681E3                     |
|                                          |                                  |                                         |                                            |                                  |                 |                      |                    |                     |                            |                             |                            |                             |
|                                          |                                  |                                         |                                            |                                  |                 |                      |                    |                     |                            |                             |                            |                             |

| ADDITIONAL ELECTRICAL DATA         |                                                                                               |                                                    |               |
|------------------------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------|---------------|
| PARAMETER                          | CONDITIONS                                                                                    | VALUE                                              |               |
|                                    |                                                                                               | AXIAL                                              | MOUNTING RING |
| Voltage                            |                                                                                               |                                                    |               |
| Surge voltage                      |                                                                                               | $U_s \leq 1.15 \times U_R$                         |               |
| Reverse voltage                    |                                                                                               | $U_{rev} \leq 1 \text{ V}$                         |               |
| Current                            |                                                                                               |                                                    |               |
| Leakage current                    | After 1 min at $U_R$ :                                                                        |                                                    |               |
|                                    | Case $\varnothing D \times L = 6.3 \text{ mm} \times 12.7 \text{ mm}$ and<br>7.7 mm x 12.7 mm | $I_{L1} \leq 0.02 C_R \times U_R + 3 \mu\text{A}$  |               |
|                                    | Case $\varnothing D \times L = 6.5 \text{ mm} \times 18 \text{ mm}$ to<br>21 mm x 38 mm       | $I_{L1} \leq 0.006 C_R \times U_R + 4 \mu\text{A}$ |               |
|                                    | After 5 min at $U_R$                                                                          | $I_{L5} \leq 0.002 C_R \times U_R + 4 \mu\text{A}$ |               |
| Inductance                         |                                                                                               |                                                    |               |
| Equivalent series inductance (ESL) | Case $\varnothing D \times L$ mm:                                                             |                                                    |               |
|                                    | 6.3 x 12.7                                                                                    | Typ. 20 nH                                         | -             |
|                                    | 7.7 x 12.7                                                                                    | Typ. 30 nH                                         | -             |
|                                    | 6.5 x 18                                                                                      | Typ. 15 nH                                         | -             |
|                                    | 8 x 18                                                                                        | Typ. 35 nH                                         | -             |
|                                    | 10 x 18                                                                                       | Typ. 69 nH                                         | -             |
|                                    | 10 x 25                                                                                       | Typ. 38 nH                                         | -             |
|                                    | 10 x 30                                                                                       | Typ. 38 nH                                         | -             |
|                                    | 12.5 x 30                                                                                     | Typ. 46 nH                                         | -             |
|                                    | 15 x 30                                                                                       | Typ. 48 nH                                         | Typ. 39 nH    |
|                                    | 18 x 30                                                                                       | Typ. 50 nH                                         | Typ. 39 nH    |
|                                    | 18 x 38                                                                                       | Typ. 54 nH                                         | Typ. 39 nH    |
|                                    | 21 x 38                                                                                       | Typ. 59 nH                                         | Typ. 39 nH    |

## CAPACITANCE (C)




Fig. 6 - Typical multiplier of capacitance as a function of ambient temperature




Fig. 7 - Typical multiplier of capacitance as a function of ambient temperature


**EQUIVALENT SERIES RESISTANCE (ESR)**


Fig. 8 - Typical multiplier of capacitance as a function of frequency




Fig. 9 - Typical multiplier of ESR as a function of ambient temperature




Fig. 10 - Typical multiplier of ESR as a function of ambient temperature




Fig. 11 - Typical multiplier ESR as a function of frequency

## EQUIVALENT SERIES RESISTANCE (ESR)




Fig. 12 - Typical multiplier ESR as a function of frequency

## IMPEDANCE (Z)

Table 4

| IMPEDANCE VS. CAPACITANCE VALUES (Case $\varnothing D \times L = 6.3$ mm x 12.7 mm to 10 mm x 25 mm) |                                                |        |        |        |        |       |        |        |
|------------------------------------------------------------------------------------------------------|------------------------------------------------|--------|--------|--------|--------|-------|--------|--------|
| $T_{amb}$                                                                                            | $Z \times C_R (\Omega \times \mu F)$ AT 10 kHz |        |        |        |        |       |        |        |
|                                                                                                      | 6.3 V                                          | 10 V   | 16 V   | 25 V   | 40 V   | 50 V  | 63 V   | 100 V  |
| + 20 °C                                                                                              | ≤ 300                                          | ≤ 200  | ≤ 160  | ≤ 120  | ≤ 90   | ≤ 70  | ≤ 80   | ≤ 80   |
| - 25 °C                                                                                              | ≤ 2000                                         | ≤ 1200 | ≤ 750  | ≤ 560  | ≤ 450  | ≤ 300 | ≤ 550  | ≤ 550  |
| - 40 °C                                                                                              | ≤ 5500                                         | ≤ 3200 | ≤ 2000 | ≤ 1500 | ≤ 1200 | ≤ 900 | ≤ 1500 | ≤ 1500 |




Fig. 13 - Typical multiplier of ESR as a function of ambient temperature at 10 kHz




Fig. 14 - Typical impedance as a function of frequency




Fig. 15 - Typical impedance as a function of frequency




Fig. 16 - Typical impedance as a function of frequency




Fig. 17 - Typical impedance as a function of frequency




Fig. 18 - Typical impedance as a function of frequency

**RIPPLE CURRENT AND USEFUL LIFE**

CCC206

$I_A$  = Actual ripple current at 100 Hz  
 $I_R$  = Rated ripple current at 100 Hz, 105 °C

<sup>(1)</sup> Useful life at 105 °C and  $I_R$  applied:  
 Case Ø D x L = 6.3 mm x 12.7 mm to 10 mm x 25 mm: 2000 h  
 Case Ø D x L = 10 mm x 30 mm to 21 mm x 38 mm: 10 000 h




Fig. 19 - Multiplier of useful life as a function of ambient temperature and ripple current load

**Table 5**

| <b>MULTIPLIER OF RIPPLE CURRENT (<math>I_R</math>) AS A FUNCTION OF FREQUENCY</b> |                                                          |                                                         |                                                          |
|-----------------------------------------------------------------------------------|----------------------------------------------------------|---------------------------------------------------------|----------------------------------------------------------|
| <b>FREQUENCY<br/>(Hz)</b>                                                         | <b><math>I_R</math> MULTIPLIER</b>                       |                                                         |                                                          |
|                                                                                   | <b><math>U_R = 6.3 \text{ V TO } 10 \text{ V}</math></b> | <b><math>U_R = 16 \text{ V TO } 25 \text{ V}</math></b> | <b><math>U_R = 40 \text{ V TO } 100 \text{ V}</math></b> |
| 50                                                                                | 0.95                                                     | 0.90                                                    | 0.85                                                     |
| 100                                                                               | 1.00                                                     | 1.00                                                    | 1.00                                                     |
| 300                                                                               | 1.07                                                     | 1.12                                                    | 1.20                                                     |
| 1000                                                                              | 1.12                                                     | 1.20                                                    | 1.30                                                     |
| 3000                                                                              | 1.15                                                     | 1.25                                                    | 1.35                                                     |
| ≥ 10 000                                                                          | 1.20                                                     | 1.30                                                    | 1.40                                                     |

Table 6

| TEST PROCEDURES AND REQUIREMENTS               |                                             |                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                           |
|------------------------------------------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TEST                                           |                                             | PROCEDURE<br>(quick reference)                                                                                                                                                                | REQUIREMENTS                                                                                                                                                                                                                                                                                                              |
| NAME OF TEST                                   | REFERENCE                                   |                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                           |
| Endurance                                      | IEC 60384-4/<br>EN130300<br>subclause 4.13  | $T_{amb} = 105\text{ }^{\circ}\text{C}$ ; $U_R$ applied;<br>Case $\emptyset D \times L$ :<br>6.3 mm x 12.7 mm to 10 mm x 25 mm: 1000 h;<br>10 mm x 30 mm to 21 mm x 38 mm: 5000 h             | $U_R \leq 6.3\text{ V}$ ; $\Delta C/C$ : + 15 %/- 30 %<br>$U_R > 6.3\text{ V}$ ; $\Delta C/C$ : $\pm 15\text{ \%}$<br>$\tan \delta \leq 1.3 \times \text{spec. limit}$<br>$Z \leq 2 \times \text{spec. limit}$<br>$I_{L5} \leq \text{spec. limit}$                                                                        |
| Useful life                                    | CECC 30301<br>subclause 1.8.1               | $T_{amb} = 105\text{ }^{\circ}\text{C}$ ; $U_R$ and $I_R$ applied;<br>Case $\emptyset D \times L$ :<br>6.3 mm x 12.7 mm to 10 mm x 25 mm: 2000 h;<br>10 mm x 30 mm to 21 mm x 38 mm: 10 000 h | $U_R \leq 6.3\text{ V}$ ; $\Delta C/C$ : + 45 %/- 50 %<br>$U_R > 6.3\text{ V}$ ; $\Delta C/C$ : $\pm 45\text{ \%}$<br>$\tan \delta \leq 3 \times \text{spec. limit}$<br>$Z \leq 3 \times \text{spec. limit}$<br>$I_{L5} \leq \text{spec. limit}$<br>no short open circuit<br>total failure percentage: $\leq 1\text{ \%}$ |
| Shelf life<br>(storage at<br>high temperature) | IEC 60384-4/<br>EN130300,<br>subclause 4.17 | $T_{amb} = 105\text{ }^{\circ}\text{C}$ ; no voltage applied;<br>500 h<br>After test: $U_R$ to be applied for 30 min,<br>24 h to 48 h before measurement                                      | $\Delta C/C$ , $\tan \delta$ , $Z$ :<br>For requirements<br>see "Endurance test" above<br>$I_{L5} \leq 2 \times \text{spec. limit}$                                                                                                                                                                                       |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9