

NTC Thermistors, Long Insulated Leads



QUICK REFERENCE DATA	
PARAMETER	VALUE
Resistance value at:	
0 °C	9000 Ω
25 °C	2769 Ω
Tolerance on R ₂₅ - value:	
0 °C	$\pm 2 \%$
25 °C	$\pm 3.82 \%$
B _{25/85} - value	3977 K
Maximum dissipation	100 mW
Dissipation factor δ	1.35 mW/K
Minimum dielectric withstanding voltage (RMS) between leads and coating	500 V
Response time	1.25 s
Operating temperature range:	
at zero power	- 40 to + 125 °C
at maximum power	0 to + 55 °C
Climatic category	40/125/56
Mass	≈ 0.16 g

FEATURES

- Long and flexible leads for special mounting or assembly requirements
- Insulated leads for prevention of short circuits
- Electrical features of 'accuracy line' sensors
- Small diameter
- Old part number was 2322 640 90059
- Components in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

APPLICATIONS

- Temperature sensing and control

These thermistors have a negative temperature coefficient. The device consists of a chip with two insulated nickel leads.

PACKAGING

The thermistors are packed in cardboard boxes; the smallest packing quantity is 1000 units.


MARKING

The body is coated with ochre-colored epoxy lacquer and is not marked.

MOUNTING

By soldering in any position

DIMENSIONS in millimeters





RESISTANCE VALUES AT INTERMEDIATE TEMPERATURES			
T_{OPER} (°C)	RESISTANCE (Ω)	TCR (%/K)	RESISTANCE TOLERANCE (%)
- 40	90 923	6.57	± 5.60
- 35	65 808	6.35	± 5.09
- 30	48 141	6.15	± 4.60
- 25	35 578	5.95	± 4.13
- 20	26 550	5.76	± 3.67
- 15	19 998	5.58	± 3.23
- 10	15 197	5.40	± 2.81
- 5	11 648	5.24	± 2.40
0	9000	5.08	± 2.00
5	7008.6	4.92	± 2.38
10	5498.8	4.78	± 2.76
15	4345.1	4.64	± 3.12
20	3457.2	4.50	± 3.47
25	2769.0	4.37	± 3.82
30	2231.7	4.25	± 4.16
35	1809.6	4.13	± 4.48
40	1476.0	4.02	± 4.80
45	1210.6	3.91	± 5.12
50	998.37	3.80	± 5.42
55	827.59	3.70	± 5.72
60	689.46	3.60	± 6.01
65	577.15	3.51	± 6.29
70	485.38	3.42	± 6.57
75	410.02	3.33	± 6.84
80	347.86	3.25	± 7.10
85	296.35	3.16	± 7.36
90	253.47	3.09	± 7.61
95	217.64	3.01	± 7.86
100	187.57	2.94	± 8.10
105	162.24	2.87	± 8.33
110	140.81	2.80	± 8.56
115	122.63	2.73	± 8.79
120	107.14	2.67	± 9.01
125	93.90	2.61	± 9.22



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9