

# Si53102-A1/A2/A3 Data Sheet

## PCI-Express Gen 1, Gen 2, Gen 3, and Gen 4 1:2 Fan-out Clock Buffer


Si53102-A1/A2/A3 is a family of high-performance 1:2 PCIe fan output buffers. This low-additive-jitter clock buffer family is compliant to PCIe Gen 1, Gen 2, Gen 3, and Gen 4 specifications. The ultra-small footprint (1.4x1.6 mm) and industry-leading low power consumption make the Si53102-A1/A2/A3 the ideal clock solution for consumer and embedded applications. Measuring PCIe clock jitter is quick and easy with the Silicon Labs PCIe Clock Jitter Tool. Download it for free at [www.silabs.com/pcie-learningcenter](http://www.silabs.com/pcie-learningcenter).

### Applications

- Network Attached Storage
- Multi-function Printer
- Wireless Access Point
- Server/Storage

### KEY FEATURES

- PCI-Express Gen 1, Gen 2, Gen 3, and Gen 4 common clock compliant
- Two low-power PCIe clock outputs
- Supports Serial-ATA (SATA) at 100 MHz
- No termination resistors required for differential clocks
- 2.5 V or 3.3 V Power supply
- Spread Spectrum Tolerant
- Extended Temperature Range
  - -40 to 85 °C
- Small package 8-pin TDFN (1.4 x 1.6 mm)
- For PCIe Gen 1: Si53102-A1
- For PCIe Gen 2: Si53102-A2
- For PCIe Gen 3/4: Si53102-A3



## 1. Ordering Guide

**Table 1.1. Ordering Guide**

| Part Number    | Package Type             | Temperature            |
|----------------|--------------------------|------------------------|
| Si53102-A1-GM  | 8-pin TDFN               | Extended, –40 to 85 °C |
| Si53102-A1-GMR | 8-pin TDFN—Tape and Reel | Extended, –40 to 85 °C |
| Si53102-A2-GM  | 8-pin TDFN               | Extended, –40 to 85 °C |
| Si53102-A2-GMR | 8-pin TDFN—Tape and Reel | Extended, –40 to 85 °C |
| Si53102-A3-GM  | 8-pin TDFN               | Extended, –40 to 85 °C |
| Si53102-A3-GMR | 8-pin TDFN—Tape and Reel | Extended, –40 to 85 °C |

# Table of Contents

- 1. Ordering Guide . . . . . 2
- 2. Electrical Specifications . . . . . 4
- 3. Test and Measurement Setup . . . . . 7
- 4. Recommended Design Guideline . . . . . 9
- 5. Pin Descriptions . . . . . 10
- 6. Package Outline . . . . . 11
- 7. Land Pattern . . . . . 13
- 8. Revision History . . . . . 14
  - 8.1 Revision 1.0 . . . . . 14
  - 8.2 Revision 1.1 . . . . . 14
  - 8.3 Revision 1.2 . . . . . 14
  - 8.4 Revision 1.3 . . . . . 14
  - 8.5 Revision 1.4 . . . . . 14

## 2. Electrical Specifications

**Table 2.1. Recommended Operating Conditions**

| Parameter                     | Symbol          | Test Condition | Min  | Typ | Max  | Unit |
|-------------------------------|-----------------|----------------|------|-----|------|------|
| Supply Voltage (3.3 V Supply) | V <sub>DD</sub> | 3.3 V ± 10%    | 2.97 | 3.3 | 3.63 | V    |
| Supply Voltage (2.5 V Supply) | V <sub>DD</sub> | 2.5 V ± 10%    | 2.25 | 2.5 | 2.75 | V    |

**Table 2.2. DC Electrical Specifications**

| Parameter                                   | Symbol           | Test Condition         | Min  | Typ  | Max  | Unit |
|---------------------------------------------|------------------|------------------------|------|------|------|------|
| Operating Voltage (V <sub>DD</sub> = 3.3 V) | V <sub>DD</sub>  | 3.3 V ± 10%            | 2.97 | 3.30 | 3.63 | V    |
| Operating Voltage (V <sub>DD</sub> = 2.5 V) | V <sub>DD</sub>  | 2.5 V ± 10%            | 2.25 | 2.5  | 2.75 | V    |
| Operating Supply Current                    | I <sub>DD</sub>  | Full Active            | —    | —    | 15   | mA   |
| Input Pin Capacitance                       | C <sub>IN</sub>  | Input Pin Capacitance  | —    | 3    | 5    | pF   |
| Output Pin Capacitance                      | C <sub>OUT</sub> | Output Pin Capacitance | —    | —    | 5    | pF   |

**Table 2.3. AC Electrical Specifications<sup>1, 2, 3</sup>**

| Parameter                                   | Symbol                          | Condition                                                                                    | Min  | Typ | Max  | Unit |
|---------------------------------------------|---------------------------------|----------------------------------------------------------------------------------------------|------|-----|------|------|
| <b>DIFFIN at 0.7 V</b>                      |                                 |                                                                                              |      |     |      |      |
| Input frequency                             | F <sub>in</sub>                 |                                                                                              | 10   | 100 | 175  | MHz  |
| DIFFIN and DIFFINb Rising/Falling Slew Rate | T <sub>R</sub> / T <sub>F</sub> | Single ended measurement:<br>V <sub>OL</sub> = 0.175 to V <sub>OH</sub> = 0.525 V (Averaged) | 0.6  | —   | 4    | V/ns |
| Differential Input High Voltage             | V <sub>IH</sub>                 |                                                                                              | 150  | —   | —    | mV   |
| Differential Input Low Voltage              | V <sub>IL</sub>                 |                                                                                              | —    | —   | –150 | mV   |
| Crossing Point Voltage at 0.7 V Swing       | V <sub>OX</sub>                 | Single-ended measurement                                                                     | 250  | —   | 550  | mV   |
| V <sub>cross</sub> Variation Over All edges | ΔV <sub>OX</sub>                | Single-ended measurement                                                                     | —    | —   | 140  | mV   |
| Differential Ringback Voltage               | V <sub>RB</sub>                 |                                                                                              | –100 | —   | 100  | mV   |
| Time before Ringback Allowed                | T <sub>STABLE</sub>             |                                                                                              | 500  | —   | —    | ps   |
| Absolute Maximum Input Voltage              | V <sub>MAX</sub>                |                                                                                              |      | —   | 1.15 | V    |
| Absolute Minimum Input Voltage              | V <sub>MIN</sub>                |                                                                                              | –0.3 | —   | —    | V    |

| Parameter                                                                                                                                           | Symbol                | Condition                                                          | Min | Typ | Max  | Unit |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|--------------------------------------------------------------------|-----|-----|------|------|
| DIFFIN and DIFFINb Duty Cycle                                                                                                                       | T <sub>DC</sub>       | Measured at crossing point VOX                                     | 45  | —   | 55   | %    |
| Rise/Fall Matching                                                                                                                                  | T <sub>RFM</sub>      | Determined as a fraction of<br>2 x (TR – TF)/(TR + TF)             | —   | —   | 20   | %    |
| DIFF Clocks                                                                                                                                         |                       |                                                                    |     |     |      |      |
| Duty Cycle                                                                                                                                          | T <sub>DC</sub>       | Measured at crossing point VOX                                     | 45  | —   | 55   | %    |
| Output Skew                                                                                                                                         | T <sub>SKEW</sub>     | Measured at 0 V differential                                       | —   | —   | 100  | ps   |
| Frequency Accuracy                                                                                                                                  | F <sub>ACC</sub>      | All output clocks                                                  | —   | —   | 100  | ppm  |
| Slew Rate                                                                                                                                           | t <sub>r/f2</sub>     | Measured differentially from<br>±150 mV                            | 0.6 | —   | 4.0  | V/ns |
| PCIe Gen 1 Pk-Pk Additive Jitter                                                                                                                    | Pk-Pk <sub>GEN1</sub> | PCIe Gen 1<br>Si53102-A1                                           | —   | —   | 10   | ps   |
| PCIe Gen 2 Additive Phase Jitter                                                                                                                    | RMS <sub>GEN2</sub>   | 10 kHz < F < 1.5 MHz,<br>Si53102-A2                                | —   | —   | 0.50 | ps   |
| PCIe Gen 2 Additive Phase Jitter                                                                                                                    | RMS <sub>GEN2</sub>   | 1.5 MHz < F < Nyquist,<br>Si53102-A2                               | —   | —   | 0.50 | ps   |
| PCIe Gen 3 Additive Phase Jitter                                                                                                                    | RMS <sub>GEN3</sub>   | Includes PLL BW 2–4 MHz,<br>CDR = 10 MHz,<br>Si53102-A3, VDD=3.3 V | —   | —   | 0.22 | ps   |
|                                                                                                                                                     |                       | Includes PLL BW 2–4 MHz,<br>CDR = 10 MHz,<br>Si53102-A3, VDD=2.5V  | —   | —   | 0.25 | ps   |
| PCIe Gen 4 Additive Phase Jitter                                                                                                                    | RMS <sub>GEN4</sub>   | PCIe Gen4, VDD=3.3V                                                | —   | —   | 0.22 | ps   |
|                                                                                                                                                     |                       | PCIe Gen4, VDD=2.5V                                                |     |     | 0.25 | ps   |
| Crossing Point Voltage at 0.7 V Swing                                                                                                               | V <sub>OX</sub>       | VDD = 3.3 V                                                        | 300 | —   | 550  | mV   |
|                                                                                                                                                     |                       | VDD = 2.5 V                                                        | 200 | —   | 550  | mV   |
| Enable/Disable and Setup                                                                                                                            |                       |                                                                    |     |     |      |      |
| Clock Stabilization from Powerup                                                                                                                    | T <sub>STABLE</sub>   | Power up to first output                                           | —   | —   | 3.0  | ms   |
| Note:                                                                                                                                               |                       |                                                                    |     |     |      |      |
| 1. Visit <a href="http://www.pcisig.com">www.pcisig.com</a> for complete PCIe specifications                                                        |                       |                                                                    |     |     |      |      |
| 2. Gen 4 specifications based on the PCI-Express Base Specification 4.0 rev. 0.5.                                                                   |                       |                                                                    |     |     |      |      |
| 3. Download the Silicon Labs PCIe Clock Jitter Tool at <a href="http://www.silabs.com/pcie-learningcenter">www.silabs.com/pcie-learningcenter</a> . |                       |                                                                    |     |     |      |      |

Table 2.4. Thermal Conditions

| Parameter                        | Symbol        | Condition       | Min | Typ | Max  | Unit |
|----------------------------------|---------------|-----------------|-----|-----|------|------|
| Temperature, Storage             | $T_S$         | Non-functional  | −65 |     | 150  | °C   |
| Temperature, Operating Ambient   | $T_A$         | Functional      | −40 |     | 85   | °C   |
| Temperature, Junction            | $T_J$         | Functional      | —   |     | 150  | °C   |
| Dissipation, Junction to Case    | $\theta_{JC}$ | JEDEC (JESD 51) | —   |     | 38.3 | °C/W |
| Dissipation, Junction to Ambient | $\theta_{JA}$ | JEDEC (JESD 51) | —   |     | 90.4 | °C/W |

Table 2.5. Absolute Maximum Conditions

| Parameter                         | Symbol         | Condition            | Min  | Typ | Max | Unit     |
|-----------------------------------|----------------|----------------------|------|-----|-----|----------|
| Main Supply Voltage               | $V_{DD\_3.3V}$ |                      | —    |     | 4.6 | V        |
| Input Voltage                     | $V_{IN}$       | Relative to $V_{SS}$ | −0.5 |     | 4.6 | $V_{DC}$ |
| ESD Protection (Human Body Model) | $ESD_{HBM}$    | JEDEC (JESD 22-A114) | 2000 |     | —   | V        |
| Flammability Rating               | UL-94          | UL (Class)           | V−0  |     |     |          |

### 3. Test and Measurement Setup

The following figures show the test load configurations for the differential clock signals.




Figure 3.1. 0.7 V Differential Load Configuration

The outputs from this device can also support LVDS, LVPECL, or CML differential signaling levels using alternative termination. For recommendations on how to achieve this, see [“AN781: Alternative Output Termination for Si5211x, Si5213x, Si5214x, Si5216x, Si5310x, Si5311x, and Si5315x PCIe Clock Generator and Buffer Families.”](#)




Figure 3.2. Differential Measurement for Differential Output Signals (AC Parameters Measurement)




Figure 3.3. Single-Ended Measurement for Differential Output Signals (AC Parameters Measurement)

#### 4. Recommended Design Guideline




Figure 4.1. Recommended Application Schematic

## 5. Pin Descriptions




Figure 5.1. 8-Pin TDFN

Table 5.1. Si53102-Ax-GM 8-Pin TDFN Descriptions

| Pin # | Name    | Type   | Description                              |
|-------|---------|--------|------------------------------------------|
| 1     | DIFFIN  | O, DIF | 0.7 V, 100 MHz differentials clock input |
| 2     | DIFFINb | O, DIF | 0.7 V, 100 MHz differentials clock input |
| 3     | DIFF1   | O, DIF | 0.7 V, 100 MHz differential clock output |
| 4     | DIFF1b  | O, DIF | 0.7 V, 100 MHz differential clock output |
| 5     | GND     | GND    | Ground                                   |
| 6     | DIFF2   | O, DIF | 0.7 V, 100 MHz differential clock output |
| 7     | DIFF2b  | O, DIF | 0.7 V, 100 MHz differential clock output |
| 8     | VDD     | PWR    | 2.5 V or 3.3 V Power supply              |

## 6. Package Outline

The figure below illustrates the package details for the Si53102-A1-A2-A3 in an 8-Pin TDFN package. The table lists the values for the dimensions shown in the illustration.




Figure 6.1. 8-Pin TDFN Package Drawing


Table 6.1. Package Diagram Dimensions

| Dimension | Min       | Nom  | Max  |
|-----------|-----------|------|------|
| A         | 0.70      | 0.75 | 0.80 |
| A1        | 0.00      | 0.02 | 0.05 |
| A3        | 0.20 REF. |      |      |
| b         | 0.15      | 0.20 | 0.25 |
| D         | 1.60 BSC  |      |      |
| D2        | 1.00      | 1.05 | 1.10 |
| e         | 0.40 BSC  |      |      |
| E         | 1.40 BSC  |      |      |
| E2        | 0.20      | 0.25 | 0.30 |
| L         | 0.30      | 0.35 | 0.40 |
| aaa       | 0.10      |      |      |
| bbb       | 0.10      |      |      |
| ccc       | 0.10      |      |      |
| ddd       | 0.07      |      |      |
| eee       | 0.08      |      |      |

| Dimension                                                                                                                                                                                                                                                                                                                 | Min | Nom | Max |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----|-----|
| <b>Note:</b> <ol style="list-style-type: none"> <li>1. All dimensions shown are in millimeters (mm) unless otherwise noted.</li> <li>2. Dimensioning and Tolerancing per ANSI Y14.5M-1994.</li> <li>3. Recommended card reflow profile is per the JEDEC/IPC J-STD-020 specification for Small Body Components.</li> </ol> |     |     |     |

## 7. Land Pattern

The following figure illustrates the land pattern details for the Si53102-A1-A2-A3 in an 8-Pin TDFN package. The table lists the values for the dimensions shown in the illustration.



**Figure 7.1. 8-Pin TDFN Land Pattern**

**Table 7.1. Land Pattern Dimensions**

| Dimension | mm   |
|-----------|------|
| C1        | 1.40 |
| E         | 0.40 |
| X1        | 0.75 |
| Y1        | 0.20 |
| X2        | 0.25 |
| Y2        | 1.10 |

### Notes:

#### General

1. All dimensions shown are in millimeters (mm).
2. This Land Pattern Design is based on the IPC-7351 guidelines.
3. All dimensions shown are at Maximum Material Condition (MMC). Least Material Condition (LMC) is calculated based on a Fabrication Allowance of 0.05 mm.

#### Solder Mask Design

1. All metal pads are to be non-solder mask defined (NSMD). Clearance between the solder mask and the metal pad is to be 60  $\mu\text{m}$  minimum, all the way around the pad.

#### Stencil Design

1. A stainless steel, laser-cut and electro-polished stencil with trapezoidal walls should be used to assure good solder paste release.
2. The stencil thickness should be 0.125 mm (5 mils).
3. The ratio of stencil aperture to land pad size should be 1:1 for all pads.

#### Card Assembly

1. A No-Clean, Type-3 solder paste is recommended.
2. The recommended card reflow profile is per the JEDEC/IPC J-STD-020 specification for Small Body Components.

## 8. Revision History

### 8.1 Revision 1.0

July 25, 2013

Full-production revision from Rev 0.4

- Updated AC Electrical Specifications table.
  - Updated input frequency min and max specs.
- Updated Test and Measurement Setup section.
  - Added text and reference to AN781.

### 8.2 Revision 1.1

August 5, 2013

- Moved Recommended Design Guideline section.
- Updated Pin Descriptions.
- Updated Package Outline.
- Added Land Pattern.

### 8.3 Revision 1.2

December 2, 2015

- Updated Features.
- Updated Description.
- Updated AC Electrical Specifications table.

### 8.4 Revision 1.3


July 21, 2017

- Updated IDD max specification.
- Separated VOX into 2.5 V and 3.3 V specifications.
- Separated PCIe Gen3 jitter into 2.5 V and 3.3 V specifications.
- Separated PCIe Gen4 jitter into 2.5 V and 3.3 V specifications.

### 8.5 Revision 1.4

July 28, 2017

- Updated [2. Electrical Specifications](#).
  - Updated PCIe Gen 4 Additive Phase Jitter max spec.
- Updated [6. Package Outline](#).
  - Added notes to [Table 6.1 Package Diagram Dimensions](#) on page 11.




Smart.  
Connected.  
Energy-Friendly.



Products

[www.silabs.com/products](http://www.silabs.com/products)



Quality

[www.silabs.com/quality](http://www.silabs.com/quality)



Support and Community

[community.silabs.com](http://community.silabs.com)

#### Disclaimer

Silicon Labs intends to provide customers with the latest, accurate, and in-depth documentation of all peripherals and modules available for system and software implementers using or intending to use the Silicon Labs products. Characterization data, available modules and peripherals, memory sizes and memory addresses refer to each specific device, and "Typical" parameters provided can and do vary in different applications. Application examples described herein are for illustrative purposes only. Silicon Labs reserves the right to make changes without further notice and limitation to product information, specifications, and descriptions herein, and does not give warranties as to the accuracy or completeness of the included information. Silicon Labs shall have no liability for the consequences of use of the information supplied herein. This document does not imply or express copyright licenses granted hereunder to design or fabricate any integrated circuits. The products are not designed or authorized to be used within any Life Support System without the specific written consent of Silicon Labs. A "Life Support System" is any product or system intended to support or sustain life and/or health, which, if it fails, can be reasonably expected to result in significant personal injury or death. Silicon Labs products are not designed or authorized for military applications. Silicon Labs products shall under no circumstances be used in weapons of mass destruction including (but not limited to) nuclear, biological or chemical weapons, or missiles capable of delivering such weapons.

#### Trademark Information

Silicon Laboratories Inc.®, Silicon Laboratories®, Silicon Labs®, SiLabs® and the Silicon Labs logo®, Bluegiga®, Bluegiga Logo®, Clockbuilder®, CMEMS®, DSPLL®, EFM®, EFM32®, EFR, Ember®, Energy Micro, Energy Micro logo and combinations thereof, "the world's most energy friendly microcontrollers", Ember®, EZLink®, EZRadio®, EZRadioPRO®, Gecko®, ISOmodem®, Micrium, Precision32®, ProSLIC®, Simplicity Studio®, SiPHY®, Telegesis, the Telegesis Logo®, USBXpress®, Zentri and others are trademarks or registered trademarks of Silicon Labs. ARM, CORTEX, Cortex-M3 and THUMB are trademarks or registered trademarks of ARM Holdings. Keil is a registered trademark of ARM Limited. All other products or brand names mentioned herein are trademarks of their respective holders.



Silicon Laboratories Inc.  
400 West Cesar Chavez  
Austin, TX 78701  
USA

<http://www.silabs.com>

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9