

Type TYC Series

Key Features

- Choice of Dielectrics (NP0, X7R, X5R, Y5V)
- 0402 to 1812 sizes as standard
- Other sizes available. 0201 available soon
- 6.3V to 50V in standard range
- Voltage ratings to 3kV on selected products
- Range of tolerances available
- RoHS Compliant
- Excellent thermal stability
- Low dissipation factor




Multilayer ceramic capacitors (MLCC) are manufactured by suspending ceramic powders in liquid and casting into a thin green sheet from 20mm in thickness to 5mm or thinner. Metal electrodes are sieved printed onto green sheets, which are later stacked to form a laminated structure. The metal electrodes are arranged so that the termination alternates from one edge to another of the capacitor.

Upon sintering at high temperature the part becomes a monolithic block, which can provide an extremely high capacitance in small mechanical volumes.

Finally, the termination electrodes are formed by composite of outer metal-glass electrode and followed by a barrier layer and pure-tin plating to permit MLCC to be soldered directly onto printed circuit board.

Structure



Class 1

No		Specifications	Material
1		Ceramic dielectric	Barium titanate base
2		Internal Electrode	Pb, PdAg
3		Inner Layer	Ag
4	End Terminal	Middle Layer	Ni
5		Outer Layer	Sn

Class 2

No		Specifications	Material
1		Ceramic dielectric	Barium titanate base
2	Internal Electrode		Pb, PbAg Ni
3		Inner Layer	Ag Cu
4	End Terminal	Middle Layer	Ni
5		Outer Layer	Sn

Type TYC Series

Capacitance & Voltage (NPO)

EIA	Size	0402				0603				0805				1206				1210				1812			
Code	VDCW	10V	16V	25V	50V	10V	16V	25V	50V	10V	16V	25V	50V	10V	16V	25V	50V	10V	16V	25V	50V	10V	16V	25V	50V
0R5	0.5pF	N	N	N	N	S	S	S	S	A	A	A	A												
1R0	1	N	N	N	N	S	S	S	S	A	A	A	A												
1R2	1.2	N	N	N	N	S	S	S	S	A	A	A	A												
1R5	1.5	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
1R8	1.8	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
2R2	2.2	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
2R7	2.7	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
3R3	3.3	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
3R9	3.9	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
4R7	4.7	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
5R6	5.6	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
6R8	6.8	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
8R2	8.2	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
100	10pF	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
120	12	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
150	15	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
180	18	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B								
220	22	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
270	27	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
330	33	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
390	39	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
470	47	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
560	56	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
680	68	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
820	82	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
101	100pF	F	N	N	N	N	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
121	120	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
151	150	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
181	180	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
221	220	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
271	270	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
331	330	N	N	N	N	S	S	S	S	A	A	A	A	B	B	B	B	C	C	C	C				
391	390	N	N			S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C				
471	470	N	N			S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C				
561	560					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C				
681	680					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C				
821	820					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C				
102	1000pF					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C	D	D	D	D
122	1200					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C	D	D	D	D
152	1500					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C	D	D	D	D
182	1800					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C	D	D	D	D
222	2200					S	S	S	S	B	B	B	B	B	B	B	B	C	C	C	C	D	D	D	D
272	2700					S	S	D	D	D	D			B	B	B	B	C	C	C	C	D	D	D	D
332	3300					S	S	D	D	D	D			B	B	B	B	C	C	C	C	D	D	D	D
392	3900									D	D	D	D	B	B	B	B	C	C	C	C	D	D	D	D
472	4700									D	D	D	D	B	B	B	B	C	C	C	C	D	D	D	D
562	5600									D	D			B	B	B	B	C	C	C	C	D	D	D	D
682	6800									D	D			C	C	C	C					D	D	D	D
822	8200									D	D			C	C	C	C					D	D	D	D
103	0.01μF									D	D		D'									D	D	D	D
123	0.012																					D	D	D	D
153	0.015																					D	D	D	D
183	0.018																					D	D	D	D
223	0.022																					D	D	D	D
273	0.027																					D	D	D	D
333	0.033																					D	D	D	D
393	0.039																					D	D	D	D
473	0.047																					D	D	D	D
563	0.056																					D	D	D	D
683	0.068																					D	D	D	D
823	0.082																					D	D	D	D
104	0.1μF									D	D											D	D	D	D

(1) [D']: The thickness spec. of said items is special defined on 1.25±0.2mm for 0805 and 1.15±0.15mm for 1206.

Size Unit: Inch (mm)	0402 (1005)	0603 (1608)	0805 (2012)	1206 (3216)	1210 (3225)	1808 (4520)	1812 (4532)
A= 0.60±0.10 mm	—	—	Paper 4Kp/reel	—	—	—	—
B= 0.80±0.10 mm	—	—	Paper 4Kp/reel	Paper 4Kp/reel	—	—	—
C= 0.95±0.10 mm	—	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	—	—
D= 1.25±0.10 mm	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 2Kp/reel	Plastic 1Kp/reel
G= 1.60±0.20 mm	—	—	—	Plastic 2Kp/reel	Plastic 2Kp/reel	—	—
S= 0.80±0.07 mm	—	Paper 4Kp/reel	—	—	—	—	—
N= 0.50±0.05 mm	Paper 10Kp/reel	—	—	—	—	—	—
K= 2.00±0.20 mm	—	—	—	—	Plastic 2Kp/reel	Plastic 1Kp/reel	Plastic 1Kp/reel
M= 2.50±0.30 mm	—	—	—	—	Plastic 1Kp/reel	—	Plastic 1Kp/reel

Type TYC Series

Capacitance & Voltage (Hi-Voltage NPO)

EIA	Size	0603	0805				1206						1210						1808			1812						
Code	VDCW	100	100	200	250	500	100	200	250	500	1000	2000	100	200	250	500	1000	2000	1000	2000	3000	100	200	250	500	1000	2000	3000
0R5	0.5pF	S	A	A	A	A																						
1R0	1	S	A	A	A	A																						
1R2	1.2	S	A	A	A	A																						
1R5	1.5	S	A	A	A	A	B	B	B	B	B	B																
1R8	1.8	S	A	A	A	A	B	B	B	B	B	B																
2R2	2.2	S	A	A	A	A	B	B	B	B	B	B																
2R7	2.7	S	A	A	A	A	B	B	B	B	B	B																
3R3	3.3	S	A	A	A	A	B	B	B	B	B	B																
3R9	3.9	S	A	A	A	A	B	B	B	B	B	B																
4R7	4.7	S	A	A	A	A	B	B	B	B	B	B																
5R6	5.6	S	A	A	A	A	B	B	B	B	B	B																
6R8	6.8	S	A	A	A	A	B	B	B	B	B	B																
8R2	8.2	S	A	A	A	A	B	B	B	B	B	B																
100	10pF	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
120	12	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
150	15	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
180	18	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
220	22	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
270	27	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
330	33	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
390	39	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
470	47	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
560	56	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D	D
680	68	S	A	A	A	A	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D	D
820	82	S	A	A	A	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D	D
101	100pF	S	A	A	A	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D	D
121	120	S	A	A	A	D	B	B	B	B	B	B	D	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D
151	150	S	A	B	B	D	B	B	B	B	C	D	C	C	C	C	C	D	D	D	D	D	D	D	D	D	D	D
181	180	S	A	B	B	D	B	B	B	B	C	G	C	C	C	C	C	D	D	D	K	D	D	D	D	D	D	D
221	220	S	A	D	D	D	B	B	B	B	D	G	C	C	C	C	C	D	D	D	K	D	D	D	D	D	D	D
271	270	S	A	D	D	D	B	B	B	C	D		C	C	C	C	C	D	D	D	K	D	D	D	D	D	D	K
331	330	S	A	D	D	D	B	B	B	C			C	C	C	C	D		D	D		D	D	D	D	D	D	K
391	390	S	B	D	D	D	B	B	B	C			C	C	C	C	D		D	K		D	D	D	D	D	D	K
471	470	S	B	D	B	C	C	C					C	C	C	C	D		D	K		D	D	D	D	D	D	K
561	560	S	B	D	B	C	C	C					C	C	C	C			K	K		D	D	D	D	D	D	
681	680	B	D	B	C	C	C						C	C	C	C			K	K		D	D	D	D	D	K	
821	820	B	D	B	C	D	D						C	C	C	C			K	K		D	D	D	D	D	K	
102	1000pF	B	B		C								C	C	C	C			K			D	D	D	D	K	K	
122	1200	B	B	C									C	D	D	D						D	D	D	D	K		
152	1500	B	B	C									C	D	D	D						D	D	D	D	K		
182	1800	B	B	C									C	D	D	D						D	D	D	D			
222	2200	B	B	D									C	D	D							D	D	D	D			
272	2700	D	B										C	D	D							D	D	D	D			
332	3300	D	B										C	D								D	D	D	D			
392	3900	D	B										C	D								D	D					
472	4700	B											C									D	D					
562	5600	B											C									D	D					
682	6800	C											C									D	D					
822	8200	C											C									D						
103	0.01μF												C									D						
123	0.012												D									D						
153	0.015												D									D						
183	0.018																					D						
223	0.022																					D						
273	0.027																					D						
333	0.033μF																					D						

Size Unit: Inch (mm)	0402 (1005)	0603 (1608)	0805 (2012)	1206 (3216)	1210 (3225)	1808 (4520)	1812 (4532)
A= 0.60±0.10 mm	—	—	Paper 4Kp/reel	—	—	—	—
B= 0.80±0.10 mm	—	—	Paper 4Kp/reel	Paper 4Kp/reel	—	—	—
C= 0.95±0.10 mm	—	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	—	—
D= 1.25±0.10 mm	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 2Kp/reel	Plastic 1Kp/reel
G= 1.60±0.20 mm	—	—	—	Plastic 2Kp/reel	Plastic 2Kp/reel	—	—
S= 0.80±0.07 mm	—	Paper 4Kp/reel	—	—	—	—	—
N= 0.50±0.05 mm	Paper 10Kp/reel	—	—	—	—	—	—
K= 2.00±0.20 mm	—	—	—	—	Plastic 2Kp/reel	Plastic 1Kp/reel	Plastic 1Kp/reel
M= 2.50±0.30 mm	—	—	—	—	Plastic 1Kp/reel	—	Plastic 1Kp/reel

Type TYC Series

Capacitance & Voltage (X7R/X5R)

EIA Code	Size	0402				0603					0805					1206					1210					1812				
	VDCW	10V	16V	25V	50V	6.3V	10V	16V	25V	50V	6.3V	10V	16V	25V	50V	6.3V	10V	16V	25V	50V	6.3V	10V	16V	25V	50V	6.3V	10V	16V	25V	50V
101	100pF	N	N	N	N		S	S	S	S		B	B	B	B															
121	120	N	N	N	N		S	S	S	S		B	B	B	B															
151	150	N	N	N	N		S	S	S	S		B	B	B	B															
181	180	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
221	220	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
271	270	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
331	330	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
391	390	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
471	470	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
561	560	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
681	680	N	N	N	N		S	S	S	S		B	B	B	B		B ^A	B ^A	B ^A	B ^A										
821	820	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B										
102	1000pF	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
122	1200	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
152	1500	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
182	1800	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
222	2200	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
272	2700	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
332	3300	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
392	3900	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
472	4700	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
562	5600	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
682	6800	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C ^A	C ^A	C ^A	C ^A		D ^A	D ^A	D ^A	D ^A
822	8200	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
103	0.01μF	N	N	N	N		S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
123	0.012	N	N				S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
153	0.015	N	N				S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
183	0.018	N	N				S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
223	0.022	N	N				S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
273	0.027	N					S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
333	0.033	N	N				S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
393	0.039	N					S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
473	0.047	N	N				S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
563	0.056	N					S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
683	0.068	*N					S	S	S	S		B	B	B	B		B	B	B	B		C	C	C	C		D ^A	D ^A	D ^A	D ^A
823	0.082	*N					S	S	S	S		B	B	B	D		B	B	B	B		C	C	C	C		D	D	D	D
104	0.1μF	*N					S	S	S	S		B	B	B	D		B	B	B	B		C	C	C	C		D	D	D	D
124	0.12						S					B	B	B	D		B	B	B	B		C	C	C	C		D	D	D	D
154	0.15						S	S				D	D	D	D		C	C	C	C		C	C	C	C		D	D	D	D
184	0.18						S					D	D	D	D'		C	C	C	C		C	C	C	C		D	D	D	D
224	0.22						S	S				D	D	D	D'		C	C	C	C		C	C	C	C		D	D	D	D
274	0.27											D	D	D			C	C	C			C	C	C	C		D	D	D	D
334	0.33						*S'					D	D	D			C	C	C			C	C	C	C		D	D	D	D
394	0.39											D	D				C	C				C	C	C	C		D	D	D	D
474	0.47						*S'					D	D	D'			D	D	D'	G'		C	C	C			D	D	D	D
564	0.56											D	D				D	D									D	D	D	D
684	0.68											D	D'				D	D									D	D	D	K
824	0.82											D					D	D									D	D	D	K
105	1μF						*S'	*S'				D	D'	D'			D	D	G'			G	G	G			D	D	D	K
225	2.2						*S'					*D'	*D'				*D'	*D'	G'			K	K	K						
335	3.3											*D'	*D'				*G'	*G'				K	K	K						
475	4.7											*D'					*G'	*G'	*G'			K	K	K						
685	6.8																					K	K	K						
106	10μF											*D'					*G'	*G'				*K	*K	*K					M	
226	22μF																*G'	*G'				*M	*M							
107	100μF																										*U		*M	

(1) [*]: The said items are made by NME (Noble Metal Electrode).

(2) [*]: The said items are available in X5R.

(3) [S]: The thickness spec. of said items is special defined on 0.80±0.15/-0.1mm.

(4) [D]: The thickness spec. of said items is special defined on 1.25±0.2mm for 0805 and 1.15±0.15mm for 1206.

(5) [G]: The thickness spec. of said items is special defined on 1.60±0.3/-0.1mm.

Size Unit: Inch (mm)	0402 (1005)	0603 (1608)	0805 (2012)	1206 (3216)	1210 (3225)	1808 (4520)	1812 (4532)
A= 0.60±0.10 mm	—	—	Paper 4Kp/reel	—	—	—	—
B= 0.80±0.10 mm	—	—	Paper 4Kp/reel	—	—	—	—
C= 0.95±0.10 mm	—	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	—	—
D= 1.25±0.10 mm	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 2Kp/reel	Plastic 1Kp/reel
G= 1.60±0.20 mm	—	—	—	Plastic 2Kp/reel	Plastic 2Kp/reel	—	—
S= 0.80±0.07 mm	—	Paper 4Kp/reel	—	—	—	—	—
N= 0.50±0.05 mm	Paper 10Kp/reel	—	—	—	—	—	—
K= 2.00±0.20 mm	—	—	—	—	Plastic 2Kp/reel	Plastic 1Kp/reel	Plastic 1Kp/reel
M= 2.50±0.30 mm	—	—	—	—	Plastic 1Kp/reel	—	Plastic 1Kp/reel
U= 2.80±0.30 mm	—	—	—	—	—	—	Plastic 0.5Kp/reel

Type TYC Series

Capacitance & Voltage (Hi-Voltage X7R)

EIA	Size	0603	0805				1206							1210					1808			1812						
Code	VDCW	100	100	200	250	500	100	200	250	500	1000	1500	2000	100	200	250	500	1000	1000	1500	2000	100	200	250	500	1000	2000	3000
101	100pF	S	B	B^	B^	B^																						
121	120	S	B	B^	B^	B^																						
151	150	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	B^						D^	D^	D^							
181	180	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	B^						D^	D^	D^							
221	220	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	B^						D^	D^	D^							
271	270	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	B^						D^	D^	D^					D^	D^	
331	330	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	B^						D^	D^	D^					D^	D^	
391	390	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	C^						D^	D^	D^					D^	D^	
471	470	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	C^						D^	D^	D^					D^	D^	
561	560	S	B	B^	B^	B^	B^	B^	B^	B^	B^	B^	C^						D^	D^	D^					D^	D^	
681	680	S	B	B^	B^	B^	B^	B^	B^	B^	B^	C^	C^						D^	D^	D^					D^	D^	K^
821	820	S	B	B^	B^	B^	B	B^	B^	B^	B^	G^	G^						D^	D^	D^					D^	D^	K^
102	1000pF	S	B	B^	B^	B^	B	B^	B^	B^	B^	G^	G^	C^	C^	C^	C^	C^	D^	D^	K^	D^	D^	D^	D^	D^	D^	K^
122	1200	S	B	B^	B^	B^	B	B^	B^	B^	B^	G^	G^	C^	C^	C^	C^	C^	D^	D^	K^	D^	D^	D^	D^	D^	D^	D^
152	1500	S	B	B^	B^	B^	B	B^	B^	B^	C^	G^		C^	C^	C^	C^	C^	D^	D^	K^	D^	D^	D^	D^	D^	D^	D^
182	1800	S	B	B^	B^	B^	B	B^	B^	B^	C^	G^		C^	C^	C^	C^	C^	D^	D^	K^	D^	D^	D^	D^	D^	D^	D^
222	2200	S	B	B^	B^	B^	B	B^	B^	B^	D^	G^		C^	C^	C^	C^	C^	D^	D^	K^	D^	D^	D^	D^	D^	D^	D^
272	2700	S	B	B^	B^	B^	B	B^	B^	B^	G^	G^		C^	C^	C^	C^	C^	D^	D^		D^	D^	D^	D^	D^	D^	D^
332	3300	S	B	B^	B^		B	B^	B^	B^	G^			C^	C^	C^	C^	D^	D^	K^		D^	D^	D^	D^	D^	D^	K^
392	3900	S	B	B^	B^		B	B^	B^	B^	G^			C^	C^	C^	C^		D^			D^	D^	D^	D^	D^	D^	K^
472	4700	S	B	B^	B^		B	B^	B^	B^				C^	C^	C^	C^		D^			D^	D^	D^	D^	D^	D^	K^
562	5600	S	B	D^	D^		B	B^	B^	B^				C^	C^	C^	C^		K^			D^	D^	D^	D^	D^	D^	
682	6800	S	B	D^	D^		B	B^	B^	B^				C^	C^	C^	C^		K^			D^	D^	D^	D^	D^	D^	
822	8200	S	B	D^	D^		B	B^	B^	C^				C	C^	C^	C^		K^			D^	D^	D^	D^	D^	D^	
103	0.01μF	S	B	D^	D^		B	B^	B^	C^				C	C^	C^	C^		K^			D^	D^	D^	D^	D^	D^	
123	0.012		B				B	B^	B^					C	C^	C^	C^					D^	D^	D^	D^	D^	D^	K^
153	0.015		B				B	C^	C^					C	C^	C^	C^					D^	D^	D^	D^	D^	D^	K^
183	0.018		B				B	C^	C^					C	C^	C^	C^					D^	D^	D^	D^	D^	D^	
223	0.022		B				B	C^	C^					C	C^	C^	D^					D^	D^	D^	D^	D^	D^	
273	0.027		D				B	C^	C^					C	C^	C^						D^	D^	D^	D^	D^	D^	
333	0.033		D				B	G^	G^					C	C^	C^						D^	D^	D^	D^	D^	D^	
393	0.039						B	G^	G^					C	C^	C^						D^	D^	D^	D^	D^	D^	
473	0.047						B	G^	G^					C	D^	D^						D^	D^	D^	D^	D^	D^	
563	0.056						B							C	D^	D^						D^	D^	D^	D^	D^	D^	
683	0.068						B							C								D^	D^	D^	D^	D^	D^	
823	0.082						D							C								D	D^	D^	D^	D^	D^	K^
104	0.1μF						D							C								D	D^	D^	D^	D^	D^	K^
124	0.12													C								D	D^	D^				
154	0.15													D								D	K^	K^				
184	0.18													D								D	K^	K^				
224	0.22													D								D	K^	K^				
274	0.27																					D						
334	0.33																					D						
394	0.39																					D						
474	0.47																					K						
564	0.56																					K						
684	0.68																					K						
824	0.82																											
105	1μF																											

(1) [A]: The said items are made by NME (Noble Metal Electrode).

Size Unit: Inch (mm)	0402 (1005)	0603 (1608)	0805 (2012)	1206 (3216)	1210 (3225)	1808 (4520)	1812 (4532)
A= 0.60±0.10 mm	—	—	Paper 4Kp/reel	—	—	—	—
B= 0.80±0.10 mm	—	—	Paper 4Kp/reel	Paper 4Kp/reel	—	—	—
C= 0.95±0.10 mm	—	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	—	—
D= 1.25±0.10 mm	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 2Kp/reel	Plastic 1Kp/reel
G= 1.60±0.20 mm	—	—	—	Plastic 2Kp/reel	Plastic 2Kp/reel	—	—
S= 0.80±0.07 mm	—	Paper 4Kp/reel	—	—	—	—	—
N= 0.50±0.05 mm	Paper 10Kp/reel	—	—	—	—	—	—
K= 2.00±0.20 mm	—	—	—	—	Plastic 2Kp/reel	Plastic 1Kp/reel	Plastic 1Kp/reel
M= 2.50±0.30 mm	—	—	—	—	Plastic 1Kp/reel	—	Plastic 1Kp/reel

Type TYC Series

Capacitance & Voltage (Y5V)

EIA	Size	0402					0603					0805					1206					1210				1812			
Code	VDCW	6.3V	10V	16V	25V	50V	6.3V	10V	16V	25V	50V	6.3V	10V	16V	25V	50V	10V	16V	25V	35V	50V	10V	16V	25V	50V	10V	16V	25V	50V
102	1000pF																												
122	1200																												
152	1500																												
182	1800																												
222	2200																												
272	2700																												
332	3300																												
392	3900																												
472	4700																												
562	5600																												
682	6800																												
822	8200																												
103	0.01μF		N	N	N	N		S	S	S	S		A	A	A	A	B	B	B		B								
123	0.012		N	N	N	N		S	S	S	S		A	A	A	A	B	B	B		B								
153	0.015		N	N	N	N		S	S	S	S		A	A	A	A	B	B	B		B								
183	0.018		N	N	N	N		S	S	S	S		A	A	A	A	B	B	B		B								
223	0.022		N	N	N	N		S	S	S	S		A	A	A	A	B	B	B		B								
273	0.027		N	N	N	N		S	S	S	S		A	A	A	A	B	B	B		B								
333	0.033		N	N	N	N		S	S	S	S		A	A	A	A	B	B	B		B								
393	0.039		N	N	N			S	S	S	S		A	A	A	A	B	B	B		B								
473	0.047		N	N	N			S	S	S	S		A	A	A	A	B	B	B		B								
563	0.056		N	N				S	S	S	S		A	A	A	A	B	B	B		B								
683	0.068		N	N				S	S	S	S		A	A	A	A	B	B	B		B								
823	0.082		N	N				S	S	S	S		A	A	A	A	B	B	B		B								
104	0.1μF		N	N				S	S	S	S		A	A	A	A	B	B	B		B	C	C	C	C	D	D	D	D
154	0.15		N					S	S	S	S		A	A	A	A	B	B	B		B	C	C	C	C	D	D	D	D
224	0.22		N					S	S	S	S		A	A	A	A	B	B	B		B	C	C	C	C	D	D	D	D
334	0.33	N	N					S	S	S			B	B	B	B	B	B	B		B	C	C	C	C	D	D	D	D
474	0.47	N	N					S	S	S			B	B	B		B	B	B		B	C	C	C	C	D	D	D	D
684	0.68							S					B	B	D		B	B	B		B	C	C	C	C	D	D	D	D
105	1μF	N						S	S				B	B	D	D'	C	C	C		C	C	C	C	C	D	D	D	D
155	1.5												D	D			C	C	C			C	C	C		D	D	D	D
225	2.2						S						D	D			C	C	C		D'	C	C	C		D	D	D	D
335	3.3												D				D	D	D			C	C	C		D	D	D	D
475	4.7						S						D	D'			D	D	D'	D'		C	C	D	G	D	D	D	D
685	6.8																D	D'				C	C			D	D	D	D
106	10μF											D'	D'				D	D'				D	D	G		D	D	D	
226	22μF																G'					K	K						
476	47μF																					K							

(1) [D']: The thickness spec. of said items is special defined on 1.25±0.2mm for 0805 and 1.15±0.15mm for 1206.

(2) [G']: The thickness spec. of said items is special defined on 1.60±0.3/-0.1mm.

Size Unit: Inch (mm)	0402 (1005)	0603 (1608)	0805 (2012)	1206 (3216)	1210 (3225)	1808 (4520)	1812 (4532)
A= 0.60±0.10 mm	—	—	Paper 4Kp/reel	—	—	—	—
B= 0.80±0.10 mm	—	—	Paper 4Kp/reel	Paper 4Kp/reel	—	—	—
C= 0.95±0.10 mm	—	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	—	—
D= 1.25±0.10 mm	—	—	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 2Kp/reel	Plastic 1Kp/reel
G= 1.60±0.20 mm	—	—	—	Plastic 2Kp/reel	Plastic 2Kp/reel	—	—
S= 0.80±0.07 mm	—	Paper 4Kp/reel	—	—	—	—	—
N= 0.50±0.05 mm	Paper 10Kp/reel	—	—	—	—	—	—
K= 2.00±0.20 mm	—	—	—	—	Plastic 2Kp/reel	Plastic 1Kp/reel	Plastic 1Kp/reel

Type TYC Series

Capacitance & Voltage (Hi-Voltage Y5V)


EIA Code	Size VDCW	0805			1206			1210			1812		
		100	200	250	100	200	250	100	200	250	100	200	250
103	0.01 μ F	B	B	B	B	B	B	C	C	C	D	D	D
153	0.015	B	B	B	B	B	B	C	C	C	D	D	D
223	0.022	B	B	B	B	B	B	C	C	C	D	D	D
333	0.033	B	B	B	B	B	B	C	C	C	D	D	D
473	0.047	B	B	B	B	B	B	C	C	C	D	D	D
683	0.068	B	B	B	B	B	B	C	C	C	D	D	D
104	0.1 μ F	B			B	B	B	C	C	C	D	D	D
154	0.15				C	C	C	C	C	C	D	D	D
224	0.22				C			C			D	D	D
334	0.33							C			D	D	D
474	0.47										D	D	D
684	0.68										D	D	D
105	1 μ F										D		

Size Unit: Inch (mm)	0805 (2012)	1206 (3216)	1210 (3225)	1812 (4532)
A= 0.60±0.10 mm	Paper 4Kp/reel	—	—	—
B= 0.80±0.10 mm	Paper 4Kp/reel	Paper 4Kp/reel	—	—
C= 0.95±0.10 mm	—	Plastic 3Kp/reel	Plastic 3Kp/reel	—
D= 1.25±0.10 mm	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 3Kp/reel	Plastic 1Kp/reel
G= 1.60±0.20 mm	—	Plastic 2Kp/reel	—	—
S= 0.80±0.07 mm	—	—	—	—
N= 0.50±0.05 mm	—	—	—	—
K= 2.00±0.20 mm	—	—	—	Plastic 1Kp/reel
M= 2.50±0.30 mm	—	—	—	—

Packaging

Chip Size	Paper Tape			Plastic Tape			Chip Thickness
	Width (reel)	Thickness	Unit/Reel	Width (reel)	Thickness	Unit/Reel	
0402	8mm (7")	N	10Kp/Reel				A=0.50~0.70
0603	8mm (7")	S	4Kp/Reel				B=0.85±0.05/-0.15
	8mm (10")	S	10Kp/Reel				C=1.00±0.05/-0.13
0805	8mm (13")	S	15Kp/Reel				D=1.20±0.15
	8mm (7")	A, B	4Kp/Reel	8mm (7")	C, D	3Kp/Reel	S=0.80±0.07
	8mm (10")	A, B	10Kp/Reel	8mm (10")	C, D	3Kp/Reel	H=0.50~0.60
1206	8mm (13")	A, B	15Kp/Reel	8mm (13")	C, D	3Kp/Reel	E=0.65~0.75
	8mm (7")	A, B	4Kp/Reel	8mm (7")	C, D	3Kp/Reel	N=0.50±0.05
	8mm (10")	A, B	10Kp/Reel	8mm (10")	C, D	3Kp/Reel	F=1.40±0.05/-0.15
	8mm (13")	A, B	15Kp/Reel	8mm (13")	C, D	3Kp/Reel	G=1.60±0.05/-0.15
1210				8mm (7")	F, G	3Kp/Reel	K=2.00±0.10
				8mm (7")	K	3Kp/Reel	
				8mm (7")	C, D	3Kp/Reel	
1808				12mm (7")	F	3Kp/Reel	
				12mm (7")	C, G	3Kp/Reel	
1812				12mm (7")	K	3Kp/Reel	
				12mm (7")	D	3Kp/Reel	


Dimensions




SIZE CODE	L	W	A
0402	1.00±0.05	0.50±0.05	0.25±0.05/-0.10
0603	1.60±0.10	0.80±0.07	0.40±0.15
0805	2.00±0.15	1.25±0.10	0.50±0.20
1206	3.20±0.15	1.60±0.15	0.60±0.20
1210	3.20±0.30	2.50±0.20	0.75±0.25
1808	4.50±0.40	2.03±0.25	0.75±0.25
1812	4.50±0.40	3.20±0.30	0.75±0.25

Type TYC Series

Packaging (continued)



ϕA	ϕB	ϕC	W
178 $\pm$ 1 (7")	60.5 $\pm$ 1	13.0 $\pm$ 1	9.0 $\pm$ 1
250 $\pm$ 1 (10")	80 $\pm$ 1		13.5 $\pm$ 1
330 $\pm$ 1 (13")	100 $\pm$ 1		9.0 $\pm$ 1



Type	A	B	W	ϕD_0	E	F	P ₀	P ₁	P ₂	T
0402	0.7 $\pm$ 0.05	1.23 $\pm$ 0.05								0.6 $\pm$ 0.05
0603	1.0 $\pm$ 0.1	1.84 $\pm$ 0.1								
0805	1.55 $\pm$ 0.2	2.35 $\pm$ 0.2	8.0 $\pm$ 0.32	1.55 $\pm$ 0.05	1.70 $\pm$ 0.1	3.50 $\pm$ 0.1	4.0 $\pm$ 0.1	4.0 $\pm$ 0.1	2.0 $\pm$ 0.1	<1.0
1206	2.0 $\pm$ 0.2	3.5 $\pm$ 0.2								

How to Order

TYC	0201	A	101	B	C	T
Common Part	Size	Dielectric	Capacitance Code	Tolerance	Voltage	Packaging
TYC - Multilayer Ceramic Chip Capacitor	0201	A = NPO	101 - 100pF	B = 0.1pF C = 0.25pF D = 0.5pF F = +/- 1% G = +/- 2% J = +/- 5% K = +/- 10% M = +/- 20% Z = +80%/-20%	C = 6.3V	T = Paper (7") P = Plastic (7")
	0402				D = 10V	
	0603	B = X7R	102 - 1000pF		E = 16V	
	0805	C = X5R	103 - 0.01uF		F = 25V	
	1206	D = Y5V			G = 50V	
					H = 100V	
				J = 200V		
				L = 500V		
				P = 1KV		
				Q = 2KV		
				R = 3KV		
				S = 4KV		

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9