



# Chip Inductors – 1206CS Series (3216)

- High SRF and excellent Q values
- Tight tolerances, many values at 1%
- 31 inductance values from 3.3 to 1200 nH

Request free evaluation samples by contacting Coilcraft or visiting [www.coilcraft.com](http://www.coilcraft.com).

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>(nH) | Percent<br>tolerance <sup>3</sup> | Q min <sup>4</sup> | SRF min <sup>5</sup><br>(MHz) | DCR max <sup>6</sup><br>(Ohms) | Irms <sup>7</sup><br>(mA) |
|--------------------------|---------------------------------|-----------------------------------|--------------------|-------------------------------|--------------------------------|---------------------------|
| 1206CS-030X_L_           | 3.3 @ 100 MHz                   | <b>5</b>                          | 30 @ 300 MHz       | 6200                          | 0.050                          | 1000                      |
| 1206CS-060X_L_           | 6.8 @ 100 MHz                   | <b>5</b>                          | 30 @ 300 MHz       | 5500                          | 0.070                          | 1000                      |
| 1206CS-100X_L_           | 10 @ 100 MHz                    | <b>5</b>                          | 40 @ 300 MHz       | 4000                          | 0.080                          | 1000                      |
| 1206CS-120X_L_           | 12 @ 100 MHz                    | <b>5,2</b>                        | 40 @ 300 MHz       | 3200                          | 0.080                          | 1000                      |
| 1206CS-150X_L_           | 15 @ 100 MHz                    | <b>5,2</b>                        | 40 @ 300 MHz       | 3200                          | 0.100                          | 1000                      |
| 1206CS-180X_L_           | 18 @ 100 MHz                    | <b>5,2</b>                        | 50 @ 300 MHz       | 2800                          | 0.100                          | 1000                      |
| 1206CS-220X_L_           | 22 @ 100 MHz                    | <b>5,2</b>                        | 50 @ 300 MHz       | 2200                          | 0.100                          | 1000                      |
| 1206CS-270X_L_           | 27 @ 100 MHz                    | <b>5,2</b>                        | 50 @ 300 MHz       | 1800                          | 0.110                          | 1000                      |
| 1206CS-330X_L_           | 33 @ 100 MHz                    | <b>5,2</b>                        | 55 @ 300 MHz       | 1800                          | 0.110                          | 1000                      |
| 1206CS-390X_L_           | 39 @ 100 MHz                    | <b>5,2</b>                        | 55 @ 300 MHz       | 1800                          | 0.120                          | 1000                      |
| 1206CS-470X_L_           | 47 @ 100 MHz                    | <b>5,2</b>                        | 55 @ 300 MHz       | 1500                          | 0.130                          | 1000                      |
| 1206CS-560X_L_           | 56 @ 100 MHz                    | <b>5,2,1</b>                      | 55 @ 300 MHz       | 1450                          | 0.140                          | 1000                      |
| 1206CS-680X_L_           | 68 @ 100 MHz                    | <b>5,2,1</b>                      | 55 @ 300 MHz       | 1200                          | 0.260                          | 900                       |
| 1206CS-820X_L_           | 82 @ 100 MHz                    | <b>5,2,1</b>                      | 55 @ 300 MHz       | 1200                          | 0.210                          | 900                       |
| 1206CS-101X_L_           | 100 @ 100 MHz                   | <b>5,2,1</b>                      | 55 @ 300 MHz       | 1100                          | 0.260                          | 850                       |
| 1206CS-121X_L_           | 120 @ 100 MHz                   | <b>5,2,1</b>                      | 60 @ 300 MHz       | 1100                          | 0.260                          | 800                       |
| 1206CS-151X_L_           | 150 @ 100 MHz                   | <b>5,2,1</b>                      | 60 @ 300 MHz       | 950                           | 0.310                          | 750                       |
| 1206CS-181X_L_           | 180 @ 50 MHz                    | <b>5,2,1</b>                      | 60 @ 300 MHz       | 900                           | 0.430                          | 700                       |
| 1206CS-221X_L_           | 220 @ 50 MHz                    | <b>5,2,1</b>                      | 60 @ 300 MHz       | 760                           | 0.500                          | 670                       |
| 1206CS-271X_L_           | 270 @ 50 MHz                    | <b>5,2,1</b>                      | 55 @ 300 MHz       | 730                           | 0.560                          | 630                       |
| 1206CS-331X_L_           | 330 @ 50 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 650                           | 0.620                          | 590                       |
| 1206CS-391X_L_           | 390 @ 50 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 600                           | 0.750                          | 530                       |
| 1206CS-471X_L_           | 470 @ 50 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 550                           | 1.30                           | 490                       |
| 1206CS-561X_L_           | 560 @ 35 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 470                           | 1.34                           | 460                       |
| 1206CS-621X_L_           | 620 @ 35 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 470                           | 1.58                           | 460                       |
| 1206CS-681X_L_           | 680 @ 35 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 450                           | 1.58                           | 430                       |
| 1206CS-751X_L_           | 750 @ 35 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 440                           | 2.25                           | 320                       |
| 1206CS-821X_L_           | 820 @ 35 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 420                           | 1.82                           | 400                       |
| 1206CS-911X_L_           | 910 @ 35 MHz                    | <b>5,2,1</b>                      | 45 @ 150 MHz       | 410                           | 2.95                           | 310                       |
| 1206CS-102X_L_           | 1000 @ 35 MHz                   | <b>5,2,1</b>                      | 45 @ 150 MHz       | 400                           | 2.80                           | 320                       |
| 1206CS-122X_L_           | 1200 @ 35 MHz                   | <b>5,2,1</b>                      | 45 @ 150 MHz       | 380                           | 3.20                           | 300                       |

1. When ordering, specify **tolerance, termination and packaging** codes:

**1206CS-122XJLC**

**Tolerance:** F = 1% G = 2% J = 5%

(Table shows stock tolerances in bold.)

**Termination:** L = RoHS compliant silver-palladium-platinum-glass frit.

E = Halogen free component. RoHS compliant silver-palladium-platinum-glass frit terminations.  
Special order: T = RoHS tin-silver-copper (95.5/4/0.5) or S = non-RoHS tin-lead (63/37).

**Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape (2000 parts per full reel).

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (7500 parts per full reel).

2. Inductance measured using a Coilcraft SMD-A fixture in an Agilent/HP 4286A impedance analyzer with Coilcraft-provided correlation pieces.

3. Tolerances in bold are stocked for immediate shipment.

4. Q measured using an Agilent/HP 4291A with an Agilent/HP 16193 test fixture.

5. SRF measured using an Agilent/HP 8720D network analyzer and a Coilcraft SMD-D test fixture.

6. DCR measured on a Cambridge Technology Micro-ohmmeter and a Coilcraft CCF840 fixture.

7. Current that causes a 15°C temperature rise from 25°C ambient.

8. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.  
Refer to Doc 174 "Color Coding" for the explanation of color dots.

**COILCRAFT** ACCURATE  
**PRECISION** REPEATABLE  
MEASUREMENTS  
SEE WEB SITE **TEST FIXTURES**



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)  
**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)  
**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)  
**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)  
**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 104-1 Revised 02/23/15


© Coilcraft Inc., 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.




# 1206CS Series (3216)


## Typical Q vs Frequency



## Typical L vs Frequency



## Irms Derating



**Designer's Kit C320** contains 10 each of all 5% values

**Core material** Ceramic

**Environmental** RoHS compliant, halogen free optional

**Terminations** RoHS compliant silver-palladium-platinum-glass frit. Other terminations available at additional cost.

**Weight** 19.5 – 23.0 mg

**Ambient temperature** –40°C to +125°C with Irms current, +125°C to +140°C with derated current

**Storage temperature** Component: –40°C to +140°C.

Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Temperature Coefficient of Inductance (TCL)** +25 to +125 ppm/°C


**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

One per billion hours / one billion hours, calculated per Telcordia SR-332

**Packaging** 2000/7" reel; 7500/13" reel. Plastic tape: 8 mm wide, 0.3 mm thick, 4 mm pocket spacing, 1.6 mm pocket depth

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787\\_PCB\\_Washing.pdf](#).



| Amax  | Bmax  | Cmax  | Dref  | E     | F     | G     | H     | I     | J     |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 0.140 | 0.085 | 0.060 | 0.020 | 0.056 | 0.020 | 0.080 | 0.076 | 0.040 | 0.070 |
| 3,56  | 2,16  | 1,52  | 0,51  | 1,42  | 0,51  | 2,03  | 1,93  | 1,02  | 1,78  |

**Note:** Height dimension (C) is before optional solder application. For maximum height dimension including solder, add 0.006 in / 0,152 mm.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9