


SUGGESTED PCB LAYOUT



SCHEMATIC

POSITION	TERMINAL			
	1	2	4	8
0				
1	●			
2		●		
3	●		●	
4		●		●
5	●		●	
6		●	●	●
7	●			●
8				●
9	●			●

● CLOSED (Connected to C)

SPECIFICATIONS

FUNCTION:
1P10T

RATINGS:
Switching: 25mA 24VDC
Steady: 100mA 50VDC

OPERATING FORCE:
200gfc

CONTACT RESISTANCE:
Initial: 100mΩ Max.
After Life: 200mΩ Max.

INSULATION RESISTANCE:
100MΩ Min. at 100VDC

DIELECTRIC STRENGTH:
250VAC For 1 Minute

CAPACITANCE:
5pF Max.

SHOCK RESISTANCE:
Mil-Std. 202F, Method 213B
Gravity: 50G, 11msec.
Direction: 6 Sides
Times: 3 Each Direction

VIBRATION RESISTANCE:
Mil-Std. 202F, Method 201A
Frequency: 10-55-10Hz/1 Minute
Direction: X, Y, Z
Time: 2 Hours Each Direction

ELECTRICAL LIFE:
10,000 Steps

TEMPERATURE:
Storage: -40°C to 85°C
Operation: -30°C to 80°C

APPROVALS:
RoHS LEAD FREE
COMPLIANT PROCESS COMPATIBLE

COLORS

ACTUATOR:
White

MARKING COLOR:
Black

MATERIALS

BASE:
High-Temp Thermoplastic Nylon, UL94 V-0

COVER:
Nickel Silver

ACTUATOR:
High-Temp Thermoplastic Nylon, UL94 V-0

INNER SEAL:
Silicone Rubber

OUTER SEAL:
Silicone Rubber

SPRING PLATE:
Steel

CONTACT PLATE:
Stainless Steel

CONTACTS:
Gold Over Nickel Plated Copper Alloy

TERMINALS:
Gold Plated Brass

PACKAGING

PACKAGING TYPE:
Tube

TUBE QUANTITY:
65 Pieces

ACTUATOR	B	09/07/23	CAB
BODY	A	09/07/14	CAB
MATERIALS	A	09/07/14	CAB
PACKAGING	A	09/07/14	CAB
SPECIFICATIONS	A	09/07/14	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

B	ACTUATOR MARKING SLIGHTLY ALTERED	PCRD0046	09/07/23	CAB
A	INITIAL RELEASE	NA	NA	CAB
REV.	DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS	
INCHES [MILLIMETERS]	
GENERAL TOLERANCES	
±0.008 [±0.2] / ±1°	
SCALE	PROJECTION
DRAWING NOT TO SCALE	1:1

 E-SWITCH®		 LAMB INDUSTRIES	
DR75-AMSF-10R-B			
DRAWING NUMBER		DATE	REVISION
06-DR75AMSF10RB		JULY 23, 2009	B

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9