

## Fast Recovery Diodes (Stud Version), 6 A, 12 A



DO-203AA (DO-4)

### FEATURES

- Short reverse recovery time
- Low stored charge
- Wide current range
- Excellent surge capabilities
- Standard JEDEC® types
- Stud cathode and stud anode versions
- Fully characterized reverse recovery conditions
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

- DC power supplies
- Inverters
- Converters
- Choppers
- Ultrasonic systems
- Freewheeling diodes

### PRODUCT SUMMARY

|                       |                 |
|-----------------------|-----------------|
| $I_{F(AV)}$           | 6 A, 12 A       |
| Package               | DO-203AA (DO-4) |
| Circuit configuration | Single diode    |

### MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL        | TEST CONDITIONS | 1N3879(R) TO 1N3883(R)             | 1N3889(R) TO 1N3893(R)             | UNITS            |
|---------------|-----------------|------------------------------------|------------------------------------|------------------|
| $I_{F(AV)}$   |                 | 6 <sup>(1)</sup>                   | 12 <sup>(1)</sup>                  | A                |
|               | $T_C$ maximum   | 100                                | 100                                | °C               |
| $I_{F(RMS)}$  |                 | 9.5                                | 19                                 | A                |
| $I_{FSM}$     | 50 Hz           | 72                                 | 145                                | A                |
|               | 60 Hz           | 75 <sup>(1)</sup>                  | 150 <sup>(1)</sup>                 |                  |
| $I^2t$        | 50 Hz           | 26                                 | 103                                | A <sup>2</sup> s |
|               | 60 Hz           | 23                                 | 94                                 |                  |
| $I^2\sqrt{t}$ |                 | 363                                | 856                                | $I^2\sqrt{s}$    |
| $V_{RRM}$     | Range           | 50 to 400 <sup>(1)</sup>           | 50 to 400 <sup>(1)</sup>           | V                |
| $t_{rr}$      |                 | See Recovery Characteristics table | See Recovery Characteristics table | ns               |
| $T_J$         | Range           | -65 to +150                        | -65 to +150                        | °C               |

#### Note

<sup>(1)</sup> JEDEC® registered values



## ELECTRICAL SPECIFICATIONS

| VOLTAGE RATINGS |              |                                                                       |                                                             |                                                          |                                                           |                                                           |
|-----------------|--------------|-----------------------------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------|
| TYPE NUMBER     | VOLTAGE CODE | V <sub>RRM</sub> , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE<br>V | V <sub>RSM</sub> , MAXIMUM NON-REPETITIVE PEAK VOLTAGE<br>V | I <sub>RRM</sub> MAXIMUM AT T <sub>J</sub> = 25 °C<br>μA | I <sub>RRM</sub> MAXIMUM AT T <sub>J</sub> = 100 °C<br>mA | I <sub>RRM</sub> MAXIMUM AT T <sub>J</sub> = 150 °C<br>mA |
| 1N3879(R)       | -            | 50                                                                    | 75                                                          | 15 <sup>(1)</sup>                                        | 1.0 <sup>(1)</sup>                                        | 3.0 <sup>(1)</sup>                                        |
| 1N3880(R)       |              | 100                                                                   | 150                                                         |                                                          |                                                           |                                                           |
| 1N3881(R)       |              | 200                                                                   | 250                                                         |                                                          |                                                           |                                                           |
| 1N3882(R)       |              | 300                                                                   | 350                                                         |                                                          |                                                           |                                                           |
| 1N3883(R)       |              | 400                                                                   | 450                                                         |                                                          |                                                           |                                                           |
| 1N3889(R)       | -            | 50                                                                    | 75                                                          | 25 <sup>(1)</sup>                                        | 3.0 <sup>(1)</sup>                                        | 5.0 <sup>(1)</sup>                                        |
| 1N3890(R)       |              | 100                                                                   | 150                                                         |                                                          |                                                           |                                                           |
| 1N3891(R)       |              | 200                                                                   | 250                                                         |                                                          |                                                           |                                                           |
| 1N3892(R)       |              | 300                                                                   | 350                                                         |                                                          |                                                           |                                                           |
| 1N3893(R)       |              | 400                                                                   | 450                                                         |                                                          |                                                           |                                                           |

## Note


(1) JEDEC® registered values

| FORWARD CONDUCTION                                        |                     |                                                                         |                                     |                                                                |                           |                           |                   |  |
|-----------------------------------------------------------|---------------------|-------------------------------------------------------------------------|-------------------------------------|----------------------------------------------------------------|---------------------------|---------------------------|-------------------|--|
| PARAMETER                                                 | SYMBOL              | TEST CONDITIONS                                                         |                                     |                                                                | 1N3879(R)<br>TO 1N3883(R) | 1N3889(R)<br>TO 1N3893(R) | UNITS             |  |
| Maximum average forward current<br>at case temperature    | I <sub>F(AV)</sub>  | 180° conduction, half sine wave<br>DC                                   |                                     |                                                                | 6 <sup>(1)</sup>          | 12 <sup>(1)</sup>         | A                 |  |
|                                                           |                     |                                                                         |                                     |                                                                | 100                       | 100                       | °C                |  |
| Maximum RMS current                                       | I <sub>F(RMS)</sub> |                                                                         |                                     |                                                                | 9.5                       | 19                        |                   |  |
| Maximum peak, one-cycle<br>non-repetitive forward current | I <sub>FSM</sub>    | t = 10 ms                                                               | No voltage<br>reapplied             | Sinusoidal<br>half wave,<br>initial<br>T <sub>J</sub> = 150 °C | 85                        | 170                       | A                 |  |
|                                                           |                     | t = 8.3 ms                                                              |                                     |                                                                | 90                        | 180                       |                   |  |
|                                                           |                     | t = 10 ms                                                               | 100 % V <sub>RRM</sub><br>reapplied |                                                                | 72                        | 145                       |                   |  |
|                                                           |                     | t = 8.3 ms                                                              |                                     |                                                                | 75 <sup>(1)</sup>         | 150 <sup>(1)</sup>        |                   |  |
| Maximum I <sup>2</sup> t for fusing                       | I <sup>2</sup> t    | t = 10 ms                                                               | No voltage<br>reapplied             |                                                                | 36                        | 145                       | A <sup>2</sup> s  |  |
|                                                           |                     | t = 8.3 ms                                                              |                                     |                                                                | 33                        | 130                       |                   |  |
|                                                           |                     | t = 10 ms                                                               | 100 % V <sub>RRM</sub><br>reapplied |                                                                | 26                        | 103                       |                   |  |
|                                                           |                     | t = 8.3 ms                                                              |                                     |                                                                | 23                        | 94                        |                   |  |
| Maximum I <sup>2</sup> √t for fusing                      | I <sup>2</sup> √t   | t = 0.1 ms to 10 ms, no voltage reapplied                               |                                     |                                                                | 363                       | 1452                      | A <sup>2</sup> √s |  |
| Maximum forward voltage drop                              | V <sub>FM</sub>     | T <sub>J</sub> = 25 °C; I <sub>F</sub> = Rated I <sub>F(AV)</sub> (DC)  |                                     |                                                                | 1.4 <sup>(1)</sup>        | 1.4 <sup>(1)</sup>        | V                 |  |
|                                                           |                     | T <sub>C</sub> = 100 °C; I <sub>FM</sub> = π x rated I <sub>F(AV)</sub> |                                     |                                                                | 1.5 <sup>(1)</sup>        | 1.5 <sup>(1)</sup>        |                   |  |

## Note

(1) JEDEC® registered values

**RECOVERY CHARACTERISTICS**

| PARAMETER                       | SYMBOL               | TEST CONDITIONS                                                                                       | 1N3879(R)<br>TO 1N3883(R) | 1N3889(R)<br>TO 1N3893(R) | UNITS |  |
|---------------------------------|----------------------|-------------------------------------------------------------------------------------------------------|---------------------------|---------------------------|-------|-------------------------------------------------------------------------------------|
| Maximum reverse recovery time   | t <sub>rr</sub>      | T <sub>J</sub> = 25 °C, I <sub>F</sub> = 1 A to V <sub>R</sub> = 30 V, dI <sub>F</sub> /dt = 100 A/μs | 150                       | 150                       | ns    |                                                                                     |
|                                 |                      | T <sub>J</sub> = 25 °C, dI <sub>F</sub> /dt = 25 A/μs, I <sub>FM</sub> = π x rated I <sub>F(AV)</sub> | 300 <sup>(1)</sup>        | 300 <sup>(1)</sup>        |       |                                                                                     |
| Maximum peak recovery current   | I <sub>RM(REC)</sub> | I <sub>FM</sub> = π x rated I <sub>F(AV)</sub>                                                        | 4 <sup>(1)</sup>          | 5 <sup>(1)</sup>          | -     |                                                                                     |
| Maximum reverse recovery charge | Q <sub>rr</sub>      | T <sub>J</sub> = 25 °C, I <sub>F</sub> = 1 A to V <sub>R</sub> = 30 V, dI <sub>F</sub> /dt = 100 A/μs | 400                       | 350                       | nC    |                                                                                     |
|                                 |                      | T <sub>J</sub> = 25 °C, dI <sub>F</sub> /dt = 25 A/μs, I <sub>FM</sub> = π x rated I <sub>F(AV)</sub> | 400                       | 400                       |       |                                                                                     |

**Note**

<sup>(1)</sup> JEDEC® registered values

**THERMAL AND MECHANICAL SPECIFICATIONS**

| PARAMETER                                    | SYMBOL            | TEST CONDITIONS                            | 1N3879(R)<br>TO 1N3883(R) | 1N3889(R)<br>TO 1N3893(R) | UNITS               |
|----------------------------------------------|-------------------|--------------------------------------------|---------------------------|---------------------------|---------------------|
| Maximum junction operating temperature range | T <sub>J</sub>    |                                            | -65 to +150               |                           | °C                  |
| Maximum storage temperature range            | T <sub>Stg</sub>  |                                            | -65 to +175               |                           |                     |
| Maximum thermal resistance, junction to case | R <sub>thJC</sub> | DC operation                               | 2.5                       | 2.0                       | °C/W                |
| Maximum thermal resistance, case to heatsink | R <sub>thCS</sub> | Mounting surface, smooth, flat and greased | 0.5                       |                           |                     |
| Allowable mounting torque                    |                   | Not lubricated threads                     | 1.5 + 0 - 10 %<br>(13)    |                           | N · m<br>(lbf · in) |
|                                              |                   | Lubricated threads                         | 1.2 + 0 - 10 %<br>(10)    |                           |                     |
| Approximate weight                           |                   |                                            | 7                         |                           | g                   |
|                                              |                   |                                            | 0.25                      |                           | oz.                 |
| Case style                                   |                   | JEDEC®                                     | DO-203AA (DO-4)           |                           |                     |

 **$\Delta R_{thJC}$  CONDUCTION**

| CONDUCTION ANGLE | 1N3879(R)<br>TO 1N3883(R) | 1N3889(R)<br>TO 1N3893(R) | 1N3879(R)<br>TO 1N3883(R) | 1N3889(R)<br>TO 1N3893(R) | TEST CONDITIONS         | UNITS |
|------------------|---------------------------|---------------------------|---------------------------|---------------------------|-------------------------|-------|
|                  | SINUSOIDAL CONDUCTION     |                           | RECTANGULAR CONDUCTION    |                           |                         |       |
|                  | 180°                      | 0.58                      | 0.46                      | 0.33                      |                         |       |
| 120°             | 0.60                      | 0.48                      | 0.58                      | 0.46                      | T <sub>J</sub> = 150 °C | K/W   |
| 60°              | 1.28                      | 1.02                      | 1.28                      | 1.02                      |                         |       |
| 30°              | 2.20                      | 1.76                      | 2.20                      | 1.76                      |                         |       |

**Note**

- The table above shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC




Fig. 1 - Average Forward Current vs. Maximum Allowable Case Temperature, 1N3879 Series





Fig. 2 - Average Forward Current vs. Maximum Allowable Case Temperature, 1N3889 Series



$I_F, I_{FM}$  - Peak forward current prior to commutation  
 $-di_F/dt$  - Rate of fall of forward current  
 $I_{RM(REC)}$  - Peak reverse recovery current  
 $t_{rr}$  - Reverse recovery time  
 $Q_{rr}$  - Reverse recovered charge

Fig. 3 - Reverse Recovery Time Test Waveform






Fig. 4 - Current Rating Nomogram (Sinusoidal Waveforms), 1N3879 Series

| Conduction angle - Ø | $\Delta R$ - K/W |
|----------------------|------------------|
| 180°                 | 0.58             |
| 120°                 | 0.60             |
| 60°                  | 1.28             |
| 30°                  | 2.20             |




| Conduction angle - $\phi$ | $\Delta R$ - K/W |
|---------------------------|------------------|
| DC                        | 0                |
| $180^\circ$               | 0.33             |
| $120^\circ$               | 0.58             |
| $60^\circ$                | 1.28             |
| $30^\circ$                | 2.20             |

Fig. 5 - Current Rating Nomogram (Rectangular Waveforms), 1N3879 Series



| Conduction angle - $\phi$ | $\Delta R$ - K/W |
|---------------------------|------------------|
| $180^\circ$               | 0.46             |
| $120^\circ$               | 0.48             |
| $60^\circ$                | 1.02             |
| $30^\circ$                | 1.76             |

Fig. 6 - Current Rating Nomogram (Sinusoidal Waveforms), 1N3889 Series



| Conduction angle - $\phi$ | $\Delta R$ - K/W |
|---------------------------|------------------|
| DC                        | 0                |
| $180^\circ$               | 0.26             |
| $120^\circ$               | 0.46             |
| $60^\circ$                | 1.02             |
| $30^\circ$                | 1.76             |

Fig. 7 - Current Rating Nomogram (Rectangular Waveforms), 1N3889 Series




Fig. 8 - Maximum Forward Voltage vs. Forward Current, 1N3879 Series




Fig. 11 - Maximum High Level Forward Power Loss vs. Average Forward Current, 1N3889 Series




Fig. 9 - Maximum High Level Forward Power Loss vs. Average Forward Current, 1N3879 Series




Fig. 12 - Maximum Non-Repetitive Surge Current vs. Number of Current Pulses, 1N3879 Series




Fig. 10 - Maximum Forward Voltage vs. Forward Current, 1N3889 Series




Fig. 13 - Maximum Non-Repetitive Surge Current vs. Number of Current Pulses, 1N3889 Series




Fig. 14 - Maximum Transient Thermal Impedance, Junction to Case vs. Pulse Duration, All Series

| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95311">www.vishay.com/doc?95311</a> |

**DIMENSIONS** in millimeters (inches)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9