


Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de FCI. Droits de reproduction FCI.





All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

PRODUCT NUMBER
51761- A00CCDDEF..
NOTE ①
SEE NOTE 1



SEE NOTE 9



THIS FILE WAS ORIGINALLY CREATED IN THE PRO ENGINEER ENVIRONMENT AND ANY FUTURE REVISIONS TO THIS FILE MUST BE MADE IN THE PRO ENGINEER ENVIRONMENT

mat'l code SEE NOTE 2				tolerances unless otherwise specified		CUSTOMER COPY		 www.fciconnect.com	
lrr	ecn no.	dr	date	linear	.XX±.01/.X±.3	projection 	INCH / MM scale 1:1	title RIGHT ANGLE RECEPTACLE w/GUIDE PIN SIGNAL/ POWER	
K	DG07-0059	RYAN	02/12/07		.XXX±.005/.XX±.13				
L	DG07-0061	JULIA	02/14/07	.XXX±.0020/.XXX±.051					
M	DG08-0239	JC	09/11/08	angles 0°±2°					
N	DG09-0128	JW	04/23/09	dr DB08LE	05-18-99				
P	DG11-0074	HZ	03/14/11	enrg	J. BROWN	05-18-99	product family size	PWRBLADE dwg no	code 213
				chr	J. BROWN	05-18-99	51761		SHEET 1 OF 2
				appd	J. BROWN	05-18-99			
sheet index	revision sheet	P 1	P 2	P 3					

form no. 7530-001-103

Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

PRODUCT NUMBER		DIM		LENGTH FORMULAS (SEE NOTE 10)	
51761-A00CCDDEF-- NOTE ①		DIM "A"		$.250 [6.35] \times DD + .100 [2.54] \times (CCC/4) + .650 [16.51] \text{ (NOTE 10)}$	
SEE NOTE 1		DIM "B"		$.250 [6.35] \times DD + .100 [2.54] \times (CCC/4) + .350 [8.89]$	
		DIM "C"		$.250 [6.35] \times DD + .100 [2.54] \times (CCC/4) + .300 [7.62]$	
		DIM "D"		$.250 [6.35] \times DD + .375 [9.53] \triangle P$	
		DIM "F"		$.250 [6.35] \times DD + .100 [2.54] \times (CCC/4) + .680 [17.27]$	
		DIM "G"		$.250 [6.35] \times DD + .225 [5.72]$	

CONNECTOR NOTES

① PRODUCT NUMBER CODE:
51761 - A 00 CCC DD E F LF
NO THIS SUFFIX: 100u"/2.54um SnPb ON PCB INTERFACE
ADD THIS SUFFIX: 78u"/2.00um Sn ON PCB INTERFACE
RETENTION TO PCB (NOTE 8)
TAIL OPTIONS (NOTE 7)
NUMBER OF LEFT END POWER CONTACTS (NOTE 6)
NUMBER OF SIGNAL CONTACTS (NOTE 5)
ALWAYS '00' (ZERO, ZERO) (NOTE 4)
PLATING (NOTE 3)
BASE NUMBER

② HOUSING MATERIAL: GLASS FILLED V-O HIGH TEMP THERMO PLASTIC.
SIGNAL CONTACT MATERIAL: COPPER ALLOY
POWER CONTACT MATERIAL: COPPER ALLOY

③ PLATING OPTION:
SEE PRINT 10064183 FOR PLATING SPEC OF 51761-100CCDDEF; 51761-100CCDDEFLF

④ THIS PART IS NOT AVAILABLE WITH RIGHT SIDE POWER CONTACTS.

⑤ SIGNAL CONTACTS, 004 TO 148 AVAILABLE FOR SOLDER TO BOARD.
012 TO 148 AVAILABLE FOR PRESS FIT TO BOARD.

⑥ LEFT END POWER CONTACTS, 01 TO 20 AVAILABLE.
MAXIMUM OF 20 POWER CONTACTS PER CONNECTOR

⑦ TAIL OPTIONS:
A = $.135 \pm .010 [3.43 \pm 0.25]$ SOLDER TO BOARD
B = $.090 + .005 / -.010 [2.29 + 0.13 / -0.25]$ SOLDER TO BOARD
C = $.154 \pm .010 [3.91 \pm 0.25]$ PRESS FIT TO BOARD

⑧ RETENTION TO PCB OPTIONS:
A = BOARD LOCK (REQUIRES $.098 \pm .002 / -.001 [2.49 + 0.05 / -0.03]$ THRU HOLE IN PCB)
MOUNTING FOOT HEIGHT: $.220 [5.59]$
B = $.150 [3.81]$ THRU HOLE (REQUIRES $.158 \pm 0.003 [4.01 \pm 0.08]$ THRU HOLE IN PCB).
MOUNTING FOOT HEIGHT: $.160 [4.06]$

⑨ MANUFACTURE'S NAME, P/N, AND DATE CODE TO APPEAR ON THIS SURFACE.

10. THE MAXIMUM OVERALL LENGTH (DIM A) OF A PART IS 8.00 [203.2]

11. PRODUCT SPECIFICATION GS-12-149

12. APPLICATION SPECIFICATION BUS-20-067.

13. FOR PRESS FIT CONNECTORS USE FCI CAM TOOL 430140-XXX TO APPLY CONNECTOR TO IPCB.

PCB NOTES:

14. ALL DIMENSIONS ARE BASIC UNLESS OTHERWISE SPECIFIED.

15. ALL THROUGH HOLES ARE LOCATED WITH A TRUE POSITION OF $.004 [0.10]$

16. ALL HOLE DIAMETERS ARE FINISHED HOLE SIZE.

17. $\varnothing 0.0453 \pm .001 [1.151 \pm 0.02]$ DRILLED HOLES PLATED WITH $0.0003 [0.007]$ MIN SnPb OR Sn OVER $0.001 [0.03]$ TO $.003 [0.08]$ Cu PLATING TO ACHIEVE A $.040 \pm .003 [1.02 \pm 0.08]$ HOLE.

18. A $\triangle P$ SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.

mat'l code				tolerances unless otherwise specified		CUSTOMER COPY		FCI	
lfr	ecn no.	dr	date	linear	angles	projection	title	product family	code
P				$.XX \pm .01 / .XX \pm .3$	$0^\circ \pm 2^\circ$		RIGHT ANGLE RECEPTACLE w/GUIDE PIN SIGNAL / POWER	PWRBLADE	213
				$.XXX \pm .005 / .XX \pm .13$				size	213
				$.XXX \pm .0020 / .XXX \pm .051$		INCH / MM		dwg no	51761
						scale			SHEET 2 OF 3
				dr DBOBLE 05-18-99		1:1			
				enr J. BROWN 05-18-99					
				chr J. BROWN 05-18-99					
				appd J. BROWN 05-18-99					
sheet index	revision sheet								

THIS FILE WAS ORIGINALLY CREATED IN THE PRO ENGINEER ENVIRONMENT AND ANY FUTURE REVISIONS TO THIS FILE MUST BE MADE IN THE PRO ENGINEER ENVIRONMENT

form no. 7530-001-103





cage code 22526

Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

PRODUCT NUMBER
51761 - A00CCCDDEF--
NOTE ①



mat'l code				tolerances unless otherwise specified		CUSTOMER COPY		 www.fciconnect.com	
lfr	ecn no.	dr	date	linear	.XX±.01/.X±.3	projection 	title RIGHT ANGLE RECEPTACLE w/GUIDE PIN SIGNAL / POWER	product family PWRBLADE	code 213
P					.XXX±.005/.XX±.13				
					.XXX±.0020/.XX±.051				
				angles	0°±2°	INCH / MM  scale 1:1	size A	dwg no 51761	SHEET 3 OF 3
			dr	D.BOGLE 05-18-99					
			enrg	J. BROWN 05-18-99					
			chr	J. BROWN 05-18-99					
			appd	J. BROWN 05-18-99					
sheet index	revision sheet								

form no. 7530-001-103

cage code 22526

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9