

## Sensor/Actuator cable - SAC-4P-M12MR/ 2,0-28X OD - 1407965

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/Actuator cable, 4-position, PE-X halogen-free, black-gray RAL 7021, Plug angled M12, A-coded, on free cable end, Cable length: 2 m, for outdoor applications, with high-grade steel knurl

### Key Commercial Data

|                                      |                                                                                                       |
|--------------------------------------|-------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 STK                                                                                                 |
| GTIN                                 | <br>4 046356 783453 |
| Weight per Piece (excluding packing) | 101.7 g                                                                                               |
| Weight per piece (including packing) | 103.2 g                                                                                               |
| Country of origin                    | Poland                                                                                                |
| Note                                 | Made to Order (non-returnable)                                                                        |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 2 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Ambient temperature (operation) | -40 °C ... 105 °C (Plug / socket) |
| Degree of protection            | IP65                              |
|                                 | IP67                              |
|                                 | IP68                              |
|                                 | IP69K                             |

#### General

|                              |                               |
|------------------------------|-------------------------------|
| Rated current at 40°C        | 4 A                           |
| Rated voltage                | 250 V                         |
| Number of positions          | 4                             |
| Insulation resistance        | ≥ 100 MΩ                      |
| Coding                       | A - standard                  |
| Standards/regulations        | M12 connector IEC 61076-2-101 |
| Status display               | No                            |
| Protective circuit/component | Unwired                       |
| Degree of pollution          | 3                             |

# Sensor/Actuator cable - SAC-4P-M12MR/ 2,0-28X OD - 1407965

## Technical data

### General

|                             |                        |
|-----------------------------|------------------------|
| Insertion/withdrawal cycles | ≥ 100                  |
| Torque                      | 0.4 Nm (M12 connector) |

### Material

|                                        |                 |
|----------------------------------------|-----------------|
| Flammability rating according to UL 94 | V0              |
| Contact material                       | CuSn            |
| Contact surface material               | Ni/Au           |
| Contact carrier material               | PP              |
| Material of grip body                  | PP              |
| Material, knurls                       | Stainless steel |
| Sealing material                       | FPM             |

### Standards and Regulations

|                                        |                 |
|----------------------------------------|-----------------|
| Standard designation                   | M12 connector   |
| Standards/regulations                  | IEC 61076-2-101 |
| Flammability rating according to UL 94 | V0              |

### Cable

|                                               |                                      |
|-----------------------------------------------|--------------------------------------|
| Cable type                                    | PE-X black                           |
| Cable type (abbreviation)                     | 28X                                  |
| Cable abbreviation                            | Li2X2X                               |
| Conductor cross section                       | 4x 0.5 mm <sup>2</sup> (Signal line) |
| AWG signal line                               | 20                                   |
| Conductor structure signal line               | 28x 0.15 mm                          |
| Core diameter including insulation            | 1.6 mm ±0.05 mm (Signal line)        |
| Thickness, insulation                         | approx. 0.3 mm (Core insulation)     |
|                                               | approx. 0.6 mm (Outer cable sheath)  |
| Wire colors                                   | brown, white, blue, black            |
| Overall twist                                 | 4 wires, twisted                     |
| Length of twist, overall twist                | 61.6 mm                              |
| External sheath, color                        | black-gray RAL 7021                  |
| External cable diameter D                     | 5.2 mm ±0.2 mm                       |
| Smallest bending radius, fixed installation   | 26 mm                                |
| Smallest bending radius, movable installation | 52 mm                                |
| Number of bending cycles                      | 2000000                              |
| Bending radius                                | 52 mm                                |
| Traversing path                               | 10 m                                 |
| Traversing rate                               | 3 m/s                                |
| Acceleration                                  | 10 m/s <sup>2</sup>                  |
| Cable weight                                  | 44 kg/km                             |
| Outer sheath, material                        | PE-X                                 |
| Material conductor insulation                 | PE-X                                 |

# Sensor/Actuator cable - SAC-4P-M12MR/ 2,0-28X OD - 1407965

## Technical data

### Cable

|                                 |                                                       |
|---------------------------------|-------------------------------------------------------|
| Conductor material              | Bare Cu litz wires                                    |
| Insulation resistance           | $\geq 100 \text{ M}\Omega \cdot \text{km}$ (at 20 °C) |
| Conductor resistance            | $\leq 39 \text{ }\Omega/\text{km}$ (at 20 °C)         |
| Nominal voltage, cable          | $\leq 300 \text{ V AC}$                               |
| Test voltage, cable             | $\geq 3000 \text{ V AC}$                              |
| Flame resistance                | According to DIN 60332-1-2                            |
|                                 | According to DIN EN 50266-2-5                         |
|                                 | according to IEC 60332-3-25 (bunched fire test)       |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815              |
| Resistance to oil               | in accordance with DIN EN 60811-2-1                   |
| Other resistance                | UV resistant According to DIN VDE 0276-605            |
| Ambient temperature (operation) | -40 °C ... 105 °C (cable, fixed installation)         |
|                                 | -15 °C ... 105 °C (cable, flexible installation)      |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |

## Approvals

### Approvals

## Sensor/Actuator cable - SAC-4P-M12MR/ 2,0-28X OD - 1407965

### Approvals

Approvals

GL

Ex Approvals


Approvals submitted

### Approval details

GL


### Drawings

Schematic diagram




Pin assignment M12 plug, 4-pos., A-coded, view plug side

Cable cross section




PE-X black [28X]

Dimensional drawing



M12 x 1 male plug, angled

Circuit diagram



Contact assignment of the M12 plugs

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9