

## 1U Rack-Mount Power Strip, 120V, 20A, 5-20P, 12 Outlets (6 Front-Facing, 6-Rear-Facing) 15-ft. Cord

MODEL NUMBER: RS-1215-20



### Highlights

- Designed for standard 19-inch racks (1U high)
- 12 outlets (6 front / 6 rear)
- 15 ft. cord
- 20-amp circuit breaker

### Package Includes

- RS-1215-20
- Warranty information
- Instruction manual

### Description

Tripp Lite's RS-1215-20 Power Strip offers 20 amp capacity AC power distribution in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under-counter installation. Uses only 1 rack space (1U) when installed in any 19 inch rack meeting EIA standards. Unfiltered electrical pass-through makes RS-1215-20 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 12 NEMA5-20R outlets (6 front/6 rear), 15 ft AC power cord and lighted switch with cover prevents risk of accidental turn-off.

PLUG/OUTLET: Input: NEMA 5-20P

Output: 12 NEMA5-20R (6 front & 6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 20A (Requires NEMA 5-20R wall receptacle)

FORMAT: 19 in. rackmount (uses 1 rack space/1U), wallmount, under-counter and more

### Features

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- Uses one rack space (1U) in standard 19 inch rack ("zero U" mounting possible in many racks)
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 12 NEMA5-20R output receptacles (6 front/6 rear)
- 15 foot AC cord NEMA5-20P plug connection
- Lighted power switch confirms power on/off status
- Snap-in switch guard prevents accidental turn off
- 20 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

## Specifications



| <b>OVERVIEW</b>                              |   |
|--|---|
| UPC Code                                     | 037332099372  |
| <b>INPUT</b>                                 |   |
| Nominal Input Voltage(s) Supported           | 120V AC   |
| Recommended Electrical Service               | 20A 120V  |
| Voltage Compatibility (VAC)                  | 120   |
| Input Plug Type                              | NEMA 5-20P  |
| Input Cord Length (ft.)                      | 15  |
| Input Cord Length (m)                        | 4.57  |
| Integrated Cord Clip                         | No  |
| <b>OUTPUT</b>                                |   |
| Frequency Compatibility                      | 50 / 60 Hz  |
| Output (Watts)                               | 2400  |
| Output Receptacles                           | (12) 5-15/20R   |
| Circuit Breaker (amps)                       | 20  |
| Transformer Accommodation                    | (3) Yes   |
| Outlet Orientation                           | 6 front facing / 6 rear facing  |
| Right-Angle Outlets                          | No  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Switches                                     | Red illuminated 2 position switch controls power to all outlets                 |
| Locking Switch Cover                         | Transparent locking switch cover prevents accidental shutoff                    |
| <b>PHYSICAL</b>                              |   |
| Anti-Microbial Protective Coating            | No  |
| Color  | Black   |
| Color (AC Line Cord)                         | Black   |
| Form Factors Supported                       | 1U rackmount, wall-mount and undercounter installation supported                |
| Included Mounting Accessories                | Rackmount flanges   |
| Integrated Keyhole Mounting Slots            | No  |
| Material of Construction                     | Sheet metal   |
| Outlets Measurement (Center to Center)       | Distance between Front outlets = 51.6mm; Distance between Rear outlets = 71.1mm |
| Receptacle Color                             | Black   |
| Shipping Dimensions (hwd / cm)               | 23.37 x 6.60 x 51.56  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Shipping Dimensions (hwd / in.)     | 9.20 x 2.60 x 20.30                   |
| Shipping Weight (kg)                | 2.68                                  |
| Shipping Weight (lbs.)              | 5.90                                  |
| Unit Dimensions (hwd / cm)          | 4.445 x 44.45 x 11.4                  |
| Unit Dimensions (hwd / in.)         | 1.75 x 17.5 x 4.5                     |
| Unit Weight (kg)                    | 2.09                                  |
| Unit Weight (lbs.)                  | 4.6                                   |
| <b>SPECIAL FEATURES</b>             |                                       |
| TVSS Grounding                      | Back panel nut and bolt grounding lug |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                                       |
| Canada                              | cUL                                   |
| UL1363 (Power Tap)                  | UL1363 (UR status)                    |
| <b>WARRANTY</b>                     |                                       |
| Product Warranty Period (Worldwide) | Lifetime limited warranty             |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9