# **Low Voltage Comparator**

The NCS2220A is an industry first sub–one volt, low power dual comparator. This device consumes only 0.85  $\mu A$  per Comparator of supply current. It is guaranteed to operate at a low voltage of 0.85 V which allows it to be used in systems that require less than 1.0 V and is fully operational up to 6.0 V. Additional features include no output phase inversion with overdriven inputs, internal hysteresis, which allows for clean output switching, and rail–to–rail input and output performance. The NCS2220A is available in the tiny UDFN 1.6 X 1.6 package.

#### **Features**

- Operating Voltage of 0.85 V to 6.0 V
- Rail-to-Rail Input/Output Performance
- Low Supply Current of 7.5 μA per Comparator Typ
- No Phase Inversion with Overdriven Input Signals
- Internal Hysteresis
- Propagation Delay of 0.5 μs
- These are Pb-Free Devices

#### **Typical Applications**

- Single Cell NiCd/NiMH Battery Powered Applications
- Cellular Telephones
- Alarm and Security Systems
- Personal Digital Assistants



## ON Semiconductor®

http://onsemi.com



UDFN8 1.6 X 1.6 MU SUFFIX CASE 517AC MARKING DIAGRAMS



CZ = Specific Device Code

M = Date Code


■ = Pb-Free Package

(Note: Microdot may be in either location)

#### **ORDERING INFORMATION**

Device	Package	Shipping <sup>†</sup>
NCS2220AMUT1G	UDFN8 (Pb-Free)	3000/ Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.



NOTE: The NCS2220A has three exposed pads on the bottom side which may be used to reduce thermal resistance by soldering to a copper heat-spreader. Electrically the exposed pads must be allowed to float.

Figure 1. Pin Connections

#### **MAXIMUM RATINGS**

Rating	Symbol	Value	Unit
Supply Voltage Range (V <sub>CC</sub> to V <sub>EE</sub> )	V <sub>S</sub>	6.0	V
Non-inverting/Inverting Input to V <sub>EE</sub>	_	-0.2 to (V <sub>CC</sub> + 0.2)	V
Operating Junction Temperature	T <sub>J</sub>	150	°C
Operating Ambient Temperature	T <sub>A</sub>	-40 to +105	°C
Storage Temperature Range	T <sub>stg</sub>	-65 to +150	°C
Output Short Circuit Duration Time (Note 1)	t <sub>S</sub>	Indefinite	s
ESD Tolerance (Note 2) Human Body Model Machine Model	-	2000 200	V
Thermal Resistance, Junction-to-Ambient UDFN	$R_{ hetaJA}$	350	°C/W

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. The maximum package power dissipation limit must not be exceeded.

$$P_D = \frac{T_{J(max)} - T_A}{R_{\theta JA}}$$

2. ESD data available upon request.

 $\textbf{ELECTRICAL CHARACTERISTICS} \text{ (For all values V}_{CC} = 0.85 \text{ V to } 6.0 \text{ V, V}_{EE} = 0 \text{ V, T}_{A} = 25^{\circ}\text{C, unless otherwise noted.)} \text{ (Note 3)}$ 

Characteristics	Symbol	Min	Тур	Max	Unit
Input Hysteresis T <sub>A</sub> = 25°C	V <sub>HYS</sub>	2.0	4.5	20	mV
Input Offset Voltage $V_{CC} = 0.85 \text{ V}$ $T_{A} = 25^{\circ}\text{C}$ $T_{A} = -40^{\circ}\text{C to } 105^{\circ}\text{C}$	V <sub>IO</sub>	-10 -12	0.5 -	+10 +12	mV
$V_{CC} = 3.0 \text{ V}$ $T_A = 25^{\circ}\text{C}$ $T_A = -40^{\circ}\text{C}$ to 105°C $V_{CC} = 6.0 \text{ V}$		-6.0 -8.0	0.5 -	+6.0 +8.0	
$T_A = 25$ °C $T_A = -40$ °C to 105°C		-5.0 -7.0	0.5 -	+5.0 +7.0	
Common Mode Voltage Range	$V_{CM}$	-	V <sub>EE</sub> to V <sub>CC</sub>	-	V
Output Short-Circuit Sourcing or Sinking	Isc	-	60	_	mA
Common Mode Rejection Ratio V <sub>CM</sub> = V <sub>CC</sub>	CMRR	53	70	_	dB
Input Bias Current	I <sub>IB</sub>	-	1.0	-	pА
Power Supply Rejection Ratio $\Delta V_S = 2.575 \text{ V}$	PSRR	45	80	-	dB
Supply Current per Comparator $V_{CC} = 0.85 \text{ V}$ $T_A = 25^{\circ}\text{C}$ $T_A = -40^{\circ}\text{C}$ to $105^{\circ}\text{C}$	Icc	-	7.5 -	15 17	μΑ
$V_{CC} = 3.0 \text{ V}$ $T_A = 25^{\circ}\text{C}$ $T_A = -40^{\circ}\text{C}$ to $105^{\circ}\text{C}$ $V_{CC} = 6.0 \text{ V}$ $T_A = 25^{\circ}\text{C}$		-	8.0 - 9.0	15 17 15	
$T_A = -40^{\circ}$ C to 105°C			-	17	
Output Voltage High $V_{CC} = 0.85 \text{ V, } I_{source} = 0.5 \text{ mA}$ $T_{A} = 25^{\circ}\text{C}$ $T_{A} = -40^{\circ}\text{C to } 105^{\circ}\text{C}$	V <sub>OH</sub>	V <sub>CC</sub> - 0.25 V <sub>CC</sub> - 0.275	V <sub>CC</sub> - 0.12	-	V
$V_{CC} = 3.0 \text{ V, } I_{source} = 3.0 \text{ mA}$ $T_A = 25^{\circ}\text{C}$ $T_A = -40^{\circ}\text{C to } 105^{\circ}\text{C}$ $V_{CC} = 6.0 \text{ V, } I_{source} = 5.0 \text{ mA}$		V <sub>CC</sub> - 0.3 V <sub>CC</sub> - 0.35	V <sub>CC</sub> - 0.12 -	-	
$T_A = 25^{\circ}C$ $T_A = -40^{\circ}C$ to 105°C		V <sub>CC</sub> - 0.3 V <sub>CC</sub> - 0.35	V <sub>CC</sub> – 0.17 –	-	
Output Voltage Low $V_{CC}=0.85 \text{ V, } I_{sink}=0.5 \text{ mA}$ $T_{A}=25^{\circ}\text{C}$ $T_{A}=-40^{\circ}\text{C to } 105^{\circ}\text{C}$ $V_{CC}=3.0 \text{ V, } I_{sink}=3.0 \text{ mA}$	V <sub>OL</sub>	-	V <sub>EE</sub> + 0.10	V <sub>EE</sub> + 0.25 V <sub>EE</sub> + 0.275	V
$T_A = 25^{\circ}\text{C}$ $T_A = -40^{\circ}\text{C to } 105^{\circ}\text{C}$ $V_{CC} = 6.0 \text{ V, } I_{\text{sink}} = 5.0 \text{ mA}$		-	V <sub>EE</sub> + 0.12 -	V <sub>EE</sub> + 0.3 V <sub>EE</sub> + 0.35	
$T_A = 25^{\circ}C$ $T_A = -40^{\circ}C$ to 105°C		-	V <sub>EE</sub> + 0.12 -	V <sub>EE</sub> + 0.3 V <sub>EE</sub> + 0.35	
Propagation Delay 20 mV Overdrive, C <sub>L</sub> = 15 pF	t <sub>PHL</sub> t <sub>PLH</sub>	- -	0.5 0.5	- -	μs
Output Fall Time V <sub>CC</sub> = 6.0 V, C <sub>L</sub> = 50 pF (Note 4)	t <sub>FALL</sub>	-	20	-	ns
Output Rise Time V <sub>CC</sub> = 6.0 V, C <sub>L</sub> = 50 pF (Note 4)	t <sub>RISE</sub>	_	16	_	ns

<sup>3.</sup> The limits over the extended temperature range are guaranteed by design only.4. Input signal: 1 kHz, squarewave signal with 10 ns edge rate.




Figure 1. Supply Current versus Temperature/Comparator




Figure 2. Supply Current versus Output Transition Frequency/Comparator




Figure 3. Supply Current versus Supply Voltage/Comparator




Figure 4. Output Voltage High State versus Output Source Current




Figure 5. Output Voltage Low State versus Output Sink Current




Figure 6. Output Voltage Low State versus Temperature




Figure 7. Output Voltage High State versus Temperature




Figure 8. Propagation Delay versus Temperature




Figure 9. Output Response Time versus Supply Voltage




Figure 10. Propagation Delay versus Input Overdrive




Figure 11. Propagation Delay versus Input
Overdrive




Figure 12. Powerup Delay




Figure 13. Input Common Mode Voltage Range versus Supply Voltage

### **OPERATING DESCRIPTION**

The NCS2220A is an industry first sub-one volt, low power comparator. This device is designed for rail-to-rail input and output performance. This device consumes only 7.5  $\mu$ A/Comparator of supply current while achieving a typical propagation delay of 0.5  $\mu$ s at a 20 mV input overdrive. Figures 10 and 11 show propagation delay with various input overdrives. This comparator is guaranteed to operate at a low voltage of 0.85 V up to 6.0 V. This is accomplished by the use of a modified analog CMOS process that implements depletion MOSFET devices. The common-mode input voltage range extends 0.1 V beyond

the upper and lower rail without phase inversion or other adverse effects. This device has a typical internal hysteresis of  $\pm 8.0$  mV. This allows for greater noise immunity and clean output switching.

### **Output Stage**

The NCS2220A has a complementary P and N Channel output stage that has capability of driving a rail-to-rail output swing with a load ranging up to 5.0 mA. It is designed such that shoot-through current is minimized while switching. This feature eliminates the need for bypass capacitors under most circumstances.






Figure 14. NCS2220A Complementary Output Configuration



The oscillation frequency can be programmed as follows:


$$f = \frac{1}{T} = \frac{1}{2.2 \; R_X C_X}$$

Figure 15. Schmitt Trigger Oscillator



The resistor divider  $R_1$  and  $R_2$  can be used to set the magnitude of the input pulse. The pulse width is set by adjusting  $C_1$  and  $R_3$ .

Figure 16. One-Shot Multivibrator



This circuit converts 5 V logic to 3 V logic. Using the NCS2220/A allows for full 5 V logic swing without creating overvoltage on the 3 V logic input.

Figure 17. Logic Level Translator





Figure 18. Zero-Crossing Detector

#### PACKAGE DIMENSIONS

#### UDFN8, 1.6x1.6, 0.4P CASE 517AC-01 **ISSUE A**




C

**SIDE VIEW** 

#### NOTES:

- IES:
  DIMENSIONING AND TOLERANCING PER
  ASME Y14.5M, 1994.
  CONTROLLING DIMENSION: MILLIMETERS.
  DIMENSION & APPLIES TO PLATED TERMINAL
- AND IS MEASURED BETWEEN 0.25 AND 0.30 mm FROM TERMINAL.
- COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
- EXPOSED PADS CONNECTED TO DIE FLAG. USED AS TEST CONTACTS.

	MILLIMETERS			
DIM	MIN	NOM	MAX	
Α	0.45	0.50	0.55	
A1	0.00	0.03	0.05	
А3	0.127 REF			
b	0.15	0.20	0.25	
D	1.60 BSC			
D2	0.70	0.80	0.90	
E	1.60 BSC			
E2	0.40	0.50	0.60	
е	0.40 BSC			
K	0.20			
L	0.20	0.30	0.40	



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and un are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, ON semiconductor and war registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC wors the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdt/Patent—Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implications the policy of other applications intended to surgical implication in which the failure of the SCILLC product could create a situation where surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### **PUBLICATION ORDERING INFORMATION**

0.08 C

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor P.O. Box 5163, Denver, Colorado 80217 USA

**Phone**: 303-675-2175 or 800-344-3860 Toll Free USA/Canada **Fax**: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910

Japan Customer Focus Center Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

## **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

## http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

## Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru\_4 moschip.ru\_9